

AHSANULLAH UNIVERSITY OF SCIENCE AND TECHNOLOGY



Department of Computer Science and Engineering

Course No: CSE 2103

Course Title: Data Structures Lab

Assignment No: 06

Date of Submission: 28/2/2026

Submitted by,

Name: Durjoy Roy

Student ID: 00724105101055

Lab Section: B1

Academic Semester: Spring 2025

Program: BSc in CSE

Question:

Write a program to support multi-digit numbers in the conversion of an infix expression to postfix notation and the evaluation of the resulting postfix expression. For example, your code should convert this infix expression to its

appropriate postfix notation: $(12 + 34) * 56 - 78 / 9$. Then evaluate the result of this expression from the postfix notation.

Solution:

```
#include<bits/stdc++.h>
```

```
using namespace std;
```

```
stack<char>S;
```

```
stack<int>P;
```

```
int priority(char s)
```

```
{
```

```
    if(s == '^') return 100;
```

```
    else if(s == '*' || s == '/') return 50;
```

```
    else if(s == '+' || s == '-') return 20;
```

```
    else return 0;
```

```
}
```

```
int main()
```

```
{
```

```
    string infix, postfix = "";
```

```
    cin >> infix;
```

```
    for(int i=0; i<infix.size(); i++)
```

```
    {
```

```
        char symbol = infix[i];
```

```
        if(symbol == ' ') continue;
```

```
if(symbol >= '0' && symbol <= '9')
{
    while(i < infix.size() && infix[i] >= '0' && infix[i] <= '9')
    {
        postfix += infix[i];
        i++;
    }
    postfix += ' ';
    i--;
}
else if(symbol == '(')
{
    S.push(symbol);
}
else if(symbol == ')')
{
    while(!S.empty() && S.top() != '(')
    {
        postfix += S.top();
        S.pop();
    }
    S.pop();
}
else
{

```

```
while(!S.empty() && priority(S.top()) >= priority(symbol))
{
    postfix += S.top();
    S.pop();
}
S.push(symbol);
}
```

```
while(!S.empty())
{
    postfix += S.top();
    S.pop();
}
```

```
cout << "Postfix: " << postfix << endl;
```

```
for(int i=0; i<postfix.size(); i++)
{
    char token = postfix[i];

    if(token == ' ') continue;
    if(token >= '0' && token <= '9')
    {
        int num =0;
        while(i < postfix.size() && postfix[i]>= '0' && postfix[i] <= '9')
```

```

    {
        num = num*10 + (postfix[i] - '0');
        i++;
    }
    P.push(num);
    i--;
}
else
{
    int a = P.top();
    P.pop();
    int b = P.top();
    P.pop();
    int c;
    if(token == '+') c = b+a;
    else if(token == '-') c = b-a;
    else if(token == '*') c = b*a;
    else if(token == '/') c = b/a;
    else if(token == '^') c = pow(b,a);
    P.push(c);
}
}

cout << "Evaluate result: " << P.top();
return 0;
}

```

Input: $(12+34)*56-78/9$

Output:

Postfix: 12 34 +56 *78 9 /-

Evaluate result: 2568