

Domaća naloga 4 – Marko Tojagić

Spodaj prilagam slike ukazov katere sem uporabljal za ustvarjanje lokalnega repozitorija z uporabo GIT. Github sem namestil in konfiguriral ter naložil gor lokalni repozitorij.

```
PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT
$ mkdir tojagic_marko

PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT
$ cd tojagic_marko/

PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko
$ git init
Initialized empty Git repository in C:/Users/PC/Downloads/GIT/tojagic_marko/.git
/

PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ mkdir srecanje1
mkdir srecanje2
mkdir srecanje3
mkdir srecanje4

PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ dir
srecanje1  srecanje2  srecanje3  srecanje4

PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ git add .

$ git commit -m "Marko Tojagic"
Author identity unknown

*** Please tell me who you are.

Run

    git config --global user.email "you@example.com"
    git config --global user.name "Your Name"

to set your account's default identity.
Omit --global to set the identity only in this repository.

fatal: unable to auto-detect email address (got 'PC@DESKTOP-PILOBQB.(none)')

PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ ^C

PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ git config --global user.email "marko.tojagic@almamater.si"

PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ git config --global user.name "Marko"

PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ git config --global user.name "Marko Tojagić"

PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ git commit -m "Prvo dodajanje"
```

```
PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ git remote add origin https://github.com/almaTojagic2026/alma2026TojagicDelo.git

PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ git branch -M master

PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ git push -u origin main
error: src refspec main does not match any
error: failed to push some refs to 'https://github.com/almaTojagic2026/alma2026TojagicDelo.git'
```

```
PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ git push -u origin master
Enumerating objects: 37, done.
Counting objects: 100% (37/37), done.
Delta compression using up to 4 threads
Compressing objects: 100% (36/36), done.
Writing objects: 100% (37/37), 2.14 MiB | 1.54 MiB/s, done.
Total 37 (delta 1), reused 0 (delta 0), pack-reused 0 (from 0)
remote: Resolving deltas: 100% (1/1), done.
To https://github.com/almaTojagic2026/alma2026TojagicDelo.git
 * [new branch]      master -> master
branch 'master' set up to track 'origin/master'.
```

```
PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ |
```

```
PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ git add .
```

```
PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ git commit -m "DN4 dodano"
[master 1041672] DN4 dodano
 4 files changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 srecanje4/dn4 (1).PNG
 create mode 100644 srecanje4/dn4 (2).PNG
 create mode 100644 srecanje4/dn4 (3).PNG
 create mode 100644 srecanje4/dn4 (4).PNG
```

```
PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ git push
Enumerating objects: 9, done.
Counting objects: 100% (9/9), done.
Delta compression using up to 4 threads
Compressing objects: 100% (7/7), done.
Writing objects: 100% (7/7), 74.19 KiB | 18.55 MiB/s, done.
Total 7 (delta 1), reused 0 (delta 0), pack-reused 0 (from 0)
remote: Resolving deltas: 100% (1/1), completed with 1 local object.
To https://github.com/almaTojagic2026/alma2026TojagicDelo.git
 b52486d..1041672 master -> master
```

```
PC@DESKTOP-PILOBQB MINGW64 ~/Downloads/GIT/tojagic_marko (master)
$ |
```

2.1

Zakaj je cloud primeren za Proof of Concept?

Cloud je primeren za proof of concept, ker omogoča hitro postavitve rešitve z nizkimi stroški, saj plačamo le dejansko porabljene vire.

Kako cloud olajša delo z velikimi količinami podatkov?

Cloud olajša delo z velikimi količinami podatkov, ker omogoča cenejšo in enostavnejšo obdelavo, del infrastrukture pa upravlja ponudnik.

Kdo je odgovoren za “mechanical and electrical” infrastrukturo v public cloudu?

Za to infrastrukturo je v javnem oblaku odgovoren ponudnik storitve, ne uporabnik.

Kaj v oblaku nadomešča switch-e, router-je in firewall-e?

V oblaku te naprave nadomeščajo virtualna omrežja in njihove nastavitve.

Kaj točno pomeni traffic bursting?

Traffic bursting pomeni začasno povečanje obremenitve sistema, na primer v obdobjih večjega povpraševanja.

2.2

i.

EC2 - IaaS

GitHub - SaaS

Virtualni računalnik s prvega predavanja (Debian, NAT) - ni oblačna storitev

EC2 je infrastruktura v oblaku, saj kot uporabniki “vzamemo v najem” infrastrukturo, ter jo sami upravljamo in nastavljamo po naši želji, GitHub pa je že spletna storitev (SaaS). Lokalni VM ni cloud, ker teče na lokalnem računalniku, nismo ponudniki cloud rešitev.

ii.

EC2 - compute

GitHub - storage

EC2 je compute, ker poganja virtualne računalnike. GitHub je najbližje storage, ker hrani kodo, repozitorije in datoteke.

iii.

EC2 - IaaS

GitHub - SaaS

EC2 je IaaS, ker dobimo virtualno infrastrukturo za upravljanje. GitHub je SaaS, ker uporabljamo končno aplikacijo prek interneta.

iv.

EC2:

Gostovanje strežnikov / podatkovnih baz / aplikacij

Backup storitve, macOS developing

GitHub:

Hranijo se podatki za razvoj aplikacij

Več razvijalcev lahko dela na istem projektu (deljeni projekti)