


SPARE PARTS AND ACCESSORIES FOR YAMAHA XV 500 SE SPECIAL 26R

Specifications*



1983 - 1987

opeomeanone	
Engine size:	493
Cylinders:	2
hp/kW:	49/36, 27/20
Vehicle weight (kg):	185
Seat height (mm):	745
Valve clearance (intake):	KALT 0,07-0,12 MM
Valve clearance (exhaust):	KALT 0,12-0,17 MM
Engine idle speed:	1200 ± 50 U/MIN
Carburettor air screw:	2 AUSDREHUNGEN
Tyre pressure (front):	2,0 BAR
Tyre pressure (rear):	2,3 BAR
Spark plug 1:	NGK BPR7ES
Spark plug 2:	NGK BPR7EIX
Electrode gap:	0,8 MM
Fork tube diam.:	36 MM TELEGABEL
Chain/Final drive:	KARDAN

Capacities*

Fork oil per rod:	296 ML SAE 10W
Engine oil w/o filter:	2,4 L SAE 20W-40
Engine oil with filter:	2,5 L MIN. API SE
Brake fluid:	DOT 4
Final drive oil:	190 ML SAE 80 GL-4
Fuel:	11,4 LITER
Coolant:	LUFTGEKÜHLT

Test reports and information

TOURENFAHRER 6/84

Find used value: DAT GmbH