## Data cleaning and feature engineering

- 1. Deleting Unnecessary Columns
- 2. Removing the Duplicates
- 3. Remove the NaN values from the dataset
- 4. Changing the column names
- 5. Data Transformations
- 6. Data Cleaning
- 7. Adjust the column names

```
zomato=zomato_real.drop(['url','dish_liked','phone'],ax
is=1) #Dropping the column "dish_liked", "phone", "url"
and saving the new dataset as "zomato"
#Removing the Duplicates
zomato.duplicated().sum()
zomato.drop_duplicates(inplace=True)
#Remove the NaN values from the dataset
zomato.isnull().sum()
zomato.dropna(how='any',inplace=True)
#Changing the column names
zomato = zomato.rename(columns={'approx_cost(for two
people)':'cost','listed_in(type)':'type',
'listed_in(city)':'city'})
#Some Transformations
zomato['cost'] = zomato['cost'].astype(str) #Changing
the cost to string
zomato['cost'] = zomato['cost'].apply(lambda x:
x.replace(',',','.')) #Using lambda function to replace
',' from cost
zomato['cost'] = zomato['cost'].astype(float)
#Removing '/5' from Rates
zomato = zomato.loc[zomato.rate !='NEW']
zomato = zomato.loc[zomato.rate !
='-'].reset_index(drop=True)
remove_slash = lambda x: x.replace('/5', '') if
isinstance(x, str) else x
```

```
zomato.rate =
zomato.rate.apply(remove_slash).str.strip().astype(
at')
# Adjust the column names
zomato.name = zomato.name.apply(lambda x:x.title())
zomato.online_order.replace(('Yes','No'),(True,
False), inplace=True)
zomato.book_table.replace(('Yes','No'),(True,
False), inplace=True)
## Computing Mean Rating
restaurants = list(zomato['name'].unique())
zomato['Mean Rating'] = 0
for i in range(len(restaurants)):
    zomato['Mean Rating'][zomato['name'] ==
restaurants[i]] = zomato['rate'][zomato['name'] ==
restaurants[i]].mean()
from sklearn.preprocessing import MinMaxScaler
scaler = MinMaxScaler(feature_range = (1,5))
zomato[['Mean Rating']] =
scaler.fit_transform(zomato[['Mean Rating']]).round
```