

4.1 Ansible Inventory



Overview

- ▶ Group Name in [brackets]
 - ▶ Common variables can be in group_vars
- ▶ One line per host
- ▶ Host can be in multiple groups
- ▶ Can specify host and group variables in file (not recommended by Ansible)
- ▶ Default location: /etc/ansible/hosts
 - ▶ Contains examples you can reference

Example

[ios-devices]

iosv-1

iosv-2 ansible_host=172.16.1.83 ansible_user=cisco1

[TOR]

iosv-1

iosv-2

vyos

Example

```
[SPINE]
```

```
iosv-[1:2]
```

```
[SPINE:vars]
```

```
ansible_network_os='ios'
```

Resources

▶ Ansible Inventory

http://docs.ansible.com/ansible/latest/user_guide/intro_inventory.html#working-with-inventory

▶ INI File Format

https://en.wikipedia.org/wiki/INI_file

Next: Inventory Examples



Playbook

```
1  --
2  - name: First Network Playbook
3    connection: network_cli
4    hosts: all
5    tasks:
6      - name: show version
7        ios_command:
8          commands: show version
9
10       register: output
11
12     - name: show output
13       debug:
14         var: output.stdout
15
16     - name: copy output to file
17       copy: content="{{ output }}" dest=./output/{{ inventory_hostname }}.txt
18  ...
```

Playbook

Play

Task

Modules

YAML

```
1  --
2  - name: First Network Playbook
3    connection: network_cli
4    hosts: all
5    tasks:
6      - name: show version
7        ios_command:
8          commands: show version
9
10       register: output
11
12       - name: show output
13         debug:
14           var: output.stdout
15
16       - name: copy output to file
17         copy: content="{{ output }}" dest=./output/{{ inventory_hostname }}.txt
18  ...
```

Dictionary

List

YAML Beginning / End

List

OSPF Configuration Workflow

- ▶ Configure Basic OSPF
- ▶ Verifying OSPF Adjacencies
- ▶ Verifying the OSPF Database


New in Version 2

“Up and Running” with Network Devices

Save Time + Be More Productive

Prerequisites

- ▶ (optional) Basic Networking Knowledge




Why Ansible?


Ansible has thousands of users, hundreds of customers and over 2,400 community contributors

600+	29,000+	230+
ANSIBLE MODULES	GITHUB STARS	MEETUPS WORLDWIDE

[JOIN OUR COMMUNITY](#)




“ The work the Ansible team is doing... is something the entire industry should be paying attention to.




Lew Tucker
VP & CTO, Cloud Computing
Cisco

[OpenStack Integration](#)



“ Red Hat Ansible Tower allows us to easily streamline the delivery of applications and services to both OpenStack & Amazon Clouds in a cost effective, simple, & secure manner.



Jeremy Pruitt
Cloud & Automation
Juniper

[IT Automation with Ansible Tower](#)

Credit: <https://www.ansible.com/>

Come Join me to save time and be more
productive as Network Engineers!

OSPF Configuration Workflow

- ▶ Configure Basic OSPF
- ▶ Verifying OSPF Adjacencies
- ▶ Verifying the OSPF Database

Tracking Topology Changes

▶ When a new LSA is received it is checked against the database for changes such as...

- Sequence number is used to:
 - track new vs old LSAs
- Age is used to:
 - Keep information new
 - Withdraw old information
 - Periodic flooding occurs after 30 minutes
 - “paranoid” update
 - LSAs that reach MaxAge (60 minutes) are withdrawn
- Checksum
 - Used to avoid transmission & memory corruption

Tracking Topology Changes

- ▶ When a new LSA is received it is checked against the database for changes such as...
 - Sequence number
 - Age
 - Used to keep information new
 - Withdraw old information
 - Periodic flooding occurs after 30 minutes
 - LSAs that reach MaxAge (60 minutes) are withdrawn
 - Checksum
 - Used to avoid transmission & memory corruption


Tracking Topology Changes

- ▶ When a new LSA is received it is checked against the database for changes such as...
 - Sequence number
 - Age
 - Used to keep information new and withdraw old information
 - Periodic flooding occurs after 30 minutes
 - LSAs that reach MaxAge (60 minutes) are withdrawn
 - Checksum
 - Used to avoid transmission & memory corruption


Tracking Topology Changes

▶ When a new LSA is received it is checked against the database for changes such as...

- Sequence number
- Age
- Checksum



Product/Topology Diagram



Wireshark is used to capture data and display it for review so that you can look through it and attempt to find answers to questions around problems.