6.1 Ansible Playbooks



Ansible Modules

- Scripts that accomplish a task
- Mostly in Python, small percentage of them are in PowerShell for Windows.
- Self-made modules can be in any language
- **▶**Lots of Network Modules



Ansible Run Methods

- ▶Use ssh to copy the Python module to remote host, run, clean up.
- Run locally and use Paramiko to ssh to host or call remote host API (This is the way most network modules are run).
- ▶AdHoc one-liner



Ansible Playbooks

- Modules are your tools, Playbook is the instruction manual for which tool to use, when to use them, and in what order.
- No need to learn all the features at once, start small and pick up more features as you need them.



Playbook

```
Plavbook
     name: First Network Playbook
                                                                      Play
     connection: network_cli
     hosts: all
     tasks:
 6
       - name: show version
                                                                      Task
         ios_command:
           commands: show version
                                               Modules
9
10
11
12
         register: output
       - name: show output
13
14
         debug:
           var: output.stdout
15
16
       - name: copy output to file
17
         copy: content="{{ output }}" dest=./output/{{ inventory_hostname }}.txt
```



YAML

- ▶Starts with "---" and end with "..."
- All members of a list are lines with the same indentation level with '-' and a space
- A Dictionary are lines with the same indentation level with (key: value) pair
- ▶Indentation is important



YAML

```
name: First Network Playbook
    connection: network_cli __ Dictionary
     hosts: all <
                                         List
     tasks:
 6
      - name: show version
         ios_command:
           commands: show version
9
                                                   YAML Beginning / End
10
         register: output
                              List
11
12
       - name: show output
13
         debug:
14
           var: output.stdout
15
16
       - name: copy output to file
17
         copy. content="{{ output }}" dest=./output/{{ inventory_hostname }}.txt
18
```



Resources

▶Intro to Playbooks

http://docs.ansible.com/ansible/playbooks_intro.html

►YAML Syntax

http://docs.ansible.com/ansible/YAMLSyntax.html

►Working with Modules

http://docs.ansible.com/ansible/latest/user_guide/modules.html

>YAML Lint

http://www.yamllint.com/



Next: Playbook Examples



Suggestion

Keep in simple, follow a pattern ©

.... at least for now



Playbook

```
Plavbook
     name: First Network Playbook
                                                                      Play
     connection: network_cli
     hosts: all
     tasks:
 6
       - name: show version
                                                                      Task
         ios_command:
           commands: show version
                                               Modules
9
10
11
12
         register: output
       - name: show output
13
14
         debug:
           var: output.stdout
15
16
       - name: copy output to file
17
         copy: content="{{ output }}" dest=./output/{{ inventory_hostname }}.txt
```



YAML

```
name: First Network Playbook
    connection: network_cli __ Dictionary
     hosts: all <
                                         List
     tasks:
 6
      - name: show version
         ios_command:
           commands: show version
9
                                                   YAML Beginning / End
10
         register: output
                              List
11
12
       - name: show output
13
         debug:
14
           var: output.stdout
15
16
       - name: copy output to file
17
         copy. content="{{ output }}" dest=./output/{{ inventory_hostname }}.txt
18
```



OSPF Configuration Workflow

- **Configure Basic OSPF** ▶
- ▶Verifying OSPF Adjacencies
- ▶Verifying the OSPF Database



New in Version 2

"Up and Running" with Network Devices

Save Time + Be More Productive






Prerequisites

▶ (optional) Basic Networking Knowledge



Why Ansible?





Credit: https://www.ansible.com/

Come Join me to save time and be more productive as Network Engineers!



OSPF Configuration Workflow

- **Configure Basic OSPF** ▶
- ▶Verifying OSPF Adjacencies
- ▶Verifying the OSPF Database



- ► When a new LSA is received it is checked against the database for changes such as...
 - Sequence number is used to:
 - track new vs old LSAs
 - Age is used to:
 - Keep information new
 - Withdraw old information
 - Periodic flooding occurs after 30 minutes
 - · "paranoid" update
 - LSAs that reach MaxAge (60 minutes) are withdrawn
 - Checksum
 - Used to avoid transmission & memory corruption



- ▶ When a new LSA is received it is checked against the database for changes such as...
 - Sequence number
 - Age
 - Used to keep information new
 - Withdraw old information
 - Periodic flooding occurs after 30 minutes
 - LSAs that reach MaxAge (60 minutes) are withdrawn
 - Checksum
 - Used to avoid transmission & memory corruption




- ▶ When a new LSA is received it is checked against the database for changes such as...
 - Sequence number
 - Age
 - Used to keep information new and withdraw old information
 - Periodic flooding occurs after 30 minutes
 - LSAs that reach MaxAge (60 minutes) are withdrawn
 - Checksum
 - Used to avoid transmission & memory corruption



- When a new LSA is received it is checked against the database for changes such as...
 - Sequence number
 - Age
 - Checksum





Product/Topology Diagram



Wireshark is used to capture data and display it for review so that you can look through it and attempt to find answers to questions around problems.

