Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev = 0, remainder;
   while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

int main()
{
    int n, rev = 0, remainder;
    int count = 3;

    scanf("%d",&n);

    while(n != 0)
    {
        count++;

        remainder = n % 10;
        count++;

        rev = rev * 10 + remainder;
        count++;

        n = n / 10;
        count++;
    }

    printf("%d", count);

    return 0;
}
```

	Input	Expected	Got	
✔	12	11	11	✔

	Input	Expected	Got	
✔	1234	19	19	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```
#include<stdio.h>

int main()
{
    int n;
    int c = 0;

    scanf("%d",&n);

    int count = 1;
    for(int i=n/2; i<n; i++)
    {
        count++;

        for(int j=1; j<n; j=j*2)
        {
            count++;

            for(int k=1; k<n; k=k*2)
            {
                count++;
                c++;
                count++;
            }

            count++;
        }

        count++;
    }

    count++;

    printf("%d",count);

    return 0;
}
```

	Input	Expected	Got	
✔	4	30	30	✔
✔	10	212	212	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{
   for (i = 1; i <= num;++i)
   {
    if (num % i== 0)
       {
         printf("%d ", i);
       }
    }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```
#include<stdio.h>
int main(){
    int n;
    scanf("%d",&n);
    int c=0;
    c++;
    for(int i=1;i<=n;i++){
        c++;
        if(n%i==0){
            c++;
        }
        c++;
    }
    printf("%d",c);
}
```

	Input	Expected	Got	
✔	12	31	31	✔
✔	25	54	54	✔
✔	4	12	12	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

```
#include<stdio.h>

int main()
{
    int n;
    int count = 0;

    scanf("%d",&n);

    if(n==1)
    {
        printf("*");
    }
    else
    {
        int i,j;

        count += 1;

        for(i=1; i<=n; i++)
        {
            count += 1;
            count += 1;

            for(j=1; j<=n; j++)
            {
                count += 1;

```

```
29                  break;
30              }
31
32              count += 1;
33
34              count += 1;
35          }
36
37          count += 1;
38      }
39
40      printf("%d",count);
41
42      return 0;
43  }
```

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔
✔	143	717	717	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;
    int s =1;
    while(s <= n)
    {
         i++;
         s += i;
     }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n;
    scanf("%d", &n);

    int counter = 0;
    int i = 1;
    int s = 1;

    counter += 2;
    while (1)
    {
        counter++;
        if (!(s <= n))
            break;

        i++;
        counter++;

        s += i;
        counter++;
    }

    printf("%d", counter);

    return 0;
}
```

	Input	Expected	Got	
✔	9	12	12	✔
✔	4	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course