

Citadel Protocol Specification

Dusk Network

May 2, 2023

Contents

1	General Overview	2
1.1	What is Citadel	2
1.2	Document Organization	2
2	Definitions	2
2.1	The Roles Involved	2
2.2	The Elements Involved	2
3	Protocol Workflow	3

1 General Overview

1.1 What is Citadel

A Self-Sovereign Identity (SSI) protocol serves the purpose of allowing users of a given service to manage their identities in a fully transparent manner. In other words, every user can know which information about them is shared with other parties, and accept or deny any request for personal information.

Citadel is a SSI protocol built on top of Dusk Network. Users of a service can get a *license*, which represents their *right* to use such a service. In particular, **Citadel** allows for the following properties:

- **Proof of Ownership:** users can prove ownership of a license that allows them to use a given service.
- **Proof of Validity:** users can prove that a license has not been revoked and hence, it is a valid license.
- **Unlinkability:** activities from the same user in the network cannot be linked to each other by other parties.
- **Decentralized Session Opening:** when users use a license to open a session to use a service, everyone in the network learns that this happened, so it cannot be used again.
- **Attribute Blinding:** users can decide what information they want to share, hiding any other sensitive information and providing only the desired one.

1.2 Document Organization

In Section 2, we define all the object types and entities involved in the protocol. In Section 3, we roll out the protocol with full details.

2 Definitions

2.1 The Roles Involved

- **User:** an entity that interacts with the wallet to request licenses and prove ownership of those.
- **License Provider (LP):** an entity that receives requests for licenses, and upon acceptance, issues them.
- **Service Provider (SP):** the entity that provides a service upon verification that a service request is correct. The SP may be the same as the LP entity or a different one.

2.2 The Elements Involved

- **Request:** a request includes the encryption of a stealth address belonging to the user, where the license has to be sent to, and a symmetric key. The structure is as follows:

Element	Type	Info.
$(\text{rpk}, R_{\text{req}})$	StealthAddress	It is a request stealth address of the LP.
enc	PoseidonCipher[6]	It is the encryption of a license stealth address of the user and a symmetric key.
nonce	BlsScalar	Randomness needed to compute enc.

- **License:** a license is an asset that represents the right of a user to use a given service. The structure is as follows:

Element	Type	Info.
$(\text{lpk}, R_{\text{lic}})$	StealthAddress	It is a license stealth address of the user.
enc	PoseidonCipher[4]	It is the encryption of some user attributes and its signature.
nonce	BlsScalar	Randomness needed to compute enc.
pos	BlsScalar	It is the position of the license in the Merkle tree of licenses.

- **LicenseProverParameters:** a prover needs some auxiliary parameters to compute the proof that proves the ownership of a license. Some of the items of this table are related to the session and session cookie elements. The structure is as follows:

Element	Type	Info.
lpk	JubJubAffine	The license public key of the user.
lpk'	JubJubAffine	A variation of the license public key of the user computed with a different generator.
sig _{lic}	Signature	The signature of the license attributes.
com ₀ ^{hash}	BlsScalar	A hash of the public key of the LP.
com ₁	JubJubExtended	A Pedersen Commitment of the attributes.
com ₂	JubJubExtended	A Pedersen Commitment of the c value.
session_hash	BlsScalar	The hash of the public key of the SP together with some randomness.
sig_session_hash	dusk_schnorr::Proof	The signature of the session hash signed by the user.
merkle_proof	PoseidonBranch	Membership proof of the license in the Merkle tree of licenses.

- **Session:** a session is a public struct known by all the validators. The structure is as follows:

Element	Type	Info.
session_hash	BlsScalar	The hash of the public key of the SP together with some randomness.
session_id	BlsScalar	The id of a session open using a given license.
com ₀ ^{hash}	BlsScalar	A hash of the public key of the LP.
com ₁	JubJubExtended	A Pedersen Commitment of the attributes.
com ₂	JubJubExtended	A Pedersen Commitment of the c value.

- **SessionCookie:** a session cookie is a secret value known only by the user and the SP. It contains a set of openings to a given set of commitments. The structure is as follows:

Element	Type	Info.
pk _{SP}	JubJubAffine	The public key of the SP.
r _{session}	BlsScalar	Randomness for computing the session hash.
session_id	BlsScalar	The id of a session open using a given license.
pk _{LP}	JubJubAffine	The public key of the LP.
attr	JubJubScalar	The attributes of the user.
c	JubJubScalar	The challenge value.
s ₀	JubJubScalar	Randomness used to compute the com ₀ ^{hash} .
s ₁	BlsScalar	Randomness used to compute the com ₁ .
s ₂	BlsScalar	Randomness used to compute the com ₂ .

3 Protocol Workflow

In Citadel, each party involved in the protocol keeps static keys, as we detail now. Let $G, G' \leftarrow \mathbb{J}$ be two generators for the subgroup \mathbb{J} of order t of the Jubjub. The keys of each party as the following.

- *Secret key:* $\text{sk} = (a, b)$, where $a, b \leftarrow \mathbb{F}_t$.
- *Public key:* $\text{pk} = (A, B)$, where $A = aG$ and $B = bG$.

The workflow of the Citadel protocol is depicted in Figure 1, and described with full details as follows.

1. **(user) request_license :** compute a license stealth address $(\text{lpk}, R_{\text{lic}})$ belonging to the user, using the user's own public key, as follows.
 - (a) Sample r uniformly at random from \mathbb{F}_t .
 - (b) Compute a symmetric Diffie–Hellman key $k = rA_{\text{user}}$.
 - (c) Compute a one-time public key $\text{lpk} = H^{\text{BLAKE2b}}(k)G + B_{\text{user}}$.
 - (d) Compute $R_{\text{lic}} = rG$.

Compute also an additional key $k_{\text{lic}} = H^{\text{BLAKE2b}}(\text{lsk})G$, by computing first the license secret key $\text{lsk} = H^{\text{BLAKE2b}}(k) + b_{\text{user}}$. Then, compute the request stealth address $(\text{rpk}, R_{\text{req}})$ using the LP's public key, as follows.




Figure 1: Overview of the protocol messages exchanged between the user, the Dusk Network, and the SP.

- (a) Sample r uniformly at random from \mathbb{F}_t .
- (b) Compute a symmetric Diffie–Hellman key $k_{\text{req}} = rA_{\text{LP}}$.
- (c) Compute a one-time public key $\text{rpk} = H^{\text{BLAKE2b}}(k_{\text{req}})G + B_{\text{LP}}$.
- (d) Compute $R_{\text{req}} = rG$.

And finally send the following request to the network:

$$\text{req} = ((\text{rpk}, R_{\text{req}}), \text{enc}, \text{nonce}),$$

where

$$\text{enc} = \text{Enc}_{k_{\text{req}}}((\text{lpk}, R_{\text{lic}}) || k_{\text{lic}}; \text{nonce}).$$

- 2. **(LP)** `get_license_request` : continuously check the network for incoming license requests, by checking if $\text{rpk} \stackrel{?}{=} H^{\text{BLAKE2b}}(\tilde{k}_{\text{req}})G + B_{\text{LP}}$, where $\tilde{k}_{\text{req}} = a_{\text{LP}}R_{\text{req}}$.
- 3. **(LP)** `issue_license` : upon receiving a request from a user, define a set of attributes `attr` representing the license, and compute a digital signature as follows:

$$\text{sig}_{\text{lic}} = \text{sign_single_key}_{\text{sk}_{\text{SP}}}(\text{lpk}, \text{attr})$$

.

Then, send the following license to the network:

$$\text{lic} = ((\text{lpk}, R_{\text{lic}}), \text{enc}, \text{nonce}, \text{pos}),$$

where

$$\text{enc} = \text{Enc}_{k_{\text{lic}}}(\text{sig}_{\text{lic}} || \text{attr}; \text{nonce}).$$

- 4. **(user)** `get_license` : receive the license by scanning the incoming transactions, and checking if $\text{lpk} \stackrel{?}{=} H^{\text{BLAKE2b}}(\tilde{k}_{\text{lic}})G + B_{\text{user}}$, where $\tilde{k}_{\text{lic}} = H^{\text{BLAKE2b}}(\text{lsk})G$.
- 5. **(user)** `use_license` : when using the license, open a session with a specific SP by executing a call to the license contract. The following steps are performed:

- The user issues a transaction that calls the license contract, which includes a ZKP that is computed out of the gadget depicted in Figure 2.
- The network validators will execute the smart contract, which verifies the proof. Upon success, the following session will be added to a shared list of sessions:

$$\text{session} = \{\text{session_hash}, \text{session_id}, \text{com}_0^{\text{hash}}, \text{com}_1, \text{com}_2\},$$

where $\text{session_hash} = H^{\text{Poseidon}}(\text{pk}_{\text{SP}} || r_{\text{session}})$, and r_{session} is sampled uniformly at random from \mathbb{F}_t .

6. **(user)** `request_service` : request the service to the SP, establishing communication using a secure channel, and providing the session cookie that follows.

$$\text{sc} = \{\text{pk}_{\text{SP}}, r_{\text{session}}, \text{session_id}, \text{pk}_{\text{LP}}, \text{attr}, c, s_0, s_1, s_2\}$$

7. **(SSP)** `get_session` : receive a session from the list of sessions, where $\text{session.session_id} = \text{sc.session_id}$.

8. **(SSP)** `grant_service` : grant or deny the service upon verification of the following steps:

- Check whether the values $(\text{attr}, \text{pk}_{\text{LP}}, c)$ included in the `sc` are correct.
- Check whether the opening $(\text{pk}_{\text{SP}}, r_{\text{session}})$ included in the `sc` matches the `session_hash` found in the session.
- Check whether the openings $((\text{pk}_{\text{LP}}, s_0), (\text{attr}, s_1), (c, s_2))$ included in the `sc` match the commitments $(\text{com}_0^{\text{hash}}, \text{com}_1, \text{com}_2)$ found in the session.




Figure 2: Arithmetic circuit for proving a license's ownership.

Furthermore, the SP might want to prevent the user from using the license more than once (e.g. this is a single-use license, like entering a concert). This is done through the computation of `session_id`. The deployment of this part of the circuit has two different possibilities:

- If we set $c = 0$ (or directly remove this input from the circuit), the license can be used only once.
- If the SP requests the user to set a custom value for c (e.g. the date of an event), the license can be reused only under certain conditions.