

Nov 20, 18 20:33

gpu_matrixMultiply.c

Page 1/3

```

/*
 * Purpose: Demonstrate matrix multiplication in
 * CPU and GPU with global memory and shared memory usage
 * Date and time: 04/09/2014
 *
 * Last modified: Dustin (Ting-Hsuan) Ma
 * Date : November 20, 2018
 * Author: Inanc Senocak
 *
 * to compile blas: nvcc -lcublas -O2 gpu_matrixMultiply.cu -o GPU.exe
 * to execute: ./matrixMult.exe <m> <n> <k>
 */

#include "cublas_v2.h"
#include "timer.h"
#include <math.h>
#include <stdio.h>
#include <stdlib.h>
#include <sys/resource.h>
#include <time.h>

#define BLOCKSIZE 16

typedef double REAL;
typedef int INT;

void printMatrix(REAL *matrix, const int nrow, const int ncol)
{
    int i, j, idx;
    for (j = 0; j < nrow; j++) {
        for (i = 0; i < ncol; i++) {
            idx = i + j * ncol;
            printf("%8.2f", matrix[idx]);
        }
        printf("\n");
    }
    printf("\n");
}

void InitializeMatrices(REAL *a, REAL *b, const int M, const int N, const int K)
{
    int i, j, idx;
    // initialize matrices a & b
    for (j = 0; j < M; j++) {
        for (i = 0; i < N; i++) {
            idx = i + j * N;
            a[idx] = (REAL) idx;
        }
    }
    for (j = 0; j < N; j++) {
        for (i = 0; i < K; i++) {
            idx = i + j * K;
            b[idx] = (REAL) idx;
        }
    }
}

__global__ void matrixMultiplyGPU_gl(REAL *a, REAL *b, REAL *c, const int M, const int N,
const int K)
{
    // Block index
    int bx = blockIdx.x;
    int by = blockIdx.y;

    // Thread index
    int tx = threadIdx.x;
    int ty = threadIdx.y;

    // Row index of matrices a and c
    int row = by * BLOCKSIZE + ty;

    // Column index of matrices a and b
    int col = bx * BLOCKSIZE + tx;

    REAL C_temp = 0.;
    for (int k = 0; k < N; k++)
        C_temp += a[k + row * N] * b[col + k * K];

    c[col + row * K] = C_temp;
}

```

Tuesday November 20, 2018

gpu_matrixMultiply.c

Nov 20, 18 20:33

gpu_matrixMultiply.c

Page 2/3

```

}

int main(INT argc, char *argv[])
{
    if (argc < 3) {
        perror("Command-line usage: executableName <M> <N> <K>");
        exit(1);
    }

    int M = atoi(argv[1]);
    int N = atoi(argv[2]);
    int K = atoi(argv[3]);

    REAL *a_d, *b_d, *c_d, *d_d, *e_d;

    cudaMallocManaged(&a_d, M * N * sizeof(*a_d));
    cudaMallocManaged(&b_d, N * K * sizeof(*b_d));
    cudaMallocManaged(&c_d, M * K * sizeof(*c_d)); // Used for GPU
    cudaMallocManaged(&d_d, M * K * sizeof(*d_d)); // Used for cublasDDOT
    cudaMallocManaged(&e_d, M * K * sizeof(*e_d)); // Used for cublasDAXPY

    InitializeMatrices(a_d, b_d, M, N, K);

    // Setting up GPU enviroment
    dim3 dimBlock(BLOCKSIZE, BLOCKSIZE);
    dim3 dimGrid((K + BLOCKSIZE - 1) / BLOCKSIZE, (M + BLOCKSIZE - 1) / BLOCKSIZE);

    float elapsedTime_gpu, elapsedTime_DDOT, elapsedTime_DAXPY;

    printf("====MultKernel====\n");
    cudaEvent_t timeStart, timeStop; // WARNING!!! use events only to time the device
    cudaEventCreate(&timeStart);
    cudaEventCreate(&timeStop);
    cudaEventRecord(timeStart, 0);

    matrixMultiplyGPU_gl<<<dimGrid, dimBlock>>>(a_d, b_d, c_d, M, N, K);

    cudaDeviceSynchronize();
    cudaEventRecord(timeStop, 0);
    cudaEventSynchronize(timeStop);
    cudaEventElapsedTime(&elapsedTime_gpu, timeStart, timeStop);

    // printMatrix( c_d, M, K );
    printf("C[2]=%3.1f\n", c_d[2]);
    printf("elapsed wall time (GPU) = %5.2f ms\n", elapsedTime_gpu);

    printf("====cublasDDOT====\n");
    cublasHandle_t handle;
    cublasCreate(&handle);

    cudaEventRecord(timeStart, 0);

    for (int i = 0; i < M; i++) {
        for (int j = 0; j < K; j++) {
            cublasDdot(handle, N, a_d + j * N, 1, b_d + i, K, d_d + i + j * K);
        }
    }

    cudaEventRecord(timeStop, 0);
    cudaEventSynchronize(timeStop);
    cudaEventElapsedTime(&elapsedTime_DDOT, timeStart, timeStop);
    // printMatrix( d_d, M, K );
    printf("D[2]=%3.1f\n", d_d[2]);
    printf("elapsed wall time (cublasDDOT) = %5.2f ms\n", elapsedTime_DDOT);

    printf("====cublasDAXPY====\n");
    cudaEventRecord(timeStart, 0);

    for (int j = 0; j < M; j++) {
        for (int i = 0; i < K; i++) {
            cublasDaxpy(handle, M, b_d + j + i * K, a_d + i, N, e_d + j, K);
        }
    }

    cudaEventRecord(timeStop, 0);
    cudaEventSynchronize(timeStop);
    cudaEventElapsedTime(&elapsedTime_DAXPY, timeStart, timeStop);
    // printMatrix( e_d, M, K );
    printf("E[2]=%3.1f\n", e_d[2]);
    printf("elapsed wall time (cublasDAXPY) = %5.2f ms\n", elapsedTime_DAXPY);
    printf("\n");
    cublasDestroy(handle);

    // Deallocating Memory
    cudaFree(a_d);
    cudaFree(b_d);
}

```

1/2

Nov 20, 18 20:33

gpu_matrixMultiply.c

Page 3/3

```
    cudaFree(c_d);  
    cudaFree(d_d);  
    cudaFree(e_d);  
    cudaEventDestroy(timeStart);  
    cudaEventDestroy(timeStop);  
  
    return (EXIT_SUCCESS);  
}
```