

Nov 20, 18 20:33

cpu_matrixMultiply.c

Page 1/2

```

/*
 * Purpose: Demonstrate and time matrix multiplication on the CPU
 *
 * Date and time: 04/09/2014
 * Last modified: 03/16/2016
 * Author: Inanc Senocak
 *
 * to compile: gcc -O2 -lcblas -o CPU.exe cpu_matrixMultiply.c
 * to execute: ./CPU <m> <n> <k>
 */

#include "timer.h"
#include <cblas.h>
#include <math.h>
#include <stdio.h>
#include <stdlib.h>
#include <sys/resource.h>
#include <time.h>

typedef double REAL;

void printMatrix(REAL *matrix, const int nrow, const int ncol)
{
    int i, j, idx;
    for (j = 0; j < nrow; j++) {
        for (i = 0; i < ncol; i++) {
            idx = i + j * ncol;
            printf("%8.2f;", matrix[idx]);
        }
        printf("\n");
    }
    printf("\n");
}

void InitializeMatrices(REAL *a, REAL *b, const int M, const int N, const int K)
{
    int i, j, idx;
    // initialize matrices a & b
    for (j = 0; j < M; j++) {
        for (i = 0; i < K; i++) {
            idx = i + j * K;
            a[idx] = (REAL) idx;
        }
    }
    for (j = 0; j < K; j++) {
        for (i = 0; i < N; i++) {
            idx = i + j * N;
            b[idx] = (REAL) idx;
        }
    }
}

void matrixMultiply(REAL *a, REAL *b, REAL *c, const int M, const int N, const int K)
{
    // this function does the following matrix multiplication c = a * b
    // a(m x k); b(k x n); c(m x n)

    int i, j, idk, idx;
    REAL sum = 0.f;
    // multiply the matrices C=A*B
    for (i = 0; i < M; i++) {
        for (j = 0; j < N; j++) {
            for (idk = 0; idk < K; idk++) {
                sum += a[idk + j * K] * b[i + idk * N];
            }
            c[i + j * N] = sum;
            sum = 0.f;
        }
    }
}

void my_ddot(REAL *A, REAL *B, REAL *C, const int M, const int N, const int K)
{
    int i, j;
    for (j = 0; j < M; j++) {
        for (i = 0; i < N; i++) {
            C[i + j * N] = cblas_ddot(K, A + j * K, 1, B + i, N);
        }
    }
}

double my_daxpy(REAL *A, REAL *B, REAL *C, const int M, const int N, const int K)

```

Nov 20, 18 20:33

cpu_matrixMultiply.c

Page 2/2

```

{
    int i, idk;
    for (i = 0; i < N; i++) {
        for (idk = 0; idk < K; idk++) {
            cblas_daxpy(M, B[i + idk * N], A + idk * K, C + i, N);
        }
    }
}

int main(int argc, char *argv[])
{
    if (argc < 3) {
        perror("Command-line usage: executableName <m> <k> <n>");
        exit(1);
    }

    int M = atof(argv[1]);
    int K = atof(argv[2]);
    int N = atof(argv[3]);

    REAL *a = (REAL *) calloc(M * K, sizeof(*a));
    REAL *b = (REAL *) calloc(K * N, sizeof(*b));

    REAL *c = (REAL *) calloc(M * N, sizeof(*c)); // Used for CPU
    REAL *d = (REAL *) calloc(M * N, sizeof(*d)); // Used for DDOT
    REAL *e = (REAL *) calloc(M * N, sizeof(*e)); // Used for DAXPY

    InitializeMatrices(a, b, M, N, K);

    double startCPU, finishCPU, elapsedTimeCPU;
    GET_TIME(startCPU);
    matrixMultiply(a, b, c, M, N, K);
    GET_TIME(finishCPU);
    elapsedTimeCPU = finishCPU - startCPU;

    printf("====CPU====\n");
    printf("CPU C[2]=%3.1f\n", c[2]);
    // printMatrix(c, M, N);
    printf("elapsed wall time (CPU) = %.6f microseconds\n", elapsedTimeCPU * 1.0e6);
    printf("\n");

    double startDDOT, finishDDOT, elapsedTimeDDOT;
    GET_TIME(startDDOT);
    my_ddot(a, b, d, M, N, K);
    GET_TIME(finishDDOT);
    elapsedTimeDDOT = finishDDOT - startDDOT;

    printf("====DDOT()====\n");
    printf("DDOT d[2]=%3.1f\n", d[2]);
    // printMatrix(d, M, N);
    printf("elapsed wall time (DDOT) = %.6f microseconds\n", elapsedTimeDDOT * 1.0e6);
    printf("\n");

    double startDAXPY, finishDAXPY, elapsedTimeDAXPY;
    GET_TIME(startDAXPY);
    my_daxpy(a, b, e, M, N, K);
    GET_TIME(finishDAXPY);
    elapsedTimeDAXPY = finishDAXPY - startDAXPY;

    printf("====DAXPY()====\n");
    printf("DAXPY e[2]=%3.1f\n", e[2]);
    // printMatrix(e, M, N);
    printf("elapsed wall time (DAXPY) = %.6f microseconds\n", elapsedTimeDAXPY * 1.0e6);
    printf("\n");

    // Deallocating Memory
    free(a);
    a = NULL;
    free(b);
    b = NULL;
    free(c);
    c = NULL;
    free(d);
    d = NULL;
    free(e);
    e = NULL;
    return (EXIT_SUCCESS);
}

```