

Decision Trees

Welcome to machine learning!

Let's play 20 questions

To play on your own, visit [this simple webapp](#)

Classifying with Histograms

Let's imagine that we want to classify observations based on a binary dependent variable, y .

- Two possible outcomes
- We classify each observation based on which outcome is most likely

$$p(y|x) \geq .5 \Rightarrow \hat{y} = 1$$


$$p(y|x) < .5 \Rightarrow \hat{y} = 0$$

Classifying with Histograms


Let's draw some classifiers on the white board.

- Divide the data in half for each of two x variables
- Each separate bin can then be classified separately
- We can increase the granularity of our classifier by adding more breaks to each x variable

Classifying with Histograms



Classifying with Histograms



Classifying with Histograms

Is there a more efficient way?

- Imagine we only divide variables in half
- How many discrete bins of data would exist if we looked at each of 16 variables in this way?

Classifying with Histograms

Is there a more efficient way?

- Imagine we only divide variables in half
- How many discrete bins of data would exist if we looked at each of 16 variables in this way?
 - $2^{16} = 65,536$ possible bins
 - We would then need 65,536 observations at the **minimum** to obtain **any** information about each cell
- This is **not** efficient

Instead, we use Decision Trees

In effect, we will choose the **most useful** bins to explore

But first, we need to learn about entropy...

Entropy is a measure of uncertainty (or information) about the world, or, more specifically, uncertainty about the true value of an outcome in a given model.

Lower entropy: less uncertainty

Higher entropy: greater uncertainty

Measuring Entropy

Entropy can be calculated using the following equation

$$H(x) = - \sum_{i=0}^n p(x_i) \ln p(x_i)$$

This is *Nat* Entropy (Shannon entropy is calculated using \log_2 , and Hartley entropy uses \log_{10} , but it doesn't actually matter which we use so long as we are **consistent**)

Measuring Entropy

1. More possible outcomes leads to higher entropy
2. Greater uncertainty among outcomes leads to higher entropy

The goal of all of our predictive measures will be to reduce entropy (or maximize information gain) at each step in our model

Remember: information gain should be relative to the universe, not our sample

Exercise

Write a function to estimate the Nat Entropy of a set of outcomes, given the observed probability for each outcome in an arbitrary set. Use your function to answer:

1. If the probability of 5 outcomes are .2, .3, .1, .1, and .3, then what is the entropy of the system?
2. If the probability of each of 5 outcomes is .2, then what is the entropy of the system?
3. If the probability of each of 10 outcomes is .1, then what is the entropy of the system?

Exercise Answer

```
import numpy as np

def natEnt(listP):
    entropy = 0
    n = len(listP)
    for i in range(n):
        entropy += listP[i] * np.log(listP[i])
    entropy *= -1
    return entropy

print(natEnt([.2,.3,.1,.1,.3]))
print(natEnt([.2]*5))
print(natEnt([.1]*10))
```

Using Entropy

We need to determine how we can reduce the entropy of our system by dividing data.

1. Choose the most informative Variable
2. Choose how to best divide the selected variable in order to gain information
3. Repeat until we reach a stopping point
 - We need to predetermine a stopping rule

Using Entropy

In order to choose the most informative variable, we need to first determine how informative each variable is

- Search across each variable for the optimal decision point
- Determine the information gain from that variable and decision point
- Compare the information gain across the available variables

Information Gain

We can define information gain from a binary split of our data as follows:

$$IG = H_0(x) - H_1(x)$$

Where H_0 is the original entropy, and H_1 is the entropy after the split.

Information Gain

We can calculate H_1 as

$$H_1(x) = \omega_1 \cdot H_{11}(x) + \omega_2 \cdot H_{12}(x)$$

- ω_1 and ω_2 : the fraction of elements in each respective child node relative to the parent node (should add up to 1)
- H_{11} and H_{12} : the entropy of each child node

Implementing a Decision Tree

We will be using the `sklearn` library today. It is the most robust machine learning library available, and allows us to implement many kinds of tests and algorithms. [Click here for sci-kit learn documentation.](#)

Fitting Data with Sci-kit Learn

```
# Our import statements for this problem
import pandas as pd
import numpy as np
import patsy as pt

from sklearn.tree import DecisionTreeClassifier
from sklearn.metrics import accuracy_score
from sklearn.model_selection import train_test_split
```

Fitting Data with Sci-kit Learn

```
# The code to implement a decision tree
data = pd.read_csv(
    "https://github.com/dustywhite7/Econ8310/"
    + "raw/master/DataSets/titanic.csv")

model = DecisionTreeClassifier()

# As usual, Patsy makes data prep easier
y, x = pt.dmatrices("Survived ~ -1 + Sex + Age
                    + SibSp + Pclass", data=data)

x, xt, y, yt = train_test_split(x, y,
                                test_size=0.33, random_state=42)

res = model.fit(x,y)

print("\n\nIn-sample accuracy: %s%%\n\n"
      % str(round(100*accuracy_score(y, model.predict(x)), 2)))
```


How does it do?

Using the Titanic dataset, and predicting survival with sex, age, siblings, and class (how fancy the passenger was traveling) results in the following printout:

In-sample accuracy: 94.35%


For being easy to implement, that is a pretty good prediction!

Visualizing the Model



Didn't you say that this would be **human** interpretable?

Bias and Variance



Bias and Variance

Bias: When we predict using a model, the bias is the difference between our predicted outcome and the true outcome

Variance: When we predict one observation using various models, the variance is the dispersion of outcomes for that single observation

- Do all models tend to say the same thing? That would indicate low variance

Bias and Variance

Typically, both bias and variance can be reduced by training models on a larger data set[†]. This is unsurprising, since more information about an outcome should enable us to make better decisions regarding that outcome

- These models are designed to converge on truth
- Assuming that we have **representative** data

[†] *This is why everyone wants to get your data online*

Bias and Variance

While more data is better for both, bias and variance are opposites when it comes to model complexity

- Bias declines as complexity increases
- Variance increases as complexity increases

Our job is to identify the sweet spot where the **combined** error is lowest

Overfitting

Overfitting is when we allow our model to overemphasize the random variation between observations in our sample. This practice will lead to higher in-sample accuracy (frequently we will even achieve 100% accuracy in-sample!), but reduce our accuracy out of sample.

Underfitting

Underfitting is when we fail to take advantage of available information, and induce higher errors both in- and out-of-sample

- If we don't make use of our data, then we can't make quality decisions

Overfitting in Decision Trees

Remember our crazy decision tree? If we want a model to be readable for a human, we should probably try to keep the model simpler. This will also improve out-of-sample accuracy.

```
print("\n\nIn-sample accuracy: %s%%\n\n"  
      % str(round(100*accuracy_score(y, model.predict(x)), 2)))  
print("\n\nOut-of-sample accuracy: %s%%\n\n"  
      %str(round(100*accuracy_score(yt, model.predict(xt)), 2)))
```

In-sample accuracy: 94.35%

Out-of-sample accuracy: 75.85%

Performance is much worse out of sample

Overfitting Decision Trees

Let's restrict our tree to only 5 levels, and see what happens. We only need to modify one line of our code:


```
model = DecisionTreeClassifier(max_depth=5)
```

In-sample accuracy: 86.82%

Out-of-sample accuracy: 77.12%

By simplifying, we actually do **better** out of sample, even though training accuracy suffers!

The Tree



Overfitting Decision Trees

Let's make one more change, and restrict our tree to leaves with 10 or more observations:


```
model = DecisionTreeClassifier(max_depth=5,  
                               min_samples_leaf=10)
```

In-sample accuracy: 84.52%

Out-of-sample accuracy: 78.39%

Again, we simplify and do **better** out of sample!

The Tree



It's small on the slide, but it is now a reasonably readable algorithm. At most, you have to ask 5 questions to arrive at an answer.

Lab time!