2022 부트캠프 048

- React: Local Env Set-up / creat-react-app

!Tips & Links

※ 강의

https://www.udemy.com/course/the-complete-web-development-bootcamp/

실습) calculator 함수묶음 불러오기 JSX import & Export	① 함수명 export / name matches // 하나하나 골라 쓰기
	calc.jsx export { add, subtract, multiply, divide } index.js import {add, subtract, multiply, divide} from "./calc" {add(1, 2)}
	② * as 이름으로 import / dictionary 이름 지정 // 와일드카드 import
	calc.jsx export {add, subtract, multiply, divide} index.js import * as Calc from "./calc" <[Calc.add(1, 2)]
	③ default object로 export / default export를 import // default 내보내기
	calc.jsx export default [add, subtract, multiply, divide] index.js import Calc from "./calc" < i> Calc.add(1, 2)]

※ *React App 시작하기* : Create React App ~ npm start

- ① Node -v 확인(latest LTS: Long Term Support) // nvm list available > nvm install 버전
- ② VSC사용, VSC Extension: sublime babel, vscode-icons 익스텐션 설치!
- ③ Create new React App https://ko.reactjs.org/docs/create-a-new-react-app.html

```
● npx create-react-app 앱이름 cd 앱이름 npm start create React app! npx? ☞ package runner tool that comes with npm. cd over to the location + npm start
```

⑤ index.html, index.js 뼈대만 남기고 삭제 ~> 연습 시작

```
index.js
                                                                                index.html
                                                            <!DOCTYPE html>
import React from 'react';
                                                            <html lang="en">
import ReactDOM from 'react-dom/client';
                                                               <head>
                                                                 <meta charset="utf-8" />
import App from "./App"
                                                                 <title>React App</title>
const root =
                                                               </head>
React DOM. create Root (document.get Element By Id ('root')); \\
                                                               <body>
                                                                 <script src="./src/index.js"></script>
root.render(
  <App />
                                                                 <div id="root"></div>
                                                               </body>
);
                                                             </html>
```

- ※ CodeSandbox에서 Local로 복사/ Export to zip > 압축풀기 > cd over to dir > npm install > npm start
- ※ "App.jsx" is a point of contention / AirBnB style guide에서 recommend, ~for Atlassian, Bitbucket etc...