

Best website for interview preparation: [www.prodevelopertutorial.com](http://www.prodevelopertutorial.com)

## TCS 'c'

1.The C language terminator is

- a.semicolon b.colon c.period d.exclamation mark

2.What is false about the following ' A compound statement is '

a.A set of simple statments b.Demarcated on either side by curly brackets c.Can be used in place of simple statement

- d.A C function is not a compound statement.

3.What is true about the following ' C Functions'

- a.Need not return any value b.Should always return an integer c.Should always return a float  
d.Should always return more than one value.

4.Main must be written as

- a.the first function in the program b.Second function in the program c.Last function in the program  
d.any where in the program

5.Which of the following about automatic variables within a function is correct ?

- a.its type must be declared before using the variable b.they are local c.they are not initialised to zero  
d.they are global.

6.Write one statement equalent to the following two statements

```
x=sqr(a);
```

```
return(x);
```

- a.return(sqr(a)); b.printf("sqr(a)"); c.return(a\*a\*a); d.printf("%d",sqr(a));

7.Which of the following about the C comments is incorrect ?

- a.commentscan go over multiple lines b.comments can start any where in the line  
c.a line can contain comments with out any language statements d.comments can occur within comments

8.What is the value of y in the following code?

```
x=7;y=0;
```

```
if(x=6)
```

[Buy top competitive programming and coding question book to clear interview. 100+ solved questions](#)  
[Buy top data structure and algorithm book to clear interview. 90+ Chapters](#)  
[Join telegram channel for placement materials](#)

Best website for interview preparation: [www.prodevelopertutorial.com](http://www.prodevelopertutorial.com)

```
y=7;
```

```
else
```

```
y=1;
```

a.7      b.0      c.1      d.6

9.Read the function conv() given below

```
conv(int t)
```

```
{
```

```
int u;
```

```
u=5/9 * (t-32);
```

```
return(u0;
```

```
}
```

What

a.15      b.0      c.16.1      d.29

10.which of the following represents true statement either x is in the range of 10 and 50 or y is zero

a. $x \geq 10 \ \&\& \ x \leq 50 \ || \ y == 0;$       b.      c.      d.

11.Which of the following is not an infinite loop ?

a.while(1){

```
....
```

```
}
```

b.for(;;){

```
...
```

```
}
```

c.x=0;

```
do{
```

```
/*x unaltered within the loop*/
```

[Buy top competitive programming and coding question book to clear interview. 100+ solved questions](#)  
[Buy top data structure and algorithm book to clear interview. 90+ Chapters](#)  
[Join telegram channel for placement materials](#)

Best website for interview preparation: [www.prodevelopertutorial.com](http://www.prodevelopertutorial.com)

```
...
}while(x==0);

d.# define TRUE 0

...

while(TRUE){

....

}
```

12.what does the following function print?

```
func(int i)
{
if(i%2)return 0;
eale return 1;
}

main()
{
int =3;
i=func(i);
i=func(i);
printf("%d",i);}

a.3    b.1    c.0    d.2
```

13.how does the C compiler interpret the following two statements

```
p=p+x;
q=q+y;
```

a.p=p+x;q=q+y

b.p=p+xq=q+y

c.p=p+xq;q=q+y

d.p=p+x/q=q+y

For questions 14,15,16,17 use the following alternatives

[Buy top competitive programming and coding question book to clear interview. 100+ solved questions](#)  
[Buy top data structure and algorithm book to clear interview. 90+ Chapters](#)  
[Join telegram channel for placement materials](#)

Best website for interview preparation: [www.prodevelopertutorial.com](http://www.prodevelopertutorial.com)

a.int

b.char

c.string

d.float

14.'9'

15."1 e 02"

16.10e05

17. 15

18.read the following code

```
# define MAX 100
```

```
# define MIN 100
```

```
....
```

```
....
```

```
if(x>MAX)
```

```
    x=1;
```

```
else if(x<MIN)
```

```
    x=-1;
```

```
    x=50;
```

if the initial value of x=200,what is the vlaue after executing this code?

a.200   b.1   c.-1   d.50

19.a memory of 20 bytes is allocated to a string declared as char \*s

then the following two statements are executed:

```
s="Etrance"
```

```
l=strlen(s);
```

what is the value of l ?

[Buy top competitive programming and coding question book to clear interview. 100+ solved questions](#)  
[Buy top data structure and algorithm book to clear interview. 90+ Chapters](#)  
[Join telegram channel for placement materials](#)

Best website for interview preparation: [www.prodevelopertutorial.com](http://www.prodevelopertutorial.com)

a.20    b.8    c.9    d.21

20.given the piece of code

```
int a[50];
```

```
int *pa;
```

```
pa=a;
```

to access the 6th element of the array which of the following is incorrect?

a. \*(a+5)

b.a[5]

c.pa[5]

d.>(\*pa + 5)

21.consider the following structure:

```
struct num nam{
```

```
    int no;
```

```
    char name[25];
```

```
};
```

```
struct num nam n1[]={12,"Fred"},{15,"Martin"},{8,"Peter"},{11,Nicholas}};
```

```
.....
```

```
.....
```

```
printf("%d%d",n1[2],no,(*(n1 + 2),no) + 1);
```

What does the above statement print?

a.8,9    b.9,9    c.8,8    d.8,unpredictable value

22.identify the in correct expression

a.a=b=3=4;    b.a=b=c=d=0;

float a=int b=3.5;

d.int a;

[Buy top competitive programming and coding question book to clear interview. 100+ solved questions](#)  
[Buy top data structure and algorithm book to clear interview. 90+ Chapters](#)  
[Join telegram channel for placement materials](#)

Best website for interview preparation: [www.prodevelopertutorial.com](http://www.prodevelopertutorial.com)

```
float b;
```

```
a=b=3.5;
```

23.regarding the scope of the variables;identify the incorrect statement:

a.automatic variables are automatically initialised to 0   b.static variables are are automatically initialised to 0

c.the address of a register variable is not accessiable   d.static variables cannot be initialised with any expression

24.cond 1?cond 2?cond 3?:exp 1:exp 2:exp 3:exp 4; is equivalent to which of the following?

a.if cond 1

```
exp 1;
```

```
else if cond 2
```

```
exp 2;
```

```
else if cond 3
```

```
exp 3;
```

```
else
```

```
exp 4;
```

b.if cond 1

```
if cond 2
```

```
if cond 3
```

```
exp 1;
```

```
else
```

```
exp 2;
```

```
else
```

```
exp 3;
```

```
else
```

```
exp 4;
```

[Buy top competitive programming and coding question book to clear interview. 100+ solved questions](#)  
[Buy top data structure and algorithm book to clear interview. 90+ Chapters](#)  
[Join telegram channel for placement materials](#)

Best website for interview preparation: [www.prodevelopertutorial.com](http://www.prodevelopertutorial.com)

c.if cond 1 && cond 2 && cond 3

exp 1 | exp 2 | exp 3 | exp 4;

d.if cond 3

exp 1;

else if cond 2

exp 2;

else if cond 3

exp 3;

else

exp 4;

25.the operator for exponencation is

a.\*\* b.^ c.% d.not available

26.which of the following is invalid

a.a+=b b.a\*=b c.a>=b d.a\*\*=b

27.what is y value of the code if input x=10

y=5;

if (x==10)

else if(x==9)

elae y=8;

a.9 b.8 c.6 d.7

28.what does the following code do?

fn(int n,int p,int r)

{

static int a=p;

switch(n){

[Buy top competitive programming and coding question book to clear interview. 100+ solved questions](#)  
[Buy top data structure and algorithm book to clear interview. 90+ Chapters](#)  
[Join telegram channel for placement materials](#)

Best website for interview preparation: [www.prodevelopertutorial.com](http://www.prodevelopertutorial.com)

```
case 4:a+=a*r;  
case 3:a+=a*r;  
case 2:a+=a*r;  
case 1:a+=a*r;  
}  
}
```

- a.computes simple interest for one year  
1 to 4 years
- b.computes amount on compound interest for  
1 to 4 years
- c.computes simple interest for four year
- d.computes compound interest for 1 year

29.a=0;

```
while(a<5)
```

```
printf("%d\n",a++);
```

how many times does the loop occurs?

- a.infinite      b.5      c.4      d.6

30.how many times does the loop iterated ?

```
for (i=0;i=10;i+=2)
```

```
printf("Hi\n");
```

- a.10      b.2      c.5      d.....

31.what is incorrect among the following

A recursive function

- a.calls itself      b.is equivalent to a loop      c.has a termination condition      d.does not  
have a return value at all

32.which of the following go out of the loop if expn 2 becoming false

- a.while(expn 1){...if(expn 2)continue;}      b.while(!expn 1){if(expn 2)continue;...}  
c.do{..if(expn 1)continue;..}while(expn 2);      d.while(!expn 2){if(expn 1)continue;..}

33.consider the following program

[Buy top competitive programming and coding question book to clear interview. 100+ solved questions](#)  
[Buy top data structure and algorithm book to clear interview. 90+ Chapters](#)  
[Join telegram channel for placement materials](#)



Best website for interview preparation: [www.prodevelopertutorial.com](http://www.prodevelopertutorial.com)

```
main()
{
    unsigned int i=10;
    while(i>=0){
        printf("%u",i)
        i--;
    }
}
```

how many times the loop wxecuted

a.10    b.9    c.11    d.infinite

34.pick out the add one out

a.malloc()    b.calloc()    c.free()    d.realloc()

35.consider the following program

```
main()
{
    int a[5]={1,3,6,7,0};
    int *b;
    b=&a[2];
}
```

the value of b[-1] is

a.1    b.3    c.-6    d.none

36.# define prod(a,b)=a\*b

```
main()
{
    int x=2;
    int y=3;
```

[Buy top competitive programming and coding question book to clear interview. 100+ solved questions](#)  
[Buy top data structure and algorithm book to clear interview. 90+ Chapters](#)  
[Join telegram channel for placement materials](#)

Best website for interview preparation: [www.prodevelopertutorial.com](http://www.prodevelopertutorial.com)

```
printf("%d",prod(x+2,y-10)); }
```

the output of the program is

a.8      b.6      c.7      d.none

37.consider the following program sigment

```
int n,sum=1;

switch(n) {

case 2:sum=sum+2;

case 3:sum*=2;

        break;

default:sum=0;}
```

if n=2, what is the value of sum

a.0      b.6      c.3      d.none

38.identify the incorrect one

1.if(c=1)      2.if(c!=3)      3.if(a<b)then      4.if(c==1)

a.1 only      b.1&3      c.3 only      d.all

39.teh format specified for hexa decimal is

a.%d      b.%o      c.%x      d.%u

40.find the output of the following program

```
main()

{

int x=5, *p;

p=&x;

printf("%d",++*p);

}
```

[Buy top competitive programming and coding question book to clear interview. 100+ solved questions](#)  
[Buy top data structure and algorithm book to clear interview. 90+ Chapters](#)  
[Join telegram channel for placement materials](#)

Best website for interview preparation: [www.prodevelopertutorial.com](http://www.prodevelopertutorial.com)

a.5      b.6      c.0      d.none

41.consider the following C code

```
main()
{
    int i=3,x;
    while(i>0)
    {
        x=func(i);
        i--;
    }
    int func(int n)
    {
        static sum=0;
        sum=sum+n;
        return(sum);
    }
```

the final value of x is

a.6      b.8      c.1      d.3

43.int \*a[5] refers to

a.array of pointers      b.pointer to an array      c.pointerto a pointer      d.....

46.which of the following statements is incorrect

```
a.typedef struct new{
    int n1;
    char n2;
} DATA;
```

[Buy top competitive programming and coding question book to clear interview. 100+ solved questions](#)  
[Buy top data structure and algorithm book to clear interview. 90+ Chapters](#)  
[Join telegram channel for placement materials](#)

Best website for interview preparation: [www.prodevelopertutorial.com](http://www.prodevelopertutorial.com)

b.typedef struct {

int n3;

char \*n4;

}ICE;

c.typedef union {

int n5;

float n6;

} UDT;

d.#typedef union {

int n7;

float n8;

} TUDAT;

ANSWERS:

1-5 D,C,D,C,C 6-10 D,C,C,A,D 11-15 D,C,A,A,A 16-20 B,C,D,C,A 21-25 C,D,B,D,A 26-30 C,B,B,A,D  
31-35 B,C,C,C,B

36-40 A,B,A,B,B 41-45 A,D,D,D,A 46-50 B,C,C,A,A