

Sample Paper

1. Write sequence in which nodes of the graph (Fig. 5) have been traversed using DFS and BFS, starting at vertex . To make a unique solution, assume that whenever you faced with a decision of which node to pick from a set of nodes, pick the node whose label occurs earliest in the alphabet.

Topic: GRAPHS

Difficulty: 3

2. Let each node in a binary search tree keeps an attribute that points to inorder successor. Give a pseudocode for INSERT on a binary search tree using this representation.

Topic: BST

Difficulty: 5

3. Find a pair with the given sum in an array

Topic: SORTING

Difficulty: 5

4. WAP to Construct the longest palindrome by shuffling or deleting characters from a string

Topic: HASHING

Difficulty: 9

5. You are given N identical eggs and you have access to a K -floored building from 1 to K . There exists a floor f where $0 \leq f \leq K$ such that any egg dropped at a floor higher than f will break, and any egg dropped at or below floor f will not break. There are few rules given below. An egg that survives a fall can be used again. A broken egg must be discarded. The effect of a fall is the same for all eggs. If the egg doesn't break at a certain floor, it will not break at any floor below. If the eggs breaks at a certain floor, it will break at any floor above. Return the minimum number of moves that you need to determine with certainty what the value of f is.

Topic: DP

Difficulty: 9

6. Execute the algorithm given in Fig. 5 on an array $A[1..15] = [0, 70, 74, 52, 86, 84, 62, 90, 56, 91, (10) 75, 94, 89, 58, 78, 88]$. Write the final contents of an array $A[]$ and stack $S1$. //Q1 and Q2 are empty Queues, S1 and S2 are empty Stacks, an Integer i is initialized to 1, j is an //Integer, and flag is a Boolean.

```

Build_Min_Heap(A);
17. if (A.heap_size)
18. { Q1.enqueue(A[i]);
19. while (!Q1.empty() || !Q2.empty())
20. { flag = !true;
21. while (!Q1.empty())
22. S2.push(A[Right(i)]); } Q1.dequeue(); } flag = true; while (!Q2.empty()) { i++;
23. if(!flag)
24. { S1.push(Q1.front());
25. if(!S2.empty())
26. S1.push(S2.top());
27. flag = !flag ? !flag : flag; }
28. if (Left(i) <= A.heap_size)
29. Q2.enqueue(A[Left(i)]);
30. if (Right(i) <= A.heap_size)
31. { Q2.enqueue(A[Right(i)]);
32. { i++; if(flag) { S1.push(Q2.front());
S1.push(S2.top()); flag = !flag ? !flag : !flag; } if (Left(i) <= A.heap_size)
Q1.enqueue(A[Left(i)]); if (Right(i) <= A.heap_size) { Q1.enqueue(A[Right(i)]);
S2.push(A[Right(i)]); } Q2.dequeue(); } } }

```

Topic: HEAP

Difficulty: 9

7. N Queens Problem

Topic: BACKTRACKING

Difficulty: 9

8. How to find a median of two sorted arrays?

Topic: ARRAY

Difficulty: 9

9. How do you find the distance between two nodes in a binary tree?

Topic: TREE

Difficulty: 9

10. Is this optimization problem on a bipartite graph NP-9?

Topic: P and NP

Difficulty: 9