



# Android Google Services

Ngu Phuc Huy



# Agenda

- Introduction to Google services
- Google Map service on Android
- Assignment
- Q&A

# Course Audience and Prerequisite

- The course is for programmers who are interested in Android development.
- The following are prerequisites to this course:
  - Java and OOP
  - Google services
  - Android programming basic

# Assessment Disciplines

- Class Participation: 40%
- Assignment: 60%
- Final Exam: 0%
- Passing Scores: 70%

# Course Administration

In order to complete the course you must:

- Sign in the Class Attendance List
- Participate in the course
- Provide your feedback in the End of Course Evaluation



# Google Services

Introduction to Google services

# Google services

Give your apps more features to attract users on a wider range of devices.

- Google Maps
- Google Cloud Messaging
- Google Analytic
- Google adMobs Ads
- Google Play In-app billing



# How Google service works on devices

- Google Play services client library
  - contains the interfaces to the individual Google services
  - allows you to obtain authorization from users to gain access to these services with their credentials.
- The Google Play services APK
  - contains the individual Google services and runs as a background service in the Android OS
  - is delivered through the Google Play Store





# Google Maps

- Embed maps to an activity as a fragment
- Customize the map
  - Add marker
  - Draw polylines and polygons
- Control user's view
  - Control the rotation, pan, view, etc



# Google Cloud Messaging (GCM)

GCM allows you to send data from your server to your Android devices and vice versa:

- Send data from server to Android devices
- Send “Send-sync-messages”
- Send messages with payload



# Google Analytic

Allow developers to collect user engagement data from their apps

- The number of active users are using their applications.
- From where in the world the application is being used.
- Adoption and usage of specific features.
- In-app purchases and transactions.
- The number and type of application crashes.





# Google Map service on Android


Deliver Google Map service to Android device

# Prerequisites

- ADT Bundle (Android SDK, Eclipse, SDK Manager)
- Google API service SDK
- Google Play service framework
- Google API key


# Setting up environment

- Deploy ADT Bundle
- Install Google Play Services from SDK Manager
- Import project library to WorkSpace
- Set GooglePlay service library as an Android library
- Obtain the API key from Google service




# Install Google Play service API

- Launch SDK Manager
- Select Extra->Google Play services



# Install Google Play service API


The service library locates at Android SDK-> extras->google->google-play-services







# Import library project into workspace

Click File->Import, select Android->Existing Android code into Workspace




# Set GooglePlay library as Android library

Right click and choose google-play-services\_lib->Property->Android



# Add the library to app project

Project name ->property->android




# Obtain API key from Google service

- Google provide separate Maps API keys for debug keystore and release keystore.
- Retrieve information about app certificate
- Register a project in Google APIs Console and add Maps API as a service request
- Generate the key

# Certificate Info & SHA1 Fingerprint

Locate Keystore: Go to Preferences-> Android-> Build



# Get SHA1 Fingerprint

Open cmd and use the keytool to access debug keyStore and create SHA1

```
C:\>cd C:\Program Files (x86)\Java\jre6\bin


C:\Program Files (x86)\Java\jre6\bin>keytool -list -v -keystore C:\Users\hngu3\.\
android\debug.keystore -alias androiddebugkey -storepass android -keypass androi
d
Alias name: androiddebugkey
Creation date: Jun 22, 2013
Entry type: PrivateKeyEntry
Certificate chain length: 1
Certificate[1]:
Owner: CN=Android Debug, O=Android, C=US
Issuer: CN=Android Debug, O=Android, C=US
Serial number: 51c5881c
Valid from: Sat Jun 22 18:18:52 ICT 2013 until: Mon Jun 15 18:18:52 ICT 2043
Certificate fingerprints:
    MD5:  C7:B1:AA:60:35:CF:41:D6:24:40:DE:02:EE:55:38:EE
    SHA1: 6F:A0:57:B4:29:57:2B:09:90:EF:A7:D7:16:12:36:1A:03:AE:F6:68
    Signature algorithm name: SHA1withRSA
    Version: 3
```

# Creating Google API project

- Navigate to Google API Console and Login with Gmail ID.  
<https://code.google.com/apis/console/>
- Enable Google Android Map V2 from the service list
- Create new Android key

# Creating Google API project

Navigate to Google API Concole <https://code.google.com/apis/console/> and Login with Gmail ID.



Google apis

API Project ▼

- Overview
- Services
- Team
- API Access

## API Access

To prevent abuse, Google places limits on API requests. Using a valid OAuth token or API key allows you to exceed anonymous limits.

### Authorized API Access

OAuth 2.0 allows users to share specific data with you (for example, contact lists) while keeping their usernames, passwords, and other information private. A single project may contain up to 20 client IDs. [Learn more](#)

[Create an OAuth 2.0 client ID...](#)

























### Notification Endpoints

Use notification endpoints to identify domains that may receive webhook notifications from your API. [Learn more](#)



# Create Google API project

## Enable Google Android Map V2 from the service list

 Google Cloud Storage JSON API		<input type="checkbox"/> OFF	
 Google Compute Engine		<a href="#">Request access...</a>	<a href="#">Pricing</a>
 Google Contacts CardDAV API		<input type="checkbox"/> OFF	Courtesy limit: 10,000 requests/day
 Google Maps Android API v2		<input type="checkbox"/> OFF	
 Google Maps API v2		<input type="checkbox"/> OFF	Courtesy limit: 25,000 requests/day • <a href="#">Pricing</a>
 Google Maps API v3		<input type="checkbox"/> OFF	Courtesy limit: 25,000 requests/day • <a href="#">Pricing</a>
 Google Maps Coordinate API		<input type="checkbox"/> OFF	Courtesy limit: 1,000 requests/day
 Google Maps Engine API		<input type="checkbox"/> OFF	Courtesy limit: 10,000 requests/day
 Google Maps Geolocation API		<input type="checkbox"/> OFF	Courtesy limit: 0 requests/day • <a href="#">Pricing</a>
 Google Maps SDK for iOS		<input type="checkbox"/> OFF	
 Google Maps Tracks API		<input type="checkbox"/> OFF	
 Google Play Android Developer API		<input type="checkbox"/> OFF	Courtesy limit: 15,000 requests/day

# Create Google API project

## Enable Google Android Map V2 from the service list



### Google Maps/Google Earth APIs Terms of Service

Last Updated: May 10, 2013

#### 1. Your relationship with Google.

1.1 Use of the Service is Subject to these Terms. Your use of any of the Google Maps/Google Earth APIs (referred to in this document as the "**Maps API(s)**" or the "**Service**") is subject to the terms of a legal agreement between you and Google (the "**Terms**"). "Google" means either (a) Google Ireland Limited, with offices at Gordon House, Barrow Street, Dublin 4, Ireland, if Customer's billing address is in any country within Europe, the Middle East, or Africa ("**EMEA**"); (b) Google Asia Pacific Pte. Ltd., with offices at 8 Marina View Asia Square 1 #30-01 Singapore 018960, if Customer's billing address is in any country within the Asia Pacific region ("**APAC**"); or (c) Google Inc., with offices at 1600 Amphitheatre Parkway, Mountain View, California 94043, USA, if Customer's billing address is in any country in the world other than those in EMEA and APAC.

1.2 The Terms include Google's Legal Notices and Privacy Policy.

- (a) Unless otherwise agreed in writing with Google, the Terms will include the following:
- (i) the terms and conditions set forth in this document (the "**Maps APIs Terms**");
  - (ii) the [Legal Notices](#); and
  - (iii) the [Privacy Policy](#).

☒ I agree to these terms.

Accept Decline



# Generate the API key

Create new Android key:  
SHA1 key; android package

## Simple API Access

Use API keys to identify your project when you do not need to access user data. [Learn more](#)

### Key for browser apps (with referers)

API key: AIzaSyC0MrRdu3CcRGuIy8ZguU68gW-mgL1b97w

Referers: Any referer allowed

Activated on: Jun 22, 2013 4:52 AM

Activated by: phuchuy86@gmail.com – **you**

Create new Server key...

Create new Browser key...

Create new Android key...

Create new iOS key...

## Configure Android Key for API Project

**This key can be deployed in your Android applications.**

API requests are sent directly to Google from your clients' Android devices. Google verifies that each request originates from an Android application that matches one of the certificate SHA1 fingerprints and package names listed below. You can discover the SHA1 fingerprint of your developer certificate using the following command:

```
keytool -list -v -keystore mystore.keystore Learn more
```

**Accept requests from an Android application with one of the certificate fingerprints and package names listed below:**

```
6F:A0:57:B4:29:57:2B:09:90:EF:A7:D7:16:12:36:1A:03:AE:F6:68;com.android.  
map
```

One SHA1 certificate fingerprint and package name (separated by a semicolon) per line. Example:  
45:B5:E4:6F:36:AD:0A:98:94:B4:02:66:2B:12:17:F2:56:26:A0:E0;com.example

Create

Cancel

# Generate the API key

Navigate to homepage of Google Service project

## Key for Android apps (with certificates)

API key: AIzaSyAx2uVg-1cibGhsyFblQb1\_6H0C5-SxOJA

Android apps: 6F:A0:57:B4:29:57:2B:09:90:EF:A7:D7:16:12:36:1A:03:AE:F6:68;com.android.map

Activated on: Jun 23, 2013 9:25 PM

Activated by: phuchuy86@gmail.com – you

# Android app configuration

- Adding API key to Android app
- Adding necessary permissions to Android app

# Adding key to Android app

Insert the API key into <meta-data> of Android manifest file

```
<meta-data  
    android:name="com.google.android.maps.v2.API_KEY"  
    android:value="your_apikey" />
```

# Adding permission to Android app

```
<uses-permission android:name="android.permission.INTERNET" />
<uses-permission android:name="android.permission.ACCESS_NETWORK_STATE"/>
<uses-permission android:name="android.permission.WRITE_EXTERNAL_STORAGE" />
<uses-permission android:name="com.google.android.providers.gsf.permission.READ_GSERVICES" />
<uses-permission android:name="android.permission.ACCESS_COARSE_LOCATION" />
<uses-permission android:name="android.permission.ACCESS_FINE_LOCATION" />
```

Name	Description
Internet	Download map tiles from Google Map server
Access_Network_State	Check connection status
Write_External_Storage	Allow to cache map data into external storage
Read_GServices	Access Google Web-based services
Access_Coarse_Location	Allow to use Wifi or mobile cell data to find location
Access_Fine_Location	Allow to use GPS to find location

# Adding Map to Android app

Use **Fragment** class to provide access to Google map

- Act as container for a map
- Multiple fragments in a single activities
- Android API 12 or upper

```
<fragment
    android:id="@+id/map"
    android:name="com.google.android.gms.maps.MapFragment"
    android:layout_width="match_parent"
    android:layout_height="match_parent" />
```





# Adding Map to Android app

```
public class MainActivity extends Activity {  
  
    private GoogleMap gmap;  
    @Override  
    protected void onCreate(Bundle savedInstanceState) {  
        super.onCreate(savedInstanceState);  
        setContentView(R.layout.activity_main);  
        gmap = ((MapFragment) getSupportFragmentManager().findFragmentById(R.id.map)).getMap();  
        gmap.setMapType(GoogleMap.MAP_TYPE_HYBRID);  
    }  
}
```

Set the Map type: Hybrid, Normal,  
Terrain

# Adding Map to Android app



# Adding Map to Android app

```
import android.app.Activity;

public class MainActivity extends Activity {

    private GoogleMap gmap;
    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);
        gmap = ((MapFragment) getFragmentManager().findFragmentById(R.id.map)).getMap();
        gmap.setMapType(GoogleMap.MAP_TYPE_HYBRID);
        gmap.setMyLocationEnabled(true);
    }
}
```

Enable My Location Layer on map



## Assignment





**Q&A**

# Revision History

Date	Version	Description	Updated by	Reviewed and Approved By
June 20, 2013	1		Huy Ngu	



BUSINESS SOLUTIONS  
TECHNOLOGY  
OUTSOURCING