

Package ‘Homework1’

November 8, 2013

Type Package

Title Advanced Statistics Computing HW1 Fast Algorithm

Version 1.0

Date 2013-11-08

Author Yu Du<ydu@jhsph.edu>

Maintainer Yu Du<ydu@jhsph.edu>

Description

Homework 1 in Advanced Statistics Computing Class which includes two functions. One function is to fit a fast linear model and the other function is to calculate multivariate normal densities.

License GPL

R topics documented:

Homework1-package	1
dmvnorm	2
fastlm	3

Index	4
--------------	----------

Homework1-package	<i>Homework 1</i>
-------------------	-------------------

Description

Advanced Statistics Computing Homework 1 which includes fastlm() and dmvnorm() two functions.

Details

Package: Homework1
Type: Package
Version: 1.0
Date: 2013-11-08

run `fastlm()` to fit a linear model and `dmvnorm()` to evaluate mvn density.

Author(s)

Yu Du

Maintainer: Yu Du<ydu@jhsph.edu>

References

Advanced Statistics Computing Class. Dr. Peng.

dmvnorm

Fast Multivariate Normal Density

Description

Evaluates the k-dimensional multivariate Normal density with mean μ and covariance matrix S .

Usage

```
dmvnorm(x, mu, S, log = TRUE)
```

Arguments

<code>x</code>	<code>x</code> is a n-by-k matrix with each row is a sample from a k-dimensional multivariate normal distribution
<code>mu</code>	<code>mu</code> is the mean vector of length k for the given multivariate normal distribution.
<code>S</code>	<code>S</code> is the p-by-p variance covariance matrix for the given multivariate normal distribution.
<code>log</code>	if <code>log=TRUE</code> which is the default value, the logged density values will be returned otherwise the original density value will be returned.

Details

This function evaluates the k-dimensional multivariate Normal density with mean μ and covariance matrix S .

Value

A vector of length n of density values will be returned. n is the number of rows of input matrix `x`.

Author(s)

Yu Du

References

Advanced Statistics Computing Class, Dr. Peng.

fastlm*Fast Linear Model Fitting*

Description

fit a linear regression model to outcome data y and predictor data in a matrix X.

Usage

```
fastlm(X, y, na.rm = FALSE)
```

Arguments

X	X is a design matrix including predictor data and intercept.
y	y is a vector of outcome data.
na.rm	na.rm=TRUE to remove NA values otherwise the default value is FALSE.

Details

This function fits a linear regression model to outcome data y and predictor data in a matrix X. Matrix X also includes the intercept, i.e. the design matrix. This is faster than `lm.fit()`.

Value

coefficients	The coefficients returned are the fitted regression coefficient to the input dataset.
vcov	The vcov returned is the variance-covariance matrix of the estimated coefficients.

Author(s)

Yu Du

References

Advanced Statistics Computing Class, Dr. Peng.

Index

*Topic **package**

Homework1-package, [1](#)

dmvnorm, [2](#)

fast.linear (fastlm), [3](#)

fastlm, [3](#)

Homework1 (Homework1-package), [1](#)

Homework1-package, [1](#)

mvn.density (dmvnorm), [2](#)