

Package ‘Homework1’

November 8, 2013

Type Package

Title Advanced Statistics Computing HW1 Fast Algorithm

Version 1.0

Date 2013-11-08

Author Yu Du<ydu@jhsph.edu>

Maintainer Yu Du<ydu@jhsph.edu>

Description

Homework 1 in Advanced Statistics Computing Class which includes two functions. One function is to fit a fast linear model and the other function is to calculate multivariate normal densities.

License GPL

R topics documented:

Homework1-package	1
dmvnorm	2
fastlm	3

Index	6
--------------	----------

Homework1-package	<i>Homework 1</i>
-------------------	-------------------

Description

Advanced Statistics Computing Homework 1 which includes fastlm() and dmvnorm() two functions.

Details

Package: Homework1
Type: Package
Version: 1.0
Date: 2013-11-08
License: GPL

run `fastlm()` to fit a linear model and `dmvnorm()` to evaluate mvn density.

Author(s)

Yu Du

Maintainer: Yu Du <ydu@jhsph.edu>

References

Advanced Statistics Computing Class. Dr. Peng.

dmvnorm

Fast Multivariate Normal Density

Description

Evaluates the k-dimensional multivariate Normal density with mean μ and covariance matrix S .

Usage

```
dmvnorm(x, mu, S, log = TRUE)
```

Arguments

<code>x</code>	<code>x</code> is a n-by-k matrix with each row is a sample from a k-dimensional multivariate normal distribution
<code>mu</code>	<code>mu</code> is the mean vector of length k for the given multivariate normal distribution.
<code>S</code>	<code>S</code> is the p-by-p variance covariance matrix for the given multivariate normal distribution.
<code>log</code>	if <code>log=TRUE</code> which is the default value, the logged density values will be returned otherwise the original density value will be returned.

Details

This function evaluates the k-dimensional multivariate Normal density with mean μ and covariance matrix S .

Value

A vector of length n of density values will be returned. n is the number of rows of input matrix `x`.

Author(s)

Yu Du

References

Advanced Statistics Computing Class, Dr. Peng.

Examples

```
## Create the covariance matrix
n <- 100
n2 <- n^2
xg <- seq(0, 1, length = n)
yg <- xg
g <- data.matrix(expand.grid(xg, yg))
D <- as.matrix(dist(g))
phi <- 5

S <- exp(-phi * D)
mu <- rep(0, n2)
set.seed(1)
x <- matrix(rnorm(n2), byrow = TRUE, ncol = n2)
dmvnorm(x, mu, S, log = TRUE)

## The function is currently defined as
dmvnorm <- function(x, mu, S, log = TRUE) {
  if (!is.matrix(x)){
    x=t(as.matrix(x))
  }
  k=length(mu)
  n=nrow(x)

  ##Check if S is positive definite
  R=tryCatch({chol(S)},
    error=function(e){
      message("S is not positive definite")
    })

  logdetS=2*sum(log(diag(R)))
  T=x-rep(1,n)
  C=forwardsolve(t(R),t(T))
  term3=diag(crossprod(C))
  fx=(-k/2)*log(2*pi)-(1/2)*logdetS-(1/2)*term3
  if(log==TRUE){
    fx=fx
  }else {
    fx=exp(fx)
  }
  return(fx)
}
```

fastlm

Fast Linear Model Fitting

Description

fit a linear regression model to outcome data y and predictor data in a matrix X.

Usage

```
fastlm(X, y, na.rm = FALSE)
```

Arguments

<code>X</code>	<code>X</code> is a design matrix including predictor data and intercept.
<code>y</code>	<code>y</code> is a vector of outcome data.
<code>na.rm</code>	<code>na.rm=TRUE</code> to remove NA values otherwise the default value is <code>FALSE</code> .

Details

This function fits a linear regression model to outcome data `y` and predictor data in a matrix `X`. Matrix `X` also includes the intercept, i.e. the design matrix. This is faster than `lm.fit()`.

Value

<code>coefficients</code>	The coefficients returned are the fitted regression coefficient to the input dataset.
<code>vcov</code>	The <code>vcov</code> returned is the variance-covariance matrix of the estimated coefficients.

Author(s)

Yu Du

References

Advanced Statistics Computing Class, Dr. Peng.

Examples

```
set.seed(2)
## Generate predictor matrix
n <- 100000
p <- 500
X <- cbind(1, matrix(rnorm(n * (p - 1)), n, p - 1))

## Coefficients
b <- rnorm(p)

## Response
y <- X %*% b + rnorm(n)

fit <- fastlm(X, y)
str(fit)

## The function is currently defined as
fastlm=function(X,y,na.rm=FALSE){
  if(na.rm==TRUE){
    r=cbind(X,y)
    X=X[complete.cases(r),]
    y=as.matrix(y[complete.cases(r)])
  }

  ##Cholesky factorization for coefficients
  A=crossprod(X)
  B=crossprod(X,y)
  R=chol(A)
  Rbeta=forwardsolve(t(R),B)
```

```
coefficients=backsolve(R,Rbeta)

##Calculate VCOV
n=length(y)
p=ncol(X)
sigmahat2=(crossprod(y)-crossprod(coefficients,B))/(n-p)
Ainv=chol2inv(R)
vcov=as.numeric(sigmahat2)*Ainv

return(list(coefficients=coefficients,vcov=vcov))
}
```

Index

*Topic **package**

Homework1-package, [1](#)

dmvnorm, [2](#)

fast.linear (fastlm), [3](#)

fastlm, [3](#)

Homework1 (Homework1-package), [1](#)

Homework1-package, [1](#)

mvn.density (dmvnorm), [2](#)