

**Ex. No.: 4****Date:****RSA****Aim:**

To implement RSA asymmetric key cryptosystem using C.

**Algorithm:**

1. Select two large prime numbers p and q
2. Compute  $n=p \times q$
3. Choose system modulus:  $\phi(n)=(p-1) \times (q-1)$
4. Select a random encryption key e such that  $\gcd(e, \phi(n))=1$
5. Decrypt by computing  $d=1 \bmod \phi(n)$
6. Print the public key {e,n}
7. Print the private key {d,n}

**Program Code:**

```
#include <stdio.h>
#include <math.h>
int power(int,unsigned int,int);
int gcd(int,int);
int multiplicativeInverse(int,int,int);
int main()
{
    int p,q,n,e,d,phi,M,C;

    printf("\nEnter two prime numbers p and q that are not equal : ");
    scanf("%d %d",&p,&q);
    n = p * q;
    phi = (p - 1)*(q - 1);
    printf("Phi(%d) = %d",n,phi);
    printf("\nEnter the integer e : ");
    scanf("%d",&e);
    if(e >= 1 && e < phi)
    {
        if(gcd(phi,e)!=1)
        {
            printf("\nChoose proper value for e !!!\n");
            return 1;
        }
    }

    //Key Generation
    d = multiplicativeInverse(e,phi,n);

    printf("\nPublic Key PU = { %d,%d}",e,n);
```

```
printf("\nPrivate Key PR = { %d,%d}",d,n);
```

```
//Encryption
```

```
printf("\nMessage M = ");
```

```
scanf("%d",&M);
```

```
C = power(M,e,n);
```

```
printf("\nCiphertext C = %d \n",C);
```

```
//Decryption
```

```
M = power(C,d,n);
```

```
printf("\nDecrypted Message M = %d \n",M);
```

```
return 0;
```

```
}
```

```
int power(int x, unsigned int y, int p)
```

```
{
```

```
    int res = 1;    // Initialize result
```

```
    x = x % p; // Update x if it is more than or equal to p
```

```
    while (y > 0)
```

```
    {
```

```
        // If y is odd, multiply x with
        result if (y & 1)
```

```
        res = (res*x) % p;
```

```
        // y must be even now
```

```
        y = y>>1; // y = y/2
```

```
        x = (x*x) % p;
```

```
    }
```

```
    return res;
```

```
}
```

```
int gcd ( int a, int b )
```

```
{
```

```
    int c;
```

```
    while ( a != 0 )
```

```
    {
```

```
        c = a;
```

```
        a = b % a;
```

```
        b = c;
```

```
    }
```

```
    return b;
```

```
}
```

```
int multiplicativeInverse(int a, int b, int n)
{
    int sum,x,y;

    for(y=0;y<n;y++)
    {
        for(x=0;x<n;x++)
        {
            sum=a*x + b*(-y);
            if(sum==1)
                return x;
        }
    }
}
```

**Output:**

```
error: compilation failed
[student@aachu ~]$ java exp.java
Message data = 12.0
Encrypted data = 18.0
Original Message Sent = 29.0
[student@aachu ~]$
```

**Result:**