```sql
CREATE view low_position_employee_sales AS
select position_description, sale_from_transaction, CONCAT(fname, ' ',
lname) AS Employee_name
from employees
join positions on employees.position_id = positions.position_id
join sales on sales.employee_id = employees.employee_id
where base_hourly_wage < 15;

CREATE VIEW sale_transaction_view AS\
select employee_id, sale_from_transaction, date_of_sale, quantity,
item_name, profit_per_item
from sale_items_link\
join sales on sales.sales_id = sale_items_link.sales_id
join items on items.item_id = sale_items_link.item_id;

CREATE VIEW customer_sales AS\
select CONCAT(fname, ' ', lname) AS customer_name, sale_from_transaction
as sale_total
from customers
join sales on customers.customer_id = sales.customer_id
Group by sales.customer_id
order by sale_total;

CREATE view Employee_most_hours_under_10_years AS
Select Concat(fname, ' ', lname) AS Employee_name, hours_worked, salary
from employees
join payroll on payroll.payroll_id = employees.payroll_id
where year_worked < 10
order by hours_worked DESC;

CREATE VIEW sale_transaction_view AS
select employee_id, sale_from_transaction, date_of_sale, quantity,
item_name, profit_per_item
from sale_items_link
join sales on sales.sales_id = sale_items_link.sales_id
join items on items.item_id = sale_items_link.item_id;
```