

Near boundary

Condition	N	Method	R / NR / A	95% rejection interval	Nominal test target
Phase-tolerance ratio 1/2	65537	Imaginary coherency	400/0/0	[0.990, 1.000]	Zero observed imaginary coherency
Phase-tolerance ratio 1/2	65537	Independent windows	400/0/0	[0.990, 1.000]	Zero observed lag contrast
Phase-tolerance ratio 1/2	65537	independent windows phase adjusted	0/400/0	[0.000, 0.010]	Observed lag contrast within plug-in phase tolerance
Phase-tolerance ratio 1/2	65537	Moving-block bootstrap	400/0/0	[0.990, 1.000]	Zero observed lag contrast
Phase-tolerance ratio 1/2	65537	moving block phase adjusted	0/400/0	[0.000, 0.010]	Observed lag contrast within plug-in phase tolerance
Phase-tolerance ratio 1/2	65537	Calibrated	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 1/2	65537	Calibrated, maximum variance ceiling	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 1/2	65537	Covariance bound not supplied	0/0/400	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 1/2	65537	Relative phase bound not supplied	0/0/400	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 1/2	65537	Calibrated, factor-two operator allowance	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 1/2	65537	Phase ignored	400/0/0	[0.990, 1.000]	Zero observed two-channel contrast
Phase-tolerance ratio 1/2	65537	Calibrated, shape factor 1/2	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions

R, rejection; NR, nonrejection; A, abstention. Intervals use all records. Displayed endpoints round outward to 0.001. The nominal target does not give a size guarantee. Violated source, covariance, response, or error assumptions remove that guarantee. The baseline comparators have no finite-record source-null guarantee here.

Near boundary

Condition	N	Method	R / NR / A	95% rejection interval	Nominal test target
Phase-tolerance ratio 1/2	65537	Calibrated, shape factor 2/3	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Imaginary coherency	400/0/0	[0.990, 1.000]	Zero observed imaginary coherency
Phase-tolerance ratio 99/100	65537	Independent windows	400/0/0	[0.990, 1.000]	Zero observed lag contrast
Phase-tolerance ratio 99/100	65537	independent windows phase adjusted	0/400/0	[0.000, 0.010]	Observed lag contrast within plug-in phase tolerance
Phase-tolerance ratio 99/100	65537	Moving-block bootstrap	400/0/0	[0.990, 1.000]	Zero observed lag contrast
Phase-tolerance ratio 99/100	65537	moving block phase adjusted	0/400/0	[0.000, 0.010]	Observed lag contrast within plug-in phase tolerance
Phase-tolerance ratio 99/100	65537	Calibrated	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, fractional grid bits 12	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, maximum variance ceiling, fractional grid bits 12	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Covariance bound not supplied, fractional grid bits 12	0/0/400	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Relative phase bound not supplied, fractional grid bits 12	0/0/400	[0.000, 0.010]	Source reversibility under stated assumptions

R, rejection; NR, nonrejection; A, abstention. Intervals use all records. Displayed endpoints round outward to 0.001. The nominal target does not give a size guarantee. Violated source, covariance, response, or error assumptions remove that guarantee. The baseline comparators have no finite-record source-null guarantee here.

Near boundary

Condition	N	Method	R / NR / A	95% rejection interval	Nominal test target
Phase-tolerance ratio 99/100	65537	Calibrated, factor-two operator allowance, fractional grid bits 12	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Phase ignored, fractional grid bits 12	400/0/0	[0.990, 1.000]	Zero observed two-channel contrast
Phase-tolerance ratio 99/100	65537	Calibrated, shape factor 1/2, fractional grid bits 12	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, shape factor 2/3, fractional grid bits 12	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, fractional grid bits 8	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, maximum variance ceiling, fractional grid bits 8	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Covariance bound not supplied, fractional grid bits 8	0/0/400	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Relative phase bound not supplied, fractional grid bits 8	0/0/400	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, factor-two operator allowance, fractional grid bits 8	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Phase ignored, fractional grid bits 8	400/0/0	[0.990, 1.000]	Zero observed two-channel contrast
Phase-tolerance ratio 99/100	65537	Calibrated, shape factor 1/2, fractional grid bits 8	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions

R, rejection; NR, nonrejection; A, abstention. Intervals use all records. Displayed endpoints round outward to 0.001. The nominal target does not give a size guarantee. Violated source, covariance, response, or error assumptions remove that guarantee. The baseline comparators have no finite-record source-null guarantee here.

Near boundary

Condition	N	Method	R / NR / A	95% rejection interval	Nominal test target
Phase-tolerance ratio 99/100	65537	Calibrated, shape factor 2/3, fractional grid bits 8	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, maximum variance ceiling	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Covariance bound not supplied	0/0/400	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Relative phase bound not supplied	0/0/400	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, factor-two operator allowance	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Phase ignored	400/0/0	[0.990, 1.000]	Zero observed two-channel contrast
Phase-tolerance ratio 99/100	65537	Calibrated, recorder bits 12	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, maximum variance ceiling, recorder bits 12	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Covariance bound not supplied, recorder bits 12	0/0/400	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Relative phase bound not supplied, recorder bits 12	0/0/400	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, factor-two operator allowance, recorder bits 12	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions

R, rejection; NR, nonrejection; A, abstention. Intervals use all records. Displayed endpoints round outward to 0.001. The nominal target does not give a size guarantee. Violated source, covariance, response, or error assumptions remove that guarantee. The baseline comparators have no finite-record source-null guarantee here.

Near boundary

Condition	N	Method	R / NR / A	95% rejection interval	Nominal test target
Phase-tolerance ratio 99/100	65537	Phase ignored, recorder bits 12	400/0/0	[0.990, 1.000]	Zero observed two-channel contrast
Phase-tolerance ratio 99/100	65537	Calibrated, shape factor 1/2, recorder bits 12	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, shape factor 2/3, recorder bits 12	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, recorder bits 8	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, maximum variance ceiling, recorder bits 8	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Covariance bound not supplied, recorder bits 8	0/0/400	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Relative phase bound not supplied, recorder bits 8	0/0/400	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, factor-two operator allowance, recorder bits 8	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Phase ignored, recorder bits 8	400/0/0	[0.990, 1.000]	Zero observed two-channel contrast
Phase-tolerance ratio 99/100	65537	Calibrated, shape factor 1/2, recorder bits 8	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, shape factor 2/3, recorder bits 8	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions

R, rejection; NR, nonrejection; A, abstention. Intervals use all records. Displayed endpoints round outward to 0.001. The nominal target does not give a size guarantee. Violated source, covariance, response, or error assumptions remove that guarantee. The baseline comparators have no finite-record source-null guarantee here.

Near boundary

Condition	N	Method	R / NR / A	95% rejection interval	Nominal test target
Phase-tolerance ratio 99/100	65537	Calibrated, shape factor 1/2	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 99/100	65537	Calibrated, shape factor 2/3	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 9/10	65537	Imaginary coherency	400/0/0	[0.990, 1.000]	Zero observed imaginary coherency
Phase-tolerance ratio 9/10	65537	Independent windows	400/0/0	[0.990, 1.000]	Zero observed lag contrast
Phase-tolerance ratio 9/10	65537	independent windows phase adjusted	0/400/0	[0.000, 0.010]	Observed lag contrast within plug-in phase tolerance
Phase-tolerance ratio 9/10	65537	Moving-block bootstrap	400/0/0	[0.990, 1.000]	Zero observed lag contrast
Phase-tolerance ratio 9/10	65537	moving block phase adjusted	0/400/0	[0.000, 0.010]	Observed lag contrast within plug-in phase tolerance
Phase-tolerance ratio 9/10	65537	Calibrated	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 9/10	65537	Calibrated, maximum variance ceiling	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 9/10	65537	Covariance bound not supplied	0/0/400	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 9/10	65537	Relative phase bound not supplied	0/0/400	[0.000, 0.010]	Source reversibility under stated assumptions

R, rejection; NR, nonrejection; A, abstention. Intervals use all records. Displayed endpoints round outward to 0.001. The nominal target does not give a size guarantee. Violated source, covariance, response, or error assumptions remove that guarantee. The baseline comparators have no finite-record source-null guarantee here.

Near boundary

Condition	N	Method	R / NR / A	95% rejection interval	Nominal test target
Phase-tolerance ratio 9/10	65537	Calibrated, factor-two operator allowance	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 9/10	65537	Phase ignored	400/0/0	[0.990, 1.000]	Zero observed two-channel contrast
Phase-tolerance ratio 9/10	65537	Calibrated, shape factor 1/2	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions
Phase-tolerance ratio 9/10	65537	Calibrated, shape factor 2/3	0/400/0	[0.000, 0.010]	Source reversibility under stated assumptions

R, rejection; NR, nonrejection; A, abstention. Intervals use all records. Displayed endpoints round outward to 0.001. The nominal target does not give a size guarantee. Violated source, covariance, response, or error assumptions remove that guarantee. The baseline comparators have no finite-record source-null guarantee here.