

1 Operational Semantics

1.1 Environments

E - a mapping from identifiers to values

F - a mapping from identifiers to function definitions.

A function definition has three fields:

prog: a statement of the form P (see context free grammar)

r: a statement of the form e that comes after the ret keyword.

p_list: a list of identifiers that make up the parameter list of the function definition.

1.2 The Fundamental crumbL Statement

$$\frac{\begin{array}{l} E, F \vdash S_1 : E', F' \\ E', F' \vdash S_2 : E'', F'' \end{array}}{E, F \vdash S_1 S_2 : E'', F''}$$

1.3 Constants

$$\frac{}{E, F \vdash \text{INT_CONST} : \text{INT_CONST}}$$

$$\frac{}{E, F \vdash \text{STRING_CONST} : \text{STRING_CONST}}$$

$$\frac{}{E, F \vdash \text{Nil} : \text{Nil}}$$

1.4 Arithmetic

$$\frac{\begin{array}{l} E, F \vdash e_1 : i_1 \\ E, F \vdash e_2 : i_2 \end{array}}{E, F \vdash e_1 \oplus e_2 : i_1 \oplus i_2}$$

where $\oplus \in \{+, -, *, \%\}$

$$\frac{\begin{array}{l} E, F \vdash e_1 : i_1 \\ E, F \vdash e_2 : i_2 \\ i_2 \neq 0 \end{array}}{E, F \vdash e_1 / e_2 : i_1 / i_2}$$

$$\frac{\begin{array}{l} E, F \vdash e_1 : s_1 \\ E, F \vdash e_2 : s_2 \end{array}}{E, F \vdash e_1 :: e_2 : s_1 s_2}$$

1.5 Lists

$$\frac{E, F \vdash e_1 : v_1 \quad E, F \vdash e_2 : v_2 \text{ (not Nil)}}{E, F \vdash e_1 @ e_2 : [v_1, v_2]}$$

$$\frac{E, F \vdash e_1 : v_1 \quad E, F \vdash e_2 : \text{Nil}}{E, F \vdash e_1 @ e_2 : v_1}$$

$$\frac{E, F \vdash e : [v_1, v_2]}{E, F \vdash !e : v_1}$$

$$\frac{E, F \vdash e : [v_1, v_2]}{E, F \vdash \#e : v_2}$$

$$\frac{E, F \vdash e : v_1 \text{ (not a list)}}{E, F \vdash !e : v_1}$$

$$\frac{E, F \vdash e : v_1 \text{ (not a list)}}{E, F \vdash \#e : \text{Nil}}$$

1.6 Boolean Logic

$$\frac{E, F \vdash e_1 : i_1 \quad E, F \vdash e_2 : i_2}{E, F \vdash e_1 \odot e_2 : i_1 \odot i_2}$$

where $\odot \in \{<, >, <=, >=, ==, !=, \text{and}, \text{or}\}$

$$\frac{E, F \vdash e_1 : \text{nonzero int}}{E, F \vdash \text{not } e_1 : \text{False}}$$

$$\frac{E, F \vdash e_1 : 0}{E, F \vdash \text{not } e_1 : \text{True}}$$

$$\frac{E, F \vdash e_1 : \text{Nil}}{E, F \vdash \text{isNil } e_1 : \text{True}}$$

$$\frac{E, F \vdash e_1 : \text{not Nil}}{E, F \vdash \text{isNil } e_1 : \text{False}}$$

1.7 Conditional Statements

$$\frac{\begin{array}{c} E, F \vdash C : True \\ E, F \vdash S_1 : E', F' \end{array}}{E, F \vdash \text{if } (C) \text{ then } S_1 \text{ else } S_2 \text{ fi} : E', F'}$$

$$\frac{\begin{array}{c} E, F \vdash C : False \\ E, F \vdash S_2 : E', F' \end{array}}{E, F \vdash \text{if } (C) \text{ then } S_1 \text{ else } S_2 \text{ fi} : E', F'}$$

$$\frac{E, F \vdash C : False}{E, F \vdash \text{while}(C) \text{ do } S \text{ od} : E, F}$$

$$\frac{\begin{array}{c} E, F \vdash C : True \\ E, F \vdash S : E', F \end{array}}{E', F \vdash \text{while}(C) \text{ do } S \text{ od} : E'', F}$$

$$E, F \vdash \text{while}(C) \text{ do } S \text{ od} : E'', F$$

Note: Under this rule, the statement S must not change the function environment .

1.8 Identifiers and Functions

$$\frac{\begin{array}{c} E, F \vdash e : v \\ E(id) \text{ does not exist} \end{array}}{E, F \vdash id = e; : E[id \leftarrow v], F}$$

$$\frac{E, F \vdash v = E[id]}{E, F \vdash id : v}$$

$$\frac{\begin{array}{c} fentry = \{\text{prog: } P, \text{r: } e, \text{p_list: } p_list\} \\ F' = F[\mathbf{fname} \leftarrow fentry] \end{array}}{E, F \vdash \text{func } \mathbf{fname}(p_list) P \text{ ret } e; \text{ cnuf} : E, F'}$$

$$\frac{\begin{array}{c} fentry = F[\mathbf{fname}] \\ E' = \text{apply}(fentry.p_list, \text{call_list}) \\ p = fentry.prog \\ E', F \vdash p : E'' \\ E'', F \vdash fentry.r : v \end{array}}{E, F \vdash \mathbf{fname}(\text{call_list}) : v}$$

Note: apply is just an operational semantics subroutine to construct a new environment for a called function, and is not useable from source code.

$$\begin{array}{c}
E, F \vdash \text{p_list} = [p_1, R_1] \\
E, F \vdash \text{call_list} = [e_1, R_2] \\
E, F \vdash e_1 : v_1 \\
E, F \vdash \text{apply}(R_1, R_2) : E' \\
E'' = E'[p_1 \leftarrow v_1] \\
\hline
E, F \vdash \text{apply}(\text{p_list}, \text{call_list}) : E''
\end{array}$$

$$\frac{}{\text{apply}(\epsilon, \epsilon) : \emptyset}$$

1.9 I/O

$$\frac{E, F \vdash e : v}{E, F \vdash \text{print}(e); : E, F, \text{ print out } v}$$