

1 Operational Semantics

1.1 Environments

E - a mapping from identifiers to values

F - a mapping from identifiers to function definitions.

A function definition has three fields:

prog: a statement of the form P (see context free grammar)

r: a statement of the form e that comes after the ret keyword.

p_list: a list of identifiers that make up the parameter list of the function definition.

1.2 The Fundamental crumbL Statement

$$\frac{\begin{array}{l} E, F \vdash S_1 : E', F' \\ E', F' \vdash S_2 : E'', F'' \end{array}}{E, F \vdash S_1 S_2 : E'', F''}$$

1.3 Constants

$$\frac{\text{integer } i}{E, F \vdash i : i}$$
$$\frac{\text{String } s}{E, F \vdash s : s}$$
$$\frac{}{E, F \vdash \text{Nil} : \text{Nil}}$$

1.4 Arithmetic

$$\frac{\begin{array}{l} E, F \vdash e_1 : i_1(\text{integer}) \\ E, F \vdash e_2 : i_2(\text{integer}) \end{array}}{E, F \vdash e_1 \oplus e_2 : i_1 \oplus i_2}$$

where $\oplus \in \{+, -, *, \%\}$

$$\frac{\begin{array}{l} E, F \vdash e_1 : i_1(\text{integer}) \\ E, F \vdash e_2 : i_2(\text{integer}) \\ i_2 \neq 0 \end{array}}{E, F \vdash e_1/e_2 : i_1/i_2}$$

$$\frac{E, F \vdash e : i(\text{integer})}{E, F \vdash -e : -i}$$

$$\frac{E, F \vdash e_1 : s_1(\text{string}) \quad E, F \vdash e_2 : s_2(\text{string})}{E, F \vdash e_1 :: e_2 : s_1 s_2}$$

1.5 Lists

$$\frac{E, F \vdash e_1 : v_1(\text{not a list}) \quad E, F \vdash e_2 : v_2(\text{not Nil})}{E, F \vdash e_1 @ e_2 : [v_1, v_2]}$$

$$\frac{E, F \vdash e_1 : v_1(\text{not a list}) \quad E, F \vdash e_2 : \text{Nil}}{E, F \vdash e_1 @ e_2 : v_1}$$

$$\frac{E, F \vdash e : [v_1, v_2]}{E, F \vdash !e : v_1}$$

$$\frac{E, F \vdash e : [v_1, v_2]}{E, F \vdash \#e : v_2}$$

$$\frac{E, F \vdash e : v_1(\text{not a list})}{E, F \vdash !e : v_1}$$

$$\frac{E, F \vdash e : v_1(\text{not a list})}{E, F \vdash \#e : \text{Nil}}$$

1.6 Boolean Logic

$$\frac{E, F \vdash e_1 : v_1 \quad E, F \vdash e_2 : v_2}{E, F \vdash e_1 \odot e_2 : v_1 \odot v_2}$$

where v_1 and v_2 are either both strings or both integers. If strings, comparisons are lexicographic.

$$\odot \in \{<, >, <=, >=, ==, !=\}$$

Let **False** be "", 0, or Nil.

True is any expression that evaluates to something that is not **False**.

$$\frac{E, F \vdash e_1 : \text{True} \quad E, F \vdash e_2 : \text{True}}{E, F \vdash e_1 \text{ and } e_2 : 1}$$

$$\frac{E, F \vdash e_1 : \text{False}}{E, F \vdash e_1 \text{ and } e_2 : 0}$$

$$\frac{\begin{array}{l} E, F \vdash e_1 : \text{True} \\ E, F \vdash e_2 : \text{False} \end{array}}{E, F \vdash e_1 \text{ and } e_2 : 0}$$

$$\frac{E, F \vdash e_1 : \text{True}}{E, F \vdash e_1 \text{ or } e_2 : 1}$$

$$\frac{\begin{array}{l} E, F \vdash e_1 : \text{False} \\ E, F \vdash e_2 : \text{False} \end{array}}{E, F \vdash e_1 \text{ or } e_2 : 0}$$

$$\frac{\begin{array}{l} E, F \vdash e_1 : \text{False} \\ E, F \vdash e_2 : \text{True} \end{array}}{E, F \vdash e_1 \text{ or } e_2 : 1}$$

$$\frac{E, F \vdash e_1 : \text{True}}{E, F \vdash \text{not } e_1 : 0}$$

$$\frac{E, F \vdash e_1 : \text{False}}{E, F \vdash \text{not } e_1 : 1}$$

$$\frac{E, F \vdash e_1 : \text{Nil}}{E, F \vdash \text{isNil } e_1 : 1}$$

$$\frac{E, F \vdash e_1 : \text{not Nil}}{E, F \vdash \text{isNil } e_1 : 0}$$

1.7 Conditional Statements

$$\frac{\begin{array}{l} E, F \vdash C : \text{True} \\ E, F \vdash S_1 : E', F' \end{array}}{E, F \vdash \text{if } (C) \text{ then } S_1 \text{ else } S_2 \text{ fi} : E', F'}$$

$$\frac{\begin{array}{l} E, F \vdash C : \text{False} \\ E, F \vdash S_2 : E', F' \end{array}}{E, F \vdash \text{if } (C) \text{ then } S_1 \text{ else } S_2 \text{ fi} : E', F'}$$

$$\frac{E, F \vdash C : \text{True} \quad E, F \vdash S : E', F'}{E, F \vdash \text{if}(C) \text{ then } S \text{ fi} : E', F'}$$

$$\frac{E, F \vdash C : \text{False}}{E, F \vdash \text{if}(C) \text{ then } S \text{ fi} : E, F}$$

$$\frac{E, F \vdash C : \text{False}}{E, F \vdash \text{while}(C) \text{ do } S \text{ ob} : E, F}$$

$$\frac{E, F \vdash C : \text{True} \quad E, F \vdash S : E', F' \quad E', F \vdash \text{while}(C) \text{ do } S \text{ ob} : E'', F}{E, F \vdash \text{while}(C) \text{ do } S \text{ ob} : E'', F}$$

Note: Under this rule, the statement S must not change the function environment.

1.8 Identifiers and Functions

$$\frac{E, F \vdash e : v}{E, F \vdash id = e; : E[id \leftarrow v], F}$$

$$\frac{}{E, F \vdash \text{lazy } id = e; : E[id \leftarrow e], F}$$

$$\frac{e = E[id] \quad E, F \vdash e : v \quad E' = E[id \leftarrow v]}{E, F \vdash id : v, E', F}$$

$$\frac{fentry = \{\text{prog: } P, \text{r: } e, \text{p_list: } p_list\} \quad F' = F[\mathbf{fname} \leftarrow fentry]}{E, F \vdash \text{func } \mathbf{fname}(p_list) \text{ } P \text{ ret } e; \text{ cnuf} : E, F'}$$

$$\frac{fentry = F[\mathbf{fname}] \quad E' = \text{apply}(fentry.p_list, \text{call_list}) \quad p = fentry.prog \quad E', F \vdash p : E'' \quad E'', F \vdash fentry.r : v}{E, F \vdash \mathbf{fname}(\text{call_list}) : v}$$

Note: apply is just an operational semantics subroutine to construct a new environment for a called function, and is not useable from source code.

$$\begin{array}{c}
E, F \vdash \text{p_list} = [p_1, R_1] \\
E, F \vdash \text{call_list} = [e_1, R_2] \\
E, F \vdash e_1 : v_1 \\
E, F \vdash \text{apply}(R_1, R_2) : E' \\
E'' = E'[p_1 \leftarrow v_1] \\
\hline
E, F \vdash \text{apply}(\text{p_list}, \text{call_list}) : E''
\end{array}$$

$$\begin{array}{c}
E, F \vdash \text{p_list} = [\text{lazy } p_1, R_1] \\
E, F \vdash \text{call_list} = [e_1, R_2] \\
E, F \vdash \text{apply}(R_1, R_2) : E' \\
E'' = E'[p_1 \leftarrow e_1] \\
\hline
E, F \vdash \text{apply}(\text{p_list}, \text{call_list}) : E''
\end{array}$$

$$\frac{}{\text{apply}(\epsilon, \epsilon) : \emptyset}$$

1.9 I/O

$$\frac{E, F \vdash e : v}{E, F \vdash \text{print}(e); : E, F, \text{ print out } v}$$

$$\frac{
\begin{array}{c}
T \vdash e_1 : \alpha_1 \\
T \vdash e_2 : \alpha_2 \\
\alpha_2 = \alpha_1 \text{ or } \alpha_2 = \alpha_1 \text{List}
\end{array}
}{T \vdash e_1 @ e_2 : \alpha_1 \text{List}}$$