Private Access (ZPA)

Understanding User Activity Log Fields

The Log Streaming Service (LSS) can send User Activity log information to any third-party log analytics tool. By default, the User Activity log type includes the fields listed in the following table for each log template (i.e., CSV, JSON, TSV). While configuring your log receiver, you can edit the default log stream content to capture only specific fields, and create a custom log template.

View an example User Activity log.


```
{"LogTimestamp": "Fri May 31 17:35:42 2019","Customer": "ANZ Team/zdemo in beta","Sess
ionID": "SqyZIMkg0JTj7EABsvwA","ConnectionID": "SqyZIMkg0JTj7EABsvwA,Q+EjXGdrvbF2lPiBb
edm","InternalReason": "","ConnectionStatus": "active","IPProtocol": 6,"DoubleEncrypti
on": 0,"Username": "ZPA LSS Client","ServicePort": 10011,"ClientPublicIP": "34.209.18
9.218","ClientPrivateIP": "","ClientLatitude": 45.000000,"ClientLongitude": -119.00000
0,"ClientCountryCode": "US","ClientZEN": "broker1b.pdx2","Policy": "ANZ Lab Apps_1","C
onnector": "ZDEMO ANZ Lab-1","ConnectorZEN": "broker1b.pdx2","ConnectorIP": "192.168.
1.53","ConnectorPort": 60266,"Host": "192.168.1.57","Application": "ANZ Lab Apps","App
Group": "ANZ Lab Apps","Server": "0","ServerIP": "192.168.1.57","ServerPort": 10011,"P
olicyProcessingTime": 28,"CAProcessingTime": 1330,"ConnectorZENSetupTime": 191017,"Con
nectionSetupTime": 192397,"ServerSetupTime": 465,"AppLearnTime": 0,"TimestampConnectio
nStart": "2019-05-30T08:20:42.230Z","TimestampConnectionEnd": "","TimestampCATx": "201
9-05-30T08:20:42.230Z","TimestampCARx": "2019-05-30T08:20:42.231Z","TimestampAppLearnS
tart": "","TimestampZENFirstRxClient": "2019-05-30T08:20:42.424Z","TimestampZENFirstTx
Client": "","TimestampZENLastRxClient": "2019-05-31T17:34:27.348Z","TimestampZENLastTx
Client": "","TimestampConnectorZENSetupComplete": "2019-05-30T08:20:42.422Z","Timestam
pZENFirstRxConnector": "","TimestampZENFirstTxConnector": "2019-05-30T08:20:42.424
Z","TimestampZENLastRxConnector": "","TimestampZENLastTxConnector": "2019-05-31T17:34:
27.348Z","ZENTotalBytesRxClient": 2406926,"ZENBytesRxClient": 7115,"ZENTotalBytesTxCli
ent": 0,"ZENBytesTxClient": 0,"ZENTotalBytesRxConnector": 0,"ZENBytesRxConnector":
0,"ZENTotalBytesTxConnector": 2406926,"ZENBytesTxConnector": 7115,"Idp": "Example IDP
Config", "ClientToClient": "0", "ClientCity": "San Jose", "MicroTenantID": "1452574807
99129312", "AppMicrotenantID": "145257480799129312", "Platform": "windows", "Hostnam
e": "DESKTOP-P669MN4", "PRAApprovalID": "15787", "PRACapabilityPolicyID": "72057597259
256663", "PRAConsoleType": "SSH", "PRACredentialUserName": "SafemarchUser", "PRACreden
tialLoginType": "Username-Password", "PRACredentialPolicyID": "72057597259256964", "PR
AConnectionID": "$b381e220-fb0f-4dc5-9c2a-e3e0fb2e5efb", "PRAErrorStatus": "Upstream E
rror", "PRAFileTransferList": "{\"file_list\":[{\"name\":\"\\/d546509ab6670f9ff31783ed
72875dfc0f37fa2b666bd5870eecaaed2ebea4a8.elf\",\"action\":\"Upload\",\"status\":\"Insp
ection denied upload\",\"start_ts\":1704225544,\"end_ts\":1704225547,\"inspected\":\"T
rue\",\"file_type\":\"elf\",\"md5\":\"4DDE761681684D7EDAD4E5E1FFDB940B\",\"inspection_
verdict\":\"{\\n\\t\\\"code\\\": 200,\\n\\t\\\"message\\\": \\\"response OK\\\",\\n\\t
\\\"virusName\\\": \\\"iot.trojan.gafgyt.botnet\\\",\\n\\t\\\"virusType\\\": \\\"Virus
\\\",\\n\\t\\\"fileType\\\": \\\"elf\\\",\\n\\t\\\"md5\\\": \\\"4DDE761681684D7EDAD4E5
E1FFDB940B\\\",\\n\\t\\\"sandboxSubmission\\\": \\\"Virus\\\"\\n}\",\"inspection_time
\":\"less than 1 second\"},{\"name\":\"\\/4ce39251817198bbec7b84782507394e7d68bfe3a79b
```


©2026 Zscaler, Inc. All rights reserved.

```
89be363f0c1e05558ef1.zip\",\"action\":\"Upload\",\"status\":\"Inspection denied upload
\",\"start_ts\":1704225552,\"end_ts\":1704225557,\"inspected\":\"True\",\"file_type
\":\"zip\",\"md5\":\"F5F7995BACD88A4BCF2D69DF063184AB\",\"inspection_verdict\":\"{\\n
\\t\\\"code\\\": 200,\\n\\t\\\"message\\\": \\\"File not submitted to Sandbox\\\",\\n
\\t\\\"fileType\\\": \\\"zip\\\",\\n\\t\\\"md5\\\": \\\"F5F7995BACD88A4BCF2D69DF063184
AB\\\",\\n\\t\\\"sandboxSubmission\\\": \\\"File not Submitted to Sandbox\\\"\\n}
\",\"inspection_time\":\"less than 1 second\"},{\"name\":\"\\/4ce39251817198bbec7b8478
2507394e7d68bfe3a79b89be363f0c1e05558ef1.xlsx\",\"action\":\"Upload\",\"status\":\"Ins
pection denied upload\",\"start_ts\":1704225568,\"end_ts\":1704225573,\"inspected
\":\"True\",\"file_type\":\"xlsx\",\"md5\":\"FF43FB09E69439FCD3DD8196F5BCE11F\",\"insp
ection_verdict\":\"{\\n\\t\\\"code\\\": 200,\\n\\t\\\"message\\\": \\\"response OK
\\\",\\n\\t\\\"virusName\\\": \\\"xls.downloader.qakbot\\\",\\n\\t\\\"virusType\\\":
\\\"Sandbox Malware\\\",\\n\\t\\\"fileType\\\": \\\"xlsx\\\",\\n\\t\\\"md5\\\": \\\"FF
43FB09E69439FCD3DD8196F5BCE11F\\\",\\n\\t\\\"sandboxSubmission\\\": \\\"Sandbox Malwar
e\\\"\\n}\",\"inspection_time\":\"less than 1 second\"},{\"name\":\"\\/Populate_Existi
ng_Flags_And_Overrides.xlsx\",\"action\":\"Upload\",\"status\":\"Success\",\"start_ts
\":1704225591,\"end_ts\":1704225593,\"inspected\":\"True\",\"file_type\":\"xlsx\",\"md
5\":\"D1A0596352BE4A1260B0419C7046F8FA\",\"inspection_verdict\":\"{\\n\\t\\\"code\\\":
200,\\n\\t\\\"message\\\": \\\"No active content found. File not suspicious\\\",\\n\\t
\\\"fileType\\\": \\\"xlsx\\\",\\n\\t\\\"md5\\\": \\\"D1A0596352BE4A1260B0419C7046F8FA
\\\",\\n\\t\\\"sandboxSubmission\\\": \\\"File not Submitted to Sandbox\\\"\\n}\",\"in
spection_time\":\"less than 1 second\"}]}", "PRARecordingStatus": "Available", "PRASha
redUserList": "{\"shared_user_list\":[{\"name\":\"lisa@zerotrust.to\"}]}", "PRASession
Type": "PRA", "PRASharedMode": "control"}
```


The following table includes descriptions and supported field format specifications for each field within the template. To learn more about the format specifications listed for each field, including examples, see Understanding the Log Stream Content Format.

Field	Description	Supported Field Format Specifications
AppGroup	The application group name	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
AppLearnTime	The time in microseconds taken for App Connectors to learn about the requested application and report the learned information to the central authority	• %[OPT]s • %[OPT]j • %[OPT]J

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
Application	The application name	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
AppMicroTenantID	The Microtenant ID of the application	• %[OPT]s • %[OPT]j
CAProcessingTime	The time in microseconds taken for processing in the central authority	• %[OPT]s • %[OPT]j • %[OPT]J
ClientCountryCode	The country code of the Zscaler Client Connector location	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
ClientLatitude	The latitude coordinate of the Zscaler Client Connector location	• %[OPT]f • %[OPT]o
ClientLongitude	The longitude coordinate of the Zscaler Client Connector location	• %[OPT]f • %[OPT]o
ClientPrivateIP	The private IP address of the Zscaler Client Connector	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
ClientPublicIP	The public IP address of the Zscaler Client Connector	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
ClientCity	The city of the client	• %[OPT]s • %[OPT]j
ClientToClient	The status of the client-to-client connection	• %[OPT]s
ClientZEN	The Public Service Edge for Private Access that received the request from the Zscaler Client Connector	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
ConnectionID	The application connection ID	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
ConnectionSetupTime	The time taken by the App Connector to process a notification from the App Connector selection microservice and set up the connection to the application server	• %[OPT]s • %[OPT]j • %[OPT]J
ConnectionStatus	The status of the connection. The expected values for this field are: • Open • Close • Active	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
Connector	The App Connector name	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
ConnectorIP	The source IP address of the App Connector	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
ConnectorPort	The source port of the App Connector	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
ConnectorZEN	The Public Service Edge that sent the request from the App Connector	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
ConnectorZENSetupTime	The time in microseconds taken for setting up the connection between the App Connector and Public Service Edge	• %[OPT]s • %[OPT]j • %[OPT]J
Customer	The customer name	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
DoubleEncryption	The double encryption status. The expected values for this field are: • On	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
	• Off	
Host	The destination host domain or IP address	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
Hostname	The name of the device as reported by Zscaler Client Connector. This field only provides valid values for Zscaler Client Connector and machine tunnel client types.	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
Idp	The name of the identity provider (IdP) as configured in the Zscaler Admin Console	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
InternalReason	The internal reason for the status of the transaction	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
IPProtocol	The IP protocol number	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
LogTimestamp	The timestamp when the log was generated	• %[OPT]s • %[OPT]j • %[OPT]J

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
MicroTenantID	The Microtenant ID of the user accessing the application	• %[OPT]s • %[OPT]j
Platform	The platform on the device as reported by Zscaler Client Connector (e.g., Windows)	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
Policy	The access policy rule name	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
PolicyProcessingTime	The time in microseconds taken for processing the access policy associated with the application	• %[OPT]s • %[OPT]j • %[OPT]J
PRAApprovalID	The privileged approval ID	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
PRACapabilityPolicyID	The privileged capabilities policy ID	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
PRAConnectionID	The Privileged Remote Access (PRA) connection ID	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
PRAConsoleType	The privileged console type. The expected values for this field are: • RDP • SSH • VNC	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
PRACredentialLoginType	The login type of the privileged credential. The expected values for this field are: • Username/Password • SSH Key • Password	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
PRACredentialPolicyID	The privileged credential policy ID	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
PRACredentialUserName	The name of the user that is logged in to the target privileged console	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
PRAErrorStatus	The PRA session error status, if available	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
PRAFileTransferList	The files transferred during the PRA session	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
PRARecordingStatus	The recording status of the PRA file transfer. The expected values for this field are: • Available • Not Available • Started	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
PRASessionType	The PRA session type. The expected value is PRA.	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
PRASharedMode	The PRA shared mode. The expected values for this field are: • Monitor • Control	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
PRASharedUserList	The users that the PRA session was shared with	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
Server	The server ID name. The server ID must be set to zero if Dynamic Server Discovery is enabled.	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
ServerIP	The destination IP address of the server	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
ServerPort	The destination port of the server	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
ServerSetupTime	The time in microseconds taken to set up the connection at the server	• %[OPT]s • %[OPT]j • %[OPT]J
ServicePort	The service port associated with the application request	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
SessionID	The TLS session ID	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
TimestampConnectionStart	The timestamp in microseconds when the Public Service Edge or Private Service Edge for Private Access received the initial request from Zscaler Client Connector to start the connection	• %[OPT]s • %[OPT]j • %[OPT]J
TimestampConnectionEnd	The timestamp in microseconds when the Public Service Edge	• %[OPT]s • %[OPT]j

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
	or Private Service Edge terminated the connection	• %[OPT]J
TimestampCATx	The timestamp in microseconds when the central authority sent a request to the Public Service Edge or Private Service Edge	• %[OPT]s • %[OPT]j • %[OPT]J
TimestampCARx	The timestamp in microseconds when the central authority received a request from the Public Service Edge or Private Service Edge	• %[OPT]s • %[OPT]j • %[OPT]J
TimestampAppLearnStart	The timestamp in microseconds when Private Access services start the process to learn about an application	• %[OPT]s • %[OPT]j • %[OPT]J
TimestampZENFirstRxClient	The timestamp in microseconds when the Public Service Edge received the first byte from the Zscaler Client Connector	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
TimestampZENFirstTxClient	The timestamp in microseconds when the Public Service Edge sent the first byte to the Zscaler Client Connector	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
TimestampZENLastRxClient	The timestamp in microseconds when the Public Service Edge received the last byte from the Zscaler Client Connector	• %[OPT]s • %[OPT]j • %[OPT]J

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
TimestampZENLastTxClient	The timestamp in microseconds when the Public Service Edge sent the last byte to the Zscaler Client Connector	• %[OPT]s • %[OPT]j • %[OPT]J
TimestampConnectorZENSetupComplete	The timestamp in microseconds when the Public Service Edge received a request from the App Connector to set up a data connection. The request from the App Connector is triggered by the initial request for a specific application from Zscaler Client Connector.	• %[OPT]s • %[OPT]j • %[OPT]J
TimestampZENFirstRxConnector	The timestamp in microseconds when the Public Service Edge received the first byte from the App Connector	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
TimestampZENFirstTxConnector	The timestamp in microseconds when the Public Service Edge sent the first byte to the App Connector	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
TimestampZENLastRxConnector	The timestamp in microseconds when the Public Service Edge received the last byte from the App Connector	• %[OPT]s • %[OPT]j • %[OPT]J
TimestampZENLastTxConnector	The timestamp in microseconds when the Public Service Edge sent the last byte to the App Connector	• %[OPT]s • %[OPT]j • %[OPT]J

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
Username	The username as entered into Zscaler Client Connector	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
ZENBytesRxClient	The additional bytes received from Zscaler Client Connector since the last transaction log	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
ZENBytesTxClient	The additional bytes transmitted to Zscaler Client Connector since the last transaction log	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
ZENBytesRxConnector	The additional bytes received from the App Connector since the last transaction log	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
ZENBytesTxConnector	The additional bytes transmitted by the App Connector since the last transaction log	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
ZENTotalBytesRxClient	The total bytes received from Zscaler Client Connector by the Public Service Edge	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
ZENTotalBytesTxClient	The total bytes transmitted to Zscaler Client Connector from the Public Service Edge	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
ZENTotalBytesRxConnector	The total bytes received from the App Connector by the Public Service Edge	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
ZENTotalBytesTxConnector	The total bytes transmitted to the App Connector from the Public Service Edge	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o

©2026 Zscaler, Inc. All rights reserved.