Private Access (ZPA)

Understanding User Status Log Fields

The Log Streaming Service (LSS) can send User Status log information to any third-party log analytics tool. By default, the User Status log type includes the fields listed in the following table for each log template (i.e., CSV, JSON, TSV). While configuring your log receiver, you can edit the default log stream content to capture only specific fields, and create a custom log template.

View an example User Status log.


```
{"LogTimestamp": "Fri May 31 17:34:48 2019","Customer": "ANZ Team/zdemo in beta","User
name": "ZPA LSS Client","SessionID": "cKgzUERSLl09Y+ytH8v5","SessionStatus": "ZPN_STAT
US_AUTHENTICATED","Version": "19.12.0-36-g87dad18","ZEN": "broker1b.pdx2","Certificate
CN": "slogger1b.pdx2.zpabeta.net","PrivateIP": "","PublicIP": "34.216.108.5","Latitud
e": 45.000000,"Longitude": -119.000000,"CountryCode": "US","TimestampAuthentication":
"2019-05-29T21:18:38.000Z","TimestampUnAuthentication": "","TotalBytesRx": 31274866,"T
otalBytesTx": 25424152,"Idp": "Example IDP Config","Hostname": "DESKTOP-2K299HC","Plat
form": "windows","ClientType": "zpn_client_type_zapp","TrustedNetworks": "TN1_stc1","T
rustedNetworksNames": "145248739466947538","SAMLAttributes": "myname:jdoe,myemail:jdoe
@zscaler.com","PosturesHit": "sm-posture1,sm-posture2","PosturesMisses": "sm-posture1
1,sm-posture12","ZENLatitude": 47.000000,"ZENLongitude": -122.000000,"ZENCountryCode":
"", "FQDNRegistered": "0","FQDNRegisteredError": "","City": "San Jose", "MicroTenantI
D": "145257480799129312"}
```


The following table includes descriptions and supported field format specifications for each field within the template. To learn more about the format specifications listed for each field, including examples, see Understanding the Log Stream Content Format.

Field	Description	Supported Field Format Specifications
LogTimestamp	The timestamp when the log was generated	• %[OPT]s • %[OPT]j • %[OPT]J
Customer	The customer name	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
Username	The user name	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
SessionID	The TLS session ID	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
SessionStatus	The status of the session. The expected values for this field are: • ZPN_STATUS_AUTHENTICATED: The user successfully authenticated in Private Access • ZPN_STATUS_AUTH_FAILED: The user failed to authenticate in Private Access • ZPN_STATUS_DISCONNECTED: The user connected from a Public Service Edge for Private Access or a Private Service Edge for Private Access	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
Version	The Zscaler Client Connector version	• %[OPT]s • %[OPT]j • %[OPT]J

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
		• %[OPT]o
ZEN	The Public Service Edge that was selected for the connection	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
CertificateCN	The certificate common name	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
PrivateIP	The private IP address of Zscaler Client Connector	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
PublicIP	The public IP address of Zscaler Client Connector	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
Latitude	The latitude coordinate of the Zscaler Client Connector location	• %[OPT]f • %[OPT]o
Longitude	The longitude coordinate of the Zscaler Client Connector location	• %[OPT]f • %[OPT]o
CountryCode	The country code of the Zscaler Client Connector location	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
TimestampAuthentication	Timestamp in microseconds when Zscaler Client Connector was authenticated	• %[OPT]s • %[OPT]j • %[OPT]J
TimestampUnAuthentication	Timestamp in microseconds when Zscaler Client Connector was unauthenticated	• %[OPT]s • %[OPT]j • %[OPT]J
TotalBytesRx	The total bytes received	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
TotalBytesTx	The total bytes transmitted	• %[OPT]d • %[OPT]x • %[OPT]f • %[OPT]o
Idp	The name of the identity provider (IdP) as configured in the Zscaler Admin Console	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
Hostname	The name of the device as reported by Zscaler Client Connector	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
Platform	The platform on the device as reported by Zscaler Client Connector	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
ClientType	The client type for the request (i.e., Zscaler Client Connector, ZPA LSS, or Web Browser)	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
TrustedNetworks	The unique IDs for the trusted networks that Zscaler Client Connector has determined for this device	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
TrustedNetworksNames	The names for the trusted networks that Zscaler Client Connector has determined for this device	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
SAMLAttributes	The list of SAML attributes reported by the IdP	• %[OPT]s • %[OPT]j • %[OPT]J
PosturesHit	The posture profiles that Zscaler Client Connector verified for this device	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
PosturesMiss	The posture profiles that Zscaler Client Connector failed to verify for this device	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
ZENLatitude	The latitude coordinates for the Public Service Edge	• %[OPT]f • %[OPT]o

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
ZENLongitude	The longitude coordinates for the Public Service Edge	• %[OPT]f • %[OPT]o
ZENCountryCode	The country code for the Public Service Edge	• %[OPT]s • %[OPT]j • %[OPT]J • %[OPT]o
FQDNRegistered	The status of the hostname for the client-to-client connection. The expected values for this field are true or false.	• %[OPT]s
FQDNRegisteredError	The status of the registered hostname. The expected value if the hostname matches the regular expression is FQDN_MATCH. The expected values if the hostname does not match the regular expression are: • FQDN_NO_MATCH: The hostname does not match with the configured regular expression • FQDN_BAD_SCHEMA: Client-to-client communication is disabled for the Public Service Edge • FQDN_BAD_REGEX: The configured regular expression in the Zscaler	• %[OPT]s

©2026 Zscaler, Inc. All rights reserved.

Field	Description	Supported Field Format Specifications
	Admin Console is incorrect • FQDN_TOO_MANY_REGEX : Invalid regular expression configuration due to multiple configured regular expressions • FQDN_NO_ENTRIES: Your admin has not configured a regular expression in the Zscaler Admin Console • FQDN_EMPTY: The FQDN received from the Zscaler Client Connector is null or empty • BROKER_NOT_ENABLED: Client-to-client communication is disabled for the Public Service Edge • CUSTOMER_NOT_ENABLED: Client-to-client communication is disabled for the current customer	
City	The city of the client	• %[OPT]s • %[OPT]j
MicroTenantID	The Microtenant ID of the user accessing the application	• %[OPT]s • %[OPT]j

©2026 Zscaler, Inc. All rights reserved.