

WSCAN+ One?Page Summary (Non? Coding)

Date: 2026-03-19 (America/Los_Angeles)

What?s Verified Now

- **Wi?Fi scan with Wi?Fi OFF** works only if `wifi_scan_always_enabled=1`.
- **wpa_supplicant logcat** emits deauth/disconnect reason codes (usable via ADB).
- **Altitude** exists in fused/network provider but is **stale** without active updates.
- **Mock location** can inject altitude (FakeGPS Route), and OS marks `mock`.
- **Dev build** already has runtime permissions + foreground `WatchdogService`.
- **WiGLE exports** provide CSV/KML schema; `.m8b` format spec documented.

What Requires App?Side Instrumentation

- BLE scan results
- Live location updates to avoid stale altitude
- Heuristic scoring output logs

Evidence & Retention Policy

- Retain timestamps, RSSI history, SSID/BSSID/MAC, and coarse geo.
- Evidence mode **overrides redaction** on anomaly detection.
- Alerts should be gated by **repeat evidence** to reduce false positives.

Reason?Code Rules (Verified Meanings Only)

- Reason codes are from 802.11 definitions (not attack labels).
- Use frequency/time windows to mark **anomalies**, not attacks.

Device ? Desktop Data Flow

```
flowchart LR
    A["Android Device"] --> B["Local Scan Capture"]
    B --> C["Observation Store"]
    C --> D["Anomaly Candidate Scoring"]
    D --> E["Alert Event (Evidence Mode)"]
    C --> F["Export/Sync Queue"]
    F --> G["Desktop Hub (Debian/Kali)"]
    G --> H["Timeline + Heuristic Review"]
```

Key Docs

- docs/codex_findings_gaps/47_verification_status.md
- docs/codex_findings_gaps/48_claude_briefing.md
- docs/codex_findings_gaps/46_reason_code_frequency_ruleset.md
- docs/codex_findings_gaps/42_minimal_retention_schema.md
- docs/codex_findings_gaps/33_wigle_export_schema.md