# VERTICAL AUTOCLAVE (NB-1045/NB-1060/NB-1080/NB-1100)

It is a high pressure autoclave which is suitable for general lab. With the highest work efficiency and safety features, it provides the cost-effective sterilization system.



### **FEATURES**

- Fully Automatic Autoclave
   Heat-up, Exhaust, Sterilize, and Pressure
- Safety Valve for Discharging Pressure
- Chamber made of SUS304 for Resistance to Decomposition
- Precise Electronic Timer
- Microprocessor PID Control for Temperature



[CONTROL PANEL]















402-803 Techno-Park, 655 Pyeongcheon-Ro, Wonmi-Gu, Bucheon-Si, Republic of KOREA (Zip Code 14502)
E-mail: export@n-biotek.com / Tel: +82-32-321-2100

Website: www.n-biotek.com

## **COMPONENT**



[HEATER]



[HEATER COVER]



[GASKET]



[DRAIN VALVE]



[MANUAL STEAM VALVE]



**[STEAM BOTTLE** (EXHAUST)]

## **ACCESSORY**





[BASKETS]

## Specification

Items	Unit	NB-1045	NB-1060	NB-1080	NB-1100
Use Temp.		121°C(Standard), 132°C(Option)			
Temp. Accuracy		±0,5℃ At 121℃			
Operating Pressure		0.1~0.21 Mpa			
Temp. Control		Digital P.I.D Controller			
Timer		Electronic Type, 0~99h 59min,			
Pressure Gauge		Mechanical Gauge 0~0.3 Mpa			
Air Exhaust		Adjustable Valve			
Safety Device		Over Temp, limit By Controller			
		Over Heat Limit By Safety S/w Over Pressure Limit By Protector Valve			
		Water Level Sensor Protector			
Monitor Unit		Audible & Visible Device			
Basket		Mesh Type, Standard / 2ea			
Dimension (in)		300 ø x630mm	350 ø x630mm	400 ø x630mm	450 ø x630mm
(out)		670x470x1080(h)mm	670x470x1080(h)mm	810x630x1150(h)mm	810x630x1150(h)mm
Capacity		45Liter	60Liter	80Liter	100Liter
Heater		2Kw×1EA	3Kw×1EA	$4Kw(2Kw \times 2EA)$	$4Kw(2Kw \times 2EA)$
Weight		71Kg	73Kg	120Kg	125Kg
Power		220V,50/60Hz (Standard), 110V,50/60Hz(Option)			



402-803 Techno-Park, 655 Pyeongcheon-Ro, Wonmi-Gu, Bucheon-Si, Republic of KOREA (Zip Code 14502)
E-mail: <a href="mailto:export@n-biotek.com">export@n-biotek.com</a> / Tel: +82-32-321-2100

Website: www.n-biotek.com