E1 213 Pattern Recognition and Neural Network Assignment 1

Dwaipayan Haldar
March 15, 2026

Phase 1: Bio-Optic Sensor Calibration

1.1 Gradient Descent vs. Closed Form

Ans: Ordinary least squares solution is implemented via the closed form solution $(X^T X)^{-1} X y$ and also using the vectorized gradient descent algorithm with learning rate $\alpha = 0.01$ and number of iterations equal to 2000. The L2 norm difference between the two methods comes as 1.62×10^{-14}.

1.2 Primal to Dual Translation

Ans: The target dataset is threshold by median to give a binary dataset. The data is not linearly separable. So hard margin SVM will not be able to fit in the data. I used `scipy.optimize.minimize` to optimize, it is not able to converge and going on some infinite loop. Using `cvxopt.solvers.qp` was able to solve the problem but all the mu was very large suggesting that all of them are support vectors which is clearly not the case. So they are all garbage values.

Phase 2: Oncology Array

2.3 The Singularity Trap

Ans: Since $D > N$, so the rank of the matrix can be at best N and $X^T X$ is a 1000×1000 matrix. So clearly, the matrix is singular. There is no `LinAlgError` in this case because of floating point approximation. But the high condition number of 9.66×10^{18} shows that the inverse is unstable and not reliable. Fig. 1a gives the condition number vs λ values plot, it can be seen with the increase of lambda there is a decrease in the condition number.

2.4 Lasso Sparsity

Ans: Fig. 1b shows the variation of the l_1 norm of weight value with $log(\lambda)$. The exact value of λ for which exactly 50% is equal to 0 is 0.37.



(a) κ vs λ for l_1 regularization



(b) l_1 norm of the weight vector vs $\log(\lambda)$

Phase 3: High Frequency ICU Telemetry

3.5 Vectorized Logistic Regression

Ans: The Lipschitz smoothness factor for this case is very small $\frac{1}{L} = 0.003396$. So even when 2 or 3 times the factor is taken, the curve converges as the absolute value of the α is small. Only when very high value is taken then the curve does not converge. Fig. 2a gives the loss curve for a α that is close to the factor and Fig. 2b gives the loss curve for a very high α.



(a) Loss vs iteration curve for $\alpha = 0.00339$



(b) Loss vs iteration curve for $\alpha = 33.96$

3.6 GMM Intialization & The E-Step

Ans: The initial log likelihood is -2857267.241 and after one iteration the log likelihood becomes -1771352.38.

3.7 EM Convergence and crashes

Ans: Fig. 3a, Fig. 3b and Fig. 3c gives the plots of Log-Likelihood vs Iteration for different values of K = 2,4 and 6. When one of the matrix is made singular, then the function cannot invert the matrix for the multivariate normal equation to work, so it cannot calculate the value of the function at that sample. So, the python breaks with error `LinAlgError`.



(a) Log-likelihood vs Iteration for $K = 2$



(b) Log-likelihood vs Iteration for $K = 4$



(c) Log-likelihood vs Iteration for $K = 6$

3.8 Decision Boundaries

Ans: Fig. 4a gives the plot of the decision boundary along with the Gaussians.

3.9 SVM with Slack KKT Verification

Ans: Index of point exactly on the margin 3374 and the value of mu for this is 0.0004879. Index of point classified safely outside the margin 8564 and the value of mu for this is 7.87×10^{-13}. No point classified outside the margin, i.e., there is 100% training accuracy.

3.10 Mercer's Condition

Ans: The Kernel matrix satisfy the Mercer's condition. The highest and the lowest eigenvalue is near 1 for small λ and when the λ becomes high, the matrix is ill conditioned but the lowest eigen value is always greater than 0.

3.11 Hyperparameter Topography

Ans: Fig. 4b gives the heatmap of the search in the parameter space. Overfit occurs for all the $C \in \{1, 10, 100\}$ and $\sigma \in \{0.001, 0.01, 0.1, 1\}$. Only $\sigma = 10$ is able to fit the data properly.



(a) GM Decision Boundary



(b) Heatmap of the training and validation accuracies