## Specifications in detail

- a) All RCC works will be carried out as per Structured Consultant drawings.
- b) Basement height not escapeding 36"
  from the natural ground level, filled
  with good quality pit sand with foroper
  consolidation.
- Consolidation. treatment out of proper past Control will be carried out at different stages as per poro cedure.
- at different stopen on pur poro cedure.

  d) All outerwalls will be of 9" and 41/2"

  thick respectively bout with well burnt

  chamber Red bricks.
- e) All electrical works will be carried out as per electrical drawings issued by Architects Complete wires are of Kundan/Malla/ or of equivalent make and Scritches of DB Board are of Legrand make.

## b) Joinerias D

- 1) For main door both for frames and shutters burna teals wood will be und with panelled shutters.
- 2) For all other doors first quality Endian Teck wood will be used for frames and for bedroom door shutters stin door will be used and for toilets and service areas water proof this does will be used.
- 3) Uprc windows either opening or sliding type will be provided as per Architect suggestion.
- 4) All fiftings for Main door is of Brass and rest of the doors are of SS type.

Hooning

- 1) For general flooring 2'0" x 2'0" vitrified tiles will be provided basic not exceeding 1360/= per sqft including
  - 2) For hathroom and kitchen well tiles will be provided for To" and 2's" height respectively and the basic rate of which will not occeed \$ 60/2 per Soft.
  - 3) Star care steps and landing area granite will be provided and SS Handrail of 304 grade will be provided.

ZK











Painting

- 1) Melamine polish will be forovided for orain door and for other doors and shutter enemel paint will be forovided over
- 2) For inner walls Birla cement based patty will be promided.

  Our which 2 eachs of emmls ion paint will be promided.
- 3) For all extenors walls 2 easts of apex emulsion will be provided over a cost of primer.
- 4) R.C.C over head fank mill be from ded in the gadepart copacity
- 5) under ground water storage sump will be formided with capacity not less than 16,000 litres.

6/ Rubber would paver blocks will be provided for all set back areas and can parking arean

7) polished blank granite will be provided for Cooling platform with Canysil sink of adequate size.

8/ RCe lofts will be provided for storage in all bet Room and katcher.

9) Cuddapah Raeles will be forvided for all wandroter and shelves.

10) Weathering Conse with Conventional method will be formided orn which presed tiles 9"x9" size will be laid.

1) M.S Safety qu'il se pourided for all main doors. parapet with 9" thick will be from ded for 3'-3" height

13) power back up for lift and all common area lights
will be provided.

(4) CCTV Camera parties Security purpose will be
prided along with vides door phone.