

Homework 7

1. Create a Solidity contract with one function

The function should return the amount of ETH that was passed to it, and the function body should be written in assembly

2. Do you know what this code is doing ?

```
push9 0x601e8060093d393df3
msize
mstore                                # mem = 000...000 601e8060093d393df3
                                      #      = 000...000 spawned constructor payload

# copy the runtime bytecode after the constructor code in mem
codesize                              # cs
returndatasize                        # 0 cs
msize                                 # 0x20 0 cs
codecopy                              # mem = 000...000 601e8060093d393df3
RUNTIME_BYTECODE

                                      # --- stack ---
push1 9                               # 9
codesize                              # cs 9
add                                  # cs+9 = CS = total codesize in memory

push1 23                             # 23 CS
returndatasize                        # 0 23 CS
dup3                                  # CS 0 23 CS

dup3                                  # 23 CS 0 23 CS
callvalue                             # v 23 CS 0 23 CS
create                                # addr1 0 23 CS
pop                                   # 0 23 CS

create                                # addr2

selfdestruct
```

See [gist](#)

The runtime bytecode for this contract is

0x68601e8060093d393df35952383d59396009380160173d828234f050f0ff

3. Explain what the following code is doing in the Yul ERC20 contract

```
function allowanceStorageOffset(account, spender) -> offset {  
    offset := accountToStorageOffset(account)  
    mstore(0, offset)  
    mstore(0x20, spender)  
    offset := keccak256(0, 0x40)  
}
```