

## NAME

**mbprocess** – this program performs a variety of swath data processing functions in a single step (producing a single output swath data file), including merging navigation, recalculating bathymetry from travel time and angle data by raytracing through a layered water sound velocity model, applying changes to ship draft, roll bias and pitch bias, applying tides, and applying bathymetry edits from edit save files.

## VERSION

Version 5.0

## SYNOPSIS

```
mbprocess --input=infile {-infile}
[--threads=value {-Cvalue}
--format=value {-Fvalue}
--strip-comments {-N}
--output=file {-Ofile}
--force {-P}
--print-status {-S}
--test {-T}
--verbose {-V}
--help {-H}]
```

## DESCRIPTION

The program **mbprocess** is a tool for processing swath sonar bathymetry data. This program can perform a variety of swath data processing functions in a single step (producing a single output swath data file), including:

- Merge edited navigation generated by **mbnavedit**.
- Apply bathymetry edit flags from **mbedit** and **mbclean**
- Recalculate bathymetry from raw travel time and angle data by raytracing through water sound speed models from **mbvelocitytool** or **mbsvplist**.
- Apply changes to roll bias, pitch bias, heading bias, and draft values.
- Recalculate sidescan from raw backscatter samples (Simrad multibeam data only).
- Apply corrections to sidescan based on amplitude vs grazing angle tables obtained with **mbbackangle**.
- Apply tides to bathymetry.
- Insert metadata.

The actions of **mbprocess** are controlled by text parameter files. Each **mbprocess** parameter file contains single line commands that set processing modes and parameters. The program **mbset** can be used to create and modify **mbprocess** parameter files. Other programs such as **mbedit**, **mbnavedit**, **mbvelocitytool**, **mbnavadjust**, and **mbclean** modify or create (if needed) **mbprocess** parameter files.

The input file "infile" must be specified with the **-I** option. If "infile" is a datalist, then **mbprocess** will attempt to process each swath data file identified by recursively reading the datalist. Otherwise, **mbprocess** will attempt to process "infile" directly.

For any swath data file "datafile", the program will look for and use a parameter file with the name "datafile.par". If no parameter file exists, **mbprocess** will infer a reasonable processing path by looking for navigation and mbedit edit save files. The data format can also be specified, though the program can infer the

format if the standard MB-System suffix convention is used (\*.mbXX where XX is the MB-System format id number).

The processed output swath files produced by **mbprocess** are named using a convention based on the data format id. **MB-System** data formats are specified using two-digit or three-digit numbers (see the **MBIO** manual page). If an input swath data file is named "root.mbXX", where XX is the format id, then the default processed output file will be "rootp.mbXX" (e.g. mydata.mb71 -> mydatap.mb71). The "p" inserted before the ".mbXX" suffix indicates the output file has been created by **mbprocess**. If the input file does not follow the \*.mbXX naming convention, then the output filename will just consist of the input name with "p.mbXX" added as a suffix (e.g. mydata -> mydatap.mb71)

By default, **mbprocess** will only process a swath data file if the processed output file is either missing or out of date relative to the input swath data file, the parameter file, or any of the ancillary data files referred to in the parameter file (e.g. navigation files, edit save files, svp files). If the **-P** option is specified, **mbprocess** will process every file, whether it needs it or not.

As of release 5.7.7, **mbprocess** can process files in parallel using multiple threads. By default a single thread is used, but the **-Cthreads** option allows more threads to be used. The maximum number of threads available corresponds to the number of CPU cores available on the relevant computer.

## MBPROCESS PARAMETER FILE COMMANDS

The **mbprocess** commands found in parameter files are:

### GENERAL PARAMETERS:

#### EXPLICIT

- causes mbprocess to set modes implicitly
- e.g. the SVPFILE command will also set raytracing on even if the RAYTRACE command is not given [explicit mode commands required]

#### FORMAT constant

- sets format id [no default]

#### INFILE filename

- sets input file path [no default]

#### OUTFILE filename

- sets output file path [no default]

### NAVIGATION MERGING:

#### NAVMODE boolean

- sets navigation merging [0]
- 0: navigation merge off
- 1: navigation merge on

#### NAVFILE filename

- sets navigation file path [no default]

#### NAVFORMAT constant

- sets navigation file format [9]
- see below (NAVIGATION FORMATS section) for documentation of the supported navigation formats;
- formats 1-10 are ASCII text, format 11 is RVDAS binary-like text, and format 12 is Kongsberg Navlab binary

#### NAVHEADING boolean

- sets heading to be merged from navigation file
- note: heading merged from navigation before

heading correction applied  
0: heading not changed  
1: heading merged from navigation file

NAVSPEED boolean  
sets speed to be merged from navigation file  
0: speed not changed  
1: speed merged from navigation file

NAVDRAFT boolean  
sets draft to be merged from navigation file  
– note: draft merged from navigation before draft correction applied  
0: draft not changed  
1: draft merged from navigation file

NAVATTITUDE boolean  
sets roll, pitch and heave to be merged from navigation file  
– note: roll, pitch, and heave merged from navigation before roll bias and pitch bias corrections applied  
0: roll, pitch, and heave not changed  
1: roll, pitch, and heave merged from navigation file

NAVINTERP boolean  
sets navigation interpolation algorithm [0]  
0: linear interpolation (recommended)  
1: spline interpolation

NAVTIMESHIFT constant  
sets navigation time shift (seconds) [0.0]  
– note: time shift added to timestamps of navigation fixes read in from NAVFILE prior to merging

NAVIGATION OFFSETS AND SHIFTS:  
– These offsets and shifts will be applied to the original navigation and to any merged navigation, but will not be applied to adjusted navigation (because generally adjusted navigation generated by mbnavadjust already has offsets and shifts applied).

NAVSHIFT boolean  
sets navigation offset [0]  
– note: offsets and shifts are applied to navigation values from both survey and navigation records, and are applied to navigation read in from NAVFILE prior to merging  
– note: offsets and shifts are NOT applied to adjusted navigation values from NAVADJFILE

NAVOFFSETX constant  
sets navigation athwartship offset (meters) [0.0]  
– note: the effective navigation shift is (NAVOFFSETX – SONAROFFSETX), and the navigation is corrected by subtracting this effective shift.

- note: athwartship shift is positive to starboard.

**NAVOFFSETY** constant

sets navigation fore-aft offset (meters) [0.0]

- note: the effective navigation shift is (NAVOFFSETY – SONAROFFSETY), and the navigation is corrected by subtracting this effective shift.

- note: fore-aft shift is positive forward.

**NAVOFFSETZ** constant

sets navigation vertical offset (meters) [0.0]

- note: this value is not yet used for anything.

- note: vertical shift is positive down.

**NAVSHIFTLON** constant

sets navigation longitude shift (degrees) [0.0]

**NAVSHIFTLAT** constant

sets navigation latitude shift (degrees) [0.0]

**NAVSHIFTX** constant

sets navigation longitude shift (meters) [0.0]

**NAVSHIFTY** constant

sets navigation latitude shift (meters) [0.0]

**ADJUSTED NAVIGATION MERGING:****NAVADJMODE** mode

sets navigation merging from mbnadjust [0]

- can apply to longitude and latitude only or longitude, latitude, and depth offset
- 0: adjusted navigation merge off
- 1: adjusted navigation merge on
- 2: adjusted navigation and depth offset merge on

**NAVADJFILE** filename

sets adjusted navigation file path

- this file supercedes navigation file for lon and lat only
- uses mbnadjust output

**NAVADJINTERP** boolean

sets adjusted navigation interpolation algorithm [0]

- 0: linear interpolation (recommended)
- 1: spline interpolation

**ATTITUDE MERGING:****ATTITUDEMODE** mode

sets attitude (roll, pitch, and heave) merging [0]

- roll, pitch, and heave merged before roll bias and pitch bias corrections applied
- attitude merging from a separate file supercedes attitude merging from a navigation file
- 0: attitude merging off
- 1: attitude merging on

**ATTITUDEFILE** filename

sets attitude file path

**ATTITUDEFORMAT** constant

sets attitude file format [1]  
 – attitude files can be in one of several formats:  
 1: format is <time\_d roll pitch heave>  
 2: format is <yr mon day hour min sec roll pitch heave>  
 3: format is <yr jday hour min sec roll pitch heave>  
 4: format is <yr jday daymin sec roll pitch heave>  
 9: format is full MBPRONAV (\*.nve) format with  
     roll, pitch, and heave fields  
 11: RVDAS \$SPRINT format; roll and pitch extracted;  
     heave set to zero  
 12: Kongsberg Navlab binary (navlab\_smooth.bin);  
     roll from field 7, pitch from field 8;  
     heave set to zero (not available)  
 – time\_d = decimal seconds since 1/1/1970  
 – daymin = decimal minutes start of day  
 – roll = positive starboard up, degrees  
 – pitch = positive forward up, degrees  
 – heave = positive up, meters

#### SONARDEPTH MERGING:

SONARDEPTHMODE mode  
 sets sonardepth merging [0]  
 – sonardepth merged before  
     draft corrections applied  
 – sonardepth merging from a separate file supersedes  
     draft merging from a navigation file  
 0: sonardepth merging off  
 1: sonardepth merging on

#### SONARDEPTHFILE filename

sets sonardepth file path

#### SONARDEPTHFORMAT constant

sets sonardepth file format [1]  
 – sonardepth files can be in one of several formats:  
 1: format is <time\_d sonardepth>  
 2: format is <yr mon day hour min sec sonardepth>  
 3: format is <yr jday hour min sec sonardepth>  
 4: format is <yr jday daymin sec sonardepth>  
 9: format is full MBPRONAV (\*.nve) format;  
     sonardepth from the sensordepth field  
 11: RVDAS \$SPRINT format; depth extracted from  
     the depth field of the \$SPRINT sentence  
 12: Kongsberg Navlab binary (navlab\_smooth.bin);  
     sensordepth from field 3 (meters, positive down)  
 – time\_d = decimal seconds since 1/1/1970  
 – daymin = decimal minutes start of day  
 – sonardepth = sonar depth positive down, meters

#### DATA CUTTING:

##### DATAUTCLEAR

removes all existing data cutting commands

##### DATAUTC kind mode min max

adds new data cutting command, where:

kind = 0 : cut applied to bathymetry data

kind = 1 : cut applied to amplitude data  
kind = 2 : cut applied to sidescan data  
mode = 0 : no data are flagged or zeroed  
mode = 1 : min and max indicate start and end  
beam/pixel numbers between which data  
are flagged or zeroed  
mode = 2 : min and max indicate start and end  
acrosstrack distance (m) between which  
data are flagged or zeroed  
mode = 3 : min and max indicate minimum and  
platform speed (km/hr) between which  
data are flagged or zeroed

**BATHCUTNUMBER min max**

adds new bathymetry data cutting command where  
min and max are the start and end beam numbers  
between which data are flagged (note that  
flagging bathymetry also flags amplitude data)

**BATHCUTDISTANCE min max**

adds new bathymetry data cutting command where  
min and max are the start and end acrosstrack  
distance (m) between which data are flagged  
(note that flagging bathymetry also flags  
amplitude data)

**BATHCUTSPEED min max**

adds new bathymetry data cutting command where  
all beams are flagged for pings with a ship  
or vehicle speed less than min or greater than  
max (note that flagging bathymetry also flags  
amplitude data)

**AMPCUTNUMBER min max**

adds new amplitude data cutting command where  
min and max are the start and end beam numbers  
between which amplitude data are zeroed (note  
that zeroing amplitude data has no impact on  
bathymetry data)

**AMPCUTDISTANCE min max**

adds new amplitude data cutting command where  
min and max are the start and end acrosstrack  
distance (m) between which amplitude data are  
zeroed (note that zeroing amplitude data has  
no impact on bathymetry data)

**AMPCUTSPEED min max**

adds new amplitude data cutting command where  
all amplitude values are zeroed for pings with  
a ship or vehicle speed less than min or greater  
than max (note that zeroing amplitude data has  
no impact on bathymetry data)

**SSCUTNUMBER min max**

adds new sidescan data cutting command where  
min and max are the start and end pixel numbers  
between which sidescan data are zeroed (note  
that zeroing sidescan data has no impact on  
bathymetry data)

**SSCUTDISTANCE min max**

adds new sidescan data cutting command where min and max are the start and end across track distance (m) between which sidescan data are zeroed (note that zeroing sidescan data has no impact on bathymetry data)

**SSCUTSPEED min max**

adds new sidescan data cutting command where all sidescan values are zeroed for pings with a ship or vehicle speed less than min or greater than max (note that zeroing sidescan data has no impact on bathymetry data)

**BATHYMETRY EDITING:****EDITSAVEMODE boolean**

turns on reading edit save file (from mbedit) [0]

**EDITSAVEFILE filename**

sets edit save file path (from mbedit) [none]

**BATHYMETRY RECALCULATION:****SVPMODE mode**

sets usage of a water sound speed model (sound velocity profile, or SVP) [0]

0: bathymetry recalculation by raytracing off

1: bathymetry recalculation by raytracing on

2: translate depths from corrected to uncorrected or vice versa depending on SOUNDSPEEDREF command

**SVPMODE filename**

sets SVP file path [no default]

**SSVMODE boolean**

sets surface sound velocity (SSV) mode [0]

0: use SSV from file

1: offset SSV from file (set by SSV command)

2: use constant SSV (set by SSV command)

**SSV constant/offset**

sets SSV value or offset (m/s) [1500.0]

**ANGLEMODE mode**

sets handling of beam angles during raytracing [1]

0: angles not changed before raytracing

1: angles adjusted using Snell's Law for the difference between the surface sound velocity (SSV) and the sound speed at the sonar depth in the SVP.

2: angles adjusted using Snell's Law and the sonar array geometry for the difference between the surface sound velocity (SSV) and the sound speed at the sonar depth in the SVP.

**TTMULTIPLY multiplier**

sets value multiplied by travel times [1.0]

**SOUNDSPEEDREF boolean**

determines the handling of the sound speed reference for bathymetry [1]  
– note: if raytracing is turned off then this command implies correcting or uncorrecting using the SVP specified with the SVPFILE command  
0: produce "uncorrected" bathymetry referenced to a uniform 1500 m/s water sound speed model.  
1: produce "corrected" bathymetry referenced to a realistic water sound speed model.

#### STATIC BEAM BATHYMETRY OFFSETS:

##### STATICMODE mode

sets offsetting of bathymetry by per-beam statics [0]

0: static correction off

1: static correction by beam number

2: static correction by acrosstrack beam angle

##### STATICFILE filename

sets static per-beam file path [no default]

– static files are two-column ascii tables

– if correction is by beam number then the beam # is in column 1 and the depth offset is in m in column 2

– if correction is by beam angle then the beam angle (starboard positive) is in column 1 and the depth offset is in m in column 2

#### DRAFT CORRECTION:

##### DRAFTMODE mode

sets draft correction [0]

– note: draft merged from navigation before draft correction applied

0: no draft correction

1: draft correction by offset

2: draft correction by multiply

3: draft correction by offset and multiply

4: draft set to constant

##### DRAFT constant

sets draft value (m) [0.0]

##### DRAFTOFFSET offset

sets value added to draft (m) [0.0]

##### DRAFTMULTIPLY multiplier

sets value multiplied by draft [1.0]

#### HEAVE CORRECTION:

##### HEAVEMODE mode

sets heave correction [0]

– note: heave correction by offset and/or multiplication is added to any lever

heave correction, and then either used in bathymetry recalculation or added to existing bathymetry  
0: no heave correction  
1: heave correction by offset  
2: heave correction by multiply  
3: heave correction by offset and multiply

HEAVEOFFSET offset

sets value added to heave (m)

HEAVEMULTIPLY multiplier

sets value multiplied by heave

#### LEVER CORRECTION:

LEVERMODE mode

sets heave correction by lever calculation [0]

– note: lever heave correction is added to any heave correction by offset and/or multiplication, and then either used in bathymetry recalculation or added to existing bathymetry

0: no lever calculation

1: heave correction by lever calculation

VRUOFFSETX constant

sets athwartships offset of attitude sensor (m)

– note: positive to starboard

VRUOFFSETY constant

sets fore–aft offset of attitude sensor (m)

– note: positive forward

VRUOFFSETZ constant

sets vertical offset of attitude sensor (m)

– note: positive down

SONAROFFSETX constant

sets athwartships offset of sonar receive array (m)

– note: positive to starboard

SONAROFFSETY constant

sets fore–aft offset of sonar receive array (m)

– note: positive forward

SONAROFFSETZ constant

sets vertical offset of sonar receive array (m)

– note: positive down

#### ROLL CORRECTION:

ROLLBIASMODE mode

sets roll correction [0]

0: no roll correction

1: roll correction by single roll bias

2: roll correction by separate port and starboard roll bias

ROLLBIAS offset

sets roll bias (degrees)

ROLLBIASPORT offset

sets port roll bias (degrees)

ROLLBIASSTBD offset

sets starboard roll bias (degrees)

#### PITCH CORRECTION:

PITCHBIASMODE mode

sets pitch correction [0]

0: no pitch correction

1: pitch correction by pitch bias

PITCHBIAS offset

sets pitch bias (degrees)

#### HEADING CORRECTION:

HEADINGMODE mode

sets heading correction [no heading correction]

– note: heading merged from navigation before heading correction applied

0: no heading correction

1: heading correction using course made good

2: heading correction by offset

3: heading correction using course made good and offset

HEADINGOFFSET offset

sets value added to heading (degrees)

#### TIDE CORRECTION:

TIDEMODE mode

sets tide correction [0]

– note: tide added to bathymetry after all other calculations and corrections

0: tide correction off

1: tide correction on

TIDEFILE filename

sets tide file path

TIDEFORMAT constan

sets tide file format [1]

– tide files can be in one of four ASCII table formats

1: format is <time\_d tide>

2: format is <yr mon day hour min sec tide>

3: format is <yr jday hour min sec tide>

4: format is <yr jday daymin sec tide>

– time\_d = decimal seconds since 1/1/1970

– daymin = decimal minutes start of day

#### AMPLITUDE CORRECTION:

AMPCORRMODE boolean

sets correction of amplitude for amplitude vs grazing angle function

0: amplitude correction off

1: amplitude correction on

AMPCORRFILE filename

sets amplitude correction file path  
[no default]

**AMPCORRTYPE mode**

sets sidescan correction type [0]

0: correction by subtraction (dB scale)

1: correction by division (linear scale)

**AMPCORRSYMMETRY boolean**

forces correction function to be symmetric [1]

**AMPCORRANGLE constant**

sets amplitude correction reference angle

(deg) [30.0]

**AMPCORRSLOPE mode**

sets amplitude correction slope mode [0]

0: local slope ignored in calculating correction

1: local slope used in calculating correction

2: topography grid used in calculating correction  
but slope ignored

3: local slope from topography grid used in  
calculating correction

**SIDECAN CORRECTION:****SSCORRMODE boolean**

sets correction of sidescan for

amplitude vs grazing angle function

0: sidescan correction off

1: sidescan correction on

**SSCORRFILE filename**

sets sidescan correction file path

[no default]

**SSCORRTYPE mode**

sets sidescan correction type [0]

0: correction by subtraction (dB scale)

1: correction by division (linear scale)

**SSCORRSYMMETRY boolean**

forces correction function to be symmetric [1]

**SSCORRANGLE constant**

sets sidescan correction reference angle

(deg) [30.0]

**SSCORRSLOPE mode**

sets sidescan correction slope mode [0]

0: local slope ignored in calculating correction

1: local slope used in calculating correction

2: topography grid used in calculating correction  
but slope ignored

3: local slope from topography grid used in  
calculating correction

**AMPSSCORRTOPOFILE**

Sets topography grid used for correcting amplitude  
and sidescan

**SIDECAN RECALCULATION:****SSRECALCMODE boolean**

sets recalculation of sidescan for

Simrad multibeam data

0: sidescan recalculation off

1: sidescan recalculation on  
SSPIXELSIZE constant  
sets recalculated sidescan pixel size (m) [0.0]  
– a zero value causes the pixel size to  
be recalculated for every data record  
SSSWATHWIDTH constant  
sets sidescan swath width (degrees) [0.0]  
– a zero value causes the swath width  
to be recalculated for every data record  
SSINTERPOLATE constant  
sets sidescan interpolation distance  
(number of pixels)

#### METADATA INSERTION:

METAVESSEL string  
sets mbinfometadata string for vessel  
META-INSTITUTION string  
sets mbinfometadata string for vessel  
operator institution or company  
METAPLATFORM string  
sets mbinfometadata string for sonar  
platform (ship or vehicle)  
METASONAR string  
sets mbinfometadata string for sonar  
model name  
METASONARVERSION string  
sets mbinfometadata string for sonar  
version (usually software version)  
METACRUISEID string  
sets mbinfometadata string for institutional  
cruise id  
METACRUISENAME string  
sets mbinfometadata string for descriptive  
cruise name  
METAPI string  
sets mbinfometadata string for principal  
investigator  
METAPIINSTITUTION string  
sets mbinfometadata string for principal  
investigator  
METACLIENT string  
sets mbinfometadata string for data owner  
(usually PI institution)  
METASVCORRECTED boolean  
sets mbinfometadata boolean for sound  
velocity corrected depths  
METATIDECORRECTED boolean  
sets mbinfometadata boolean for tide  
corrected bathymetry  
METABATHEDITMANUAL boolean  
sets mbinfometadata boolean for manually  
edited bathymetry  
METABATHEDITAUTO boolean

sets mbinfo metadata boolean for automatically edited bathymetry

METAROLLBIAS constant  
sets mbinfo metadata constant for roll bias (degrees + to starboard)

METAPITCHBIAS constant  
sets mbinfo metadata constant for pitch bias (degrees + forward)

METAHEADINGBIAS constant  
sets mbinfo metadata constant for heading bias

METADRAFT constant  
sets mbinfo metadata constant for vessel draft (m)

#### PROCESSING KLUGES:

KLUGE001 boolean  
enables correction of travel times in Hydrosweep DS2 data from the R/V Maurice Ewing in 2001 and 2002.

KLUGE002 boolean  
enables correction of draft values in Simrad data

- some Simrad multibeam data has had an error in which the heave has been added to the sonar depth (draft for hull mounted sonars)
- this correction subtracts the heave value from the sonar depth

KLUGE003 boolean  
enables correction of beam angles in SeaBeam 2112 data

- a data sample from the SeaBeam 2112 on the USCG Icebreaker Healy (collected on 23 July 2003) was found to have an error in which the beam angles had 0.25 times the roll added
- this correction subtracts  $0.25 * \text{roll}$  from the beam angles before the bathymetry is recalculated by raytracing through a water sound velocity profile
- the mbprocess parameter files must be set to enable bathymetry recalculation by raytracing in order to apply this correction

KLUGE004 boolean  
deletes survey data associated with duplicate or reversed time tags

- if survey data records are encountered with time tags less than or equal to the last good time tag, an error is set and the data record is not output to the processed data file.

KLUGE005 boolean  
replaces survey record timestamps with

timestamps of corresponding merged navigation records

- this feature allows users to fix timestamp errors using MBnavedit and then insert the corrected timestamps into processed data

KLUGE006 boolean

- changes sonar depth / draft values without changing bathymetry values

KLUGE007 boolean

- processing kluge 007 (not yet defined)
- occasionally odd processing problems will occur that are specific to a particular survey or sonar version
- mbprocess will allow one-time fixes to be defined as "kluges" that can be turned on through the parameter files.

## ANCILLARY DATA FILES

**MB-System** also uses a number of ancillary data files, most of which relate to **mbprocess** in some way. By default, these ancillary data files are named by adding a short suffix to the primary data file name (e.g. ".par", ".svp", ".esf", ".nve")

The common ancillary files are listed below. The example names given here follow from an input swath data file name of mydata.mb71.

The processing parameter file used by **mbprocess** has an ".par" suffix. These files are generated or modified by **mbset**, **mbedit**, **mbnavedit**, **mbvelocitytool**, **mbnavadjust**, and **mbclean**.

mydata.mb71.par

The most prominent ancillary files are metadata or "inf" files (created from the output of **mbinfo**). Programs such as **mbgrid** and **mbm\_plot** try to check "inf" files to see if the corresponding data files include data within desired areas. The program **mbprocess** automatically generates an "inf" file for any processed output swath file. Also, the program **mbdatalist** is often used to create or update "inf" files for large groups of swath data files.

mydata.mb71.inf

The "fast bath" or "fbt" files are generated by copying the swath bathymetry to a sparse, quickly read format (format 71). Programs such as **mbgrid**, **mbswath**, and **mbcontour** will try to read "fbt" files instead of the full data files whenever only bathymetry information are required. The program **mbprocess** automatically generates an "fbt" file for any processed output swath file. Also, the program **mbdatalist** is often used to create or update "fbt" files for large groups of swath data files. These files are not generated or used when the original swath data is already in a compact bathymetry-only data format.

mydata.mb71.fbt

The "fast nav" or "fnv" files are just ASCII lists of navigation generated using **mblist** with a **-OtMXHYHSc** option. Programs such as **mbgrid**, **mbswath**, and **mbcontour** will try to read "fnv" files instead of the full data files whenever only navigation information are required. These files are not generated or used when the original data is already in a single-beam or navigation data format.

mydata.mb71.fnv

The bathymetry edit save file generated by **mbedit** and **mbclean** has an ".esf" suffix.

mydata.mb71.esf

A water sound velocity profile (SVP) file generated by **mbvelocitytool** has an ".svp" suffix unless the user specifies otherwise.

mydata.mb71.svp

Water sound velocity profile (SVP) files generated by **mbsvplist** also use the ".svp" suffix. However, multiple SVP files may be extracted from each input swath file, so the files are numbered using a "\_YYY.svp" suffix, where YYY increments from 001.

mydata.mb71\_001.svp

mydata.mb71\_002.svp

mydata.mb71\_003.svp

Edited navigation files generated by **mbnavedit** have an ".nve" suffix:

mydata.mb71.nve

These navigation files can be read independently using format 166.

Adjusted navigation files generated by **mbnavadjust** have an ".naY" suffix, where "Y" is a number between 0–9. The **mbnavadjust** package may be used multiple times for a survey; the adjustments are numbered sequentially from "0":

mydata.mb71.na0

mydata.mb71.na1

mydata.mb71.na2

and so on. These navigation files can be read independently using format 166.

## MB-SYSTEM AUTHORSHIP

David W. Caress

Monterey Bay Aquarium Research Institute

Dale N. Chayes

Center for Coastal and Ocean Mapping

University of New Hampshire

Christian do Santos Ferreira

MARUM - Center for Marine Environmental Sciences

University of Bremen

## OPTIONS

### --threads=value -Cvalue

Sets the number of separate threads launched to process swath files in parallel. The default is 1; the maximum is system dependent as it is set to the number of CPU cores available on the relevant computer.

### --format=value -Fvalue

Sets the **MBIO** integer format identifier for the input file specified with the **-I** option. By default, **mbprocess** derives the format id from the **mbprocess** parameter file associated with the input file (**-I** option) or, if necessary, infers the format from the "\*.mbXX" **MB-System** suffix convention.

### --help -H

This "help" flag causes the program to print out a description of its operation and then exit immediately.

### --input=file -Ifile

Swath data file from which the input data will be read, or a datalist file containing a list of input swath data files and/or other datalist files. If *infile* is a datalist file, then **mbprocess** will attempt to process all data files identified by recursively reading *infile*.

**--strip-comments -N**

By default, **mbprocess** passes any comment records it encounters in the input data to the output data file and additionally embeds new comment records detailing the processing parameters used by **mbprocess**. This option causes **mbprocess** to not pass new or old comment records to the output data file.

**--output=file -Ofile**

Data file to which the output data will be written. If no output file is specified, the output filename is set automatically. If an input swath data file is named "root.mbXX", where XX is the format id, then the default processed output file will be "rootp.mbXX". The "p" inserted before the ".mbXX" suffix indicates the output file has been created by **mbprocess**. If the input file does not follow the \*.mbXX naming convention, then the output filename will just consist of the input name with "p.mbXX" added as a suffix.

**--force -P**

By default, **mbprocess** will only process a swath data file if the processed output file is either missing or out of date relative to the input swath data file, the parameter file, or any of the ancillary data files referred to in the parameter file (e.g. navigation files, edit save files, svp files). If the **-P** option is specified, **mbprocess** will process every file, whether it needs it or not.

**--test -T**

This option puts **mbprocess** into a test mode. The program will report whether or not it would process a file, but it will not actually process the data or produce an output processed file.

**--print-status -S**

This option causes **mbprocess** to print out the status of each file (e.g. up to date, out of date, locked, unlocked) along with the file modification times used to determine if the output file is out of date.

**--verbose -V**

Normally, **mbprocess** works "silently" without outputting anything to the stderr stream. If the **-V** flag is given, then **mbprocess** works in a "verbose" mode and outputs the program version being used, the processing parameters being use, and some statistics regarding the processing accomplished.

## NAVIGATION FORMATS

The navigation formats that are supported for merging by **mbprocess** include the following:

| MBprocess ID | Name                                        |
|--------------|---------------------------------------------|
| -----        | -----                                       |
| 1            | Simple Decimal Time                         |
| 2            | Simple Date 1                               |
| 3            | Simple Date 2                               |
| 4            | Simple Date 3                               |
| 5            | L-DEO Processed Nav                         |
| 6            | NMEA 0183 - GLL                             |
| 7            | NMEA 0183 - GGA                             |
| 8            | Simrad 90 Nav                               |
| 9            | MBPRONAV (*.nve Files)                      |
| 10           | R2RNAV (*.hires.r2rnnav Files)              |
| 11           | RVDAS (\$SPRINT sentences)                  |
| 12           | Kongsberg Navlab Binary (navlab_smooth.bin) |

Format 1 (Simple Decimal Time):

- text
- fields separated by white space
- each line contains the following fields:  
time\_d lon lat

- time\_d : decimal seconds since 1970 Jan 1 00:00:00.00
- lon: decimal longitude (deg)
- lat: decimal latitude (deg)

#### Format 2 (Simple Date 1):

- text
- fields separated by white space
- each line contains the following fields:  
    yr mon day hour min sec lon lat
- yr: four-digit year
- mon: integer month of year
- day: integer day of month
- hour: integer hour of day
- min: integer minute of hour
- sec: decimal second of minute
- lon: decimal longitude (deg)
- lat: decimal latitude (deg)

#### Format 3 (Simple Date 2):

- text
- fields separated by white space
- each line contains the following fields:  
    yr jday hour min sec lon lat
- yr: four-digit year
- jday: integer julian day of year
- hour: integer hour of day
- min: integer minute of hour
- sec: decimal second of minute
- lon: decimal longitude (deg)
- lat: decimal latitude (deg)

#### Format 4 (Simple Date 3):

- text
- fields separated by white space
- each line contains the following fields:  
    yr jday daymin sec lon lat
- yr: four-digit year
- jday: integer julian day of year
- daymin: integer minute of day
- sec: decimal second of minute
- lon: decimal longitude (deg)
- lat: decimal latitude (deg)

#### Format 5 (L-DEO Processed Nav):

- text
- fields separated by white space
- each line contains the following fields:  
    timetag NorS latd latm EorW lond lonm src dr1 dr2
- timetag: comes in two forms  
    form 1: yy+jjj:hh:mm:ss.sss  
    form 2: yyyy+jjj:hh:mm:ss.sss
- yy: either two-digit or four-digit year
- jjj: integer julian day of year

- hh: integer hour of day
- mm: integer minute of hour
- ss.sss: decimal second of minute
- NorS: 'S' for southern hemisphere  
      'N' for northern hemisphere
- latd: integer latitude degrees
- latm: decimal latitude minutes
- EorW: 'E' for eastern hemisphere  
      'W' for western hemisphere
- lond: integer longitude degrees
- lonm: decimal longitude minutes
- src: nav source (e.g. gp1, dr, satl)  
      'gp1' - GPS receiver 1  
      'dr' - dead reckoning  
      'satl' - transit satellite
- dr1: nonzero when src is 'dr'
- dr2: nonzero when src is 'dr'

Format 6 (NMEA 0183 - GLL):

- text
- fields separated by commas
- nav derived from GLL strings

Format 7 (NMEA 0183 - GGA):

- text
- fields separated by commas
- nav derived from GGA strings

Format 8 (Simrad 90 Nav):

- text
- fields not separated by white space
- each line contains the following fields:
  - ddmmyy\_hhmmss.ss\_LLLLLLIN\_LLLLLIIIE - dd: day of month
- mm: integer month of year - yy: two-digit year
- hh: integer hour of day
- mm: integer minute of hour
- ss.ss: decimal second of minute
- LL: integer latitude degrees
- llll: integer latitude minutes X 1000
- N: 'S' for southern hemisphere  
      'N' for northern hemisphere
- LLL: integer longitude degrees
- llll: integer longitude minutes X 1000
- E: 'E' for eastern hemisphere  
      'W' for western hemisphere

Format 9 (MBPRONAV (\*.nve Files)):

- text
- fields separated by white space
- each line contains at least 9, and possibly as many as 19, of the following fields:
  - yr mn dy hr mi se td ln lt hg sp dr rl pt hv pln plt sln slt
- yr: four-digit year
- mn: integer month of year

- dy: integer day of month
- hr: integer hour of day
- mi: integer minute of hour
- se: decimal second of minute
- td : decimal seconds since 1970 Jan 1 00:00:00.00
- ln: decimal longitude (deg)
- lt: decimal latitude (deg)
- hg: decimal heading (deg)
- sp: decimal speed (km/hr)
- dr: decimal draft (m)
- rl: decimal roll (deg)
- pt: decimal pitch (deg)
- hv: decimal heave (m)
- pln: decimal longitude of portmost sounding (deg)
- plt: decimal latitude of portmost sounding (deg)
- sln: decimal longitude of starboardmost sounding (deg)
- slt: decimal latitude of starboardmost sounding (deg)

Format 10 (R2RNAV (\*\_hires.r2rnav Files)):

- text
  - also works with \*\_1min.r2rnav and \*\_control.r2rnav files
  - these lack the GPS parameters
- defined by SIO GDC as part of the R2R project
- columns separated by tabs
- each line contains the following fields
  - yyyy-mm-ddThh:mm:ss.sssZ lon lat q n d h
- yyyy: four-digit year
- mm: integer month of year
- dd: integer day of month
- T: the letter "T" is always between the date and the time
- hh: integer hour of day
- mm: integer minute of hour
- ss.sss: decimal second of minute
- Z: the letter "Z" is always there to specify UTC time zone
- lo: decimal longitude (deg) (-180 to +180)
- la: decimal latitude (deg) (-90 to +90)
- q: GPS quality
- n: number of GPS satellites
- d: GPS dilution
- h: GPS antenna height (m)

Format 11 (RVDAS (\$SPRINT sentences)):

- text
- fields separated by commas, one record per line
- each line contains the following fields:
  - yyyy-mm-ddThh:mm:ss.sssZ,\$SPRINT,roll,pitch,heading,attitude\_status,lat,lon,position\_status,vel\_fwd,vel\_stbd,vel\_down,altitude,altitude\_status,depth,depth\_status
- yyyy-mm-ddThh:mm:ss.sssZ: ISO 8601 UTC timestamp
- roll: decimal roll (deg, positive starboard up)
- pitch: decimal pitch (deg, positive bow up)
- heading: decimal heading (deg, 0-360 clockwise from north)
- attitude\_status: integer quality flag
- lat: decimal latitude (deg, positive north)

- lon: decimal longitude (deg, positive east)
- position\_status: integer quality flag
- vel\_fwd: forward velocity (m/s)
- vel\_stbd: starboard velocity (m/s)
- vel\_down: downward velocity (m/s)
- altitude: altitude above seafloor (m)
- altitude\_status: integer quality flag
- depth: sensor depth (m, positive down)
- depth\_status: integer quality flag

Format 12 (Kongsberg Navlab Binary (navlab\_smooth.bin)):

- binary
- no file header
- each record consists of exactly 21 IEEE 754 double-precision (64-bit) floating-point values in little-endian byte order
- record size: 168 bytes (21 x 8 bytes)
- typically sampled at 100 Hz (10 ms time steps)
- output of the Kongsberg Navlab post-processing software, which computes a smoothed navigation and attitude solution for Kongsberg Hugin AUVs
- fields used by mbprocess:
  - field 0: time\_d (decimal seconds since 1970 Jan 1 00:00:00.00)
  - field 1: latitude (decimal degrees, positive north)
  - field 2: longitude (decimal degrees, positive east)
  - field 3: depth (m, positive down); used as sensor depth
  - field 6: heading (deg, 0-360, clockwise from north)
  - field 7: roll (deg, positive starboard up)
  - field 8: pitch (deg, positive bow up)
- speed is not stored; set to zero when used as nav source
- heave is not stored; set to zero when used as attitude source
- NAVHEADING, NAVATTITUDE flags are supported with this format
- the same file can be specified for NAVFILE, ATTITUDEFILE, and SONARDEPTHFILE simultaneously

## EXAMPLES

Suppose the user has a Simrad EM120 data file called "0051\_20010829\_223755.mb57" that requires processing.

Editing the bathymetry data in this file with mbedit will generate an edit save file "0051\_20010829\_223755.mb57.esf" and an mbprocess parameter file "0051\_20010829\_223755.mb57.par". The contents of the parameter file are:

```
## MB-System processing parameter file
## Written by mb_pr_writepar version $Id$
## MB-system Version 5.0.beta22
## Generated by user <caress> on cpu <menard> at <Fri Sep 6 21:27:41 2002>
##
##
## Forces explicit reading of parameter modes.
EXPLICIT
##
## General Parameters:
FORMAT 57
```

```
INFILE /data/0051_20010829_223755.mb57
OUTFILE /data/0051_20010829_223755p.mb57
##
## Navigation Merging:
NAVMODE 0
NAVFILE /data/0051_20010829_223755.mb57.nve
NAVFORMAT 0
NAVHEADING 0
NAVSPEED 0
NAVDRAFT 0
NAVATTITUDE 0
NAVINTERP 0
NAVTIMESHIFT 0.000000
##
## Navigation Offsets and Shifts:
NAVSHIFT 0
NAVOFFSETX 0.000000
NAVOFFSETY 0.000000
NAVOFFSETZ 0.000000
NAVSHIFTLON 0.000000
NAVSHIFTLAT 0.000000
##
## Adjusted Navigation Merging:
NAVADJMODE 0
NAVADJFILE
NAVADJINTERP 0
##
## Attitude Merging:
ATTITUDEMODE 0
ATTITUDEFILE
ATTITUDEFORMAT 1
##
## Sonardepth Merging:
SONARDEPTHMODE 0
SONARDEPTHFILE
SONARDEPTHFORMAT 1
##
## Data cutting:
DATACUTCLEAR
##
## Bathymetry Flagging:
EDITSAVEMODE 1
EDITSAVEFILE /data/0051_20010829_223755.mb57.esf
##
## Bathymetry Recalculation:
SVPMODE 0
SVPFILE
SSVMODE 0
SSV 0.000000
TTMODE 0
TTMULTIPLY 1.000000
ANGLEMODE 0
SOUNDSPEEDREF 1
```

```
##
## Draft Correction:
DRAFTMODE 0
DRAFT 0.000000
DRAFTOFFSET 0.000000
DRAFTMULTIPLY 1.000000
##
## Heave Correction:
HEAVEMODE 0
HEAVEOFFSET 0.000000
HEAVEMULTIPLY 1.000000
##
## Lever Correction:
LEVERMODE 0
VRUOFFSETX 0.000000
VRUOFFSETY 0.000000
VRUOFFSETZ 0.000000
SONAROFFSETX 0.000000
SONAROFFSETY 0.000000
SONAROFFSETZ 0.000000
##
## Roll Correction:
ROLLBIASMODE 0
ROLLBIAS 0.000000
ROLLBIASPORT 0.000000
ROLLBIASSTBD 0.000000
##
## Pitch Correction:
PITCHBIASMODE 0
PITCHBIAS 0.000000
##
## Heading Correction:
HEADINGMODE 0
HEADINGOFFSET 0.000000
##
## Tide Correction:
TIDEMODE 0
TIDEFILE
TIDEFORMAT 1
##
## Amplitude Correction:
AMPCORRMODE 0
AMPCORRFILE
AMPCORRTYPE 0
AMPCORRSYMMETRY 1
AMPCORRANGLE 30.000000
AMPCORRSLOPE 0
##
## Sidescan Correction:
SSCORRMODE 0
SSCORRFILE
SSCORRTYPE 0
SSCORRSYMMETRY 1
```

```
SSCORRANGLE 30.000000
SSCORRSLOPE 0
##
## Sidescan Recalculation:
SSRECALCMODE 0
SSPIXELSIZE 0.000000
SSSWATHWIDTH 0.000000
SSINTERPOLATE 0
##
## Metadata Insertion:
METAVESSEL
META-INSTITUTION
METAPLATFORM
METASONAR
METASONARVERSION
METACRUISEID
METACRUISENAME
METAPI
METAPIINSTITUTION
METACLIENT
METASVCORRECTED -1
METATIDECORRECTED -1
METABATHEDITMANUAL -1
METABATHEDITAUTO -1
METAROLLBIAS 0.000000
METAPITCHBIAS 0.000000
METAHEADINGBIAS 0.000000
METADRAFT 0.000000
##
## Processing Kluges
```

Editing the navigation with `mbnavedit` will generate a navigation file named "0051\_20010829\_223755.mb57.nve" and will modify the parameter file. The changed lines in "0051\_20010829\_223755.mb57.par" are:

```
## Navigation Merging:
NAVMODE 1
NAVFILE /data/0051_20010829_223755.mb57.nve
NAVFORMAT 9
NAVHEADING 1
NAVSPEED 1
NAVDRAFT 1
NAVATTITUDE 1
```

At this point, running **mbprocess** on "0051\_20010829\_223755.mb57" will apply the bathymetry flags from **mbedit** and merge the navigation from **mbnavedit**, but will not modify the data in any other way.

If the user wants to recalculate the bathymetry using an SVP file "0051\_20010829\_223755.mb57.svp" and a roll bias correction of +0.5 degrees, the following will suffice:

```
mbset -I 0051_20010829_223755.mb57 -PSVPFILE:0051_20010829_223755.mb57.svp
-PROLLBIAS:0.5 -PDRAFT:1.95 -V
```

The affected lines in "0051\_20010829\_223755.mb57.par" are:

```
##  
## Bathymetry Recalculation:  
SVPMODE 1  
SVPFILE 0051_20010829_223755.mb57.svp  
SSVMODE 0  
SSV 0.000000  
TTMODE 0  
TTMULTIPLY 1.000000  
ANGLEMODE 0  
SOUNDSPEEDREF 1  
##  
## Draft Correction:  
DRAFTMODE 4  
DRAFT 1.950000  
DRAFTOFFSET 0.000000  
DRAFTMULTIPLY 1.000000  
##  
## Roll Correction:  
ROLLBIASMODE 1  
ROLLBIAS 0.500000  
ROLLBIASPORT 0.000000  
ROLLBIASSTBD 0.000000
```

To process the data, run mbprocess:

```
mbprocess -I0051_20010829_223755.mb57 -V
```

The output to the terminal is:

```
Program mbprocess  
MB-System Version 5.0.beta07
```

```
Program <mbprocess>  
MB-system Version 5.0.beta07
```

Program Operation:

```
Input file: 0051_20010829_223755.mb57  
Format: 57  
Files processed only if out of date.  
Comments embedded in output.
```

Data processed – out of date:

```
Input: 0051_20010829_223755.mb57  
Output: /u/mbuser/survey/0051_20010829_223755p.mb57
```

Input and Output Files:

```
Format: 57  
Input file: 0051_20010829_223755.mb57  
Output file: /u/mbuser/survey/0051_20010829_223755p.mb57  
Comments in output: ON
```

Navigation Merging:

Navigation merged from navigation file.  
Heading merged from navigation file.  
Speed merged from navigation file.  
Draft merged from navigation file.  
Navigation file: /u/mbuser/survey/0051\_20010829\_223755.mb57.nve  
Navigation algorithm: linear interpolation  
Navigation time shift: 0.000000

Navigation Offsets and Shifts:  
Navigation positions not shifted.

Adjusted Navigation Merging:  
Navigation not merged from adjusted navigation file.  
Adjusted navigation file:  
Adjusted navigation algorithm: linear interpolation

Data Cutting:  
Data cutting disabled.

Bathymetry Editing:  
Bathymetry edits applied from file.  
Bathymetry edit file: 0051\_20010829\_223755.mb57.esf

Bathymetry Recalculation:  
Bathymetry recalculated by raytracing.  
SVP file: 0051\_20010829\_223755.mb57.svp  
SSV not modified.  
SSV offset/constant: 0.000000 m/s  
Travel time multiplier: 1.000000 m

Bathymetry Water Sound Speed Reference:  
Output bathymetry reference: CORRECTED  
Depths recalculated as corrected

Draft Correction:  
Draft set to constant.  
Draft constant: 1.950000 m  
Draft offset: 0.000000 m  
Draft multiplier: 1.000000 m

Heave Correction:  
Heave not modified.  
Heave offset: 0.000000 m  
Heave multiplier: 1.000000 m

Lever Correction:  
Lever calculation off.

Tide Correction:  
Tide calculation off.

Roll Correction:  
Roll offset by bias.

Roll bias: 0.500000 deg  
 Port roll bias: 0.000000 deg  
 Starboard roll bias: 0.000000 deg

Pitch Correction:  
 Pitch not modified.  
 Pitch bias: 0.000000 deg

Heading Correction:  
 Heading not modified.  
 Heading offset: 0.000000 deg

Amplitude Corrections:  
 Amplitude correction off.

Sidescan Corrections:  
 Sidescan correction off.

Sidescan Recalculation:  
 Sidescan not recalculated.  
 Sidescan pixel size: 0.000000  
 Sidescan swath width: 0.000000  
 Sidescan interpolation: 0

Metadata Insertion:  
 Metadata vessel:  
 Metadata institution:  
 Metadata platform:  
 Metadata sonar:  
 Metadata sonarversion:  
 Metadata cruiseid:  
 Metadata cruisename:  
 Metadata pi:  
 Metadata piinstitution:  
 Metadata client:  
 Metadata svcorrected: -1  
 Metadata tidecorrected -1  
 Metadata batheditmanual -1  
 Metadata batheditauto: -1  
 Metadata rollbias: 0.000000  
 Metadata pitchbias: 0.000000  
 Metadata headingbias: 0.000000  
 Metadata draft: 0.000000

236 navigation records read  
 Nav start time: 2001 08 29 22:38:02.082999  
 Nav end time: 2001 08 29 23:37:22.322000

47 bathymetry edits read

236 input data records  
 3587 input nav records  
 17 input comment records

6617 input other records  
236 output data records  
3587 output nav records  
64 output comment records  
6617 output other records

Generating inf file for /u/mbuser/survey/0051\_20010829\_223755p.mb57  
Generating fbt file for /u/mbuser/survey/0051\_20010829\_223755p.mb57  
Generating fnv file for /u/mbuser/survey/0051\_20010829\_223755p.mb57

**SEE ALSO**

**mbsystem(1), mbset(1), mbedit(1), mbnavedit(1), mbvelocitytool(1)**

**BUGS**

You tell me.