

NAME

mbmakeplatform – creates or modifies an MB-System platform file.

VERSION

Version 5.0

SYNOPSIS

```
mbmakeplatform  
--output=plffile  
[  
  --verbose  
  --help  
  --input=plffile  
  --swath=datalist  
  --swath=swathfile  
  --swath-format=value  
  --platform-type-surface-vessel  
  --platform-type-tow-body  
  --platform-type-rov  
  --platform-type-auv  
  --platform-type-aircraft  
  --platform-type-satellite  
  --platform-name=string  
  --platform-organization=string  
  --platform-documentation-url=string  
  --platform-start-time=yyyy/mm/dd/hh/mm/ss.ssssss  
  --platform-end-time=yyyy/mm/dd/hh/mm/ss.ssssss  
  --add-sensor-sonar-echosounder  
  --add-sensor-sonar-multiechosounder  
  --add-sensor-sonar-sidescan  
  --add-sensor-sonar-interferometry  
  --add-sensor-sonar-multibeam  
  --add-sensor-sonar-multibeam-twohead  
  --add-sensor-sonar-subbottom  
  --add-sensor-camera-mono  
  --add-sensor-camera-stereo  
  --add-sensor-camera-video  
  --add-sensor-lidar-scan  
  --add-sensor-lidar-swath  
  --add-sensor-position  
  --add-sensor-compass  
  --add-sensor-vru  
  --add-sensor-imu  
  --add-sensor-ins  
  --add-sensor-ins-with-pressure  
  --add-sensor-ctd  
  --add-sensor-pressure  
  --add-sensor-soundspeed  
  --modify-sensor=sensorid  
  --modify-sensor-bathymetry  
  --modify-sensor-bathymetry1  
  --modify-sensor-bathymetry2
```

```
--modify-sensor-bathymetry3
--modify-sensor-backscatter
--modify-sensor-backscatter1
--modify-sensor-backscatter2
--modify-sensor-backscatter3
--modify-sensor-subbottom
--modify-sensor-subbottom1
--modify-sensor-subbottom2
--modify-sensor-subbottom3
--modify-sensor-camera
--modify-sensor-camera1
--modify-sensor-camera2
--modify-sensor-camera3
--modify-sensor-position
--modify-sensor-position1
--modify-sensor-position2
--modify-sensor-position3
--modify-sensor-depth
--modify-sensor-depth1
--modify-sensor-depth2
--modify-sensor-depth3
--modify-sensor-heading
--modify-sensor-heading1
--modify-sensor-heading2
--modify-sensor-heading3
--modify-sensor-rollpitch
--modify-sensor-rollpitch1
--modify-sensor-rollpitch2
--modify-sensor-rollpitch3
--modify-sensor-heave
--modify-sensor-heave1
--modify-sensor-heave2
--modify-sensor-heave3
--sensor-model=string
--sensor-manufacturer=string
--sensor-serialnumber=string
--sensor-capability-position
--sensor-capability-depth
--sensor-capability-altitude
--sensor-capability-velocity
--sensor-capability-acceleration
--sensor-capability-pressure
--sensor-capability-rollpitch
--sensor-capability-heading
--sensor-capability-magneticfield
--sensor-capability-temperature
--sensor-capability-conductivity
--sensor-capability-salinity
--sensor-capability-soundspeed
--sensor-capability-gravity
--sensor-capability-topography-echosounder
--sensor-capability-topography-interferometry
--sensor-capability-topography-sass
```

```
--sensor-capability-topography-multibeam
--sensor-capability-topography-photogrammetry
--sensor-capability-topography-structurefrommotion
--sensor-capability-topography-lidar
--sensor-capability-topography-structuredlight
--sensor-capability-topography-laserscanner
--sensor-capability-backscatter-echosounder
--sensor-capability-backscatter-sidescan
--sensor-capability-backscatter-interferometry
--sensor-capability-backscatter-sass
--sensor-capability-backscatter-multibeam
--sensor-capability-backscatter-lidar
--sensor-capability-backscatter-structuredlight
--sensor-capability-backscatter-laserscanner
--sensor-capability-photography
--sensor-capability-stereophotography
--sensor-capability-video
--sensor-capability-stereovideo
--sensor-capability1=value
--sensor-capability2=value
--sensor-offsets=x/y/z/azimuth/roll/pitch
--sensor-offset-positions=x/y/z
--sensor-offset-angles=azimuth/roll/pitch
--sensor-time-latency=value
--sensor-time-latency-model=file
--sensor-source-bathymetry
--sensor-source-bathymetry1
--sensor-source-bathymetry2
--sensor-source-bathymetry3
--sensor-source-backscatter
--sensor-source-backscatter1
--sensor-source-backscatter2
--sensor-source-backscatter3
--sensor-source-subbottom
--sensor-source-subbottom1
--sensor-source-subbottom2
--sensor-source-subbottom3
--sensor-source-camera
--sensor-source-camera1
--sensor-source-camera2
--sensor-source-camera3
--sensor-source-position
--sensor-source-position1
--sensor-source-position2
--sensor-source-position3
--sensor-source-depth
--sensor-source-depth1
--sensor-source-depth2
--sensor-source-depth3
--sensor-source-heading
--sensor-source-heading1
--sensor-source-heading2
--sensor-source-heading3
```

```
--sensor-source-rollpitch
--sensor-source-rollpitch1
--sensor-source-rollpitch2
--sensor-source-rollpitch3
--sensor-source-heave
--sensor-source-heave1
--sensor-source-heave2
--sensor-source-heave3
--modify-offsets=ioff/x/y/z/azimuth/roll/pitch
--modify-offset-positions=ioff/x/y/z
--modify-offset-angles=ioff/azimuth/roll/pitch
--modify-time-latency=value
--modify-time-latency-model=file
--end-sensor
--set-source-bathymetry=sensorid
--set-source-bathymetry1=sensorid
--set-source-bathymetry2=sensorid
--set-source-bathymetry3=sensorid
--set-source-backscatter=sensorid
--set-source-backscatter1=sensorid
--set-source-backscatter2=sensorid
--set-source-backscatter3=sensorid
--set-source-subbottom=sensorid
--set-source-subbottom1=sensorid
--set-source-subbottom2=sensorid
--set-source-subbottom3=sensorid
--set-source-camera=sensorid
--set-source-camera1=sensorid
--set-source-camera2=sensorid
--set-source-camera3=sensorid
--set-source-position=sensorid
--set-source-position1=sensorid
--set-source-position2=sensorid
--set-source-position3=sensorid
--set-source-depth=sensorid
--set-source-depth1=sensorid
--set-source-depth2=sensorid
--set-source-depth3=sensorid
--set-source-heading=sensorid
--set-source-heading1=sensorid
--set-source-heading2=sensorid
--set-source-heading3=sensorid
--set-source-rollpitch=sensorid
--set-source-rollpitch1=sensorid
--set-source-rollpitch2=sensorid
--set-source-rollpitch3=sensorid
--set-source-heave=sensorid
--set-source-heave1=sensorid
--set-source-heave2=sensorid
--set-source-heave3=sensorid ]
```

DESCRIPTION

Mbmakeplatform is used to create an **MB-System** platform file, which provides a complete description of the geometry of sensors on a survey platform, including the relative positional and angular offsets. Platform files are used by **mbpreprocess** to set up an **MB-System** processing structure for swath data. In many cases the preprocessing consists only of creating the ancillary files parallel to the raw files, but in others the data must be translated to different formats. The preprocessing step can also be used to merge navigation, attitude, sound speed, or other ancillary data with the survey data.

Platform files are needed for preprocessing only when survey data have been collected without integrating the asynchronous navigation and attitude data and when the positional and angular offsets between the survey sensor (e.g. multibeam sonar, lidar, stereo camera rig) have not been specified in the various data streams. Most often this situation is associated with custom survey systems on submerged platforms like autonomous underwater vehicles (AUVs) or remotely operated vehicles (ROVs). The few data formats supported with preprocessing functionality utilizing platform files include the Reson 7k format 88, the Teledyne 7k3 format 89, and the 3D at Depth lidar formats 232 and 233.

Generally platform files are created by a single execution of **Mbmakeplatform** with a long series of command line arguments that add sensors, set sensor capabilities, and set sensor positional and angular offsets. For some data formats **Mbmakeplatform** can initialize a platform structure by extracting the sensor offset values from swath data files. In most cases the source of position data is set as the platform origin with zero positional and angular offset values.

No platform file is needed for preprocessing when the logged datastream includes a full platform description. Specifically, all datasets collected using Kongsberg multibeam sonars do not require use of a platform file (the only exception to this would be if the positional offsets between sensors were incorrectly specified in the multibeam configuration).

Two examples are presented below, both of which are custom submerged survey platforms combining a number of both mapping and ancillary sensors, including an inertial navigation system producing navigation and attitude.

MB-SYSTEM AUTHORSHIP

David W. Caress
Monterey Bay Aquarium Research Institute
Dale N. Chayes
Center for Coastal and Ocean Mapping
University of New Hampshire
Christian do Santos Ferreira
MARUM - Center for Marine Environmental Sciences
University of Bremen

OPTIONS

--output=plffile

Specifies the path of the output platform file.

[

--verbose

By default **mbmakeplatform** outputs minimal information to the shell. This option causes the program to indicate its progress as it runs.

--help Lists the available command options.

--input=plffile

Specify an existing platform file to read and then modify with subsequent commands.

--swath=[]datalist or swathfile]

Specify a swath data input (a datalist file or an individual data file) from which **mbmakeplatform** will attempt to extract a starting platform structure, including the list of sensors and the sensor positional and angular offsets. If the input path name follows the **MB-System** convention (e.g. *.mb59 for format 59) or is otherwise recognized as associated with a known format, then the format need not be specified separately with **--swath-format**. Only the first available definition of the platform structure will be parsed, typically from the beginning of the first file referenced. This option only works for recent Kongsberg or Teledyne data formats (e.g. Kongsberg formats 58 & 59 and Teledyne formats 88 & 89).

--swath-format=value

Specify the format of the swath file or datalist from which a starting platform structure should be extracted.

--platform-type-surface-vessel

Set the platform type to be a surface vessel.

--platform-type-tow-body

Set the platform type to be a towed body.

--platform-type-rov

Set the platform type to be an ROV (remotely operated vehicle).

--platform-type-auv

Set the platform type to be an AUV (autonomous underwater vehicle).

--platform-type-aircraft

Set the platform type to be an aircraft.

--platform-type-satellite

Set the platform type to be a satellite.

--platform-name=string

Set the platform name.

--platform-organization=string

Set the name of the platform operating organization.

--platform-documentation-url=string

Set the name of the platform documentation website url.

--platform-start-time=yyyy/mm/dd/hh/mm/ss.sssss

Set the starting time for the time interval that this platform description is valid.

--platform-end-time=yyyy/mm/dd/hh/mm/ss.sssss

Set the ending time for the time interval that this platform description is valid.

--add-sensor-sonar-echosounder

Initiate adding a new sensor of type echosounder (sonar). All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-sonar-multiechosounder

Initiate adding a new sensor of type multiechosounder (sonar). All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-sonar-sidescan

Initiate adding a new sensor of type sidescan (sonar). All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-sonar-interferometry

Initiate adding a new sensor of type interferometry sidescan (sonar). All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-sonar-multibeam

Initiate adding a new sensor of type multibeam (sonar). All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-sonar-multibeam-twohead

Initiate adding a new sensor of type two-head multibeam (sonar). All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-sonar-subbottom

Initiate adding a new sensor of type subbottom (sonar). All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-camera-mono

Initiate adding a new sensor of type single still camera. All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-camera-stereo

Initiate adding a new sensor of type stereo still camera rig. All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-camera-video

Initiate adding a new sensor of type video camera. All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-lidar-scan

Initiate adding a new sensor of type 2D scanning lidar. All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-lidar-swath

Initiate adding a new sensor of type swath lidar. All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-position

Initiate adding a new sensor of type position. All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-compass

Initiate adding a new sensor of type compass. All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-vru

Initiate adding a new sensor of type vertical reference unit (VRU). All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-imu

Initiate adding a new sensor of type inertial motion unit (IMU). All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-ins

Initiate adding a new sensor of type inertial navigation system (INS). All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-ins-with-pressure

Initiate adding a new sensor of type inertial navigation system (INS) with pressure. All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-ctd

Initiate adding a new sensor of type CTD. All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-pressure

Initiate adding a new sensor of type pressure. All commands will pertain to this sensor until the command **end-sensor** is given.

--add-sensor-soundspeed

Initiate adding a new sensor of type sound speed. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor=sensorid

Initiate modifying the existing sensor *sensorid* (where sensors ids count from 0). All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-bathymetry

Initiate modifying the existing sensor that is identified as the source for bathymetry. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-bathymetry1

Initiate modifying the existing sensor that is identified as the source for bathymetry1. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-bathymetry2

Initiate modifying the existing sensor that is identified as the source for bathymetry2. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-bathymetry3

Initiate modifying the existing sensor that is identified as the source for bathymetry3. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-backscatter

Initiate modifying the existing sensor that is identified as the source for backscatter. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-backscatter1

Initiate modifying the existing sensor that is identified as the source for backscatter1. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-backscatter2

Initiate modifying the existing sensor that is identified as the source for backscatter2. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-backscatter3

Initiate modifying the existing sensor that is identified as the source for backscatter3. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-subbottom

Initiate modifying the existing sensor that is identified as the source for subbottom. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-subbottom1

Initiate modifying the existing sensor that is identified as the source for subbottom1. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-subbottom2

Initiate modifying the existing sensor that is identified as the source for subbottom2. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-subbottom3

Initiate modifying the existing sensor that is identified as the source for subbottom3. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-camera

Initiate modifying the existing sensor that is identified as the source for camera. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-camera1

Initiate modifying the existing sensor that is identified as the source for camera1. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-camera2

Initiate modifying the existing sensor that is identified as the source for camera2. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-camera3

Initiate modifying the existing sensor that is identified as the source for camera3. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-position

Initiate modifying the existing sensor that is identified as the source for position. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-position1

Initiate modifying the existing sensor that is identified as the source for position1. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-position2

Initiate modifying the existing sensor that is identified as the source for position2. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-position3

Initiate modifying the existing sensor that is identified as the source for position3. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-depth

Initiate modifying the existing sensor that is identified as the source for depth. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-depth1

Initiate modifying the existing sensor that is identified as the source for depth1. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-depth2

Initiate modifying the existing sensor that is identified as the source for depth2. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-depth3

Initiate modifying the existing sensor that is identified as the source for depth3. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-heading

Initiate modifying the existing sensor that is identified as the source for heading. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-heading1

Initiate modifying the existing sensor that is identified as the source for heading1. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-heading2

Initiate modifying the existing sensor that is identified as the source for heading2. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-heading3

Initiate modifying the existing sensor that is identified as the source for heading3. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-rollpitch

Initiate modifying the existing sensor that is identified as the source for rollpitch. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-rollpitch1

Initiate modifying the existing sensor that is identified as the source for rollpitch1. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-rollpitch2

Initiate modifying the existing sensor that is identified as the source for rollpitch2. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-rollpitch3

Initiate modifying the existing sensor that is identified as the source for rollpitch3. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-heave

Initiate modifying the existing sensor that is identified as the source for heave. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-heave1

Initiate modifying the existing sensor that is identified as the source for heave1. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-heave2

Initiate modifying the existing sensor that is identified as the source for heave2. All commands will pertain to this sensor until the command **end-sensor** is given.

--modify-sensor-heave3

Initiate modifying the existing sensor that is identified as the source for heave3. All commands will pertain to this sensor until the command **end-sensor** is given.

--sensor-model=string

Set sensor model string.

--sensor-manufacturer=string

Set sensor manufacturer string.

--sensor-serialnumber=string

Set sensor serial number string.

--sensor-capability-position

Add position to list of sensor's measurement capabilities.

--sensor-capability-depth

Add depth (typically from pressure) to list of sensor's measurement capabilities.

--sensor-capability-altitude

Add altitude to list of sensor's measurement capabilities.

--sensor-capability-velocity

Add velocity of motion to list of sensor's measurement capabilities.

--sensor-capability-acceleration

Add acceleration of motion to list of sensor's measurement capabilities.

--sensor-capability-pressure

Add pressure to list of sensor's measurement capabilities.

--sensor-capability-rollpitch

Add roll and pitch to list of sensor's measurement capabilities.

--sensor-capability-heading

Add heading to list of sensor's measurement capabilities.

--sensor-capability-magneticfield

Add magnetic field to list of sensor's measurement capabilities.

--sensor-capability-temperature

Add temperature to list of sensor's measurement capabilities.

--sensor-capability-conductivity

Add conductivity to list of sensor's measurement capabilities.

--sensor-capability-salinity

Add salinity to list of sensor's measurement capabilities.

--sensor-capability-soundspeed

Add sound speed to list of sensor's measurement capabilities.

--sensor-capability-gravity

Add gravity to list of sensor's measurement capabilities.

--sensor-capability-topography-echosounder

Add topography from echosounder to list of sensor's measurement capabilities.

--sensor-capability-topography-interferometry

Add topography from interferometric sidescan sonar to list of sensor's measurement capabilities.

--sensor-capability-topography-sass

Add topography from synthetic aperture sidescan (SASS) sonar to list of sensor's measurement capabilities.

--sensor-capability-topography-multibeam

Add topography from multibeam sonar to list of sensor's measurement capabilities.

--sensor-capability-topography-photogrammetry

Add topography from photogrammetry to list of sensor's measurement capabilities.

--sensor-capability-topography-structurefrommotion

Add topography from structure from motion to list of sensor's measurement capabilities.

--sensor-capability-topography-lidar

Add topography from lidar to list of sensor's measurement capabilities.

--sensor-capability-topography-structuredlight

Add topography from structured light to list of sensor's measurement capabilities.

--sensor-capability-topography-laserscanner

Add topography from laser scanner to list of sensor's measurement capabilities.

--sensor-capability-backscatter-echosounder

Add backscatter from echosounder to list of sensor's measurement capabilities.

--sensor-capability-backscatter-sidescan

Add backscatter from sidescan sonar to list of sensor's measurement capabilities.

--sensor-capability-backscatter-interferometry

Add backscatter from interferometric sidescan sonar to list of sensor's measurement capabilities.

--sensor-capability-backscatter-sass

Add backscatter from synthetic aperture sidescan (SASS) sonar to list of sensor's measurement capabilities.

--sensor-capability-backscatter-multibeam

Add backscatter from multibeam sonar to list of sensor's measurement capabilities.

--sensor-capability-backscatter-lidar

Add backscatter from lidar to list of sensor's measurement capabilities.

--sensor-capability-backscatter-structuredlight

Add backscatter from structured light to list of sensor's measurement capabilities.

--sensor-capability-backscatter-laserscanner

Add backscatter from laser scanner to list of sensor's measurement capabilities.

--sensor-capability-photography

Add single camera still photography to list of sensor's measurement capabilities.

--sensor-capability-stereophotography

Add stereo camera still photography to list of sensor's measurement capabilities.

--sensor-capability-video

Add video to list of sensor's measurement capabilities.

--sensor-capability-stereovideo

Add stereo video to list of sensor's measurement capabilities.

--sensor-capability1=value

Set the first of two sensor capability 4 byte bitmasks directly. The usage of the bits in this mask are:

MB_SENSOR_CAPABILITY1_NONE	0x00000000	All bits = 0
MB_SENSOR_CAPABILITY1_POSITION	0x00000001	Bit 0 = 1
MB_SENSOR_CAPABILITY1_DEPTH	0x00000002	Bit 1 = 2
MB_SENSOR_CAPABILITY1_ALTITUDE	0x00000004	Bit 2 = 4
MB_SENSOR_CAPABILITY1_VELOCITY	0x00000008	Bit 3 = 8
MB_SENSOR_CAPABILITY1_ACCELERATION	0x00000010	Bit 4 = 16
MB_SENSOR_CAPABILITY1_PRESSURE	0x00000020	Bit 5 = 32
MB_SENSOR_CAPABILITY1_ROLLPITCH	0x00000040	Bit 6 = 64
MB_SENSOR_CAPABILITY1_HEADING	0x00000080	Bit 7 = 128
MB_SENSOR_CAPABILITY1_HEAVE	0x00000100	Bit 8 = 256
MB_SENSOR_CAPABILITY1_UNUSED09	0x00000200	Bit 9 = 512
MB_SENSOR_CAPABILITY1_UNUSED10	0x00000400	Bit 10 = 1024
MB_SENSOR_CAPABILITY1_UNUSED11	0x00000800	Bit 11 = 2048

```

MB_SENSOR_CAPABILITY1_UNUSED12
                                0x00001000    Bit 12 = 4096
MB_SENSOR_CAPABILITY1_TEMPERATURE
                                0x00002000    Bit 13 = 8192
MB_SENSOR_CAPABILITY1_CONDUCTIVITY
                                0x00004000    Bit 14 = 16384
MB_SENSOR_CAPABILITY1_SALINITY
                                0x00008000    Bit 15 = 32768
MB_SENSOR_CAPABILITY1_SOUNDSPEED
                                0x00010000    Bit 16 = 65536
MB_SENSOR_CAPABILITY1_UNUSED17
                                0x00020000    Bit 17 = 131072
MB_SENSOR_CAPABILITY1_UNUSED18
                                0x00040000    Bit 18 = 262144
MB_SENSOR_CAPABILITY1_UNUSED19
                                0x00080000    Bit 19 = 524288
MB_SENSOR_CAPABILITY1_GRAVITY
                                0x00100000    Bit 20 = 1048576
MB_SENSOR_CAPABILITY1_UNUSED21
                                0x00200000    Bit 21 = 2097152
MB_SENSOR_CAPABILITY1_UNUSED22
                                0x00400000    Bit 22 = 4194304
MB_SENSOR_CAPABILITY1_UNUSED23
                                0x00800000    Bit 23 = 8388608
MB_SENSOR_CAPABILITY1_MAGNETICFIELD
                                0x01000000    Bit 24 = 16777216
MB_SENSOR_CAPABILITY1_UNUSED25
                                0x02000000    Bit 25 = 33554432
MB_SENSOR_CAPABILITY1_UNUSED26
                                0x04000000    Bit 26 = 67108864
MB_SENSOR_CAPABILITY1_UNUSED27
                                0x08000000    Bit 27 = 134217728
MB_SENSOR_CAPABILITY1_UNUSED28
                                0x10000000    Bit 28 = 268435456
MB_SENSOR_CAPABILITY1_UNUSED29
                                0x20000000    Bit 29 = 536870912
MB_SENSOR_CAPABILITY1_UNUSED30
                                0x40000000    Bit 30 = 1073741824
MB_SENSOR_CAPABILITY1_UNUSED31
                                0x80000000    Bit 31 = 2147483648

```

--sensor-capability2=value

Set the second of two sensor capability 4 byte bitmasks directly. The usage of the bits in this mask are:

```

MB_SENSOR_CAPABILITY2_NONE
                                0x00000000    All bits = 0
MB_SENSOR_CAPABILITY2_TOPOGRAPHY_ECHOSOUNDER
                                0x00000001    Bit 0 = 1
MB_SENSOR_CAPABILITY2_TOPOGRAPHY_INTERFEROMETRY
                                0x00000002    Bit 1 = 2
MB_SENSOR_CAPABILITY2_TOPOGRAPHY_SASS
                                0x00000004    Bit 2 = 4
MB_SENSOR_CAPABILITY2_TOPOGRAPHY_MULTIBEAM

```

```

0x00000008      Bit 3 = 8
MB_SENSOR_CAPABILITY2_TOPOGRAPHY_PHOTOGRAMMETRY
0x00000010      Bit 4 = 16
MB_SENSOR_CAPABILITY2_TOPOGRAPHY_STRUCTUREFROMMOTION
0x00000020      Bit 5 = 32
MB_SENSOR_CAPABILITY2_TOPOGRAPHY_LIDAR
0x00000040      Bit 6 = 64
MB_SENSOR_CAPABILITY2_TOPOGRAPHY_STRUCTUREDLIGHT
0x00000080      Bit 7 = 128
MB_SENSOR_CAPABILITY2_TOPOGRAPHY_LASERSCANNER
0x00000100      Bit 8 = 256
MB_SENSOR_CAPABILITY2_UNUSED09
0x00000200      Bit 9 = 512
MB_SENSOR_CAPABILITY2_UNUSED10
0x00000400      Bit 10 = 1024
MB_SENSOR_CAPABILITY2_UNUSED11
0x00000800      Bit 11 = 2048
MB_SENSOR_CAPABILITY2_BACKSCATTER_ECHOSOUNDER
0x00001000      Bit 12 = 4096
MB_SENSOR_CAPABILITY2_BACKSCATTER_SIDESCAN
0x00002000      Bit 13 = 8192
MB_SENSOR_CAPABILITY2_BACKSCATTER_INTERFEROMETRY
0x00004000      Bit 14 = 16384
MB_SENSOR_CAPABILITY2_BACKSCATTER_SASS
0x00008000      Bit 15 = 32768
MB_SENSOR_CAPABILITY2_BACKSCATTER_MULTIBEAM
0x00010000      Bit 16 = 65536
MB_SENSOR_CAPABILITY2_BACKSCATTER_LIDAR
0x00020000      Bit 17 = 131072
MB_SENSOR_CAPABILITY2_BACKSCATTER_STRUCTUREDLIGHT
0x00040000      Bit 18 = 262144
MB_SENSOR_CAPABILITY2_BACKSCATTER_LASERSCANNER
0x00080000      Bit 19 = 524288
MB_SENSOR_CAPABILITY2_UNUSED20
0x00100000      Bit 20 = 1048576
MB_SENSOR_CAPABILITY2_SUBBOTTOM_ECHOSOUNDER
0x00200000      Bit 21 = 2097152
MB_SENSOR_CAPABILITY2_SUBBOTTOM_CHIRP
0x00400000      Bit 22 = 4194304
MB_SENSOR_CAPABILITY2_UNUSED23
0x00800000      Bit 23 = 8388608
MB_SENSOR_CAPABILITY2_PHOTOGRAPHY
0x01000000      Bit 24 = 16777216
MB_SENSOR_CAPABILITY2_STEREOGRAPHY
0x02000000      Bit 25 = 33554432
MB_SENSOR_CAPABILITY2_VIDEO
0x04000000      Bit 26 = 67108864
MB_SENSOR_CAPABILITY2_STEREOVIDEO
0x08000000      Bit 27 = 134217728
MB_SENSOR_CAPABILITY2_UNUSED28
0x10000000      Bit 28 = 268435456
MB_SENSOR_CAPABILITY2_UNUSED29
0x20000000      Bit 29 = 536870912

```

MB_SENSOR_CAPABILITY2_UNUSED30	0x40000000	Bit 30 = 1073741824
MB_SENSOR_CAPABILITY2_UNUSED31	0x80000000	Bit 31 = 2147483648

--sensor-offsets=x/y/z/azimuth/roll/pitch

Used to set the positional (x, y, and z) and angular (azimuth, roll, and pitch) offsets for the sensor currently being added. To modify offsets of an existing sensor use **--modify-offsets**. Here x is positive to starboard, y is positive forward, and z is positive up. Roll is positive starboard up, pitch is positive forward up, and azimuth is positive clockwise from forward. Generally one sensor has zero offsets and thus serves as the platform origin. For sensors with two elements (e.g. bistatic multibeam sonars with separate transmit and receive arrays, or stereo camera rigs with two cameras), two **--sensor_offsets** calls are made. In the case of a multibeam the first set of offsets is for the transmit array, and in the case of a stereo camera rig the first offsets are for the left camera.

--sensor-offset-positions=x/y/z

Used to set the positional (x, y, and z) offsets for the sensor currently being added. To modify positional offsets of an existing sensor use **--modify-offset-positions**. Here x is positive to starboard, y is positive forward, and z is positive up. Generally one sensor has zero offsets and thus serves as the platform origin. This command is used for sensors that do not make measurements dependent on orientation, and so do not have angular offsets (e.g. sound speed, pressure, or CTD sensors).

--sensor-offset-angles=azimuth/roll/pitch

Used to set the angular (azimuth, roll, and pitch) offsets for the sensor currently being added. To modify angular offsets of an existing sensor use **--modify-offset-angles**. Here roll is positive starboard up, pitch is positive forward up, and azimuth is positive clockwise from forward. Generally one sensor has zero offsets and thus serves as the platform origin. This command is used for sensors that do not make measurements dependent on position, and so do not have positional offsets (e.g. vertical reference units (VRUs) that measure orientation only).

--sensor-time-latency=value

Sets a static time latency in seconds for the sensor currently being added.

--sensor-time-latency-model=file

Specifies a file containing a time latency model time series for the sensor currently being added. The file is in the form of two white-space delimited columns with the first column being times in epoch seconds (seconds since the start of 1970) and the second being the time latency in seconds.

--sensor-source-bathymetry

Sets the sensor currently being either added or modified to be the source for bathymetry.

--sensor-source-bathymetry1

Sets the sensor currently being either added or modified to be the source for bathymetry1.

--sensor-source-bathymetry2

Sets the sensor currently being either added or modified to be the source for bathymetry2.

--sensor-source-bathymetry3

Sets the sensor currently being either added or modified to be the source for bathymetry3.

--sensor-source-backscatter

Sets the sensor currently being either added or modified to be the source for backscatter.

--sensor-source-backscatter1

Sets the sensor currently being either added or modified to be the source for backscatter1.

--sensor-source-backscatter2

Sets the sensor currently being either added or modified to be the source for backscatter2.

--sensor-source-backscatter3

Sets the sensor currently being either added or modified to be the source for backscatter3.

--sensor-source-subbottom

Sets the sensor currently being either added or modified to be the source for subbottom.

--sensor-source-subbottom1

Sets the sensor currently being either added or modified to be the source for subbottom1.

--sensor-source-subbottom2

Sets the sensor currently being either added or modified to be the source for subbottom2.

--sensor-source-subbottom3

Sets the sensor currently being either added or modified to be the source for subbottom3.

--sensor-source-camera

Sets the sensor currently being either added or modified to be the source for camera.

--sensor-source-camera1

Sets the sensor currently being either added or modified to be the source for camera1.

--sensor-source-camera2

Sets the sensor currently being either added or modified to be the source for camera2.

--sensor-source-camera3

Sets the sensor currently being either added or modified to be the source for camera3.

--sensor-source-position

Sets the sensor currently being either added or modified to be the source for position.

--sensor-source-position1

Sets the sensor currently being either added or modified to be the source for position1.

--sensor-source-position2

Sets the sensor currently being either added or modified to be the source for position2.

--sensor-source-position3

Sets the sensor currently being either added or modified to be the source for position3.

--sensor-source-depth

Sets the sensor currently being either added or modified to be the source for depth.

--sensor-source-depth1

Sets the sensor currently being either added or modified to be the source for depth1.

--sensor-source-depth2

Sets the sensor currently being either added or modified to be the source for depth2.

--sensor-source-depth3

Sets the sensor currently being either added or modified to be the source for depth3.

--sensor-source-heading

Sets the sensor currently being either added or modified to be the source for heading.

--sensor-source-heading1

Sets the sensor currently being either added or modified to be the source for heading1.

--sensor-source-heading2

Sets the sensor currently being either added or modified to be the source for heading2.

--sensor-source-heading3

Sets the sensor currently being either added or modified to be the source for heading3.

--sensor-source-rollpitch

Sets the sensor currently being either added or modified to be the source for rollpitch.

--sensor-source-rollpitch1

Sets the sensor currently being either added or modified to be the source for rollpitch1.

--sensor-source-rollpitch2

Sets the sensor currently being either added or modified to be the source for rollpitch2.

--sensor-source-rollpitch3

Sets the sensor currently being either added or modified to be the source for rollpitch3.

--sensor-source-heave

Sets the sensor currently being either added or modified to be the source for heave.

--sensor-source-heave1

Sets the sensor currently being either added or modified to be the source for heave1.

--sensor-source-heave2

Sets the sensor currently being either added or modified to be the source for heave2.

--sensor-source-heave3

Sets the sensor currently being either added or modified to be the source for heave3.

--end-sensor

Ends the commands for adding or modifying a sensor.

--modify-offsets=ioff/x/y/z/azimuth/roll/pitch

Used to set the positional (x, y, and z) and angular (azimuth, roll, and pitch) offsets for the sensor currently being modified. To add offsets to a new sensor use **--sensor-offsets**. Here x is positive to starboard, y is positive forward, and z is positive up. Roll is positive starboard up, pitch is positive forward up, and azimuth is positive clockwise from forward. Generally one sensor has zero offsets and thus serves as the platform origin. For sensors with two elements (e.g. bistatic multibeam sonars with separate transmit and receive arrays, or stereo camera rigs with two cameras), two **--sensor_offsets** calls are made. In the case of a multibeam the first set of offsets is for the transmit array, and in the case of a stereo camera rig the first offsets are for the left camera.

--modify-offset-positions=ioff/x/y/z

Used to set the positional (x, y, and z) offsets for the sensor currently being modified. To add positional offsets to a new sensor use **--sensor-offset-positions**. Here x is positive to starboard, y is positive forward, and z is positive up. Generally one sensor has zero offsets and thus serves as the platform origin. This command is used for sensors that do not make measurements dependent on orientation, and so do not have angular offsets (e.g. sound speed, pressure, or CTD sensors).

--modify-offset-angles=ioff/azimuth/roll/pitch

Used to set the angular (azimuth, roll, and pitch) offsets for the sensor currently being modified. To add angular offsets to a new sensor use **--sensor-offset-angles**. Here roll is positive starboard up, pitch is positive forward up, and azimuth is positive clockwise from forward. Generally one sensor has zero offsets and thus serves as the platform origin. This command is used for sensors that do not make measurements dependent on position, and so do not have positional offsets (e.g. vertical reference units (VRUs) that measure orientation only).

--modify-time-latency=value

Sets a static time latency in seconds for the sensor currently being modified.

--modify-time-latency-model=file

Specifies a file containing a time latency model time series for the sensor currently being modified. The file is in the form of two white-space delimited columns with the first column being times in epoch seconds (seconds since the start of 1970) and the second being the time latency in seconds.

--set-source-bathymetry=sensorid

Set the specified sensor to be a source for bathymetry.

--set-source-bathymetry1=sensorid
Set the specified sensor to be a source for bathymetry1.

--set-source-bathymetry2=sensorid
Set the specified sensor to be a source for bathymetry2.

--set-source-bathymetry3=sensorid
Set the specified sensor to be a source for bathymetry3.

--set-source-backscatter=sensorid
Set the specified sensor to be a source for backscatter.

--set-source-backscatter1=sensorid
Set the specified sensor to be a source for backscatter1.

--set-source-backscatter2=sensorid
Set the specified sensor to be a source for backscatter2.

--set-source-backscatter3=sensorid
Set the specified sensor to be a source for backscatter2.

--set-source-subbottom=sensorid
Set the specified sensor to be a source for subbottom.

--set-source-subbottom1=sensorid
Set the specified sensor to be a source for subbottom1.

--set-source-subbottom2=sensorid
Set the specified sensor to be a source for subbottom2.

--set-source-subbottom3=sensorid
Set the specified sensor to be a source for subbottom3.

--set-source-camera=sensorid
Set the specified sensor to be a source for camera.

--set-source-camera1=sensorid
Set the specified sensor to be a source for camera1.

--set-source-camera2=sensorid
Set the specified sensor to be a source for camera2.

--set-source-camera3=sensorid
Set the specified sensor to be a source for camera3.

--set-source-position=sensorid
Set the specified sensor to be a source for position.

--set-source-position1=sensorid
Set the specified sensor to be a source for position1.

--set-source-position2=sensorid
Set the specified sensor to be a source for position2.

--set-source-position3=sensorid
Set the specified sensor to be a source for position3.

--set-source-depth=sensorid
Set the specified sensor to be a source for depth.

--set-source-depth1=sensorid
Set the specified sensor to be a source for depth1.

--set-source-depth2=sensorid
Set the specified sensor to be a source for depth2.

```

--set-source-depth3=sensorid
    Set the specified sensor to be a source for depth3.
--set-source-heading=sensorid
    Set the specified sensor to be a source for heading.
--set-source-heading1=sensorid
    Set the specified sensor to be a source for heading1.
--set-source-heading2=sensorid
    Set the specified sensor to be a source for heading2.
--set-source-heading3=sensorid
    Set the specified sensor to be a source for heading3.
--set-source-rollpitch=sensorid
    Set the specified sensor to be a source for rollpitch.
--set-source-rollpitch1=sensorid
    Set the specified sensor to be a source for rollpitch1.
--set-source-rollpitch2=sensorid
    Set the specified sensor to be a source for rollpitch2.
--set-source-rollpitch3=sensorid
    Set the specified sensor to be a source for rollpitch3.
--set-source-heave=sensorid
    Set the specified sensor to be a source for heave.
--set-source-heave1=sensorid
    Set the specified sensor to be a source for heave1.
--set-source-heave2=sensorid
    Set the specified sensor to be a source for heave2.
--set-source-heave3=sensorid
    Set the specified sensor to be a source for heave3.
]

```

EXAMPLES

The Monterey Bay Aquarium Research Institute operates a Low Altitude Survey System (LASS) that is mounted on Remotely Operated Vehicles (ROVs) and used for 1-cm-scale surveys of the seafloor. The LASS combines the following sensors:

- Kearfott SeaDevil inertial navigation system (INS)
- Paroscientific Digiquartz pressure sensor
- Teledyne Reson T50 400 kHz multibeam sonar
- 3D at Depth Wide Swath Subsea Lidar (WiSSL)
- Stereo camera rig with two Allied Vision Prosilica GX1920 color cameras
- VectorNav VN100 inertial measurement unit (IMU) and attitude heading reference system (AHRS)

MB-System processing of the various datasets collected by the LASS depend upon the platform model for the LASS, which is created by the following set of commands to **mbmakeplatform**:

```

mbmakeplatform --output=20240829ROVVentana.plf \
  --platform-type-rov \
  --platform-name="Ventana" \
  --platform-organization="Monterey Bay Aquarium Research Institute" \
  --add-sensor-ins \

```

```

--sensor-model="SeaDeViL" \
--sensor-manufacturer="Kearfott" \
--sensor-serialnumber="2" \
--sensor-capability-position \
--sensor-capability-heading \
--sensor-capability-rollpitch \
--sensor-offsets=0.0/0.0/0.0/0.0/0.0/0.0 \
--sensor-time-latency=0.0 \
--sensor-source-position \
--sensor-source-heading \
--sensor-source-rollpitch \
--sensor-source-heave \
--end-sensor \
--add-sensor-pressure \
--sensor-model="Digiquartz" \
--sensor-manufacturer="Paroscientific" \
--sensor-serialnumber="Unknown" \
--sensor-capability-depth \
--sensor-offset-positions=-0.2164694/-0.076170/-0.069085 \
--sensor-time-latency=0.0 \
--sensor-source-depth \
--end-sensor \
--add-sensor-sonar-multibeam \
--sensor-model="T50 400 kHz" \
--sensor-manufacturer="Reson" \
--sensor-serialnumber="Unknown" \
--sensor-capability-topography-multibeam \
--sensor-capability-backscatter-multibeam \
--sensor-offsets=-0.459100/0.246774/-0.180388/0.07/0.07/0.16 \
--sensor-offsets=-0.459100/0.442174/-0.211386/0.07/0.07/0.16 \
--sensor-source-bathymetry \
--sensor-source-bathymetry1 \
--sensor-source-backscatter \
--sensor-source-backscatter1 \
--end-sensor \
--add-sensor-lidar-swath \
--sensor-model="WiSSL" \
--sensor-manufacturer="3DatDepth" \
--sensor-serialnumber="1" \
--sensor-capability-topography-lidar \
--sensor-capability-backscatter-lidar \
--sensor-offsets=-0.4653/0.0160/-0.0952/0.0/0.0/0.0 \
--sensor-source-bathymetry2 \
--sensor-source-backscatter2 \
--end-sensor \
--add-sensor-camera-stereo \
--sensor-model="Prosilica GX1920" \
--sensor-manufacturer="Allied Vision" \
--sensor-serialnumber="Unknown" \
--sensor-capability-stereophotography \
--sensor-offsets=-0.559430/-0.106901/-0.136561/0.0/0.0/0.0 \
--sensor-offsets=-0.559430/-0.106901/-0.136561/0.0/0.0/0.0 \
--sensor-source-bathymetry3 \

```

```

--sensor-source-backscatter3 \
--end-sensor \
--add-sensor-ins \
--sensor-model="VN-100" \
--sensor-manufacturer="VectorNav" \
--sensor-serialnumber="Unknown" \
--sensor-capability-position \
--sensor-capability-heading \
--sensor-capability-rollpitch \
--sensor-offsets=--0.255900/0.231999/-0.004164/0.0/0.0/0.0 \
--sensor-time-latency=0.0 \
--sensor-source-position \
--sensor-source-heading \
--sensor-source-rollpitch \
--sensor-source-heave \
--end-sensor

```

Executing the above command produces a platform file named 20240829ROVVentana.plf, which has the following contents:

```

2024> ## MB-System Platform Definition File
      MB-SYSTEM_VERSION      5.8.2beta13
      FILE_VERSION           1.00
      ORIGIN                  Generated by user <seafloor> on cpu <Morgan.local> at <Thu Aug 29 14:33:58
2024>
      ##
      PLATFORM_TYPE           3 ## ROV
      PLATFORM_NAME            Ventana
      PLATFORM_ORGANIZATION    Monterey Bay Aquarium Research Institute
      DOCUMENTATION_URL
      ##
      START_TIME_D             0.000000 ## 0000/00/00 00:00:00.000000
      END_TIME_D               0.000000 ## 0000/00/00 00:00:00.000000
      ##
      PLATFORM_NUM_SENSORS     6
      ##
      ## Defined data source sensors:
      SOURCE_BATHYMETRY        2
      SOURCE_BATHYMETRY1       2
      SOURCE_BATHYMETRY2       3
      SOURCE_BATHYMETRY3       4
      SOURCE_BACKSCATTER       2
      SOURCE_BACKSCATTER1      2
      SOURCE_BACKSCATTER2      3
      SOURCE_BACKSCATTER3      4
      SOURCE_POSITION          5
      SOURCE_DEPTH              1
      SOURCE_HEADING            5
      SOURCE_ROLLPITCH         5
      SOURCE_HEAVE              5
      ##
      ## Undefined data sources:
      ## SOURCE_SUBBOTTOM

```

```

## SOURCE_SUBBOTTOM1
## SOURCE_SUBBOTTOM2
## SOURCE_SUBBOTTOM3
## SOURCE_CAMERA
## SOURCE_CAMERA1
## SOURCE_CAMERA2
## SOURCE_CAMERA3
## SOURCE_POSITION1
## SOURCE_POSITION2
## SOURCE_POSITION3
## SOURCE_DEPTH1
## SOURCE_DEPTH2
## SOURCE_DEPTH3
## SOURCE_HEADING1
## SOURCE_HEADING2
## SOURCE_HEADING3
## SOURCE_ROLLPITCH1
## SOURCE_ROLLPITCH2
## SOURCE_ROLLPITCH3
## SOURCE_HEAVE1
## SOURCE_HEAVE2
## SOURCE_HEAVE3
##
## Sensor list:
##
SENSOR_TYPE      0 101 ## INS
SENSOR_MODEL      0 SeaDeViL
SENSOR_MANUFACTURER 0 Kearfott
SENSOR_SERIALNUMBER 0 2
SENSOR_CAPABILITY1 0 193 ## position rollpitch heading heading
SENSOR_CAPABILITY2 0 0 ##
SENSOR_NUM_OFFSETS 0 1
OFFSET_POSITION 0 0 0.000000 0.000000 0.000000 ## Starboard, Forward, Up
(meters)
OFFSET_ATTITUDE 0 0 0.000000 0.000000 0.000000 ## Heading, Roll, Pitch
(degrees)
SENSOR_TIME_LATENCY_STATIC 0 0.000000 ## Seconds
##
SENSOR_TYPE      1 111 ## Pressure
SENSOR_MODEL      1 Digiquartz
SENSOR_MANUFACTURER 1 Paroscientific
SENSOR_SERIALNUMBER 1 Unknown
SENSOR_CAPABILITY1 1 2 ## depth
SENSOR_CAPABILITY2 1 0 ##
SENSOR_NUM_OFFSETS 1 1
OFFSET_POSITION 1 0 -0.216469 -0.076170 -0.069085 ## Starboard, Forward, Up
(meters)
SENSOR_TIME_LATENCY_STATIC 1 0.000000 ## Seconds
##
SENSOR_TYPE      2 30 ## Sonar multibeam
SENSOR_MODEL      2 T50 400 kHz
SENSOR_MANUFACTURER 2 Reson
SENSOR_SERIALNUMBER 2 Unknown

```

```

SENSOR_CAPABILITY1      2      0 ##
SENSOR_CAPABILITY2      2    65544 ## topography_multibeam backscatter_multibeam
SENSOR_NUM_OFFSETS      2    2
OFFSET_POSITION          2    0 -0.459100  0.246774 -0.180388 ## Starboard, Forward, Up
(meters)
OFFSET_ATTITUDE          2    0  0.070000  0.070000  0.160000 ## Heading, Roll, Pitch
(degrees)
OFFSET_POSITION          2    1 -0.459100  0.442174 -0.211386 ## Starboard, Forward, Up
(meters)
OFFSET_ATTITUDE          2    1  0.070000  0.070000  0.160000 ## Heading, Roll, Pitch
(degrees)
##
SENSOR_TYPE              3 61 ## Lidar swath
SENSOR_MODEL              3 WiSSL
SENSOR_MANUFACTURER      3 3DatDepth
SENSOR_SERIALNUMBER      3 1
SENSOR_CAPABILITY1      3      0 ##
SENSOR_CAPABILITY2      3    131136 ## topography_lidar backscatter_lidar
SENSOR_NUM_OFFSETS      3    1
OFFSET_POSITION          3    0 -0.465300  0.016000 -0.095200 ## Starboard, Forward, Up
(meters)
OFFSET_ATTITUDE          3    0  0.000000  0.000000  0.000000 ## Heading, Roll, Pitch
(degrees)
##
SENSOR_TYPE              4 51 ## Camera stereo
SENSOR_MODEL              4 Prosilica GX1920
SENSOR_MANUFACTURER      4 Allied Vision
SENSOR_SERIALNUMBER      4 Unknown
SENSOR_CAPABILITY1      4      0 ##
SENSOR_CAPABILITY2      4    33554432 ## stereophotography
SENSOR_NUM_OFFSETS      4    2
OFFSET_POSITION          4    0 -0.559430 -0.106901 -0.136561 ## Starboard, Forward, Up
(meters)
OFFSET_ATTITUDE          4    0  0.000000  0.000000  0.000000 ## Heading, Roll, Pitch
(degrees)
OFFSET_POSITION          4    1 -0.559430 -0.106901 -0.136561 ## Starboard, Forward, Up
(meters)
OFFSET_ATTITUDE          4    1  0.000000  0.000000  0.000000 ## Heading, Roll, Pitch
(degrees)
##
SENSOR_TYPE              5 101 ## INS
SENSOR_MODEL              5 VN-100
SENSOR_MANUFACTURER      5 VectorNav
SENSOR_SERIALNUMBER      5 Unknown
SENSOR_CAPABILITY1      5     193 ## position rollpitch heading heading
SENSOR_CAPABILITY2      5      0 ##
SENSOR_NUM_OFFSETS      5    1
OFFSET_POSITION          5    0  0.000000  0.000000  0.000000 ## Starboard, Forward, Up
(meters)
OFFSET_ATTITUDE          5    0  0.000000  0.000000  0.000000 ## Heading, Roll, Pitch
(degrees)
SENSOR_TIME_LATENCY_STATIC 5    0.000000 ## Seconds
##

```

The Monterey Bay Aquarium Research Institute operates two Dorado class autonomous underwater vehicles (AUVs) optimized for seafloor mapping in the deep ocean. These Mapping AUVs field the following sensors:

- Kearfott SeaDevil inertial navigation system (INS)
- Paroscientific Digiquartz pressure sensor
- Teledyne Reson T50 400 kHz multibeam sonar
- Edgetech 110 kHz chirp sidescan sonar
- Edgetech 1-6 kHz chirp subbottom profiler

MB-System processing of the various datasets collected by the Mapping AUVs depend upon the platform models for these vehicles, which are created by the following set of commands to **mbmakeplatform**:

```
mbmakeplatform --output=20240510m1_MAUV2.plf \
  --platform-type-auv \
  --platform-name="MAUV2 MBARI Dorado Class Mapping AUV" \
  --platform-organization="Monterey Bay Aquarium Research Institute" \
  --add-sensor-ins \
    --sensor-model="SeaDeViL" \
    --sensor-manufacturer="Kearfott" \
    --sensor-serialnumber="2" \
    --sensor-capability-position \
    --sensor-capability-heading \
    --sensor-capability-rollpitch \
    --sensor-offsets=0.0/0.0/0.0/0.0/0.0/0.0 \
    --sensor-time-latency=0.0 \
    --sensor-source-position \
    --sensor-source-heading \
    --sensor-source-rollpitch \
    --sensor-source-heave \
  --end-sensor \
  --add-sensor-pressure \
    --sensor-model="Digiquartz" \
    --sensor-manufacturer="Paroscientific" \
    --sensor-serialnumber="Unknown" \
    --sensor-capability-depth \
    --sensor-offset-positions=0.0/-0.6/0.0 \
    --sensor-time-latency=0.0 \
    --sensor-source-depth \
  --end-sensor \
  --add-sensor-sonar-multibeam \
    --sensor-model="7125 400 kHz" \
    --sensor-manufacturer="Reson" \
    --sensor-serialnumber="Unknown" \
    --sensor-capability-topography-multibeam \
    --sensor-capability-backscatter-multibeam \
    --sensor-offsets=0.0/0.353/-0.18/0.50/-0.16/+0.34 \
    --sensor-offsets=0.0/0.153/+0.00/0.50/-0.16/+0.34 \
    --sensor-source-bathymetry \
    --sensor-source-bathymetry1 \
    --sensor-source-backscatter \
    --sensor-source-backscatter1 \
  --end-sensor \
  --add-sensor-sonar-sidescan \
    --sensor-model="FSAU chirp 110 kHz" \
```

```

--sensor-manufacturer="Edgetech" \
--sensor-serialnumber="Unknown" \
--sensor-capability-backscatter-sidescan \
--sensor-offsets=0.0/1.353/-0.10/0.0/0.0/0.0 \
--sensor-source-backscatter2 \
--end-sensor \
--add-sensor-sonar-subbottom \
--sensor-model="FSAU chirp 1-6 kHz" \
--sensor-manufacturer="Edgetech" \
--sensor-serialnumber="Unknown" \
--sensor-capability-backscatter-sidescan \
--sensor-offsets=0.0/1.353/-0.10/0.0/0.0/0.0 \
--sensor-source-backscatter2 \
--end-sensor

```

Executing the above command produces a platform file named 20240510m1_MAUV2.plf, which has the following contents:

```

## MB-System Platform Definition File
MB-SYSTEM_VERSION      5.8.2beta02
FILE_VERSION           1.00
ORIGIN                  Generated by user <caress> on cpu <auvrouter.rc.mbari.org> at <Sun May 12
20:48:01 2024>
##
PLATFORM_TYPE          4 ## AUV
PLATFORM_NAME          MAUV2 MBARI Dorado Class Mapping AUV
PLATFORM_ORGANIZATION  Monterey Bay Aquarium Research Institute
DOCUMENTATION_URL
##
START_TIME_D           0.000000 ## 0000/00/00 00:00:00.000000
END_TIME_D             0.000000 ## 0000/00/00 00:00:00.000000
##
PLATFORM_NUM_SENSORS   5
##
## Defined data source sensors:
SOURCE_BATHYMETRY      2
SOURCE_BATHYMETRY1     2
SOURCE_BACKSCATTER     2
SOURCE_BACKSCATTER1    2
SOURCE_BACKSCATTER2    4
SOURCE_POSITION        0
SOURCE_DEPTH           1
SOURCE_HEADING         0
SOURCE_ROLLPITCH       0
SOURCE_HEAVE           0
##
## Undefined data sources:
## SOURCE_BATHYMETRY2
## SOURCE_BATHYMETRY3
## SOURCE_BACKSCATTER3
## SOURCE_SUBBOTTOM
## SOURCE_SUBBOTTOM1

```

```

## SOURCE_SUBBOTTOM2
## SOURCE_SUBBOTTOM3
## SOURCE_CAMERA
## SOURCE_CAMERA1
## SOURCE_CAMERA2
## SOURCE_CAMERA3
## SOURCE_POSITION1
## SOURCE_POSITION2
## SOURCE_POSITION3
## SOURCE_DEPTH1
## SOURCE_DEPTH2
## SOURCE_DEPTH3
## SOURCE_HEADING1
## SOURCE_HEADING2
## SOURCE_HEADING3
## SOURCE_ROLLPITCH1
## SOURCE_ROLLPITCH2
## SOURCE_ROLLPITCH3
## SOURCE_HEAVE1
## SOURCE_HEAVE2
## SOURCE_HEAVE3
##
## Sensor list:
##
SENSOR_TYPE      0 101 ## INS
SENSOR_MODEL      0 SeaDeViL
SENSOR_MANUFACTURER 0 Kearfott
SENSOR_SERIALNUMBER 0 2
SENSOR_CAPABILITY1 0 193 ## position rollpitch heading heading
SENSOR_CAPABILITY2 0 0 ##
SENSOR_NUM_OFFSETS 0 1
OFFSET_POSITION 0 0 0.000000 0.000000 0.000000 ## Starboard, Forward, Up
(meters)
OFFSET_ATTITUDE 0 0 0.000000 0.000000 0.000000 ## Heading, Roll, Pitch
(degrees)
SENSOR_TIME_LATENCY_STATIC 0 0.000000 ## Seconds
##
SENSOR_TYPE      1 111 ## Pressure
SENSOR_MODEL      1 Digiquartz
SENSOR_MANUFACTURER 1 Paroscientific
SENSOR_SERIALNUMBER 1 Unknown
SENSOR_CAPABILITY1 1 2 ## depth
SENSOR_CAPABILITY2 1 0 ##
SENSOR_NUM_OFFSETS 1 1
OFFSET_POSITION 1 0 0.000000 -0.600000 0.000000 ## Starboard, Forward, Up
(meters)
SENSOR_TIME_LATENCY_STATIC 1 0.000000 ## Seconds
##
SENSOR_TYPE      2 30 ## Sonar multibeam
SENSOR_MODEL      2 7125 400 kHz
SENSOR_MANUFACTURER 2 Reson
SENSOR_SERIALNUMBER 2 Unknown
SENSOR_CAPABILITY1 2 0 ##

```

```

        SENSOR_CAPABILITY2      2    65544 ## topography_multibeam backscatter_multibeam
        SENSOR_NUM_OFFSETS      2    2
        OFFSET_POSITION          2    0  0.000000  0.353000 -0.180000 ## Starboard, Forward, Up
(meters)
        OFFSET_ATTITUDE         2    0  0.500000 -0.160000  0.340000 ## Heading, Roll, Pitch
(degrees)
        OFFSET_POSITION          2    1  0.000000  0.153000  0.000000 ## Starboard, Forward, Up
(meters)
        OFFSET_ATTITUDE         2    1  0.500000 -0.160000  0.340000 ## Heading, Roll, Pitch
(degrees)
        ##
        SENSOR_TYPE              3 20 ## Sonar sidescan
        SENSOR_MODEL              3 FSAU chirp 110 kHz
        SENSOR_MANUFACTURER      3 Edgetech
        SENSOR_SERIALNUMBER      3 Unknown
        SENSOR_CAPABILITY1       3    0 ##
        SENSOR_CAPABILITY2       3   8192 ## backscatter_sidescan
        SENSOR_NUM_OFFSETS       3    1
        OFFSET_POSITION          3    0  0.000000  1.353000 -0.100000 ## Starboard, Forward, Up
(meters)
        OFFSET_ATTITUDE         3    0  0.000000  0.000000  0.000000 ## Heading, Roll, Pitch
(degrees)
        ##
        SENSOR_TYPE              4 40 ## Sonar subbottom
        SENSOR_MODEL              4 FSAU chirp 1-6 kHz
        SENSOR_MANUFACTURER      4 Edgetech
        SENSOR_SERIALNUMBER      4 Unknown
        SENSOR_CAPABILITY1       4    0 ##
        SENSOR_CAPABILITY2       4   8192 ## backscatter_sidescan
        SENSOR_NUM_OFFSETS       4    1
        OFFSET_POSITION          4    0  0.000000  1.353000 -0.100000 ## Starboard, Forward, Up
(meters)
        OFFSET_ATTITUDE         4    0  0.000000  0.000000  0.000000 ## Heading, Roll, Pitch
(degrees)
        ##

```

SEE ALSO

mbsystem(1), **mbpreprocess(1)**, **mbprocess(1)**

BUGS

Platform files are complicated, yet inscrutable.