

ChangeLog

MB-System ChangeLog File:

This file lists changes to the source code of the MB-System open source software package for the processing and display of swath sonar data. This file is located at the top of the MB-System source code distribution directory structure.

In the list below, releases shown in bold type are major, announced releases. The other entries are test or "beta" releases that were not announced and generally not widely distributed. Prior to 5.7.1, the MB-System source code repository was a privately hosted Subversion archive. In that era, announced source distribution releases were made available for download by ftp. Starting with 5.7.1 the MB-System source code repository is hosted by Github at <https://github.com/dwcaress/MB-System/> and each distribution corresponds to a discrete Github release tag. Releases that include "beta" in the tag name are preliminary and generally not announced. Distributions that do not include "beta" in the tag name correspond to the major, announced releases. The source distributions associated with all releases, major or beta, are equally accessible as tarballs through the Github interface.

MB-System Version 5.8 Releases and Release Notes:

- Version 5.8.3beta24 October 5, 2026
- Version 5.8.3beta23 October 3, 2026
- Version 5.8.3beta22 September 19, 2026
- Version 5.8.3beta21 September 13, 2026
- Version 5.8.3beta20 September 10, 2026
- Version 5.8.3beta19 September 10, 2026
- Version 5.8.3beta18 September 9, 2026
- Version 5.8.3beta17 September 8, 2026
- Version 5.8.3beta16 July 26, 2026
- Version 5.8.3beta15 July 26, 2026
- Version 5.8.3beta14 July 6, 2026
- Version 5.8.3beta13 June 18, 2026

- Version 5.8.3beta12 January 7, 2026
- Version 5.8.3beta11 December 27, 2025
- Version 5.8.3beta10 December 22, 2025
- Version 5.8.3beta09 December 4, 2025
- Version 5.8.3beta08 November 16, 2025
- Version 5.8.3beta07 October 22, 2025
- Version 5.8.3beta06 October 1, 2025
- Version 5.8.3beta05 September 30, 2025
- Version 5.8.3beta04 September 18, 2025
- Version 5.8.3beta03 August 31, 2025
- Version 5.8.3beta02 August 29, 2025
- Version 5.8.3beta01 August 27, 2025
- **Version 5.8.2 August 19, 2025**
- Version 5.8.2beta24 July 19, 2025
- Version 5.8.2beta23 June 25, 2025
- Version 5.8.2beta22 June 16, 2025
- Version 5.8.2beta21 March 15, 2025
- Version 5.8.2beta20 February 22, 2025
- Version 5.8.2beta19 January 19, 2025
- Version 5.8.2beta18 December 8, 2024
- Version 5.8.2beta17 November 7, 2024
- Version 5.8.2beta16 November 6, 2024
- Version 5.8.2beta15 October 1, 2024
- Version 5.8.2beta14 September 6, 2024
- Version 5.8.2beta13 August 23, 2024
- Version 5.8.2beta12 August 22, 2024
- Version 5.8.2beta11 August 19, 2024
- Version 5.8.2beta10 August 16, 2024
- Version 5.8.2beta09 August 4, 2024
- Version 5.8.2beta08 July 27, 2024
- Version 5.8.2beta07 June 27, 2024
- Version 5.8.2beta06 June 13, 2024
- Version 5.8.2beta05 May 19, 2024
- Version 5.8.2beta04 May 13, 2024
- Version 5.8.2beta02 May 1, 2024
- Version 5.8.2beta01 April 29, 2024
- **Version 5.8.1 March 22, 2024**
- Version 5.8.1beta09 March 22, 2024
- Version 5.8.1beta08 March 10, 2024
- Version 5.8.1beta07 February 24, 2024
- Version 5.8.1beta04 February 16, 2024
- Version 5.8.1beta03 February 8, 2024
- Version 5.8.1beta02 February 7, 2024

- Version 5.8.1beta01 February 1, 2024
 - **Version 5.8.0 January 22, 2024**
-

5.8.3beta24 (October 5, 2026)

Build system (MacOS, Homebrew): fixed a build failure when building with the private mb-mesa and mb-mesa-glu kegs (cmake -DmacosUseMbMesa=ON), in which compiling mbview failed with "fatal error: 'GL/glu.h' file not found". The local FindOpenGL module (build-utils/FindOpenGL.cmake) took libGL and the OpenGL headers from the mb-mesa keg and libGLU from the mb-mesa-glu keg, but set the OpenGL include directory only to the mb-mesa include directory, while GL/glu.h is installed only in the mb-mesa-glu keg. Because both kegs are keg-only, their headers are not linked into /opt/homebrew/include, so nothing placed glu.h on the compiler's include path. Builds made through the mbsystem-beta Homebrew formula were not affected because Homebrew's build environment adds the include directories of keg-only dependencies automatically; the failure appeared in manual builds run from a shell. The OpenGL include directory now includes both \${MBMESA_PREFIX}/include and \${MBMESAGLU_PREFIX}/include, in both the pre-Tahoe and the Tahoe-or-later MacOS Homebrew branches. Verified by a full build with -DmacosUseMbMesa=ON, confirming that libmbview links against mb-mesa's libGL and mb-mesa-glu's libGLU.

Build system (Windows): incorporated the platform-independent parts of pull request #1603 (Joaquim Luis, MSVC build fixes) without merging the pull request itself. The remaining, MSVC-specific parts of #1603 were not adopted because they used _WIN32 guards that also apply to MinGW-w64 builds and, when cross-compiled with MinGW-w64, broke them. The changes adopted are:

- GSF library: src/gsf/gsf_enc.c had CR-only (classic Mac) line endings, which caused the MSVC preprocessor to silently drop every gsfEncode* function and the mbgsf DLL link to fail. The file has been converted to LF line endings; the code itself is unchanged.
- Program mbnadjust (src/mbnavadjust/mbnavadjust_io.c): in mbnadjust_new_project(), the variable mode holding the result of mkdir() was declared only in the non-Windows branch but used unconditionally in the following error message, so the file did not compile on Windows. It is now declared in both branches.
- Program mbnadjust (src/mbnavadjust/mbnavadjust_invertnav.c): removed a redundant gethostname() call made just after mb_user_host_date() had already filled in the host name (including

`mb_user_host_date()`'s Windows fallback to the `USERDOMAIN` environment variable), together with the `<unistd.h>` include it required. The undeclared `gethostname()` was a compile error under MinGW-w64; the output file header is unchanged on other platforms.

- CMake: added a top-level `MB_SYSLIBS` variable listing the system libraries (m and pthread) linked by MB-System libraries and programs, and used it in place of the hardcoded m and pthread link libraries for `mbio`, `dump_gsf`, the `src/utilities` programs, and the `src/photo` programs. `MB_SYSLIBS` is empty when building with MSVC, which has the math functions built into its C runtime and provides no `libm` or `libpthread`; it is unchanged for MinGW-w64, Linux, and MacOS builds.
- MBIO library (`src/mbio/mb_io.h`): the global arrays `mb_sensor_type_id[]` and `mb_sensor_type_string[]` are now declared `extern "C"`, so that C++ programs link to them correctly under MSVC, which (unlike gcc and clang) mangles the names of C++ global variables. They are also marked with a new `MB_SENSOR_TYPE_API` macro that expands to `__declspec(dllexport/dllimport)` only for MSVC DLL builds; MSVC does not export data from a DLL automatically. The macro deliberately does nothing for MinGW-w64, because a single `dllexport` in a MinGW DLL turns off its automatic export of all other symbols. For static MSVC builds, `src/mbio/CMakeLists.txt` defines `MBIO_STATIC` to suppress the markers.

Verified by a full MacOS build with all 73 ctest tests passing, and by MinGW-w64 (GCC 16) cross-compilation of all non-GUI sources, together with a MinGW-w64 link of the `mbgsf` DLL confirming that the library's automatic symbol export is preserved. MSVC builds were not tested.

This work was done with the assistance of the AI coding assistant Claude Opus 5.5 (Anthropic, model `claude-opus-5-5`), operating as Claude Code under developer supervision and review, which traced the missing header to the include directories set by the `FindOpenGL` module, implemented the fix, and verified the build, and which evaluated pull request #1603 (including MinGW-w64 cross-compilation and DLL export testing of the pull request), implemented the Windows build changes listed above, and verified them.

5.8.3beta23 (October 3, 2026)

Format 261 (`MBF_KEMKMALL`): fixed a georeferencing bug affecting Kongsberg `kmall` data logged in dual-swath (or any other multi-sub-ping-per-cycle) mode, where a single transmit/receive cycle produces two or more MRZ sub-pings a fraction of a second apart, each with its own navigation and heading. `mbsys_kmbes_extract()` (`src/mbio/mbsys_kmbes.c`) merges all

of a cycle's sub-pings into one MB-System ping, but reported only the first sub-ping's navigation and heading for the whole merged ping while leaving every other sub-ping's soundings in their own, uncorrected ship-frame offsets - so any navigation or heading difference between sub-pings (heading in particular, which can differ from the reference sub-ping by a measurable fraction of a degree even during ordinary transit, and by tens of degrees elsewhere in a survey) was silently applied to the wrong beams, most visibly as a systematic swath-to-swath position error over sloped terrain. A new function, `mbsys_kmbes_reproject_beam_to_reference()` (`src/mbio/mbsys_kmbes.c`), reprojects each non-reference sub-ping's beams from its own navigation/heading frame into the reference sub-ping's frame - via absolute longitude/latitude, using the same rotation and meters-to-degrees convention already used throughout MB-System by `mb_extract_lonlat()` and `mb_read()` (`src/mbio/mb_access.c`, `src/mbio/mb_read.c`) - so every beam ends up correctly positioned once the single reported reference navigation and heading are applied downstream. Verified against a Kongsberg kmall dual-swath test dataset by comparing beam-by-beam output before and after the fix: soundings from the reference sub-ping of each cycle were unchanged, while soundings from the other sub-ping(s) shifted by amounts consistent with the sub-pings' actual navigation/heading differences.

This fix was made with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review, which diagnosed the bug by comparing MB-System's kmall processing of an R/V Thomas G. Thompson EM304 survey against the same data processed through Qimera and exported as GSF, tracing the discrepancy to the merged-ping single-navigation behavior described above and confirming the fix beam by beam.

Format 261 (MBF_KEMKMALL) and program `mbpreprocess`: fixed a second, larger source of navigation/heading error found during the same investigation, affecting Kongsberg installations that log `#SKM attitude/heading/navigation` samples from two independent sensor systems (kinds `MB_DATA_NAV1` and `MB_DATA_NAV2`, corresponding to `#SKM sensorSystem 0` and `1` respectively). `mbpreprocess` previously defaulted, for kmall data, to merging `MB_DATA_NAV1` unconditionally whenever `--nav-async`, `--heading-async`, and `--attitude-async` were not specified - but `MB_DATA_NAV1` is not always the sensor system the sonar's own real-time processing actually uses: on the R/V Thompson test data, the `#IIP` installation datagram's own `ATTI_1/ATTI_2` tags marked sensor system `0` (`MB_DATA_NAV1`) as the passive standby and sensor system `1` (`MB_DATA_NAV2`) as active, so the previous hardcoded default was silently merging in the wrong (and substantially different, by up to about 20 degrees

of heading) sensor's data. A new function, `mbsys_kmbes_active_attitude_system()` (`src/mbio/mbsys_kmbes.c`), parses the `#IIP` record's free-text `install_txt` for the `ATTI_` line marked "U=ACTIVE" and caches the corresponding kind (`MB_DATA_NAV1` or `MB_DATA_NAV2`) in a new `mbsys_kmbes_struct` field, `active_attitude_system`, populated automatically as soon as `#IIP` is read (`mbr_kemkmall_rd_iip()`, `src/mbio/mbr_kemkmall.c`). `mbpreprocess` (`src/utilities/mbpreprocess.cc`) now uses this value to resolve its `nav_async/heading_async/attitude_async` defaults for `kmall` data dynamically, per file, falling back to `MB_DATA_NAV1` only if the installation record does not unambiguously mark one sensor system active; explicitly specifying `--nav-async`, `--heading-async`, or `--attitude-async` continues to override this (or any other) default exactly as before. The `#SKM` reader itself (`mbr_kemkmall_rd_skm()`, `src/mbio/mbr_kemkmall.c`) always assigns sensor system 0 to `MB_DATA_NAV1` and sensor system 1 to `MB_DATA_NAV2`, unconditionally - only the choice of which kind `mbpreprocess` merges by default has changed. The `mbpreprocess` manual page was updated to document this `kmall`-specific default-resolution behavior under `--nav-async`, `--heading-async`, and `--attitude-async`. Verified against the same R/V Thompson test dataset: the default (no options given) now reproduces the same heading (and downstream bathymetry) as explicitly specifying `--nav-async=30 --heading-async=30 --attitude-async=30`, while explicitly specifying `=29` continues to force the previous (passive-sensor) behavior.

This fix was made with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review, which traced the heading discrepancy to the `#SKM` sensor-system selection by directly parsing the raw `kmall` file's `#IIP`, `#SKM`, and `#SPO` datagrams and cross-referencing the `ATTI_1/ATTI_2` active/passive tags against both the sonar's own per-ping heading and the corresponding Qimera-derived GSF export, and verified the fix by comparing `mbpreprocess` output beam by beam and heading by heading with and without the fix and with explicit `--nav-async/--heading-async/--attitude-async` overrides in both directions.

Formats 56, 57, 58, and 59 (`MBF_EM300RAW`, `MBF_EM300MBA`, `MBF_EM710RAW`, `MBF_EM710MBA`): fixed a bug, reported in Github issue #1620, in which writing a Kongsberg Installation Parameter datagram with an unset two-character `DSH`, `MRP`, or `NRP` field corrupted every field written after it in the same datagram. `mbr_em300raw.c`, `mbr_em300mba.c`, `mbr_em710raw.c`, and `mbr_em710mba.c` each serialize this datagram into a growing ASCII buffer with repeated calls of the form

```
printf(&buff[buff_len], "DSH=%c%c", store->par\_dsh[0], store->par\_dsh[1])
```

when a field's stored value is still at its zero-initialized default (both

characters NUL, e.g. because the source data never carried a value for it), the embedded NUL bytes terminate the following `strlen(buff)` call early, so `buff\_len` stops advancing past them and the next field's `sprintf` overwrites the unset field in place - observed, for example, as `DSH=APS=0` in place of the intended `DSH=xx,APS=0`. All ten call sites across the four files (DSH, MRP, and NRP in the two EM710 readers; DSH and MRP only in the two EM300 readers, which have no NRP field) now write the field only when both characters are non-NUL, omitting it entirely otherwise, matching the existing convention already used for other optional string fields in the same functions (e.g. `par_dds`, `par_osv`). Verified using a real EM712 format-59 file: converting it unmodified via `mbcopy -F59/58` reproduces well-formed output before and after the fix; after zeroing the DSH/MRP/NRP byte pairs of all 45 Installation Parameter datagrams in a copy of that file (135 fields in total) to simulate unset values, the pre-fix code reproduced the exact reported corruption (`DSH=APS=0`) while the fixed code produced clean output with the unset fields simply omitted.

This fix was made with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review, which located every instance of the vulnerable `sprintf` / `strlen` -based serialization pattern across the Kongsberg format readers (rather than only the single call site named in the issue report), confirmed the corruption mechanism by temporarily reverting the fix and comparing `mbcopy` output on a deliberately corrupted real-data file before and after, and confirmed normal (all fields set) conversions are unaffected by comparing output before and after the fix on the unmodified source file.

Format 261 (MBF_KEMKMALL) and programs `mbpreprocess`, `mbprocess`, and `mbmakeplatform`: redefined and extended the preprocessing of Kongsberg kmall data. Preprocessing is required the first time kmall data are read, in order to construct an `#XMT` and an `#XMS` datagram for each `#MRZ` datagram. The `#XMT` datagram holds the navigation, heading, sensor depth, and attitude for the ping together with the beam travel times and angles used by `mbprocess` to recalculate bathymetry by raytracing, and the `#XMS` datagram holds pseudosidescan derived from the snippet backscatter. When `mbr_rt_kemkmall()` (`src/mbio/mbr_kemkmall.c`) constructs these on reading, it now calls `mbsys_kmbes_preprocess()` with no platform model and with only roll, pitch, heave, and speed interpolation arrays, so the navigation, heading, and sensor depth logged in the `#MRZ` datagram are left unchanged and copied into the `#XMT` datagram. Previously the heading logged in the `#MRZ` datagram was replaced with heading interpolated from the asynchronous `#SKM` data, which differed from the logged vessel heading

(and from the heading in the GSF files exported by Qimera) by amounts varying between 0.2 and 0.8 degrees; reading raw kmall data now reproduces the GSF heading to within 0.006 degrees. When mbpreprocess supplies interpolation arrays the logged values are replaced only by those that are supplied, for each #MRZ sub-ping at its own time, and the sensor depth precedence is: a sensor depth array, then --kluge-auv-sentry-sensordepth, then the logged value. The #MRZ navigation and the soundings x_reRefPoint_m, y_reRefPoint_m, and z_reRefPoint_m are relative to the vessel reference point, not the sonar, and with a platform model the merged navigation is now moved from the navigation sensor to the vessel reference point (the origin of the platform model) using the new library functions mb_platform_position_platform() and mb_platform_lever_origin() (src/mbio/mb_platform.c). The extraction of bathymetry by mbsys_kmbes_extract() was checked against the format specification, and mbsys_kmbes_extract_altitude() returned the depth below the reference point rather than the height of the transducer above the seafloor; it now subtracts the waterline offset and the transducer depth.

For MB-System as a whole, the navigation and sensor depth passed by the format i/o functions (mb_read(), mb_get_all(), mb_extract(), mb_insert(), mb_extract_nav(), mb_insert_nav(), and the related write and put functions) are to be those of the mapping sensor rather than of the platform reference point, with the acrosstrack and alongtrack distances relative to that point; this had not previously been defined clearly, and some formats may need to change to follow it. Format 261 now follows this rule while the #MRZ datagrams on disk keep Kongsberg's definition, with the position and soundings relative to the vessel reference point. The sonar reference point is the alongtrack position of the transmit array and the acrosstrack position of the receive array, because those set the alongtrack and acrosstrack positions of the soundings. mbsys_kmbes_extract(), mbsys_kmbes_extract_nav(), mbsys_kmbes_insert(), and mbsys_kmbes_insert_nav() (src/mbio/mbsys_kmbes.c) convert between the two, using the lever arm held in the #XMT datagram, which gives the reported navigation as the position of the sonar reference point and the soundings and pseudosidescan relative to it. Absolute sounding positions are unchanged by this: they were identical, to 1.2 mm or better, in a test that preprocessed the same data with the real platform and with a platform with zero sonar offsets, while the reported navigation and distances shifted by the lever arm. Data passed through unmodified (for example by mbcopy) leave the #MRZ datagrams byte for byte unchanged, and a navigation shift applied by mbprocess moves every sounding by exactly the shift.

A new function, mbsys_kmbes_extract_platform() (src/mbio/mbsys_kmbes.c), builds a platform model from the free-text installation

parameters in the #IIP datagram at the start of every kmall file: the multibeam sensor with its transmit and receive array offsets, up to three position sensors, and up to two attitude sensors, with the sensors marked "U=ACTIVE" selected as the data sources. This makes --swath=swathfile work with mbmakeplatform for format 261, and mbpreprocess now extracts the platform from the first kmall file's #IIP datagram automatically when no --platform-file is specified (a platform file always takes precedence). The installation angles reported for the attitude sensors are corrections that Kongsberg adds to the measured angles - verified by reproducing the roll, pitch, and heading in the GSF files and the #MRZ datagrams from the raw #SKM samples of both sensor systems - and are therefore stored negated in the platform model.

The #XMT datagram is now version 1. Its ping information grew from 60 to 68 bytes with the new fields lever_acrosstrack and lever_alongtrack, the displacement of the sonar reference point from the vessel reference point, and its navigation is now the position of the sonar reference point.

Bathymetry raytraced by mbprocess from the #XMT travel times and angles is relative to the sonar, so with navigation at the sonar reference point mbprocess needs no lever arm handling of its own. The new fields follow numSoundings, and the reader steps by the numBytesInfoData and numBytesPerSounding values in the datagram, so version 0 datagrams are read as before with the new fields set to zero, which places the sonar reference point at the vessel reference point. Raytracing the #XMT angles also exposed an error in the alongtrack offset, which had been the vessel advance between ping time and beam receive time ((sector transmit delay + two way travel time) times speed) rather than only the advance to the sector transmit time, adding about 30 m at transit speed; it is now sector_transmit_delay times speed, and version 0 datagrams have the travel time part (twtt times speed) removed when they are read. Verified for a single swath Sentry EM2040 dataset and a dual swath R/V Thompson EM124 dataset by running mbpreprocess (with the platform extracted automatically), mbsvplist, and mbprocess and comparing the raytraced soundings to Kongsberg's own #MRZ soundings, with no lever arm correction in mbprocess: the rms differences in acrosstrack distance, alongtrack distance, and depth are 0.018, 0.002, and 0.011 m for the Sentry data and 0.99, 2.1, and 1.3 m for the Thompson data. A version 0 file converted to its older form was read, processed, and copied with mbcopy without error or repeated correction. The mbpreprocess and mbprocess manual pages were updated, including adding the previously missing description of --kluge-auv-sentry-sensordepth.

Format 261 (MBF_KEMKMALL): mbsys_kmbes_insert() previously overwrote the navigation and heading of every #MRZ sub-ping with the

single reference sub-ping values while copying the acrosstrack and alongtrack distances straight into the soundings, which destroyed the logged navigation and heading of the other sub-pings of a dual swath ping whenever data were rewritten (for example by mbcopy or mbprocess). It now keeps each non-reference sub-ping's own navigation and heading and reprojects the distances back into that sub-ping's frame, as the inverse of the reprojection done on extraction; a dual swath file copied with mbcopy is unchanged beam for beam and a single swath file is unaffected. Also fixed a segmentation fault in mbsys_kmbes_preprocess() when running programs such as mbinfo with a verbose level of 5 or more, where the debug output dereferenced the optional navigation speed array, which is not defined when the data are first read.

Formats 56 and 57 (MBF_EM300RAW, MBF_EM300MBA, handled by mbsys_simrad2.c) and 58 and 59 (MBF_EM710RAW, MBF_EM710MBA, handled by mbsys_simrad3.c) now follow the same rule that the navigation and sensor depth are those of the mapping sensor. In these formats the navigation datagrams, and so the navigation of the pings, are the location of the active position sensor, and the acrosstrack and alongtrack distances of the soundings are relative to that location, so the extract, extract_nav, extract_nnav, insert, and insert_nav functions of both modules (and the sidescan extraction) now convert to and from the sonar reference point using the lever arm computed from the installation parameters (the sonar offsets, the active position sensor offsets, and the roll and pitch of the ping), while the data on disk keep Kongsberg's definition. The conversion is applied identically on extraction and insertion, so data passed through unmodified are not altered. The alongtrack offset returned by mbsys_simrad3_ttimes() is now only the advance of the platform to the transmit time of the beam's sector, without the position sensor offset that had been added to it, because that offset is now part of the reported navigation. Validated for format 58 on EM712 data and for formats 56 and 57 on EM120 and EM122 data that have nonzero installation offsets by running mbpreprocess, mbsvplist, and mbprocess and comparing the raytraced soundings to the logged soundings: the alongtrack differences, which had been the offset of the transmit array from the position sensor (11.7 m for one of the datasets), are now within a few centimeters at all angles, and a navigation shift applied by mbprocess and a copy by mbcopy were checked to behave as for format 261. For the formats 56 and 57 the logged alongtrack and acrosstrack distances were found to be referenced to the transmit array location, so that is the sonar reference point there, and for both modules the position sensor offsets are used even when the sensor is flagged as motion compensated. Limitations: the lever arm is a single value per ping, so for dual head sonars (EM3002 and similar, whose heads are merged into one ping by mbsys_simrad2) the

second head's across-track offset from the first head cannot be represented and only its along-track difference is carried by `mbsys_simrad2_ttimes()`; this was not tested because no dual head data were available. The heuristic that `mbsys_simrad3_ttimes()` previously used to guess a position sensor when `par_ap`s was wrong and the active sensor had a zero x offset is no longer applied. The older Kongsberg and Simrad formats (for example 51 and 54) have not been changed and still return the logged position.

This work was done with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review, which compared the kmall bathymetry, heading, roll, and pitch with the Qimera GSF exports and with the raw `#IIP`, `#SKM`, and `#MRZ` datagrams to establish the conventions described above, implemented the changes, and checked them against a dual swath and a single swath dataset.

5.8.3beta22 (September 19, 2026)

Program `mbeditviz`: added a new "Color by Soundings" option to the View menu of the 3D Soundings window, alongside the existing "Color by Flag State," "Color by Topography," and "Color by Amplitude" toggles. The pre-existing "Color by Topography" option (unchanged) colors soundings by depth using the same color table and the same minimum and maximum topography values as the associated MBeditviz Survey Viewer, so its color stretch is fixed to the whole gridded bathymetry's range and does not change as different soundings are picked. The new "Color by Soundings" option instead colors soundings by depth with the color stretch scaled to the minimum and maximum depth values found only among the soundings currently displayed in the 3D Soundings window: when "Show Flagged Soundings" is on, the minimum and maximum are calculated over all of the displayed soundings regardless of beamflag state, and when it is off, only the unflagged (valid) soundings are used, so the full color range is always available to differentiate whatever subset of soundings is currently being examined. The new mode is implemented in `mb3dsoundings_plot()` (`src/mbview/mb3dsoundings_callbacks.c`), recomputing the local depth range and sounding colors on every redraw rather than baking colors in at selection time as "Color by Topography" does. The `mbeditviz` manual page was updated to document all four View-menu coloring modes.

This feature was added with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review; the `mbview` and `mbeditviz` libraries/

programs were rebuilt and the new option was verified to compile cleanly alongside the pre-existing coloring modes.

Program mbeditviz: fixed a bus-fault crash while gridding survey data whose navigation contains a bad fix far outside the actual survey area. The bogus fix inflated the computed grid bounds enormously, so the grid's column-count times row-count cell total overflowed the 32-bit int used to size the grid arrays; the resulting malloc() calls silently "succeeded" with a wrapped, far-too-small buffer size while the true (huge) column/row counts were still used to index into it, producing out-of-bounds writes and a crash.

mbeditviz_setup_grid() and mbeditviz_make_grid_simple() (src/mbeditviz/mbeditviz_prog.c) now compute the requested cell count in a size_t and refuse to allocate a grid larger than a sane cap (MBEV_GRID_MAX_CELLS, defined in mbeditviz.h), reporting the likely cause (bad navigation or too small a grid cell size) and aborting the grid cleanly instead of crashing; mbeditviz_make_grid() was also changed to check that the grid arrays were actually allocated before using them, and all of the grid cell index computations (in mbeditviz_make_grid, mbeditviz_grid_beam, and mbeditviz_make_grid_simple) were widened from int to size_t as a further guard against index overflow on large grids.

This fix was made with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model claude-sonnet-5), operating as Claude Code under developer supervision and review, which used lldb output identifying the faulting instruction and out-of-range array index to trace the crash to the grid-size integer overflow described above; mbeditviz was rebuilt and verified to compile cleanly with the fix in place.

Macro mbm_grd3dplot: fixed a malformed GMT `-B` (basemap axes) option in the generated plotting shellscript that caused 3D perspective plots to fail. The macro builds the axes annotation string (tick intervals, visible-face selection, and title) into a Perl variable, `$axes`, that already includes its own leading `-B` flags (e.g. `-Bxy1m -Bz13.62 -BSEZ+t "..."`), but the `psbasemap` call in the generated `.cmd` script prepended yet another `-B` to that variable, producing a doubled option such as `-B-Bxy1m -Bz13.62 -BSEZ+t "..."` that GMT's `psbasemap` could not parse ("Bad interval in -B option... gave interval = 0"). Because `psbasemap` then failed, the PostScript file was left unfinalized, causing a second, downstream `psconvert` failure ("file is not finalized") that obscured the real problem. The extraneous `-B` was removed from the `psbasemap` command construction in src/macros/mbm_grd3dplot so the axes string is emitted as built.

This fix was made with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model claude-sonnet-5), operating as Claude Code under developer supervision and review, which traced both reported errors to the single duplicated `-B` option and verified the fix by regenerating and running the plotting shellscript against a user-supplied grid, confirming that `psbasemap` and the subsequent `psconvert` rendering step both completed successfully.

5.8.3beta21 (September 13, 2026)

Programs mbedit, mbnaveedit, and mbvelocitytool: fixed a misleading error dialog reported in Github issue #1577, where any failure to open the input swath file (a missing file, a permissions problem, an overly long path, or anything else) produced the exact same hardcoded message asserting a single, often wrong, cause ("File may not exist or you may not have read permission in this directory!"). The underlying `mb_read_init()` failure does not preserve the original `errno` from the failed `fopen()` through to the GUI's error-dialog code, so the three programs previously had no way to tell these cases apart. A new shared helper function, `mb_file_open_error_message()` (`src/mbaux/mb_xmutil.c/.h`, part of the `libmbxmutil` library introduced in 5.8.3beta20), independently re-diagnoses the failure with `stat()/access()` at the point the dialog is raised and reports one of "File does not exist," "Path is too long (N characters)," "Permission denied," or "File exists but could not be read (wrong format?)" as appropriate, replacing the single fixed message at the corresponding call site in each of the three programs. No bug causing swath file paths of any particular length to actually fail to open was found during this investigation - `MB_PATH_MAXLINE` (1024 bytes) is used consistently for the swath file path in all three programs, from the Motif file-selection dialog through `mb_read_init()` and `mb_format.c` - so the long path reported in the original issue is understood to have hit an operating-system path-length limit rather than an MB-System bug; the fix is to the error reporting itself. All three affected programs were rebuilt and the new helper's diagnosis was verified standalone against a nonexistent file, a path of about 2000 characters, and an existing file of the wrong format.

Man pages: fixed ten manual pages that existed as files in `src/man/man1/` but were never installed because they were missing from the file lists in `src/man/man1/CMakeLists.txt`, so `cmake --install` never copied them regardless of build configuration. This included `mbphotomosaic` (reported missing from `/usr/local/share/man/man1`) along with `mbgetphotocorrection`, `mbimagecorrect`, `mbm_makeimagelist`, and `mbphotogrammetry` (all built only when `buildOpenCV` is enabled, in `src/photo`), `mbgrd2octree` and `mbgrdtilemaker` (built only when `buildTRN` is enabled, in `src/mbtrnutils`), and

mbm_phins2fnv, mbm_rollerror, and mbm_trnplot (in src/macros, built unconditionally). The fix adds all ten page names to src/man/man1/CMakeLists.txt: the three macros pages join the main unconditional list, the two TRN pages join the existing buildTRN-gated set alongside mbtrnpp.1, and the five photo pages form a new buildOpenCV-gated set, matching the conditions under which their corresponding executables are actually built. The eleven man pages gated by buildDeprecated (mb7k2ss, mb7kpreprocess, mbauvnavusbl, mbhsdump, mbhysweepprocess, mbkongsbergprocess, mbneptune2esf, mbotpsold, mbrollbias, mbstripnan, and mbswplsprocess) were confirmed to already be correctly excluded, since their corresponding programs are likewise not built or installed when buildDeprecated is off. Verified by reconfiguring and reinstalling the man1 directory and confirming `man mbphotomosaic` and the other nine previously missing pages now resolve correctly.

Program mbimagelist: added three new command line options extending the program's output modes and time filtering. The new `--imagelist` option reproduces the full eight-column row format used by imagelist files themselves (left and right image paths, left and right timestamps, left and right gains, and left and right exposures), printing "NULL" in place of a missing left or right path (and 0.0 for its associated time, gain, and exposure) for single-camera or one-sided stereo entries; this is an alternative to the pre-existing `--files` (the default) and `--settings` output modes. New `--start=yyyy/mm/dd/hh/mm/ss.ssssss` and `--end=yyyy/mm/dd/hh/mm/ss.ssssss` options (fractional seconds supported) restrict the image listings that are output to those falling within a given time period, applied uniformly across all three output modes; by default all image listings encountered are still output. Also fixed `--parameters`, which prints imagelist `#PARAMETER` entries (the camera calibration, platform, navigation, tide, image-quality, and image-correction files that an imagelist can reference for use by mbphotomosaic and related programs): a parameter whose value is one of these file paths is now output resolved relative to the current working directory rather than as the bare filename originally written in the imagelist, matching the equivalent path resolution mbphotomosaic.cc already performs when it reads these same entries, while a path that is already absolute is left unmodified; this resolution is applied in all three of mbimagelist's output modes (`--files`, `--settings`, and `--imagelist`), not only when `--imagelist` is in use. The mbimagelist manual page was updated to document all of the above, and its EXAMPLES section - previously describing an unrelated swath-datalist workflow copied from a different program's man page - was replaced with examples that actually exercise mbimagelist's imagelist parsing and the new options.

Man page audit: starting from a user-reported case where the mbphotomosaic manual page candidly documented that its --section-length-max option had no effect (the argument-parsing code re-tested for the --section option name instead of --section-length-max), all manual pages under src/man/man1 were searched for similar language admitting that an option was non-functional, dead, or otherwise not doing what it claimed. This turned up ten further cases across eight programs, each independently confirmed against the actual source before being fixed; three of these had a documented option removed outright (at the user's direction, rather than implemented), and the rest had the underlying bug fixed so the documented option actually works, with each affected manual page corrected to match.

Program mbphotomosaic: fixed --section-length-max, which sets the maximum allowed length (in output grid cells) of the longest diagonal of an image section's projected quadrilateral; the option-parsing code tested the long-option name "section" a second time instead of "section-length-max", so the value was never read and the compiled-in default of 0.5 was always used regardless of what was passed on the command line.

Program mbphotogrammetry: removed --good-fraction-threshold, which was accepted on the command line but declared and never read anywhere in the program's option-processing logic, so it had no effect under any value.

Program mbm_makeimagelist: fixed -f/--imformat=image_format, which was supposed to set the image file suffix (e.g. "tif", "jpg") searched for in the PROSILICA_L and PROSILICA_R subdirectories, but instead wrote its value into the image-directory variable (--imdir) by mistake, leaving the search suffix stuck at the compiled-in default "tif" no matter what format was requested.

Program mbhysweeppreprocess: removed -O/--output, which was intended to set the output data file path but had no effect - the program always constructs the output filename automatically from the input filename regardless of this option. Separately, and unrelated to the option audit, all five calls to mb_platform_set_sensor_offset() in this program passed 13 arguments against the function's 11-parameter declaration (each call had a stray extra boolean spliced in where position_offset_x belongs, and the sonar-sensor calls additionally duplicated that same variable a second time where the attitude offsets belong); this does not build at all with -DbuildDeprecated=ON, and, more importantly, was silently dropping the sonar's own heading/roll/pitch mounting-angle offsets even where the call happened to match by argument count. All five calls now pass exactly the arguments the function declares.

Program mbauvnavusbl: removed navformat and usblformat (the -F/--navformat and -M/--usblformat equivalents in this getopt-based program), both accepted but unused - the input navigation and USBL files are always parsed as whitespace-delimited ASCII text regardless of either value.

Program mbgetphotocorrection: removed --altitude-sensor=altitude_sensor_id, whose value was parsed and stored but never applied to the platform model, unlike the otherwise-identical --attitude-sensor, --heading-sensor, --nav-sensor, and --camera-sensor options, which do work.

Program mbgrdtilemaker: removed --mode/-M, whose value was parsed and stored but never referenced anywhere else in the program (the long-option form was in fact doubly dead, since the option-parsing chain tested for the string "tile-mode" rather than the registered long-option name "mode", so even the stale --tile-mode=mode text in the program's own usage message could never have matched). Also fixed --verbose, which previously had no effect on the volume of output: a full dump of input-grid and output-tileset parameters, plus a line per tile and a line per mbgrd2octree invocation, was always printed to stdout regardless of this setting. Now a single run without --verbose reports the input grid path and a final tile count only; --verbose restores the full parameter dumps and per-tile/per-invocation detail, routed through the program's existing verbose-controlled output stream rather than hardcoded to stdout.

Program mbimagelist: fixed --left, --right, and --single, which accepted their arguments but never filtered anything - every image listing was output regardless of which of these was given. --left and --right now restrict the listing to left-camera and right-camera images respectively (the non-selected side of a stereo pair is omitted, or written as NULL in --imagelist output), and --single restricts it to single-camera (non-stereo) images; the end-of-run left/right/single/total image counts and any file copying requested with --copy now likewise reflect only what was actually selected. This required a root-cause fix in shared code: MB_IMAGESTATUS_SINGLE and MB_IMAGESTATUS_LEFT (src/mbio/mb_status.h) were defined to the identical value, so a genuinely single-camera image and the left half of a stereo pair were indistinguishable to every piece of code that inspected an image's status. This had already made three "else if (... == MB_IMAGESTATUS_SINGLE)" branches unreachable dead code, one each in mb_format.c, mbgetphotocorrection.cc, and mbphotomosaic.cc, and had caused a real miscount in mbimagelist's own left/single image tallies. MB_IMAGESTATUS_SINGLE was given its own distinct value, and a related bug in mb_format.c's handling of the "\$SINGLE"/"#SINGLE" imagelist tag - which was setting the internal mode to MB_IMAGESTATUS_LEFT instead of

MB_IMAGESTATUS_SINGLE, presumably the original source of the aliasing - was corrected. The previously-dead SINGLE branches in mbgetphotocorrection.cc and mbphotomosaic.cc were reviewed and confirmed to behave sensibly now that they actually execute; no changes were needed to their logic.

Macro mbm_phins2fnv: implemented actual translation of processed iXblue Phins INS navigation data into MB-System's fnv navigation format, replacing a version that only parsed and echoed the input table to the shell without ever writing the output file named by -o/--output. Also implemented --verbose, which previously had no effect: it now reports the input/output filenames, warns about and skips any input line that cannot be parsed instead of aborting the whole conversion, and prints a final count of lines read, written, and skipped; without --verbose the macro now runs silently on success rather than always dumping the parsed input table.

Test suite: fixed an intermittent-failure race condition in test/xvfb_helper.py, the shared helper that starts a private Xvfb X server for the mbedit, mbnavedit, mbeditviz, mbvelocitytool, and mbnadjust GUI smoke tests (these Motif programs open an X display before parsing arguments, so even "-h" needs one). The helper previously just slept a fixed 1.5 seconds after starting Xvfb and hoped that was long enough for it to bind the display; under load - for example, running the test suite immediately after a full rebuild - this was not always long enough, and all five tests would fail together with the GUI program unable to connect. The fixed sleep was replaced with active polling for the X11 lock file that signals Xvfb has actually bound its display (with a generous timeout and a clear error if Xvfb exits early instead), and display-number selection now skips any number already locked by another X server instead of trusting random selection alone to avoid collisions. Verified by running the full test suite repeatedly, both serially and under `ctest -j8`, with all 73 tests passing consistently.

The changes described above were found, diagnosed, and made with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model claude-sonnet-5), operating as Claude Code under developer supervision and review; the affected programs and man pages were rebuilt (including a scratch build configured with -DbuildDeprecated=ON to cover mbhysweepprocess and mbauvnavusbl, which are not part of the default build) and reinstalled where applicable, and the fixes were verified after the changes were applied, including a full test suite run.

Macro mbm_grdinfo: fixed a bug that broke mbm_grdplot's -G6 and -G7 image-plotting modes whenever a -R region was given. mbm_grdinfo cuts a temporary subregion via mbm_grdcut before reporting bounds, naming the

cut file by appending "_grdcut_" to the end of the whole input filename; for an image input such as foo.png this produced foo.png_grdcut_12345, which no longer ends in a recognized image extension, so GMT's grdcut could not tell what format to write and mbm_grdplot aborted with "The program grdinfo does not appear to have worked properly." Grid files were unaffected, since GMT does not require a recognized extension to write a grid. The fix inserts the "_grdcut_" suffix before a recognized image extension (png/tif/tiff/jpg/jpeg/gif/bmp) instead of after it, so the temporary file keeps a name GMT recognizes.

Macro mbm_grdplot: fixed color_mode 6 ("Image plot using embedded georeferencing") so it no longer emits an explicit -D option to gmt grdimage. GMT (as of 6.7.0) zeroes an image's read padding as soon as -D or -Dr is passed explicitly, before it has determined whether the plot's projection will actually need to resample the image; for any non-Cartesian projection (e.g. -Jm) that does need resampling, this left grdimage aborting with "gmt_img_project: Input image does not have sufficient (2) padding" for any image large enough to take that code path, regardless of the image having valid embedded georeferencing (e.g. a PNG with an accompanying .pgw world file). grdimage already auto-detects an image's embedded georeferencing on its own when -D/-Dr is omitted, via a code path that keeps the normal padding, so dropping the explicit -D for mode 6 avoids the crash entirely; color_mode 7 ("Image plot using bounds specified with -R") still requires -Dr, since without it GMT has no way to assign real-world coordinates to a genuinely non-georeferenced image, and so remains subject to the same underlying GMT limitation if such an image needs resampling under a non-Cartesian projection. Verified by regenerating and running a user's mbm_grdplot -G6 command against a large (6471x5068) georeferenced LASS photomosaic PNG under a Mercator projection, confirming the previously-empty output plot now contains the actual projected image.

These two fixes were found and made with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model claude-sonnet-5), operating as Claude Code under developer supervision and review, in response to a user's report that mbm_grdplot was failing to plot a LASS photomosaic; both fixes were verified against the user's actual data files.

Macro mbm_grdplot: fixed four bugs in the color-palette (CPT) generation logic, found while building an independent Python re-implementation of mbm_grdplot's page-layout, projection, and color-generation logic and cross-checking every code path bit-for-bit against the Perl macro's own output on synthetic test grids.

The ratio-based azimuthal projections (-Ja, -Je, -Jg, -Js) computed the wrong map scale whenever mbm_grdplot was left to auto-fit the plot to the page rather than being given an explicit scale: the auto-fit scale is expressed as a "1:NNNN" ratio string, but the code assembling the final -J argument ran that string through a `sprintf("%g", ...)` call, and Perl's numeric coercion of a string stops at the first non-numeric character, silently truncating a scale such as "1:436897" down to "1" - a wildly wrong 1:1 map scale on any auto-scaled plot using one of these four projections. Fixed by appending the ratio string directly instead of formatting it as a number.

The continuous-style (default) histogram-equalized color stretch (-S) always dropped the true (padded) maximum data value from the generated color palette: the code asked GMT's `grdhisteq` for `ncolors` bins (`ncolors + 1` boundary values) but only ever consumed `ncolors` of them, always discarding the last one, so the final color segment fell short of the actual data range by however much the discarded bin spanned. Fixed by folding that last boundary into the final consumed slot instead of discarding it, merging what would have been the last two equalized bins into one final segment rather than truncating the color range.

Discrete-style (-W2) color palettes - both the regular single-built-in-palette case and the "Sealevel" dual-colormap case (color palette 8, and the related unnamed palette 9) - always rendered one extreme color segment solid black. Discrete style has one more color segment than continuous style, but the palette-interpolation loop that builds the underlying color samples was still sized for the continuous-style count in both cases, so the extra discrete segment read one entry past the end of the interpolated-color array; Perl's silent out-of-bounds array read returns `undef`, which a numeric `printf` renders as 0, so the darkest or lightest extreme of the palette came out solid black instead of showing an actual color. Fixed by sizing both interpolation loops off the same `ncolors_use` variable already used elsewhere in the macro to distinguish continuous- and discrete-style color counts.

A fifth, related oddity was noticed but not changed: the Sealevel dual-colormap code's guard against a negative sea-level-crossing index checks a variable (`iszero`, with an extra "s") that is never otherwise assigned or read, so the guard is dead code and the intended clamp to zero never actually happens. No real-world case triggering a negative index was found during this investigation, so this was left as a flagged, unconfirmed issue rather than fixed speculatively.

All four fixes were verified by generating synthetic test grids - including one deliberately straddling sea level, to exercise the Sealevel dual-colormap path - and comparing mbm_grdplot's own generated color-palette-table content,

before and after each fix, directly against the from-scratch Python re-implementation built for this investigation.

The changes described above were found and made with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model claude-sonnet-5), operating as Claude Code under developer supervision and review, while independently porting mbm_grdplot's layout and color-generation logic to Python; all four fixes were verified against real mbm_grdplot output on synthetic test grids before and after each change.

Macros mbpy_grdplot, mbpy_grd3dplot, mbpy_histplot, and mbpy_xyplot: added four new Python/PyGMT-era macros that generate GMT modern mode shells (`gmt begin` / `gmt end`), replacing the classic-GMT-mode Perl macros mbm_grdplot, mbm_grd3dplot, mbm_histplot, and mbm_xyplot respectively while reproducing each one's own page-layout, projection-fitting, and (where applicable) color-palette conventions closely enough to produce visually equivalent plots. The four tools share three support modules (mbpy_layout.py: page-size/projection/tick-interval math and grid metadata parsing; mbpy_color.py: color-palette/CPT generation; mbpy_misc.py: coastline/contour/navigation/xy-overlay option modeling), plus one script-generator module each (mbpy_grdplot_script.py, mbpy_grd3dplot_script.py, mbpy_histplot_script.py, mbpy_xyplot_script.py); mbpy_xyplot_script.py in turn reuses page-size and tick-interval helpers from mbpy_histplot_script.py and the baseline GMT-defaults helper from mbpy_grdplot_script.py, since mbm_xyplot's own page-size and tick-interval subs were confirmed, by direct comparison of the Perl sources, to be identical to mbm_histplot's (not mbm_grdplot's, despite superficial similarity). Unlike the Perl macros' packed single-letter "-M_{_{:...}}" option grammars, each Python macro exposes coastline, contour, navigation, xy-overlay, text-label, and length-scale-bar tuning as its own descriptive long option.

A number of real bugs - in both the original Perl macros and in early versions of this Python port - were found and fixed while cross-checking the new macros' output against the classic macros' own, on both synthetic test grids and real survey data:

mbpy_grdplot/mbpy_grd3dplot: fixed a missing fallback for grids whose metadata does not literally identify them as a UTM/projected coordinate system (e.g. MB-System's own "LTM" grids) but whose coordinate values are clearly not geographic (lon/lat) - mbm_grdplot/mbm_grd3dplot both fall back to treating such a grid as projected based on its actual coordinate bounds, a check the initial Python port omitted, causing

`gmt mapproject` to fail outright on a real projected grid. Also fixed a

case where a user-supplied -R region string overrode the plotted region but not the xmin/xmax/ymin/ymax values driving the page-fit/scale computation, producing a wildly wrong plot aspect ratio for any sub-region request; and a case where the corrected projected/geographic determination above was not propagated to the shading commands that separately consult it, so

`grdgradient`'s -fg flag could disagree with the layout calculation that had just been corrected. Separately, `run_grdinfo()` (both macros' shared `gmt_grdinfo` output parser) crashed with a `UnicodeDecodeError` on a real grid whose embedded NetCDF metadata contained a non-UTF-8 byte; it now decodes that output with `errors="replace"`.

`mbpy_histplot`: fixed three compounding bugs in the default (no explicit -J) page-fit scale computation, found by comparing a generated plot against real `mbm_histplot` output for the same data. `mbm_histplot` has its own `GetPageSize` subroutine, distinct from `mbm_grdplot`'s (no color-scale-bar-placement branching, and, unlike `mbm_grdplot`'s version, no clamping of margins to an absolute maximum); the initial port wrongly reused `mbm_grdplot`'s version. `mbm_histplot` also computes two independent x and y scales that each separately fill the page (appropriate since a histogram's value and frequency-percent axes have unrelated units and ranges) and always defaults to landscape orientation, rather than `mbm_grdplot`'s single aspect-ratio-preserving scale; the initial port wrongly reused that logic too, which visibly squashed a real histogram plot down to a fraction of an inch wide. A third, smaller bug remained after both fixes: the no-map-scale default scale value was incorrectly run through logic meant only for a partially-parsed user-supplied -J flag, producing a garbled probe value used to test the plot's apparent size. All three fixes were confirmed by matching the macro's computed plot scale to the real `mbm_histplot` output to 8+ significant figures. Separately, classic `pshistogram`'s outline-pen option, -L, is not accepted by the current `gmt_histogram` module (which uses -W like nearly every other GMT plotting module); `mbpy_histplot` emits the current -W syntax.

`mbpy_xyplot`: a new macro with no classic-mode-only options list. Beyond page-layout parity with `mbm_xyplot` (confirmed identical to `mbm_histplot`'s own algorithm, as above), this macro's main design goal was eliminating `mbm_xyplot`'s persistent-temporary-file behavior: `mbm_xyplot` preprocesses every -I input file (delimiter-splitting, and evaluating any user-supplied per-file column-selection/ math expression) into a file named "<input><n>.<pid>" left behind in the working directory after every run, whether or not the generated plot script is ever executed. `mbpy_xyplot` instead performs the equivalent column-selection/math once in memory, in Python, to determine the auto-fit plot bounds, and pipes each input file through a small `awk` program

straight into `gmt plot`'s standard input at plot time - a live, ephemeral pipe, with nothing written to disk. While validating this against real data, two further issues surfaced: `mbm_xyplot`'s own per-line numeric-result validation is an unintentional no-op (its regex is satisfied by the empty string), so an ordinary text header line at the top of a data file passes through unfiltered - and because `gmt plot` infers each column's data type from the first record it reads, that single non-numeric first line silently discarded every subsequent, valid row instead of just itself; `mbpy_xyplot` validates each computed x/y pair with a real numeric check instead. And a data column that is exactly constant across an entire file (e.g. a real "heave" trace logged as 0.0 for a whole survey) collapses to a zero-width plot axis that neither classic nor modern GMT can project at all; `mbpy_xyplot` now pads such a degenerate axis by a small margin so it still renders as a visible flat line rather than aborting. (A genuine, separate bug was also found in `mbm_xyplot`'s own -MGT text-label option - the extraction regex tests for "GP" where the surrounding check tests for "GT", almost certainly a copy/paste slip, so no -MGT label has ever actually been added to a plot - but `mbpy_xyplot` has nothing to port this into, since it exposes text labels as a plain --text long option rather than reproducing the "-M<sub>:<sub>:..." grammar at all.)

Manual pages were written for all four new macros (`mbpy_grdplot.1`, `mbpy_grd3dplot.1`, `mbpy_histplot.1`, `mbpy_xyplot.1`), and `mbsystem.1` and `src/html/mbsystem_man_list.html` were updated to list all four alongside their classic-macro counterparts.

The four new macros and their manual pages were found, built, and documented with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review; each macro was verified against real survey data (including, for `mbpy_xyplot`, generating eight time-series plots of navigation and attitude data from a real AUV mission) as well as the regression test suite covering the shared `mbpy_layout/mbpy_color/mbpy_misc` modules, and the man pages were verified to render cleanly and to accurately match each tool's current command-line options.

////////////////////////////////////

5.8.3beta20 (September 10, 2026)

Programs `mbedit`, `mbnavedit`, `mbvelocitytool`, `mbgrdviz`, `mbeditviz`, and `mbnavadjust` (all of the interactive Motif-based bathymetry/navigation editors and 3-D viewers, plus the `mbnavadjustmerge` command-line tool that shares `mbnavadjust`'s project file I/O code): a follow-on memory-management and array-bounds audit, extending the `mbedit/mbnavedit/mbvelocitytool` review

from 5.8.3beta19's release notes to the three remaining interactive programs that had not yet been covered. Many real, independently confirmed bugs were found and fixed; the most significant are summarized below by program. As with the earlier audit, each finding was verified against the actual code before being fixed rather than assumed from a pattern match, and every affected program was rebuilt and smoke-tested afterward.

A new shared helper function, `mb_get_text_string()` (`src/mbaux/mb_xmutil.c/.h`, built as the new library `libmbxmutil`), replaces five independent implementations of the same "read a Motif text widget's contents into a fixed-size buffer" helper that had accumulated across `mbedit`, `mbnavedit`, `mbvelocitytool`, `mbeditviz`, and `mbnavadjust` as each program's GUI code evolved separately over the years. All five were doing an unbounded `strcpy()` of the widget's text (none of the underlying text widgets set `XmNmaxLength`) into destination buffers as small as 40 bytes, an easy stack overflow for anyone able to type or paste into the affected dialog field. `mbedit`, `mbnavedit`, and `mbvelocitytool` had already had this specific bug fixed in place as part of the 5.8.3beta19 audit, but each program's copy remained a separate piece of code; this release consolidates all five onto the one bounded, NULL-safe shared implementation and deletes the local copies (`mbgrdviz` did not have a named helper of its own but had the identical unguarded pattern at one call site, which was converted to use the new shared function as well).

Program `mbgrdviz`: fixed a NULL-pointer-check written in the wrong order in `do_mbgrdviz_openfile()` -

```
strlen(file_ptr) <= 0 && file_ptr != NULL
```

 evaluates `strlen()` on `file_ptr` before confirming it is non-NULL, so a NULL return from `XmStringUnparse()` would crash before the guard intended to catch it ever ran; fixed by testing `file_ptr` for NULL first. Fixed an unbounded `strcpy()` from the Area/Route name text field into a static 1024-byte buffer, reachable on every keystroke while typing a survey/route name (now uses the new shared `mb_get_text_string()` helper). Fixed four unbounded `sscanf(optarg, "%s", ...)` command-line option parsers (both the `--grid-file/--overlay-file` long-option handlers and their `-I/-J` short-option equivalents) that could overflow the destination path buffers given an implausibly long argument; all four now use a field-width-limited `"%1023s"` instead. Fixed a `size_t` underflow parsing a route file whose `### ROUTENAME` header line has no name after it -

```
route_name[strlen(route_name) - 1]
```

 wrapped to `SIZE_MAX` when the string was empty, producing an out-of-bounds access; now guarded against the zero-length case. Fixed a `strcpy()/strcat()` pair building a status message that could overflow its destination buffer by roughly 20 bytes given a near-maximum-length swath file path, by replacing it with a single bounds-

checked `snprintf()`. Fixed a missing `if (status == MB\_SUCCESS)` guard in the interactive survey-line generator that would write through a NULL pointer following a failed memory allocation, and a related sequence of chained reallocations reading navigation data that could similarly write through a NULL array pointer after a failed reallocation partway through the chain. Added missing NULL checks after `malloc()/strdup()` calls building the argument list used to launch `mbedit`, `mbnavedit`, `mbvelocitytool`, and `mbeditviz` as background subprocesses from `mbgrdviz`'s swath-file and navigation-file context menus - all four of these near-identical "launch a companion tool" functions now report an error and decline to launch rather than crashing if memory could not be allocated for the subprocess's argument vector. Fixed a version-string-detection comparison in the site file reader that compared only the first two characters of the file's header line ("##") rather than the full 21-character label, which made the branch match any comment line rather than specifically the version header.

Program `mbeditviz`: fixed a heap buffer overflow copying a GUI-selected swath file's path into a fixed 1024-byte struct field with an unbounded `strcpy()`, reachable simply by selecting or typing a sufficiently long path in the Open Swath Data file-selection dialog; and a matching stack overflow in the `--input/-I` command-line option parser using the same unbounded `sscanf()` pattern noted above for `mbgrdviz` - both replaced with bounds-checked copies. Fixed three unchecked `realloc()` calls, all in the interactive 3-D point-cloud selection code (selecting soundings by region, by area, and by navigation point), where a failed reallocation both leaked the previous, still-valid buffer and was then written through as if it had succeeded; all three now `realloc` into a temporary pointer, verify it before committing, and cleanly abandon the append on failure instead. Fixed five unchecked `mb_mallocd()` calls in the interactive sensor-bias optimization routine (used by the "Optimize" button in the 3-D soundings editor's bias-parameter dialog), where a single failed allocation partway through the chain could be masked by a later successful one and ultimately `memset()` through a NULL pointer; the chain is now correctly short-circuited on the first failure. Fixed eight sites building per-file auxiliary-sensor-data filenames via `strcpy()+strcat()` with no headroom for the appended suffix, all replaced with a single bounds-checked `snprintf()` each. Fixed a copy-paste variable-name error in the `sensordepth`-data fallback loader, which checked whether heading data was missing (`file->n_async_heading`) instead of whether `sensordepth` data was missing (`file->n_async_sensordepth`) before attempting to load `sensordepth` from an alternate file format - this both skipped the fallback when it was actually needed and, when it ran under the wrong trigger condition, could overwrite a previously loaded `sensordepth` array without freeing it first, leaking memory;

both the wrong condition and the missing free were fixed. Also fixed an unchecked malloc() building the file-list display's array of Motif string objects.

Programs mbnadjust and mbnadjustmerge: this was the most extensive part of the audit, reflecting mbnadjust's status as the largest and most complex of the programs reviewed. In mbnadjust_io.c (the project file reader/writer shared by both programs): fixed a missing upper-bound check on the reference-grid count (NUMREFERENCEGRIDS) read directly from a project (.nvh) file header, which was later used unchecked as a loop bound writing into fixed 25-element arrays - a corrupted or hand-edited project file naming more than 25 reference grids would overrun those arrays on load; the count is now clamped to the array capacity, with a warning, immediately after being read. Fixed a navigation-tie snav index (snav_1/snav_2) read from a project file that was checked only against its upper bound, not for being negative, so a negative value in a malformed file would be used directly as a negative array index into several fixed per-section arrays; the same "fixup" already applied to out-of-range-high values is now also applied to negative values, and the fixup's own internal division was additionally guarded against a zero divisor. Fixed three separate sites where a crossing or section array was grown with realloc() and then used or reported as successful without checking whether the reallocation itself had failed (in mbnadjust_findcrossingsfile(), mbnadjust_addcrossing(), and - originally left as a flagged follow-up during the main audit pass and completed immediately afterward in a dedicated follow-up review - mbnadjust_import_file()'s per-section array, whose fix required tracing roughly 700 lines of ping-by-ping import logic to identify a safe place to abort the import cleanly on allocation failure); all three, plus a fourth occurrence found independently during the audit's own verification pass in mbnadjust_remove_short_sections(), now realloc into a temporary pointer, verify it, and only commit the new pointer and proceed to use the array once success is confirmed, matching the safe pattern already used correctly elsewhere in the same file. Fixed a chain of mb_mallocd()/mb_reallocd() calls loading section ping data that reused a single status variable in a way that let a later successful call mask an earlier failure, then proceeded to copy data into the resulting (possibly still-NULL) buffers. Fixed an inconsistency where a global tie could be marked as set (a non-"none" status) while its associated navigation-point index was left at the "unset" sentinel value of -1, which would then be used as a negative array index in three separate places; the inconsistency is now resolved once, at load time. Fixed a use of project->logfp (the project's open log-file handle) that was not guarded against being NULL if a previous attempt to reopen the log file for the current session had failed; both the root cause (the project being left marked "open" despite the failed log reopen) and the unguarded use were fixed. Fixed a

negative array index reached when merging a too-short section into a preceding section that itself has zero navigation points. Fixed two functions that built `project.path/project.home/project.datadir` from an externally supplied path via unbounded `strcpy()/strcat()` chains with no check that the result would fit the 1024-byte destination fields.

In `mbnavadjust_prog.c`: fixed the same unbounded `sscanf(optarg, "%s", ...)` pattern noted above for the `-l/--input` option. Fixed three chained-`mb_mallocd()` sites in the navigation-inversion setup code with the same status-masking hazard described above for `mbnavadjust_io.c`. Fixed a concrete, easily reachable array-corruption bug in the `--reset-crossings/-R` option's handling: a loop meant to zero each navigation point's offset arrays used its own loop variable to compute values but never actually used that variable as the array index, instead repeatedly writing to a single fixed index (the section's total navigation-point count) every iteration - for any section with a full set of navigation points (the ordinary case), this silently corrupted adjacent struct fields on every project processed with `--reset-crossings`; the loop now correctly indexes by its own loop variable. Fixed an incomplete field copy when deleting a navigation tie from the middle of a crossing's tie list, which copied only a handful of the tie structure's roughly two dozen fields during the compacting shift, leaving `sigma`, `inversion-result`, and `block-association` fields stale after any non-last tie was deleted; the partial field-by-field copy was replaced with a single whole-structure assignment that is guaranteed to copy every field. Fixed nine model-plot mouse-pick handler functions that read uninitialized local variables when no navigation point happened to be visible in the plot at the time of the click; all nine locals are now initialized to the project's own "nothing selected" sentinel value at declaration. Fixed a `realloc()` of the contour-plotting vector buffer that lost the previous, still-valid buffer on failure, and a related double-counted size increment in the same buffer's growth logic. Fixed a stale `project.path` left over from a previous project when creating a new project by a bare filename with no directory component, by adding the same current-working-directory fallback already used correctly in the sibling project-opening function.

In `mbnavadjust_callbacks.c`: replaced this file's own independent, unbounded copy of the `get_text_string()` helper described above with the new shared implementation, fixing the same stack-overflow-prone pattern at its three call sites (the worst being a 40-byte destination buffer reachable from the Import Data dialog's format field). Fixed three GUI menu actions ("Show Selected File," "Show With Selected File," "Show With Selected Section") that changed the project's view mode unconditionally, without checking that a file or section had actually been selected first, which could lead a later status-display routine to read `project.files[-1]`; all three now check for a valid selection first. Fixed two sites using the C library's `free()` instead of

Motif's XtFree() to release memory returned by XmListGetSelectedPos(), an allocator mismatch that is usually harmless on this codebase's current Linux/macOS Xt implementations but is a real portability hazard for the ongoing Windows port effort. Fixed two strncpy() calls that did not reserve room for an explicit null terminator, unlike the already-correct pattern used a few lines earlier in the same file. Fixed four sites checking only the lower bound of a reference-grid index before using it, adding the missing upper-bound check against the project's actual reference-grid count. Added missing NULL checks after all twenty-three malloc() calls building the Motif string-list arrays used to populate mbnadjust's various list-view displays.

In mbnadjust_invertnav.c (the navigation-inversion/least-squares solver): fixed a copy-paste bug in the z-only global-tie handling that read from the parallel xy-tie index arrays instead of the z-tie index arrays, both mis-indexing a smaller array (an out-of-bounds read) and computing the wrong file/section for a diagnostic warning message - and, while tracing this bug, found and fixed the same file/section index confusion in the analogous xy-tie warning code as well. Fixed the sparse inversion matrix's per-row storage stride, which had been sized from the total number of navigation-point unknowns across the whole project rather than the true maximum per-row width actually used by the matrix-filling code (the number of survey blocks); for a realistic project with many navigation points and comparatively few survey blocks this could allocate a dramatically larger matrix than necessary. Fixed a smoothing-constraint row-count formula that undercounted relative to the loop that actually generates those rows, silently dropping smoothing rows from the per-survey inversion pass in a way that degraded but did not crash the solution. Fixed an unbounded strcpy()/strcat() chain building a tie-solution output filename, and a copy-paste sizeof() argument that measured the wrong (but coincidentally smaller and therefore non-overflowing) buffer in an snprintf() call.

In mbnadjust_autopick.c (automatic crossing/tie detection): fixed a misfit-grid realloc() chain whose individual reallocations were each checked, but whose subsequent binning and misfit-calculation loops did not confirm that the whole chain had succeeded before using the resulting buffers, and whose failure-cleanup path freed buffers without clearing the now-dangling pointers, risking a double-free on a subsequent call.

In mbnadjustmerge.c (the command-line project-merging tool): fixed a non-positive-value check missing from the --zoffsetwidth option, whose value is used as a divisor in the automatic-tie misfit calculation - a value of zero produced a division by zero and a wild array index; the option is now validated at parse time. Fixed three CLI actions (--set-tie, --triangulate-section, --remove-file) that used file/section indices taken directly from the

command line to index the project's file and section arrays with no bounds check, unlike the already-hardened `--add-crossing` action in the same file; all three now use the same bounds-checking pattern. Fixed unbounded `%s` conversions parsing a `--import-tie-list` file's TIE and GLOBALTIE lines into fixed-size path buffers, and six sites dereferencing the result of `strchr(path, '/') + 1` without checking for NULL, which would crash given a bare filename with no directory separator. Fixed the same incomplete-tie-field-copy pattern described above for `mbnavadjust_prog.c`, here occurring during tie deduplication while importing a tie list. Fixed a file-section cross-reference (`file_id`) that was not being remapped to the merged project's own file numbering when files were copied in during a project merge.

In `mbnavadjust_fine.cc` and `mbnavadjust_icp.cc` (the optional PCL-based fine ICP registration tool, `mbnavadjustfine`, built only when PCL is available): fixed an unbounded `strcpy()` for the `--input` option's project path. Fixed a `--threads` option whose value was clamped to an upper bound of 8 but not to a lower bound of 1, so `--threads=0` produced a division by zero. Fixed two call sites that used a crossing's loaded swath data without checking whether the load had actually succeeded. Fixed a `--try-all` code path that read a crossing's first tie unconditionally even when the crossing had zero ties, using uninitialized offset values as the registration's initial alignment guess; a zero-offset default is now used in that case instead. Fixed a debug/PLY-export color-scaling divide-by-zero when every point correspondence happens to have the same distance, and added a missing check for the "no correspondence found" sentinel index before using it to index a point cloud, mirroring an equivalent guard that already existed in the corresponding header-only function.

The `mbedit/mbnavedit/mbvelocitytool/mbgrdviz/mbeditviz/mbnavadjust/mbnavadjustmerge` changes described above were found, diagnosed, and made with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review; all affected programs were rebuilt from source and smoke-tested after the changes were applied. The two `mbnavadjustfine/mbnavadjust_icp.cc` source files could not be compiled in the development environment used for this pass, since the optional PCL (Point Cloud Library) dependency they require was not installed there; those two files' changes were reviewed by hand (including a targeted check for the specific comment-syntax error described immediately below) but should be verified with a real PCL-enabled build before this release is finalized.

One of the fixes described above (in `mbnavadjustmerge.c`) was initially written with a C-style block comment whose text happened to contain the two-character sequence `"*/"`, which closed the comment early and broke

compilation; this was caught during a final full-project rebuild performed specifically to verify every change in this release, and is noted here as a reminder that even a change confirmed correct by an independent read-through and a brace-balance check still needs to actually compile.

5.8.3beta19 (September 10, 2026)

Library mbview (affecting programs mbgrdviz, mbnadjust, and mbeditviz, which share this 3-D visualization library): Fixed a segmentation fault reported by a user running mbgrdviz on macOS (Homebrew private tap dwcaress/mbsystem, formula mbsystem-beta): after loading a bathymetry grid and a large set of navigation files, the very first attempt to interactively pick navigation in the 3-D/2-D view crashed the program. A debug session using lldb pinned the crash to a heap out-of-bounds read inside mbview_findpointrez(), called from mbview_findpoint(), called from mbview_pick_nav_select() - i.e., in the generic terrain-point-picking routine used by every pick mode (site, route, navigation, vector), not something specific to navigation; the user's report happened to be the first pick attempted in that session. The root cause was an off-by-one error in mbview_findpoint() (src/mbview/mbview_plot.c): the initial pick search bounds were set to

`{0, primary\_n\_columns, 0, primary\_n\_rows}`, but every other use of these bounds inside mbview_findpointrez() (including its own narrowing of the search window between successive low/high/full-resolution passes) treats the upper bounds as an inclusive last valid grid index, i.e.

`primary\_n\_columns - 1` and `primary\_n\_rows - 1`. With the too-large initial bounds, the triangle-rasterization loop used to render the OpenGL selection buffer could, once the scan reached the rightmost column or bottom row of the grid, compute a vertex index of the form

`(i + stride) * primary\_n\_rows + j` equal to `primary\_n\_columns * primary\_n\_rows + j` - one full row-block past the end of the primary_data/primary_x/ primary_y/primary_z arrays (each allocated with exactly `primary_n_columns * primary_n_rows` elements, src/mbview/mbview_primary.c) - and read that heap memory directly, crashing whenever the grid's column or row count divided evenly by the resolution's pick stride. Fixed by initializing ijbounds in mbview_findpoint() as

`{0, primary\_n\_columns - 1, 0, primary\_n\_rows - 1}`, matching the inclusive-index convention used throughout the rest of the picking code.

Library mbview: While investigating the crash above, a broader review of the navigation-picking code in `src/mbview/mbview_nav.c` and `src/mbview/mbview_plot.c` turned up two further latent bugs, neither of which caused the reported crash but both of which could cause a similar segmentation fault under other circumstances. First, in `mbview_pick_nav_select()`, all four places that search for the nearest active navigation point to a pick location (first-point and second-point/move handling, in both ordinary `MBV_NAV_VIEW` mode and `mbnavadjust`'s `MBV_NAV_MBNADJUST` mode) recorded the winning navigation file/point indices into `shared.shreddata.nav_selected[]/ nav_point_selected[]`, initialized to the sentinel `MBV_SELECT_NONE (-1)`, but then unconditionally used those indices to dereference `shared.shreddata.navs[...] .navpts[...]` afterward - if every loaded navigation file happened to be deactivated (deactivating a nav via the Nav List dialog is normal usage) or an active file had zero points, the search loop never assigned a valid index and the code dereferenced `navs[-1]`, an out-of-bounds/undefined access. Fixed by restructuring each of the four call sites so the pick-location/pick-marker code only runs once a valid navigation point has actually been found, otherwise falling through to the existing "unselect nav pick" handling. Second, in `mbview_drapesegmentw_grid()` (used to drape navigation pick-marker geometry onto the terrain), the row-index bounds `jstart/jend` were being clamped against `data->primary_n_columns` instead of `data->primary_n_rows`; for any non-square grid (the normal case for real bathymetry data), a computed row index that exceeded `primary_n_rows` but not `primary_n_columns` escaped clamping entirely. Fixed both comparisons to clamp against `primary_n_rows`.

The mbview changes described above were found, diagnosed, and made with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review.

Library mbio: Fixed a latent memory-corruption bug in `mb_update_arrayptr()` (`src/mbio/mb_mem.c`). This function is called by `mb_read()`, `mb_get()`, and `mb_get_all()` to rebind a caller's local array-pointer variables (`beamflag`, `bath`, `bathacrosstrack`, `bathalongtrack`, `amp`, `ss`, `ssacrosstrack`, `ssalongtrack`) whenever the preceding `mb_read_ping()` call has grown MBIO's internal arrays and moved them to a new allocation. It identified which caller pointer to rebind by comparing its *value* against a list of pre-reallocation ("old") array addresses recorded by `mb_update_arrays()`, but never cleared an old-address entry once it had been consumed. A stale entry could therefore persist indefinitely, and if the heap allocator later handed that same address to an unrelated allocation - a foreseeable occurrence given that `mb_update_arrays()` reallocates several same-sized arrays back to back -

the next call to `mb_update_arrayptr()` could silently repoint an unrelated pointer at the wrong array, corrupting it. Fixed by having `mb_update_arrays()` clear all recorded old-address entries at the start of every call and having `mb_update_arrayptr()` clear an entry as soon as it is consumed, and by adding a more robust primary match against the registered pointer variable's own stable address before falling back to the value-based comparison. A new regression test (`test/mbio/mb_mem_test.cc`) reproducing the false-match scenario, which was confirmed to cause a heap double-free and crash under the prior code, was added along with the fix. Diagnosed and fixed by Danny Neville of Spatialnetics, with involvement by Vicki Ferrini and Lindsay Gee, and merged as pull request #1615; the fix and test were independently reviewed and verified, including reproducing the prior code's crash and confirming the fix resolves it, with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review.

5.8.3beta18 (September 9, 2026)

Programs `mbedit`, `mbnavedit`, `mbnavadjust`, `mbvelocitytool`, `mbgrdviz`, `mbeditviz`: Fixed these Motif GUI programs printing spurious locale-related warnings to `stderr` on macOS, of the form "Warning: Locale not supported for `XmbTextListToTextProperty`" and "Warning: Cannot convert `XmString` to compound text", repeated once for every dialog or window created during a session. The root cause is that macOS's system Xlib ships locale data only for the "C" locale; when a program's environment requests a UTF-8 locale (the default in a normal macOS Terminal session), Xt's language procedure leaves `libc` and Xlib in a mismatched locale state, and Motif's `XmString`-to-compound-text conversion routines fail on every dialog as a result. Fixed by forcing the process environment (`LC_ALL` and `LANG`) to "C" before `XtSetLanguageProc()/XtVaOpenApplication()` read it, so Xt's own locale fallback completes in a consistent state instead. Three of the six programs (`mbnavadjust`, `mbvelocitytool`, `mbgrdviz`) already had a call to `XtSetLanguageProc()` present but commented out; the other three (`mbedit`, `mbnavedit`, `mbeditviz`) had no locale handling at all. This still left two harmless, one-time warnings at startup ("locale not supported by Xlib, locale set to C" and "X locale modifiers not supported, using default"), printed by Xt's own default language procedure via `XtWarning()`; these were eliminated as well by installing a temporary, silent `XtWarningHandler` for the duration of the `XtVaOpenApplication()` call in each program (the underlying `XSupportsLocale()/XSetLocaleModifiers()` calls still run normally, and the default warning handler is restored immediately afterward so any other, genuine Xt warning later in the program's life remains visible). All six

programs were confirmed to launch a real GUI session, with dialogs, completely silent under both a UTF-8 locale and an unset one.

Library mbview (affecting programs mbgrdviz, mbnadjust, and mbeditviz, which share this 3-D visualization library): Changed the "MBVIEW GEOMETRY" diagnostic messages, which report the OpenGL drawing area's size as tracked internally versus what X11 and GLX/Mesa actually report (used to help localize a rendered-image/mouse-pick coordinate offset seen with some Mesa versions on macOS), to only print when running with verbose output enabled (-V or higher), rather than unconditionally. This affected an unconditional fprintf() in the OpenGL drawing area's resize callback (do_mbview_glwda_resize() in src/mbview/mbview_callbacks.c) and the several unconditional fprintf() calls inside the mbview_debug_glgeometry() diagnostic function in src/mbview/mbview_plot.c (currently invoked only from commented-out call sites, kept available for future debugging).

Programs mbgrdviz and mbeditviz: Fixed a hang when using mbgrdviz's feature (available after loading navigation and selecting one or more files in an mbview 3-D display) to open the selected survey files in a new mbeditviz session: the new mbeditviz window would appear but never finish loading data and never become responsive. The immediate cause was a recent hardening change to how mbgrdviz creates the temporary datalist file it hands to mbeditviz: the old, predictable filename ("tmp_datalist_mb-1", fopen()'ed for write in the current directory) was replaced with a securely created mkstemp() file in the process's temp directory, which incidentally carries no recognizable format-identifying suffix at all. mbgrdviz launches mbeditviz as a fully separate process (double-fork/exec) passing only "-l

Homebrew formula mb-mesa (private tap dwcaress/homebrew-mbsystem, used only for building and testing MB-System's macOS/Homebrew distribution): Homebrew's own "mesa" formula moved to Mesa 26.2.2, which introduced a regression affecting mbgrdviz, mbnadjust, and mbeditviz on macOS: gridded surface data displayed in the 2-D map view appeared vertically shifted relative to its correct position. Added a private formula that builds Mesa 26.1.4 (the last version confirmed not to exhibit this regression) from source, resolving three problems specific to building an older Mesa release against Homebrew's current toolchain. First, Mesa 26.1.4's own meson.build looks for an OpenCL "libclc" pkg-config module by that literal name, but the "mesa-libclc" resource it must be paired with (a fork Mesa itself recommends, needed because upstream libclc built against LLVM 23+ no longer provides a required SPIR-V target) installs its pkg-config file as "mesa-libclc.pc"; later Mesa releases added a fallback that checks for "mesa-libclc" first, but 26.1.4 predates that fix, so the built mesa-libclc.pc is

now also installed under the name libclc.pc to satisfy the older lookup. Second, rather than force the whole build to configure against the "llvm@22" dependency (needed only to work around a separate rust-bindgen/LLVM-23 incompatibility), the formula isolates llvm@22 to just that purpose - exposing it only via CLANG_PATH and stripping it back out of CMAKE_PREFIX_PATH/PKG_CONFIG_PATH/PATH before configuring Mesa itself - matching how Homebrew's own current mesa formula handles the same llvm@22 dependency; this avoids Meson picking llvm@22 as the LLVM to build against and then requiring an "LLVMSPIRVLib" version that only matches llvm@22, which the regular, already-installed spirv-llvm-translator package (built against the newer default "llvm") cannot satisfy. Third, the formula is marked keg-only, since it installs the same file paths (e.g. bin/gls_l_compiler, include/EGL/egl.h) as the standard mesa formula and must not be linked into the shared Homebrew prefix alongside it.

Homebrew formula mb-mesa-glu (private tap dwcaress/homebrew-mbssystem): Added a companion formula building the Mesa GLU utility library against mb-mesa specifically, rather than the standard mesa formula that Homebrew's own mesa-glu package depends on. This is required, not merely preferable: mesa does not build GLU itself, and if a program links against mb-mesa's libGL while its GLU functions come from a libGLU built against the standard mesa, two independent libGL library images end up loaded in the same process, each with its own OpenGL context state. The GL context actually gets created and made current through whichever libGL the program itself links directly; GLU's internal calls (e.g. inside gluPerspective) are resolved against the other, contextless libGL image and are therefore silently no-ops per the OpenGL specification. This was the root cause of a separate bug introduced by switching mbview-based programs (mbgrdviz, mbnavadjust, mbeditviz) to the private mb-mesa build: the 3-D perspective view of a gridded surface stopped appearing at all (2-D map view, which uses glOrtho() rather than GLU, was unaffected), because gluPerspective()'s no-op left the projection matrix as an untouched identity matrix, clipping the entire scene out of view; forcing Mesa's software (llvmpipe) or Vulkan-based (zink) rendering backend via the GALLIUM_DRIVER environment variable made no difference, confirming the bug was independent of which Gallium driver either Mesa build used. Confirmed via otool -L library-dependency inspection that mb-mesa-glu's libGLU links against mb-mesa's libGL, matching what mbview itself links against. Like mb-mesa, this formula is keg-only.

Build system (CMakeLists.txt, build-utils/FindOpenGL.cmake): Added a macosUseMbMesa CMake option (default OFF) that, when enabled on macOS with Homebrew, points OpenGL/GLU discovery at the private mb-mesa/mb-mesa-glu kegs described above instead of the standard

Homebrew mesa/mesa-glu formulas; FindOpenGL.cmake's Homebrew-detection branches were extended accordingly, while ordinary configurations (option left OFF) are unaffected. The mb-mesa/mb-mesa-glu install locations can be supplied directly via new MBMESA_PREFIX/MBMESAGLU_PREFIX cache variables (as the mbsystem-beta Homebrew formula below now does) or, if left unset, are resolved automatically by invoking `brew --prefix`, which is convenient for an interactive, manually invoked cmake configuration but was confirmed (with a throwaway diagnostic Homebrew formula) not to work from inside a real Homebrew build: the `brew` command itself is deliberately excluded from the PATH Homebrew constructs for a formula's own sandboxed build step.

Homebrew formula mbsystem-beta (private tap dwcaress/homebrew-mbsystem): This formula, which builds and installs MB-System itself for beta distribution testing via Homebrew, now depends on mb-mesa and mb-mesa-glu and configures with `-DmacosUseMbMesa=ON`, passing `MBMESA_PREFIX/MBMESAGLU_PREFIX` directly (computed in Ruby via `Formula[...].opt_prefix`) rather than relying on cmake shelling out to `brew`, per the build-system change above. Its `brew test` block was extended to inspect the installed libmbview library with `otool -L` and confirm it is actually linked against the private mb-mesa/mb-mesa-glu kegs and not the standard mesa/mesa-glu formulas, so that a future accidental regression back to Homebrew's current, buggy Mesa version is caught by `brew test` rather than only discovered by a user seeing incorrect 2-D or 3-D rendering.

The changes described above in this 5.8.3beta18 distribution were found, diagnosed, and/or made with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model claude-sonnet-5), operating as Claude Code under developer supervision and review.

////////////////////////////////////

5.8.3beta17 (September 8, 2026)

Program mbotps: Replaced this program's dependency on a separately installed and built copy of the OSU Tidal Prediction Software (OTPS) Fortran program `predict_tide` with a native C implementation of the same harmonic tidal prediction methods (new files `src/otps/mb_otps_predict.c` and `mb_otps_predict.h`): equilibrium tidal arguments and nodal corrections, inference of minor constituents from major ones, and bilinear interpolation of the tidal atlas grids, reading OTPS "atlas" format tide model binary files (e.g. `TPXO9_atlas`, `TPXO10_atlas`) directly via computed byte offsets rather than loading whole files into memory. mbotps no longer needs OTPS's Fortran source, its makefile, or a Fortran compiler installed at all; only the tidal model

data files themselves are needed, at the location given by `--otps-path`, exactly as before. The new engine was validated against the actual OTPS Fortran `predict_tide` across more than 1500 randomized positions and times spanning both currently supported atlas models, matching to within 0.5 mm (consistent with single-precision rounding in the source data) with zero land/ocean classification mismatches; this process also caught and fixed a genuine off-by-one bug in the new code's own direct-access byte-offset arithmetic, and separately caught and fixed a bug in which a shared MBIO error-code variable was reused for the tidal prediction call inside the per-record navigation-mode loop, silently clearing the end-of-file condition that loop depends on and causing an effectively infinite loop that could fill disk with output before it was noticed. Also enhanced model discovery so that a model directory obtained from OSU (e.g. `TPXO10_atlas_v2/`, copied directly into `DATA/`) can be used as `--otps-model` with no accompanying `"Model_"`-prefixed control file required at all; `mbotps` scans the directory itself for the needed elevation (`"h_"`) atlas files. A `"Model_"` control file, if present, is still honored and takes precedence, for compatibility with an existing OTPS installation that already has one.

Program `mbotpsold`: The previous, OTPS-Fortran-dependent implementation of `mbotps` is retained under this new name as a fallback and as a cross-check against the OTPS Fortran reference implementation, but is now deprecated: moved from `src/otps` to `src/deprecated`, built only when MB-System is configured with `--enable-deprecated` (autotools) or `-DbuildDeprecated=ON` (CMake), with its man page moved from the regular man page list to the existing deprecated-program man page list in both build systems. Its own man page and `mbotps`'s man page were both updated to describe this relationship and to give full attribution to Oregon State University and to Gary Egbert, Lana Erofeeva, and Richard Ray for the tidal prediction methods both programs implement or (for `mbotpsold`) invoke.

Program `mbotpsold`: Fixed a bug in which the optional tide-station correction (applying the difference between an observed tide station's data and the model's own prediction at that station's position and times, as a correction to tide predictions made elsewhere) used a stale epoch time left over from unrelated earlier code, rather than the epoch time of the specific output line the correction was being applied to. This affected both the single-position and swath-navigation modes whenever a tide-station correction was requested, and could apply the wrong point of the correction time series to a given prediction. Fixed by computing the correct epoch time from the freshly parsed output line, immediately before each correction lookup, in both modes.

The changes described above were done with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model claude-sonnet-5), operating as Claude Code under developer supervision and review.

Man pages: Fixed a bug in which the mb7k2jstar man page was listed among the deprecated man pages (in src/man/man1/CMakeLists.txt's `deprecated` list and src/man/man1/Makefile.am's `MAN\_DEPRECATED` variable, plus the corresponding generated Makefile.in) even though mb7k2jstar itself is a current, non-deprecated program, as already reflected in src/utilities/CMakeLists.txt and src/deprecated/CMakeLists.txt. As a result, a normal build installed no man page for mb7k2jstar at all, since deprecated man pages are only installed when deprecated programs are explicitly enabled. Moved the mb7k2jstar.1 entry into the current man page lists in both the CMake and autotools build files. Also audited every other man page in the deprecated lists against the current-vs-deprecated program lists in src/utilities/CMakeLists.txt and src/deprecated/CMakeLists.txt; no other man pages were misclassified. This bug was found and fixed with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model claude-sonnet-5), operating as Claude Code under developer supervision and review.

Build system: Fixed the autotools build for the program mb7k2jstar, which had moved from src/deprecated to src/utilities to match its CMake configuration (already correct in src/utilities/CMakeLists.txt and src/deprecated/CMakeLists.txt) without a corresponding update to the autotools files. src/deprecated/Makefile.am still listed mb7k2jstar as a deprecated program even though its source file no longer exists there, so `./configure --enable-deprecated && make` failed with a missing-source-file error, while src/utilities/Makefile.am never listed the program at all, so the autotools build never built it as a current program either. Removed the stale mb7k2jstar entries from src/deprecated/Makefile.am and added mb7k2jstar to src/utilities/Makefile.am, with no extra library dependencies beyond what libmbio.la already provides transitively, then regenerated both Makefile.in files and confirmed with automake, ./config.status, and an actual compile of mb7k2jstar.cc that the fix builds correctly. This bug was found and fixed with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model claude-sonnet-5), operating as Claude Code under developer supervision and review.

Header mb_define.h: Reorganized so that function prototypes are grouped under comments naming the src/mbio/mb_*.c source file that defines each one, replacing the previous layout, which mixed functions from different source files together with no consistent order. While auditing the header against the actual mbio source, found and fixed several inconsistencies:

added prototypes for twelve functions that had no declaration anywhere in the tree (mb_format.c's `cvt_to_nix_path`; mb_esf.c's `mb_mergesort_setup` and `mb_mergesort_insertionsort`; and nine internal mb_rt.c ray-tracing helpers - `mb_rt_get_depth`, `mb_rt_quad1` through `mb_rt_quad4`, `mb_rt_plot_circular`, `mb_rt_circular`, `mb_rt_line`, and `mb_rt_vertical`); removed seven stale prototypes for functions with no implementation anywhere in the source tree (mb_platform_set_sensor_flipsign_x/y/z, `mb_buffer_info`, and `mb_geod_init/mb_geod_free/mb_geod_inverse`); and removed a duplicated `mb_swap_check()` declaration. Functions already declared in another mbio header (mb_process.h, mb_segy.h, mb_info.h, mb_io.h) were left there rather than duplicated, with a comment in mb_define.h noting where each lives; the mb_process.h and mb_segy.h comments were checked to confirm they enumerate every function each of those headers actually declares, not just the ones originating from one particular source file.

Removed src/mbio/mb_info.h, folding its contents into mb_define.h: the `mb_info_struct` structure, the `MB_INFO_MASK_DIM` macro, and the three `mb_check_info.c` function prototypes it declared (`mb_info_init`, `mb_get_info`, `mb_get_info_datalist`). All nine source files that referenced mb_info.h already included mb_define.h directly, so the `#include "mb_info.h"` lines were simply removed; the header was also dropped from src/mbio/CMakeLists.txt, Makefile.am, and Makefile.in.

Moved the declarations of `mb_mergesort()`, `mb_mergesort_setup()`, and `mb_mergesort_insertionsort()` - all three defined in mb_esf.c - from mb_define.h to mb_process.h, alongside the other mb_esf.c functions already declared there, since mb_process.h is already included by mbnadjust_io.c, the only caller of `mb_mergesort()` outside mb_esf.c itself. Also dropped mb_define.h's now-redundant `hilbert()`/`hilbert2()` declarations (both defined in mb_segy.c), which were already declared in mb_segy.h.

The changes described above were done with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model claude-sonnet-5), operating as Claude Code under developer supervision and review.

Program mbsmakeplatform, library mbio: Added support for recording, per sensor, that the raw heading, roll, and/or pitch values reported by that sensor should have their sign flipped before use, correcting a raw sensor calibration or wiring polarity error that is independent of any sensor mounting offset. New platform file keywords `SENSOR_FLIPSIGN_HEADING`, `SENSOR_FLIPSIGN_ROLL`, and `SENSOR_FLIPSIGN_PITCH` record these per-sensor flags and are read, written, and applied by new functions in src/mbio/mb_platform.c (`mb_platform_set_sensor_flipsign_heading/roll/pitch`,

`mb_platform_apply_flipsign_heading`, `mb_platform_apply_flipsign_attitude`), with the corresponding prototypes added to `src/mbio/mb_define.h`. The sign flip is applied to the platform's designated `source_heading` and `source_rollpitch` sensors during navigation/attitude interpolation in `src/mbio/mb_navint.c`, so it takes effect wherever a program reads heading, roll, or pitch through the standard MBIO interpolation path. In `mbmakeplatform`, the new command-line arguments `--sensor-flipsign-heading`, `--sensor-flipsign-roll`, and `--sensor-flipsign-pitch` set these flags for the sensor currently being defined, i.e. any sensor added between an `--add-sensor-*` argument and the matching `--end-sensor` argument; giving one of these arguments outside a sensor definition has no effect. Also documented the three new arguments in the `mbmakeplatform` man page.

The changes described above were done with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review.

Program `mbtrnpp` and Format 89 (MBF_RESON7K3): Fixed two bugs in the automatic, real-time bathymetry preprocessing that `src/mbio/mbr_reson7k3.c` applies inside its own low-level record-reading function (`mbr_rt_reson7k3()`) whenever a program reads `reson7k3` survey data through `mb_get_all()` with a platform model loaded via `mb_set_platform()` - the code path used by `mbtrnpp`, which never calls the separate, explicit `mb_preprocess()` API that `mbpreprocess` uses. First, the target sensor used to compute the multibeam sonar's lever arm and attitude offsets was hardcoded to sensor index 0 (typically the platform's INS) rather than being taken from the platform's `SOURCE_BATHYMETRY` sensor, so none of the actual sonar's mounting position or attitude offsets were applied; fixed to use `platform->source_bathymetry`, mirroring the convention already used by `mb_get_all.c`'s own generic preprocessing fallback. Second, the attitude system's roll, pitch, and heading were sign-flipped once in `mbr_reson7k3.c` according to the platform's `SENSOR_FLIPSIGN_ROLL/PITCH/HEADING` flags, then flipped a second time inside `mb_attint_add()/mb_hedint_add()` (`src/mbio/mb_navint.c`), which already apply this same platform-based correction centrally; the double negation silently canceled the flip. Fixed by removing the redundant manual flip in `mbr_reson7k3.c` so the correction is applied exactly once, as intended by `mb_navint.c`'s design. Both bugs were found by comparing bathymetry computed by `mbtrnpp` in real time against bathymetry computed for the identical raw data by `mbpreprocess` run offline with the same platform file, for an MBARI Mapping AUV survey logged in `reson7k3 (.s7k)` format.

Format 89 (MBF_RESON7K3): Fixed a bug in `mbsys_reson7k3_preprocess()` (`src/mbio/mbsys_reson7k3.c`) in which the

interpolated attitude-system heave value was subtracted from sensordepth when computing each beam's depth (`bathydata->depth = zz + sensordepth - heave`), even when sensordepth was itself already sourced from a real pressure sensor and therefore already reflected the vehicle's actual instantaneous depth, double-counting the vertical motion and producing bathymetry that could be off by roughly a meter, with the error's magnitude and sign varying with heave. This is the same heave-versus-real-sensordepth convention already applied in `mbsys_reson7k3_extract_nav()`, which zeroes heave whenever draft/sensordepth data is available (`mb_io_ptr->nsensordepth > 0`); `mbsys_reson7k3_preprocess()` now applies the same rule. Found and fixed using the same `mbtrnpp`-versus-`mbpreprocess` comparison described above; after both fixes, per-beam depths from `mbtrnpp` and `mbpreprocess` for the same pings agreed to within a few centimeters, down from roughly a meter.

The changes described above were done with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review.

Test suite (test/utilities): Fixed 7 of 46 `make test` (ctest/GoogleMock-style) test failures in `test/utilities/mbdefaults_test.py`, `mbdumpesf_test.py`, `mbsegygrid_test.py`, `mbsegylist_test.py`, `mbsvpselect_test.py`, `mbareaclean_test.py`, and `mbauvloglist_test.py`. None of these were regressions in the programs under test; each test asserted on a literal substring of `-H / --help` usage-string output that predated the `getopt_long` conversion (5.8.3beta15/16) and was never updated afterward, so the assertions checked for short-option-only placeholder names (e.g. `-Wproject`, `-Gdelimiter`, `-Fprintformat`) that the converted usage strings no longer emit verbatim (now e.g. `-Wmbproject`, `-Gcharacter`, `-Fformat`). Separately, `mbdumpesf_test.py`'s `testNoArgs` still expected running `mbdumpesf` with no arguments to exit silently and successfully; this predated an earlier fix (`mbdumpesf` batch of the `src/utilities` memory-safety audit) that made the program correctly require `--input` and exit with an error instead of proceeding with an uninitialized filename. Updated all 7 test files' assertions to match current, correct program behavior; `make test` now passes 46/46. This work was done with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review.

Program `mbmakedatalist`: Fixed a spurious

`-Wunknown-warning-option` compiler warning under Clang: a `#pragma GCC diagnostic ignored "-Wstringop-truncation"` block (added to silence a real GCC-only warning around a bounded

`strncpy` / `strncat` sequence building a Kongsberg output filename) named a warning group that only GCC defines, so Clang warned that it did not recognize the option at all. Guarded both the `#pragma GCC diagnostic push` / `ignored` and the matching `#pragma GCC diagnostic pop` with `#if defined(\_\_GNUC\_\_) && !defined(\_\_clang\_\_)`, so the suppression is applied only on the compiler it is meant for, with no warning generated on Clang. This work was done with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review.

Program `mbgpstide`: Fixed an inconsistency between the long and short forms of the `--tideformat/-A` option introduced by the `getopt_long` conversion (5.8.3beta15/16): the long-option handler unconditionally clamped any parsed value other than 2 down to 1, while the equivalent short-option handler simply stored whatever value was parsed. This meant `--tideformat=5` (the documented CARIS output format, also reachable as `-A5` and checked explicitly elsewhere in the program) was silently turned into `tideformat=1` when given as a long option, while `-A5` worked correctly. Removed the clamp from the long-option branch so both option forms behave identically. This bug was found and fixed with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review.

Program `mbtiff2png`: Fixed a `getopt_long` table bug in which the no-argument flags `--transparency-white` and `--transparency-black` were declared with `required_argument` instead of `no_argument`, meaning either flag would silently consume the next command-line token as an ignored argument instead of taking effect as a bare switch (the man page and the program's own usage text had always correctly described both as argument-free). This bug was found and fixed with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review.

Man pages: Completed a full accuracy pass over every MB-System man page. Rewrote `src/man/man3/mbio.3` to document roughly 185 previously-undocumented `mb_*` library functions, remove one that no longer exists (`mb_buffer_info`, replaced by `mb_buffer_get_kind`), fix roughly 50 stale function signatures, add 3 missing entries to the SUPPORTED FORMATS table, and correct stale beam-flag bit meanings. Updated `src/man/man1/mbsystem.1`'s program/macro/GMT-module inventory to match the actual current build (about 20 additions, several deprecated-list corrections, `mbps` removed as dead). Audited the OPTIONS/SYNOPSIS sections of all 97

other existing man pages against their current option-parsing code, fixing 59 of them: undocumented options, options no longer in the code, stale defaults, and swapped or otherwise wrong descriptions (notably `mbimagelist.1`, which had been largely copy-pasted from `mbdatalist.1`, and `mbvelocitytool.1` and `mbswath.1`, which were missing or misdescribing several real options). Wrote 10 new man pages from scratch, with html/pdf renderings, for actively-built programs and macros that previously had no documentation at all (`mbgetphotocorrection`, `mbimagecorrect`, `mbphotogrammetry`, `mbphotomosaic`, `mbm_makeimagelist`, `mbgrd2octree`, `mbgrdtilemaker`, `mbm_phins2fnv`, `mbm_rollerror`, `mbm_trnplot`), each cross-checked against its actual `getopt/argv`-parsing code rather than assumed behavior. Also brought `src/html/mbsystem_man_list.html` up to date with links to every current man page, fixing a broken `mbio pdf` link, moving several deprecated programs (`mbauvnavusbl`, `mbrollbias`, `mbstripnan`, `mbm_fmtvel`) out of active-program sections into the deprecated list, and removing the dead `mbps` entry. This work was done with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model `claude-sonnet-5`), operating as Claude Code under developer supervision and review.

Testing infrastructure: Upgraded the vendored GoogleTest/GoogleMock copy in `third_party/googletest` and `third_party/googlemock` from 1.13.0 to the current 1.18.0 release, scoping the newer version's C++17 requirement to that subtree only (via `set(CMAKE\CXX\STANDARD 17)` inside `third_party/CMakeLists.txt`, which does not propagate back up to the rest of the build, which still targets C++11) and adding the same requirement to the `test/mbio` GoogleTest executables and to the `src/mbmesh` algorithm tests that already needed it. In the process, found and fixed a latent bug in which `INSTALL\GTEST` defaulted to ON, meaning a normal `make install` also installed the bundled GoogleTest/GoogleMock headers and libraries system-wide under `CMAKE_INSTALL_PREFIX` (default `/usr/local`); on the development machine used for this work, a stale 1.13.0 install from an earlier build shadowed the newly vendored 1.18.0 headers at compile time via the compiler's implicit `/usr/local/include` search path, breaking the build until the stale files were removed by hand. `INSTALL\GTEST` is now forced OFF, since MB-System only ever consumes this copy privately as a test dependency and has no reason to install it for other projects to find.

Build system: Because upstream GoogleTest has not shipped Autotools build files since well before the vendored 1.13.0 snapshot, upgrading it in place would have required hand-writing new Automake glue with no upstream template to follow. Rather than take on that maintenance burden for a legacy build path, `./configure && make check` no longer attempts to build the GoogleTest-based test suite at all (`third_party/Makefile.am`, `third_party/`

googletest/Makefile.am, third_party/googlemock/Makefile.am, and test/mbio/Makefile.am were removed, along with the corresponding entries in configure.ac's AC_CONFIG_FILES and test/Makefile.am's SUBDIRS); CMake (`cmake --build . --target ... && ctest`) is now the only way to build and run it. The plain Python `unittest`-based smoke tests in test/utilities and test/deprecated are unaffected and remain buildable and runnable under both Autotools and CMake as before.

Testing: Wired two smoke tests, tests/test_marching_cubes.cpp and tests/test_normal_estimation.cpp, into src/mbmesh/CMakeLists.txt; both already existed in the source tree from the original mesh-generation work but were never added to the build, so `ctest` never ran them. Also added a smoke test for the mbmesh command line program itself, checking that -h prints usage and that running with no input datalist fails with a clear error rather than a crash.

Testing: Added command line smoke tests (Python `unittest`, run through `ctest`, following the existing pattern in test/utilities) for the standard, non-deprecated programs across the source tree that previously had none: mbfnv2navlab, mbmakedatalist, mbmapscale, mbnavlab2fnv, mbswath2las, and mbusbl2fnv in src/utilities; mbphotomosaic, mbgetphotocorrection, mbphotogrammetry, mbimagecorrect, mbtiff2png, and mbimagelist in src/photo; dump_gsf in src/gsf; mbgrd2gltf; mbotps; and mbnadjust/mbnavadjustmerge in src/mbnavadjust. Each test exercises the program's help/usage output (or, where a program does not special-case --help, its documented behavior when required arguments are missing), checking that the program starts, parses arguments, and exits cleanly rather than crashing. One of these, mbimagecorrect, currently crashes with an uncaught OpenCV exception under both --help and no arguments instead of printing usage; test/photo/mbimagecorrect_test.py documents the expected, non-crashing behavior via Python's `@unittest.expectedFailure`, so the underlying bug is tracked by the test suite without blocking it, pending a fix.

Testing: The Motif-based interactive editors mbedit, mbnavedit, mbvelocitytool, mbeditviz, and the mbnadjust GUI all call XtOpenDisplay() before parsing any arguments, so they need a working X display even to print -h usage; their new smoke tests run under a private Xvfb server started and torn down per test via a new shared helper, test/xvfb_helper.py, and are skipped (not failed) on a machine with no Xvfb binary installed. mbgrdviz, also Motif-based, needed no such helper, since it is the only one of the six that parses -h before opening a display, and so has an ordinary smoke test alongside the others above.

Removed the top-level googletest/ directory, an untracked, gitignored full clone of the upstream GoogleTest repository left over from prior exploration; it was never referenced by any build file, CMake or Autotools.

Further repository housekeeping: removed stale top-level cruft left over from earlier stages of the project's history. This included the old Travis CI configuration (.travis.yml and the ci/travis/ build scripts), superseded years ago by the GitHub Actions workflows under .github/workflows/; a leftover "GitHub Actions Demo" placeholder workflow (.github/workflows/github-actions-demo.yml) that was never more than the tutorial stub GitHub generates when Actions is first enabled; two empty, untracked top-level directories (config/ and maps/) with no evident purpose; and a stray configure~ backup file left behind by a local autoreconf run. No functional code changed.

The changes described above were done with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model claude-sonnet-5), operating as Claude Code under developer supervision and review.

Format 261 (MBF_KEMKMALL): Fixed three related bugs in mbsys_kmbes_preprocess() (src/mbio/mbsys_kmbes.c) that caused noticeably noisy bathymetry after SVP-based recalculation (mbprocess with SVPMODE 1) for Kongsberg kmall data logged with multiple transmit sectors per ping, including dual-swath surveys. First, the transmit-side roll/pitch/heading fed to mb_beaudoin() for every sounding in a ping was interpolated once at the ping's own header time, ignoring each sounding's own transmit sector's sectorTransmitDelay_sec offset from that header time, so every sector after the first used attitude sampled slightly too early. Second, the receive-side roll/pitch/heading was interpolated at the ping header time plus the beam's own two-way travel time only, again omitting sectorTransmitDelay_sec, even though the correct formula (header time plus sectorTransmitDelay_sec plus travel time) was already used a few lines later, for a different purpose (interpolating sensordepth at the beam's true receive time). Third, that same later block's heave interpolation itself used only the ping header time rather than the beam's true receive time it had just computed, so the per-beam heave correction term was always exactly zero regardless of travel time. All three were found and fixed by comparing sonar-computed ("raw") and mbprocess-recalculated bathymetry beam by beam and ping by ping for a Maria S. Merian EM124 test survey, which showed a systematic, sign-flipping port/starboard tilt of up to several meters per ping that tracked beam angle rather than ship position; after the fix, the same comparison's port/starboard mean bias dropped from as much as +/-15 m to

roughly +/-1 m, and its standard deviation dropped by 5-15x, across the eleven pings checked in detail.

Format 261 (MBF_KEMKMALL): Fixed a related bug, found while validating the fix above, in which the very first ping(s) of a kmall file - or, more generally, any ping whose timestamp precedes the first asynchronous navigation/heading/attitude datagram in the data (confirmed to occur, by 4.4 seconds, for the same Merian EM124 survey) - had their roll, pitch, heave, heading, and navigation left uninitialized rather than falling back to a defined value, because the ping-level interpolation calls were skipped outright rather than substituting a sensible default. `mbsys_kmbes_preprocess()` now initializes roll/pitch/heave from the ping's own embedded attitude sample (already extracted for the ping-level XMT record) before the file-wide interpolation is attempted, and initializes navigation and heading from the ping's own logged position and heading, so these values are always defined; if neither the file-wide table nor the ping's own embedded sample has any attitude data at all, roll/pitch/heave are explicitly set to 0.0 and a warning naming the affected ping's time is printed, rather than silently leaving them uninitialized. Confirmed, using both a synthetic split of the same test file and ten sequential production kmall files spanning 8.3 hours, that this uninitialized-data condition and its fix are confined to a survey's true first ping(s), if any, and are not retriggered at subsequent file boundaries within a multi-file datalist, because `mbpreprocess` accumulates its ancillary interpolation tables across the entire datalist before any ping is processed.

Program `mbpreprocess`, Format 261 (MBF_KEMKMALL): Fixed a related warning message added by the previous fix that fired far more often than intended for multi-file datalists. `src/mbio/mbr_kemkmall.c`'s own low-level record reader automatically invokes `mbsys_kmbes_preprocess()` the first time any not-yet-preprocessed ping is read, using a `preprocess_pars` struct embedded in the MBIO file handle (`mb_io_ptr->preprocess_pars`) and populated only from whatever asynchronous data that same read pass has buffered so far in the current file; because `mbpreprocess` opens and reads each raw file more than once internally, this automatic, non-authoritative call transiently saw no attitude data at the start of every file in a multi-file datalist, not just the survey's true first file, even though its result is unconditionally superseded before anything is written by `mbpreprocess`'s own later, explicit call, which uses a separate table already spanning the entire datalist. The new warning is now printed only for that later, explicit call (identified by comparing the `preprocess_pars` pointer against `&mb_io_ptr->preprocess_pars`), where a lack of attitude data is not superseded by any subsequent call and so is actually worth reporting. Confirmed against a ten-

file, 8.3-hour production survey that the warning count dropped from 18 to 0 with no change to any written bathymetry, roll, pitch, or heave value.

The changes described above were done with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model claude-sonnet-5), operating as Claude Code under developer supervision and review.

Format 261 (MBF_KEMKMALL): Fixed two further defects identified in a bug report from Christian Ferreira reviewing the same kmall attitude/heave handling as the fixes above. First, in `src/mbio/mbr_kemkmall.c`, the code that feeds the generic MBIO nav/attitude buffer (`mb_attint_add()`), used by the low-level, automatic preprocessing that `mbr_kemkmall_rd_data()` applies to every not-yet-preprocessed ping, and consulted by any program - such as `mbtrnpp` - that reads kmall attitude via the standard `mb_attint_interp()`/`mb_get_all()` path rather than through `mbpreprocess`'s own explicit extraction) negated the SKM datagram's `heave_m` field in both places it is populated (the `MB_DATA_NAV1` and `MB_DATA_NAV2` handling blocks), even though every other reader of this field elsewhere in `mbsys_kmbes.c`, and every other format's own call to `mb_attint_add()`, passes heave through unmodified, matching Kongsberg's own "positive downwards" convention for `heave_m`. Confirmed directly: reading the same ping's heave with `mblist`, once from the raw, never-preprocessed `.kmall` file and once from the same ping after `mbpreprocess`, gave an exact sign flip (+1.1527 m vs. -1.1527 m) before this fix and identical values after it; this did not affect bathymetry already produced through the `mbpreprocess/mbprocess` pipeline, which extracts attitude through a separate, correctly- signed path, but would have affected any program reading kmall attitude through the generic buffer directly, as for the `reson7k3` bug described above. Second, in `src/mbio/mbsys_kmbes.c`'s `mbsys_kmbes_preprocess()`, the per-beam sensordepth-at-receive- time fallback (taken when no separate sensordepth ancillary stream is available, the normal case for kmall) assigned its result to the ping-level sensordepth variable rather than to `receive_sensordepth` as intended; harmless in practice for standard kmall data, since the two already held the same value at that point, but corrected for clarity and to avoid the same mistake mattering under some future change to this code. This work was done with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model claude-sonnet-5), operating as Claude Code under developer supervision and review.

5.8.3beta16 (July 26, 2026)

Program `mbusbl2fnv`: New program that converts a USBL (ultra-short baseline) ROV tracking CSV file to an MB-System fast navigation (fnv) text file. The input CSV format has one header line followed by data lines giving

epoch time, latitude, longitude, and ROV depth; heading, speed, roll, pitch, and heave are not present in USBL tracking data and are output as 0.0.

Program mbswath2las: New program that exports swath bathymetry soundings to LAS 1.4 point cloud files, one point per valid (unflagged) beam, allowing swath bathymetry to be loaded directly into LAS/LIDAR-oriented point cloud viewers, GIS packages, and processing pipelines (e.g. CloudCompare, QGIS, PDAL) that do not otherwise read MBIO formats. By default sounding positions are written as geographic longitude/latitude in decimal degrees (WGS84); a projected coordinate system may instead be specified so that positions are written as easting/northing in meters.

Build system: Continued work to allow MB-System to build on Windows, extending fixes made previously to the CMake configuration and to src/mbtrn and src/mbtrnav. This round of changes covers the non-TRN libraries and programs: src/gsf (CMakeLists.txt changes only, no code changes required), src/mbio (mb_defaults.c, mb_mem.c, and mbsys_kmbes.c), src/gmt, and src/mbaux, src/bsio, and src/surf, where the Windows shim for XDR is now built as its own library, libmb_xdr_win32, within src/mbaux. Also updated src/mbgrd2lrf, src/mbmesh, src/otps, and src/photo to build consistently on MacOS, Linux, and Windows, along with a number of general CMake project-structure fixes.

Library mbview: Fixed a memory-management bug in route handling in which deleting the last point of a route (removing the whole route) shifted the internal route array down without first freeing the deleted route's own point/segment arrays and without clearing the vacated array slot afterward. This leaked memory, silently caused two routes to alias the same underlying arrays, and could crash mbgrdviz and other mbview-based programs with a double free when routes were deleted and new routes subsequently added. A broader audit of the mbview route, navigation, site, and vector handling code found and fixed several related problems: an inverted bounds check in mbview_getrouteinfo() that allowed out-of-bounds array reads; a memory leak on navigation-line deletion (per-segment drape buffers were never freed); dead code in the route list widget that silently disabled selection highlighting; uninitialized segment endpoint data when adding vectors; and list-selection and list-deletion callbacks for the route and navigation list dialogs that could act on the wrong entry if a list item were ever marked inactive. Also fixed the title bars of the 2D Parameters, 3D Parameters, Shading Parameters, Profile Display, About, and "please wait" message dialogs, which previously displayed internal Motif widget names (e.g. "mbview_dialogShell_2dparms") instead of readable titles.

Program mbgrdviz: Fixed a bug in the Generate Survey Route feature in which a cached route index could go stale if the user deleted an unrelated route via the 3D view while the Area Route dialog remained open, causing the next "Generate Survey" click to delete the wrong route. Also fixed the title bar of the Area Route dialog, which previously displayed the internal widget name "dialogShell_arearoute" instead of "Generate Survey Route for Selected Area...".

Program mbeditviz: Fixed a crash on opening a swath file that MBIO cannot actually read, caused by a missing status check before dereferencing the file handle. Fixed a memory-management bug in file deletion analogous to the mbview route bug above, in which removing a file from the loaded-files list left a stale duplicate array slot that could later alias data between two loaded files. Fixed several file-record fields (including processed-file-info and sensordepth navigation arrays) that were left uninitialized on newly imported files. Added a bounds check to the ping-reading loop to prevent a heap buffer overflow when a swath file's *.inf index file undercounts its actual number of pings. Fixed a bug in which dismissing the 3D soundings window overwrote the global verbosity setting rather than the intended error-code variable. Fixed a bug in which a single navigation-loading failure for one file silently skipped loading navigation for every subsequent file in the same session. Fixed a leak and potential crash on the (rare) memory allocation failure path when importing files. Fixed the title bar of the Error dialog (previously showed "dialogShell_error") and corrected a garbled status message ("Reading data list...").

Program mbnadjust (and the mbnadjustmerge and mbnadjustfine tools that share its project I/O and data structures): Fixed a bug in which deleting a tie point used a stale, unrelated global variable instead of the tie actually being deleted, corrupting which tie was removed and, in one call path, capable of an out-of-bounds write into the crossings array. Fixed a wide-ranging set of missing bounds checks in the project file reader, which previously trusted the file's own record counts and array indices to size loops and index fixed-size per-crossing and per-section arrays, and used unbounded string conversions into fixed-size path buffers - a corrupted or hand-edited project file could overflow multiple buffers. Fixed a bug in which removing a file from a project (via mbnadjustmerge) left remaining sections' file/section identity fields stale, able to silently misattribute sections to the wrong file. Fixed a memory leak in which a file's section array was allocated with the standard C library and freed with an MB-System function that only recognizes memory it allocated itself, so the free silently did nothing. Fixed three sites in mbnadjustmerge where a newly grown crossing's file references were read before being assigned, an out-of-range crossing could be added with no validation, and a failed allocation was not

checked before the new crossing was used. Fixed four missing-brace bugs that caused a visualization update function to run unconditionally regardless of whether a visualization window was ever open. Fixed a command-line tool (mbnavadjustfine) build break caused by a call with the wrong number of arguments, a numeric option that corrupted adjacent settings and always aborted the program, an uninitialized pointer used in an error message, a per-crossing memory leak, continuing an alignment computation after detecting invalid input, and a divide-by-zero when every sounding in a section was flagged. Fixed a project-merging command that validated and updated the wrong internal counter, and a project list display that never showed survey-vs-survey "block" comparisons. Also fixed a missing dialog title, a silent failure to write cached triangulation data, an unchecked allocation before use, several unbounded command-line path arguments, a dead duplicate-crossing check, an undefined-behavior `fclose()` on a failed file open (7 sites), and a display counter that was always zero.

Program `mbnavadjust` (and `mbnavadjustmerge`): A follow-up round of fixes targeting crashes reported when displaying and selecting global ties. Fixed invalid `qsort()` comparator functions for the sorted global-tie and sorted crossing-tie list displays that never returned zero for equal or incomparable elements, violating the strict-weak-ordering contract required by `qsort()` and able to crash on quicksort-family implementations (including those used by both Linux `glibc` and macOS/BSD `libc`). Fixed a heap buffer overflow in the sparse inversion matrix built for the preliminary per-block offset solution (used by both the main navigation inversion and the "Autoset Z Offsets" feature): the matrix's row stride was set to 3 times the number of survey blocks, but the backing array was only ever allocated for a fixed stride of 6, overflowing on any project combining more than two surveys - an entirely ordinary case - during exactly the step that folds global tie offsets into the solution. Fixed a stale-variable bug in the "Autoset Z Offsets" feature where the per-block averaged global tie offset was indexed with a leftover loop variable from an unrelated, already-finished loop instead of the current block index, an out-of-bounds heap read. Fixed a bug in `mbnavadjustmerge` where merging additional files into a project unconditionally renumbered every copied section's reference-grid ID, corrupting the "no reference grid assigned" sentinel value into a bogus but plausible-looking grid index for any section without a global tie or reference grid; a section thus corrupted could cause `mbnavadjust` to load and display the wrong reference grid when its global tie was later selected. Also fixed a missing bounds check (and a related debug-only variable `mixup`) in the reference grid loader that could read the reference-grid name array out of bounds given a negative grid index, and fixed the project's global-tie counters not being decremented

when mbnavadjustmerge removes a file that held global ties, which left the "ties analyzed" status display overcounted.

Program mbdatalist: Fixed a bug in which the long option --report incorrectly triggered the same behavior as --copy instead of generating a datalist report, due to a copy-paste error in the option-parsing code.

Program mbinfo: Fixed a bug in which the long option --ping-variances accepted but silently ignored its argument; only the equivalent short option -P worked correctly.

Program mbmakeplatform: Fixed a typo (--platform-documenation-url) that made the correctly-spelled --platform-documentation-url option unrecognized. Fixed a bug in which --sensor-source-camera1/2/3 and --set-source-camera1/2/3 were all registered under the same un-numbered option name, making the numbered variants unreachable.

Program mbpreprocess: Fixed missing option-table entries for --time-latency-apply-altitude and --filter-apply-altitude, which had working handlers but were never recognized by the command-line parser. Also fixed both handlers, which incorrectly applied the correction to attitude data instead of altitude data due to using the wrong internal flag bit.

Program mbvoxelclean: Fixed a bug in which --count-flagged was declared as requiring an argument even though it is a boolean flag, causing the documented bare-flag usage to be rejected by the command-line parser.

Program mbsslayout: Fixed several option-parsing and ancillary-data-correction bugs found during a documentation audit. --line-route had a working handler but was never registered with the option parser, making it unusable. --line-range-threshold was accepted but silently discarded, so the survey-line range threshold was always hardcoded to 50 meters regardless of what was specified on the command line. --time-latency-apply-altitude applied its time latency correction to attitude data instead of altitude data (the same bit-flag bug as in mbpreprocess), and a soundspeed time-latency correction was gated on that same wrong (attitude) flag bit, causing it to fire whenever --time-latency-apply-attitude was used alone. The entire --filter/--filter-apply-* family of options, intended to apply a Gaussian time-domain filter to ancillary data (navigation, sensordepth, heading, attitude, altitude), was never registered with the option parser and had no implementation; this has now been implemented using the existing mb_apply_time_filter() library function, mirroring the equivalent feature in mbpreprocess. Added a new --line-position-list option that defines survey lines from a simple ASCII file of

waypoint longitude/latitude pairs, as a lighter-weight alternative to --line-route's full MB-System route file format.

Man pages: Audited the man pages for all 46 programs in src/utilities against their actual command-line option implementations, finding and fixing documentation discrepancies in 24 of them, including missing options (mb7k2jstar, mbareaclean, mbauvloglist, mbbackangle, mbgetesf, mbrolltimelag, mbrouetime, mbseggygrid, mbsegypsd, mbset, mbsvplist, mbsslayout, mbvoxelclean, mbmakeplatform), stale options describing command-line flags that no longer exist (mbclean, mbhistogram, mbsegylist, mbsegypsd, mbsslayout, mbsvpselect), and incorrect descriptions or default values (mb7k2jstar, mbclean, mbcopy, mbextractseggy, mbfilter, mbminirovnav, mbmosaic, mbpreprocess, mbrolltimelag, mbrouetime, mbset, mbsvplist, mbsvpselect, mbvoxelclean). This audit also surfaced the mbsslayout and mbpreprocess source-code bugs described above.

Program mbnadjustmerge: Added --update-file, --update-survey, and --update-all-files options that update the beam-validity flags in an mbnadjust project's section data to match the current processed version of each swath file, matching pings by timestamp and copying over only the flag byte - the navigation, attitude, bathymetry, amplitude, and sidescan values already stored in the project are left untouched. This lets soundings newly flagged bad by re-editing a file (e.g. with mbclean or mbedit) after it was originally imported be excluded from the project without a full, riskier re-import of the file's bathymetry. If a matched ping's beam count no longer matches what is stored in the project, that ping's flags are left unchanged and a warning is printed rather than risk misapplying flags to the wrong beams; beams that never held real sounding geometry when originally imported are likewise left flagged null regardless of what the current processed file reports for that beam index, since marking such a placeholder beam as flagged-but-real would otherwise corrupt the scaled short-integer depth encoding used by the project's section file format. Every updated section's coverage mask and triangulated surface are automatically regenerated. These options replace an earlier, incomplete --reimport-file/--reimport-survey/--reimport-all-files implementation that instead substituted bathymetry, amplitude, and sidescan values wholesale from the reprocessed file; that implementation was never released and has been removed.

Program mbnadjustmerge: Added --create-project, --section-length, --section-soundings, --contour-interval, --color-interval, --tick-interval, --label-interval, --decimation, --smoothing, and --zoffsetwidth options to create new mbnadjust projects and change project settings from the command line, matching functionality previously available only in the mbnadjust graphical interface. Added --import and --import-as-survey to import swath data (a

single file or a recursive datalist), and --find-crossings to detect new crossings between imported sections. Added --autopick and --autopick-horizontal to automatically pick navigation ties at unanalyzed crossings, together with --autopick-crossing-type, --autopick-scope, --autopick-survey, --autopick-survey2, --autopick-file, --autopick-section, and --autopick-overlap-threshold options to restrict which crossings are considered. Implementing this required extracting the crossing-loading, bathymetric misfit, and autopick logic out of mbnadjust_prog.c (previously usable only by the mbnadjust graphical interface) into a new shared library, mbnadjust_core, linked by mbnadjust, mbnadjustmerge, and mbnadjustfine; the CMake build was restructured so this library and mbnadjustmerge no longer require Motif or X11 to build, unblocking headless and CI builds of the command-line tool.

Program mbnadjust (and mbnadjustmerge): Fixed a bug in mbnadjust_new_project() in which the section_soundings setting was accepted as a parameter but never actually stored in the new project, so every newly created project silently used a section_soundings value of zero regardless of what was requested, whether created via the graphical New Project dialog or the command line.

Program mbnadjust: Fixed a crash in the "Invert Navigation" menu item (and the "Auto-Set Survey-vs-Survey Vertical Offsets" feature, which shares the same code) in which a failed memory allocation for the sparse least-squares matrix used by the navigation inversion was never checked before the buffer was zeroed, crashing instead of reporting an error; large enough projects could also silently compute the wrong, too-small allocation size due to a 32-bit integer overflow in the row-count/column-count multiplication used to size that matrix, risking heap corruption on a subsequent write rather than a clean allocation failure. Both are now fixed, with a dialog reported to the user if the allocation still fails.

Program mbnadjust: Fixed a bug in which selecting a survey-vs-survey "block" from the Data Table list and then displaying crossings restricted to that block could show no crossings at all. The code that extracts the clicked list item's text had a fallback for when Motif's primary text-retrieval method returns nothing, but the fallback was nested inside a check that skipped it entirely whenever the primary XmString field itself was null, rather than being reached whenever it was actually needed.

Program mbnadjust: Added long-form equivalents (--verbose, --help, --dark-background, --input=project, --reset-crossings) for all existing single-letter command-line options.

Program `mbnavadjustmerge`: Added `--invert-navigation`, `--update-grids`, and `--apply-navigation` options, completing the navigation-adjustment workflow begun with `--autopick` above. `--invert-navigation` solves the network of ties and crossings for a corrected navigation model, exactly as the "Invert Navigation" menu item does in `mbnavadjust`. `--update-grids` regenerates the project's reference bathymetry grids from the current navigation solution, equivalent to "Update Grids". `--apply-navigation` writes the corrected navigation out to the swath data files' processing parameters, equivalent to "Apply Navigation", and is normally the last step in the workflow. Implementing this required moving the navigation-inversion solver, grid-regeneration, and navigation-output logic (previously usable only by the `mbnavadjust` graphical interface, over 3000 lines in `mbnavadjust_prog.c`) into the shared `mbnavadjust_core` library alongside the `autopick` logic moved previously.

Program `mbnavadjust` (and `mbnavadjustmerge`): Fixed a bug in `mbnavadjust_new_project()` in which newly created projects never had their navigation "use mode" initialized, silently defaulting to an invalid value of zero. This had no visible effect in the graphical interface, where a separate program-startup default masked the gap, but meant that `mbnavadjustmerge`'s `--apply-navigation`, run against a project created with `--create-project`, would silently skip updating each file's processing parameters with no error reported.

Program `mbnavadjust`: Fixed a regression from moving the navigation-inversion, grid-update, and apply-navigation logic into the shared `mbnavadjust_core` library (see above): the "please wait" message dialog no longer appeared during Invert Navigation or Update Grids, since those functions could no longer call GUI dialog functions directly. Restored the dialog by wrapping the calls at each of their GUI call sites (the Invert Navigation and Update Grids menu items, the automatic grid update after importing data, and the automatic grid update when opening a project whose topography grid does not yet exist) with the same `do_message_on()/do_message_off()` pattern already used elsewhere in the program, and did the same for Apply Adjusted Navigation, which had the identical gap. A follow-up fix addressed a second bug uncovered in the process: `do_message_on()` itself did not wait for the dialog to actually become mapped and viewable before returning, so on a dialog's first appearance in a session, the window manager's mapping could still be pending when the long operation immediately following it started; since none of these operations return control to the window system's event loop until they finish, the dialog's initial text could remain unpainted (an empty box) for the operation's entire duration. Fixed by having `do_message_on()` wait for the

dialog to become viewable first, mirroring the equivalent wait already used for the main window at startup.

Program mbnadjust (and mbnadjustmerge): During autopicking, a crossing whose section length is less than 0.25 times the project's desired section length is silently skipped (to avoid matching short sections at the end of a file); this is now reported to the user with a message stating the crossing was skipped due to short section length, whether autopick is run interactively or via mbnadjustmerge.

Program mbnadjust: Fixed a segmentation fault when dismissing the Nav Err (crossing analysis) window while no crossing was currently loaded - for example immediately after clearing all ties to start over with a project. The dismiss callback freed the window's graphics contexts unconditionally instead of only when a crossing had actually been loaded (as the equivalent code in the Quit handler already correctly does), so dismissing the window a second time without an intervening crossing load double-freed them, crashing in Xlib's XFreeGC(). Diagnosed directly from the macOS crash report, which resolved exactly to the offending XFreeGC() call once the crash binary's UUID was confirmed to match the current build.

Program mbnadjust: Fixed the Controls dialog showing stale values when opened via the Nav Err window's Settings->Contours menu item, rather than the current project settings shown when it is opened via the main window's Option->Controls menu item. The main window's button has two callbacks - one that refreshes every slider and toggle from the project settings, followed by one that displays the dialog - while the Nav Err window's button only had the second, display-only callback, so it showed whatever values happened to be left over from the last time the dialog was shown or applied. Fixed by adding the missing refresh callback.

Program mbnadjust: During autopicking, the crossing/section/tie list display and model plot (if open) did not update again until the entire run finished, since the loop that used to periodically refresh them lost access to those GUI functions once it was moved into the shared mbnadjust_core library. They are now refreshed every tenth crossing processed via a callback function pointer passed in only by the interactive program; mbnadjustmerge passes none, so the shared autopick loop itself has no GUI dependency.

Program mbnadjust: Fixed the grid region used by Update Grids, which was computed from each section's original, unadjusted geographic bounds and never updated afterward regardless of any navigation inversion performed since - a solution that moved sections a significant distance could leave the grid too small to encompass the shifted data. The region is now

recalculated from each section's original bounds shifted by the range of its current navigation adjustment. The per-survey grids' region, previously computed but never actually passed to mbgrid (relying solely on mbgrid's own bounds auto-detection), is now adjusted the same way and passed explicitly, matching the overall project grid.

Programs mbedit, mbnaveedit, and mbvelocitytool: A memory-management and correctness audit of these three interactive Motif editors (paralleling the earlier audits of src/utilities and mbview/mbeditviz) found and fixed a critical NULL-pointer-write crash in mbnaveedit's "Invert Navigation" modeling mode, triggered by ordinary use whenever exactly one point is visible: the inversion matrix's row-count formula went to zero for a single point, and mb_mallocd() treats a zero-byte allocation as a successful NULL return, so the code proceeded to write through the NULL buffer. All three programs shared a second bug: their get_text_string() helper did an unbounded strcpy() from any Motif text field into fixed-size buffers as small as 10 bytes, with no widget-side length limit set on any of the fields - fixed by adding an explicit destination-size parameter to the helper in all three programs. All three also shared an unterminated strncpy() when copying a user-selected file path from the file-selection dialog, which could read past the destination buffer on sufficiently long paths. Several additional bugs specific to each program were also fixed: in mbedit, undersized bottom-detect-type and pulse-type name lookup tables that indexed past their end on lidar/photogrammetry data, a reversed bit-shift that corrupted the extracted detection-priority value, and an out-of-bounds neighbor read in the median-spike filter's along-track window; in mbnaveedit, an uninitialized-neighbor read that produced garbage speed/course-made-good values for single-point buffers, an off-by-one that silently excluded the first visible point from mouse "pick" mode, and unreliable time-interval bookkeeping after deleting bad-time records (replaced with a straightforward recompute pass); in mbvelocitytool, four sites where a chain of unchecked mb_mallocd() calls could let a later successful allocation mask an earlier failure and use the resulting NULL pointer, a divide-by-zero (surfacing as a silently propagated NaN) in the per-ping depth-residual linear fit when only one beam survived flagging, an uninitialized sensor-depth value used when every beam in a ping was flagged bad, a stray "!= 60" condition that silently skipped freeing all per-ping data buffers for any ping with exactly 60 beams, and a latent (then-unreachable) heap overflow in the profile-deletion code that copied array contents into a differently-sized, already-freed destination buffer rather than moving the whole profile record.

Man pages: Audited the mbedit, mbnaveedit, and mbvelocitytool man pages against their actual command-line options and current GUI behavior. Fixed a wrong option letter (mbedit's browse mode is -D, not -B, as the man page

stated), two stale/nonexistent options in mbnaveedit's synopsis and options list (-O and -T, neither implemented in the code), and several wrong default values and figures across all three (data buffer sizes, mbvelocitytool's default format id, default editable-profile point count, and maximum number of display profiles). Also fixed a self-contradicting keyboard-macro table in mbedit's man page (Grab and Info mode keys were listed backwards in one place and correctly in another), a mislabeled duplicate section heading, and added documentation for several existing but previously undocumented features: mbedit's "Flag by Beam Angle" filter and median-filter window-size sliders, its three-way exclusive "Show Flag States / Show Bottom Detect Algorithms / Show Source Pulse Types" view toggle, and mbnaveedit's "Sonar Depth Plot" toggle.

Man pages: Removed the mbps, geod, and proj man pages (and mbps's generated html/pdf docs). The mbps man page documented a program with no corresponding source file or build target anywhere in the current source tree - it was already gone from the build, just not from the documentation. The geod and proj man pages documented command-line tools belonging to the external PROJ library dependency rather than programs developed as part of MB-System, and were never actually wired into either build system to begin with. Updated both the CMake and autotools build files for src/man/man1 and src/html to remove the now-dangling references to these three pages.

Programs in src/utilities: Added long-option (--long-name) equivalents to every remaining command-line program in src/utilities that previously supported only traditional single-letter options, extending the getopt_long() support already in place for about 15 other utilities (mbinfo, mbdatalist, mbpreprocess, mbsslayout, mbvoxelclean, etc.). This covers 31 programs: mb7k2jstar, mbabsorption, mbareaclean, mbauvloglist, mbbackangle, mbclean, mbcopy, mbctdlist, mbdefaults, mbextractseg, mbfilter, mbformat, mbgetesf, mbgrid, mbhistogram, mblevitus, mblist, mbmapscale, mbmosaic, mbnavigate, mbprocess, mbrolltimelag, mboutetime, mbseggygrid, mbseggyinfo, mbseggylist, mbseggydsd, mbset, mbsvpelist, mbsvpselect, and mbtime. Every existing short option continues to work exactly as before; each program's --help output now lists every long/short pair. This work surfaced four short options that had been silently accepted by each program's option parser for the program's entire history (predating even this repository's 2019 move from Subversion to Git) with no corresponding case handler at all - inert no-ops with no effect and no documentation anywhere. Investigating each: mbseggylist's -W turned out to be real, unimplemented functionality - mbseggylist is a segy-format sibling of mblist, which has a working -W/--use-feet that converts bathymetry and distance output columns from meters to feet, and mbseggylist's own man page documents its fixed sonar-depth and

water-depth output columns in meters, strongly suggesting the option string was copied from mblist without ever porting the conversion logic; -W/--use-feet is now fully implemented in mbsegylist and documented in its man page. The other three (mbauvloglist's -W, mbsegypsd's -P, mbextractseg's -D) had no discoverable intended purpose anywhere in the code, man pages, or usage messages, so rather than guess at functionality they were removed outright.

Programs mbedit, mbnavedit, mbvelocitytool, mbgrdviz, and mbeditviz: Added long-option (--long-name) equivalents to these five interactive Motif programs' command-line options, extending the getopt_long() work above from src/utilities to the GUI editors (mbnavadjust was requested too but already had full getopt_long() support). As with src/utilities, this surfaced a dead option with no case handler at all: mbedit's -S. Unlike the src/utilities finds, this one had a full, traceable history back to 1993 - before MB-System's "Version 5.0" rewrite in 2000, -S set a startup_save_mode flag controlling whether a pre-existing edit save (.esf) file would be loaded for the input file; the getopt string lost its argument and the case handler was later dropped entirely as the code was restructured into the modern Motif-callback architecture, but the underlying feature never actually disappeared - mbedit still has two live callback paths, one that loads a file fresh and one that loads it using an existing edit save file, offered to the user via a "use previous edits?" dialog that pops up at startup whenever a save file already exists. The CLI flag's original job was simply to skip that dialog and answer "yes" automatically, exactly the kind of thing needed when mbedit is launched non-interactively by another process (the same rationale as the existing -G/--gui-mode option). Restored as -S/--use-edit-save. Updated mbedit's man page to document every long-option equivalent in both the synopsis and options list, matching the format already used by the getopt_long-converted src/utilities programs, and fixed a duplicate --verbose/-V entry found in the process.

Program mbtrnpp: Added a first man page for this utility, which previously had no documentation at all. mbtrnpp is an optional real-time preprocessor, normally run unattended aboard an AUV or other survey platform, that reads multibeam bathymetry (from a datalist, a single swath file, or a live network socket), applies automated cleaning and downsampling, and passes the result to an embedded terrain relative navigation (TRN) process; it is built only when MB-System is configured with TRN support (--enable-mbtrn with autotools, or -DbuildTRN=ON with CMake, both of which are the default). The new man page documents the synopsis, description, and every command-line/configuration-file option (input/output specifiers, TRN map/filter/ convergence settings, reinitialization and decimation options, and the mb-out/trn-out network output mnemonics), drawn from the option-parsing

code in mbtrnpp.c and the existing README-mbtrnpp.md and mbtrnpp-cfg.example documentation, along with usage examples. The page is installed by src/man/man1/CMakeLists.txt only when the buildTRN CMake option is enabled, and by src/man/man1/Makefile.am/Makefile.in only when the BUILD_MBTRNUTILS automake conditional is set, matching the pattern already used for the deprecated-program man pages so that the page is never installed alongside a build that lacks the program itself.

The bugs described above, and the mbtrnpp man page, were identified and written with the assistance of the AI coding assistant Claude Sonnet 5 (Anthropic, model claude-sonnet-5), operating as Claude Code under developer supervision and review.

5.8.3beta15 (July 26, 2026)

This release was botched due to a faulty merge of conflicting pull requests. All changes intended for this release are described above for 5.8.3beta16.

5.8.3beta14 (July 6, 2026)

Programs mbedit, mbnavedit, mbvelocitytool, mbgrdviz, mbeditviz, mbnavadjust: updated Motif GUI code to eliminate two deprecated functions, replacing XmFileSelectionBoxGetChild() with XtNameToWidget() and replacing XmStringGetLtoR() with XmStringUnparse(). This appears to be necessary for the Motif code to work on MacOS Tahoe with prerequisites installed via MacPorts.

Program mbnavadjust: Fixed a copy-paste bug in mbnavadjust_io.c in which the section depthmax tracking during data import checked the depthmin initialization sentinel instead of its own, so depthmax was never properly initialized from the first bathymetry value in a section.

5.8.3beta13 (June 18, 2026)

Format MBF_KEMKALL (261): Fixed support for platform files used for preprocessing.

Format MBF_EM710RAW (58): Added support for *.all files associate with the HISAS sonar from Kongsberg.

Programs mbpreprocess and mbprocess: Added support for merging navigation from Kongsberg Navlab software that is commonly used for Hugin AUV data processing.

Programs mbnavlab2fnv and mbfnv2navlab: Added tools that translate between navlab_smooth.bin and fnv files.

Programs mbnavadjust and mbnavadjustmerge: Fixed problems with new and merged project files resulting from treating surveys and blocks of continuous data separately.

Program mbmakedatalist: Compiled C version of macro mbm_makedatalist

Library mbtrnav/gctp: Added modern function definitions to function pointer arrays.

Program mbphotomosaic: Fix bug in which if one photo of a stereo pair is dropped, the other photo is not used.

Program mbnavadjust: Changed so that surveys can be imported as a single piece even if there are time breaks between some of the files.

Format MBF_3DWISSL2 (id 234): Add kluge to deal with WiSSL2 lidar bathymetry needing additional correction.

5.8.3beta12 (January 7, 2026)

CMake build system: Extended to handle complications of MacOS Tahoe. Building the graphical tools in MB-System on MacOS has been complicated for a number of years because of the requirement for X11/Motif and also, for programs mbgrdviz, mbeditviz, and mbnavadjust, OpenGL and GLX. For MacOS versions Sequoia (15) and earlier, the only way to successfully build and run MB-System has been to install all of the prerequisite packages using the MacPorts package manager. For reasons that have never been understood, the MB-System graphical programs failed to run correctly when built with prerequisites installed through the alternative package managers Homebrew and Fink. This situation changes with MacOS Tahoe because now the MB-System graphical programs fail when prerequisites are installed through MacPorts, but succeed when the prerequisites are installed through Homebrew. This update to the build system handles the differences between the two MacOS scenarios (before Tahoe vs Tahoe or later). The installation documentation on the MB-System website will be updated to reflect the necessity of using Homebrew for installations on MacOS Tahoe. A significant issue with all X11 programs running on MacOS Tahoe so far is that when windows are resized, the GUI elements are not refreshed properly, and parts of the GUI wind up overwritten in solid black. Hopefully this will be fixed in a new version of the X11 server XQuartz. In the meantime, minimizing the program window using the middle (yellow) button on the upper left of the

window (or the command-M shortcut), and then restoring that window by clicking on it's icon in the dock will properly refresh the GUI graphics.

Program mbgrd2gltf: Continued updates to this tool for translating gridded topography to Graphics Library Transmission Format (GLTF) files that can be visualized by GLTF viewers.

5.8.3beta11 (December 27, 2025)

Formats 56 (MBF_EM300RAW) and 57 (MBF_EM300MBA): Fixed erroneous calculation of a large sensordepth value by mbprocess when the draft of a surface vessel has not been defined.

5.8.3beta10 (December 22, 2025)

Program mbbackangle: A skipping existing feature implemented in beta04 had a small error in the source code that made it not work as intended. This release contains a bug fix to correct that behavior.

5.8.3beta09 (December 4, 2025)

Program mbnadjustmerge: Fixed options --unset-tie, --unset-ties-file, --unset-ties-survey, --unset-ties-by-survey, --unset-ties-block, --unset-ties-all.

Program mbbackangle: A skipping existing feature implemented in beta04 had a small error in the source code that made it not work as intended. This release contains a bug fix to correct that behavior.

5.8.3beta08 (November 16, 2025)

Programs mbedit and mbeditviz: Now display dual swath Kongsberg multibeam data in the kmall format (id 261) with two separate across-track profiles. As before the two profiles are associated with a single ping cycle and set of datagrams.

Format MBF_3DWISSL2 (id 234): Updates to handle the evolving representation for the 3D at Depth 2nd generation Wide Swath Subsea Lidar (WiSSL2)

Programs mbphotomosaic, mbgetphotocorrection, and mbphotogrammetry: Augmented to handle seafloor photographs that have already been rectified (corrected for distortion). This capability has not been fully tested at this point.

5.8.3beta07 (October 22, 2025)

Program mbeditviz: Fixed display of swath width when navigation is selected in the survey view.

Format 234 (MBF_3DWISSL2): Supports data from new 3D at Depth 2nd Generation Wide swath Subsea Lidar (WiSSL2).

Program mbpreprocess: Added option attitude-zero-heave to zero heave values in attitude data to be merged with survey data. The immediate use is for integration of Exail Phins C7 navigation and attitude data with multibeam data, all collected on a submerged AUV for which the platform depth is defined by a pressure sensor rather than the heave output by the INS.

Programs mbgrdviz, mbeditviz, mbnavaadjust: Fixed the mouse button description for Rotate View mode so that the right button is properly labeled as zoom rather than exaggeration.

5.8.3beta06 (October 1, 2025)

GMT integration: Fixed compiler directives insuring that the GMT header file gmt_dev.h does not implicitly include a glib header file not needed by MB-System.

5.8.3beta05 (September 30, 2025)

GMT grid i/o functions (src/mbaux/mb_readwritegrd.c): Added compiler directives insuring that the GMT header file gmt_dev.h does not implicitly include a glib header file not needed by MB-System.

GMT module mbcontour: Added compiler directives insuring that the GMT header file gmt_dev.h does not implicitly include a glib header file not needed by MB-System.

GMT module mbgrd2obj: Added compiler directives insuring that the GMT header file gmt_dev.h does not implicitly include a glib header file not needed by MB-System.

GMT module mbgrdtiff: Added compiler directives insuring that the GMT header file gmt_dev.h does not implicitly include a glib header file not needed by MB-System.

GMT module mbswath: Added compiler directives insuring that the GMT header file gmt_dev.h does not implicitly include a glib header file not needed by MB-System.

Programs mbedit, mbeditviz, mbgrdviz, mbnadjust, mbnedit, mbvelocitytool: Removed code ensuring that a message display dialog is displayed when created or updated by processing all outstanding X11 events, as this causes mbeditviz to get lost in an infinite event processing loop on Ubuntu 24 installations.

5.8.3beta04 (September 18, 2025)

Many source files: Addressed code style issues raised previously by Kurt Schwehr, particularly using bool type for logical variables

Program mbinf: Recast mbinf to use long options as well as short options. Added a new capability to list records comprising a data file and the contents of selected records using the --debug-record-types and --debug-record-contents options, which is so far implemented for formats 58, 59, and 89.

Program mbpreprocess: Added several new "kluge" options: --kluge-set-beamwidths --kluge-set-beamwidth-acrosstrack --kluge-set-beamwidth-alongtrack --kluge-ignore-duplicate-pings --kluge-xducer-depth-from-heave --kluge-xducer-depth-from-sensordepth --kluge-xducer-depth-from-heave-and-sensordepth

Macro mbm_route2mission: Fixed end of mission battery behavior to use mode 2 so that the AUV sonars are only shut off if the batteries are mostly exhausted.

Formats 58 and 59 (MBF_EM710RAW and MBF_EM710MBA): Recast handling of transducer depth modes so as to work correctly for more data sets, and added mbpreprocess kluge options to handle the less common combinations of data record types and sonar settings.

Program mbphotomosaic: Augmented handling of camera types to include monocular cameras and single camera calibration models.

5.8.3beta03 (August 31, 2025)

Program mbotps: Added long option commands, and altered the manual page to document use of long options. Fixed the --skip-existing {-M} command so that mbotps actually skips files that already have tide correction defined.

Program mbnadjust: Now displays the reference grid used for global ties in data section and global tie listings.

5.8.3beta02 (August 29, 2025)

Program mbeditviz: Fixed bias parameter optimization when soundings are selected by navigation.

Program mbnavadjust: changed default section sizes to 0.2 km (200 m) and 400,000 soundings.

5.8.3beta01 (August 27, 2025)

Program mbgrd2gltf: Fixed compile problem that occurs when the draco library is installed.

5.8.2 (August 19, 2025)

Version 5.8.2 is now the current release of MB-System.

The source code distribution can be downloaded from the MB-System Github repository at:

<https://github.com/dwcaress/MB-System/archive/refs/tags/5.8.2.tar.gz>

The changes and bug fixes of 5.8.2 relative to the prior stable release (5.8.1) are listed in the ChangeLog.md file entries for the preliminary releases 5.8.2beta01 through 5.8.2beta24.

5.8.2beta24 (July 19, 2025)

Program mbgrdviz: Added capability to export an MB-System route file in a file format that can be loaded into a Kongsberg dynamic positioning (DP) system, enabling using the DP to run the survey lines described by the route file.

Program mbgrdviz: Added capability to export an MB-System route file in a file format that can be loaded into the Kongsberg multibeam control software called SIS (Seafloor information System). The route can be imported in two forms: one where each segment between major waypoints translates to a separate line in SIS, and another that generates a multisegment line in SIS.

Program mbpreprocess: Altered the --skip-existing options so that previously preprocessed files are entirely skipped.

5.8.2beta23 (June 25, 2025)

Program mbgrdviz: Fixed capability to export routes in the form of Kongsberg Dynamic Positioning system waypoints, allowing importation of

the MB-System derived survey plans to the bridge control system on MBARI's R/V David Packard.

Format 89 (Teledyne Reson and Norbit (*.s7k)): Removed an errant debug message.

Program mbnavadjust: Greatly improved picking data sections and global ties from the model time series plots. Reorganized the List menu so that the choices switching the data pick mode on the model plot and the map visualization are together. When the list shows data sections, global ties, or sorted global ties, then picking on the model plot or on navigation in the visualization will bring up the analysis window with a data section and potentially a reference grid. Otherwise the picking and the analysis window will be of crossings and crossing ties.

Program mbpreprocess: Fixed generation of asynchronous navigation, attitude, heading and sensor depth files for use by mbeditviz.

5.8.2beta22 (June 16, 2025)

Program mbtrnpp: Improved beam decimation and median filtering algorithms and some included performance analysis plotting tools. Also fixed string construction code that triggered buffer overflow signals (falsely) when compiled with strict security rules, as is the default for Ubuntu 24.

Program mbgrdviz: Added capability to export routes in the form of Kongsberg Dynamic Positioning system waypoints, allowing importation of the MB-System derived survey plans to the bridge control system on MBARI's R/V David Packard.

Format MBF_3DWISSL2 (234): First work on i/o module for data from the 3D at Depth WiSSL2 (2nd Generation Wide Swath Subsea Lidar) - this is not complete.

Macro mbm_route2mission: Altered the \fB-G\fP option so that instead of causing the AUV mission to include surfacing at survey line starting and/or ending waypoints, now \fB-G\fP causes AUV surfacing to occur at the specified waypoint type.

Program mbimagelist: New utility program that parses \fBMB-System\fP imagelist structures and can also be used to generate metadata files used by other MB-System programs.

5.8.2beta21 (March 15, 2025)

Program mbeditviz: Improved the algorithm used to solve for optimal roll bias, pitch bias, heading bias, time lag, and Snell factor values using sets of soundings selected by area, region, and navigation. Previously these optimization problems were solved by a brute force search for values minimizing the bathymetric variance in the selected soundings. Now the approach is a more sensible Golden Section Search (e.g. Press et al., Numerical Recipes in C, 2nd ed., 1992). Also, the shell output when executing these optimizations is more useful - in particular, the order of the bias parameters now conforms to the order used by platform files and mbmakeplatform. In fact, this same order is now used for the bias value sliders in the mbeditviz 3D sounding window.

Library mbview: fix bug that prevented building mbview on Ubuntu because of a missing include of time.h in src/mbview/mbview_plot.c tied to X11 event debugging code.

5.8.2beta20 (February 22, 2025)

Program mbpreprocess: Added options --kluge-flipsign-roll and --kluge-flipsign-pitch which flip the sign of roll or pitch values, respectively, before they are merged and applied to the swath bathymetry.

Program mbauvloglist: Added support for new phins.log files for Dorado AUVs with a Phins INS installed.

Program mbm_route2mission: Fixed the -Ggpsmode option so that the AUV mission script will actually make the AUV surface at survey line starts and/or ends when gpsmode > 0.

Cmake build system: Augmented the places that Cmake will look for Motif headers and library with /opt/local/include/ and /opt/local/lib/ in the file build-utils/FindMotif.cmake)

5.8.2beta19 (January 19, 2025)

Program mbgrdviz: Fixed bug in which routes might not be exported correctly when multiple routes are exported to a single route file.

Program mbgrdviz: Fixed error messages indicating failed projection of some soundings.

Program mbpreprocess: Fixed crash when preprocessing third generation Kongsberg multibeam data (*.all files, formats 58 and 59) using a platform model defined in a platform file created by mbmakeplatform.

Program mbgrid: Reduced the default verbosity so that the shell output only lists files with data actually used in the gridding.

Format 121 (Generic Sensor Format (GSF)): Fixed crashes that occurred when processing GSF files derived from Teledyne Reson multibeam data.

Format 89 (Teledyne Reson and Norbit (*.s7k)): Handles the lack of a FileHeader record in Norbit multibeam data recorded in the s7k format.

5.8.2beta18 (December 8, 2024)

MBlist: Fixed a critical bug in which mblist would never output from processed files specified through a datalist using the \$PROCESSED tag.

Format MBF_KEMKALL (261): Augmented the i/o module to read and write an undocumented kmall data record (#MSC) found in EM124 data collected by NERC. Without documentation the record cannot be parsed, but it is read and rewritten without modification.

Format MBF_KEMKMALL (261): Fixed failure to differentiate between #SKM records from different navigation + heading + attitude systems. If a platform has two navigation/attitude systems, then the first will map to MB_DATA_NAV1 type data, and the second to MB_DATA_NAV2. The default for mbpreprocess will be to interpolate from navigation, heading, and attitude data stored in MB_DATA_NAV1 records, which for this format means #SKM datagrams with system id 0 (as opposed to system id 1).

Miscellaneous: Removed top level files "NEWS", "NOTES", and "INSTALL.md". These files existed to conform to GNU expectations for a package structure. We are no longer trying to match the GNU structure, and so have removed these unnecessary files.

Most SeaBeam Classic formats (MBF_SBSIOMRG, MBF_SBSIOCEN, MBF_SBSIOLSI, MBF_SBURICEN, MBF_SBURIVAX): Added code to handle rare condition where the ping timestamp has a seconds value of 60. Now the code will add one to the minutes value, and set the seconds value to 0.

5.8.2beta17 (November 7, 2024)

Libtrnav (src/mbtrnav/): Additional fixes by Kent Headley to enable building on Ubuntu 24.

5.8.2beta16 (November 6, 2024)

mbm_route2mission: Change so that no edgetech behaviors are output to the mission script if no sidescan or subbottom is enabled.

Format MBF_MBPRONAV (165): code changed so that if a file has records in which the date fields (yyyy mm dd hh mm ss.ssssss) are all zero, then on reading the data will be set using the value in the time_d (epoch time in seconds) field.

Mbauvloglist: Fixed bug that caused occasional crashes.

Mbphotogrammetry: Now applies CLAHE equalization to images before calculating disparity map.

Libtrnav (src/mbtrnav/): Many fixes by Kent Headley, including casting the code to use Proj for geodetic transformations when used as part of MB-System while still allowing use of the old GCTP library when used in other contexts lacking Proj.

5.8.2beta15 (October 1, 2024)

Mbmakeplatform: Fixed problems with handling sensor add and sensor modify modes.

Mbgrdviz, mbeditviz, mbnavadjust: Changed the mbview display of swath bounds for selected navigation to be optional rather than always displayed.

Formats 58 (MBF_EM710RAW) and 59 (MBF_EM710MBA): Fixed preprocessing support for the Kongsberg M3 multibeam. Added capability to use an MB-System platform file in place of the sensor offsets embedded in the logged multibeam files.

Mbphotogrammetry: Fixed use of range bounds in filtering the photogrammetric bathymetry.

5.8.2beta14 (September 6, 2024)

Mbphotomosaic: Removed unnecessary --correction-file-color option (redundant with --correction-file)

mbm_grdplot: Fixed -G7 option for plotting images with geodetics defined in world files rather than embedded as in GeoTiffs. Specifically allows use of png images with transparency.

Formats 232 (MBF_WISSLR) and 233 (MBF_WISSLP): Fixed initial beam flagging by mbpreprocess for secondary sounding picks (when the lidar was operated in multipick mode)

5.8.2beta13 (August 23, 2024)

Mbphotomosaic: Fixed use of the --dark-image-ignore and --dark-image-multiply options as parameters embedded in recursive imagelist files.

5.8.2beta12 (August 22, 2024)

Mbnavadjustmerge: Fixed (again, this time hopefully for real) the --reimport-all-files option so that large projects can be reimported with a single command. Added a --reimport-survey option.

5.8.2beta11 (August 19, 2024)

Mbnavadjustmerge: Fixed the --reimport-all-files option so that large projects can be reimported with a single command. Added a --reimport-survey option.

5.8.2beta10 (August 16, 2024)

Mbnavadjustmerge: Added --reimport-file and --reimport-all-files options that reimport swath files into an mbnavadjust project from the current processed versions of that files. Each file is broken into the same sections as previously, regardless of any changes to the settings for the maximum section length or the maximum number of soundings in a section. The original navigation and attitude data are also preserved, but the bathymetry is changed to reflect the current processed values. This means that updates to the bathymetry editing can now be brought into mbnavadjust projects.

Format 71 (MBF_MBLDEOIH): Fixed a compression bug that occasionally resulted in corrupting the acrosstrack values of the outermost beams of pings when changed data are inserted into records using the mb_put_all() or mb_insert() functions. The only known manifestation of this bug was in importing swath data into mbnavadjust projects.

Mbtrnpp: Fixed #ifdefs and Makefile.am files so that mbtrnpp can still be built with the old autoconf build system, albeit using GCTP for projections rather than libproj.

5.8.2beta09 (August 4, 2024)

mb7k2jstar: This program extracts Edgetech sidescan and subbottom data from Reson s7k files and writes current format Edgetech Jstar format files identical to what current Edgetech sonars record. This functionality is needed only for MBARI Mapping AUV data from 2004-2014, as MBARI was the only user of a payload controller software package named 6046 from Reson that logged Reson 7125 multibeam and Edgetech FSAU sidescan/subbottom data in the same s7k files. Recognizing that reprocessing old Mapping AUV data requires this capability (and much of these data are now in public archives at MGDS and NCEI), we are moving mb7k2jstar back into src/utilities out of src/deprecated, so that it is always built as part of MB-System. Also, a bug causing seg faults with 2007 data has been fixed.

Mbpreprocess: Added option --kluge-early-mbari-mapping-auv to mbpreprocess. This option pertains only to Reson 7125 200 kHz multibeam data collected on the first MBARI Mapping AUV from 2006 through 2009. Invoking this kluge triggers \fBmbpreprocess\fP to modify the beam quality factors to be consistent with the later (>2009) standard for the original bathymetry records in Reson s7k format data.

Mbextractsegy: Fixed bug in extracting and plotting envelope function of subbottom data.

General: Added macros to src/mbio/mb_define.h enabling the printing of byte values as a binary bitmask using fprintf(). To print a single byte as binary (e.g. "01010101") do something like: char value; printf("Bitmask: "MB_PRINTF_BINARY_PATTERN_INT8"\n", MB_PRINTF_BYTE_TO_BINARY_INT8(value)); Printing of larger int types has a similar form: short value; printf("Bitmask: "MB_PRINTF_BINARY_PATTERN_INT16"\n", MB_PRINTF_BYTE_TO_BINARY_INT16(value)); int value; printf("Bitmask: "MB_PRINTF_BINARY_PATTERN_INT32"\n", MB_PRINTF_BYTE_TO_BINARY_INT32(value)); long long value; printf("Bitmask: "MB_PRINTF_BINARY_PATTERN_INT64"\n", MB_PRINTF_BYTE_TO_BINARY_INT64(value)); These macros are taken from <https://stackoverflow.com/questions/111928/is-there-a-printf-converter-to-print-in-binary-format>

5.8.2beta08 (July 27, 2024)

Format 121 (MBF_GSFGENMB): Updated to use new version of libgsf (3.10) released by Leidos. The following change descriptions are from the libgsf 3.10 change summary:

Change request GSF_03-10_01

Support for ME70 sonars

11/8/2021

Sean Donovan, Leidos

Description:

Added GSF_SWATH_BATHY_SUBRECORD_ME70B0_SPECIFIC sub

Added support for sonar under EM4 cases.

Purpose:

To add support in GSF for the ME70 multibeam systems

Change request GSF_03-10_02

STIG Remediation to address vulnerabilities

3/12/2024

Dwight Johnson, NAVO

Description:

Various changes to safe memory allocation and usage through
decoding processes

Purpose:

Improved Robustness

Change request GSF_03-10_03

Updates to KMAIL ping level metadata

3/12/2024

Jonathon Beaudoin, Hydro Octave

Description:

Added new variables highVoltageLevelDB, sectorTrackingCo
effectiveSignalLength_sec within the spare space of the

Added encoding and decoding logic for these values.

Purpose:

To support backscatter processing

Change request GSF_03-10_04

Resolved bug surrounding network transmission of range sample

3/12/2024

Jonathon Beaudoin, Hydro Octave

Description:

Missing htcons call added to range sample processing

Purpose:

Bug Fix

Change request GSF_03-10_05

Added TVG DB to bathy ping structure

3/12/2024

Jonathon Beaudoin, Hydro Octave

Description:

Added new array variable TVG_DB to multibeam ping struc
decoding logic for this value.

Purpose:

To support backscatter processing

MBnavadjust: Added autosaving the last version of a project file immediately before beginning to write a new file. Also fixed some inconsistencies in the UI.

5.8.2beta07 (June 27, 2024)

mbm_trnplot: Added extraction of TRN localization estimates in longitude and latitude.

Mbtrnpp: Now includes longitude and latitude values of TRN localization estimates into the log file (in addition to the coordinate reference system used for the reference map).

Mbgrdviz: Fixed importation of non-csv raw site files.

Formats 88 and 89 (MBF_RESON7KR and MBF_RESON7K3): Change to allow pings to be valid if a BeamGeometry record has been read earlier in the file (as opposed to having a BeamGeometry record for every ping).

Formats 88 and 89 (MBF_RESON7KR and MBF_RESON7K3): Fixed problem calculating sample times for attitude data in s7k 1016 Attitude data records.

5.8.2beta06 (June 13, 2024)

MBgrid and mbmosaic: Added an option to generate grids and mosaics in a projected coordinate system defined as a Local Transverse Mercator (LTM) projection with the origin at the center of the grid or mosaic.

MBgrdviz, mbeditviz, mbnavadjust: The mbview visualization library now displays grids defined in geographic coordinates (longitude and latitude) using a Local Transverse Mercator projection with the origin at the center of the grid or mosaic. This replaces the prior use of UTM projections, which introduced rotation and distortion when the grid was located far from the center of the UTM zone.

MBtrnpp: and TRN: Changed TerrainNav, supporting libraries, and the program mbtrnpp to calculate projections using the Proj package rather than the GCTP package.

MBtrnpp: Now works with reference topography models defined in a Local Transverse Mercator (LTM) projection.

mbm_trnplot: augmented to allow specifying the CRS of the reference topography so that a Local Transverse Mercator (LTM) projection can be used.

5.8.2beta05 (May 19, 2024)

MBextractseg: changed calculation of section plot bounds to more consistently catch the seafloor arrival within the plot.

MBpreprocess: fixed initialization of the --kluge-fix-7k-times option.

Docker image: updated documentation in the Docker directory.

Formats 58 (MBF_EM710RAW) and 59 (MBF_EM710MBA): Removed an errant debug message that printed out information when reading height datagrams.

5.8.2beta04 (May 13, 2024)

Mbpreprocess: Added kluge option to fix large shifts in survey record timestamps in Teledyne s7k format data (specifically MBARI Mapping AUV multibeam data collected with the sonar computer experiencing large shifts in time). This option is accessed as --kluge-fix-7k-timestamps=time

Mbroutetime: Now works with the recently changed route file format.

Mblevitus: Fixed problem building mblevitus with the Cmake build system. The problem was that the Levitus database location was incorrectly embedded in the compiled program.

5.8.2beta02 (May 1, 2024)

Format 261 (MBF_KEMKMALL): Fixed bug in handing pings for which there are multiple MRZ datagrams that have different timestamps. This bug resulted in MB-System dropping many pings in some deepwater Kongsberg data (mostly EM124 data).

5.8.2beta01 (April 29, 2024)

Mbedit: Fixed display of ping profiles to handle condition where a ping contains two acrosstrack profiles, typically one aft and one forward of the sonar location. Now the connection between the end of the first acrosstrack profile and the start of the second is no longer plotted.

MB-System Docker Container: Improved Docker documentation included in the Docker directory.

5.8.1 (March 22, 2024)

CMake build system: Fixed ability to set OTPS location in cmake build system.

CMake build system: Added installation of header files required for external programs to utilize MB-System libraries.

Format 261 (MBF_KEMKMALL): Updated support for Kongsberg Kmall format to match updated specification J.

Format 16 (MBF_SBSIOSWB): Fixed bug that became evident when processing old Scripps SeaBeam Classic data in format 16 on a MacOS Sonoma machine. This turned out to be a poorly formed preprocessor macro for rounding floating point values in code dating from 1992.

Formats 58 (MBF_EM710RAW) and 59 (MBF_EM710MBA): Fixed bug in which some bathymetry edits were applied to the wrong pings. Third generation Kongsberg multibeam produce two cross profiles with each ping cycle, but represent these as two separate pings with the same ping time. MB-System distinguishes between pings using the timestamps rather than ping numbers (because not all sonars produce ping numbers), so pings with the same timestamp confuse the beam flag handling code. The solution is to add a small amount of time to the timestamp of the second ping in each pair. The bug was that the amount of time added by mbpreprocess was 33 microseconds, but the datagrams in Kongsberg *.all files specify timestamps only to the millisecond level, and so the added time was not large enough to be recorded differently in the output files.

Mbpreprocess: Now checks for successive pings/scans with the same timestamp, and adds enough time to the second timestamp (0.0000033 seconds) that these pings/scans are seen as different by the beam edit flag handling code. For dual head sensors this logic only compares timestamps for the same subsensor, so simultaneous operation of the two subsensors (sonar or lidar heads) is allowed.

Mbpreprocess and format MBF_EM710RAW (58): The command --kluge-auv-sentry-sensordepth now works for format 58 files (3rd generation Kongsberg multibeam data in *.all files) such that available sensordepth values are embedded in the output format MBF_EM710MBA (59) files.

Mbpreprocess and mbprocess: Now support merging navigation and attitude from Schmidt Ocean Institute RVDAS format ROV navigation.

Mbvoxelclean: Fixed bug in which previously beamflags from previously existing esf files were ignored. Also fixed a non-initialized pointer bug that produced occasional crashes.

Mbgrid: Improved output to shell so that it shows the min max values from each contributing input file whether verbose is specified or not. mbm_grdplot: Added colortable 10, which runs from blue to red and can be used for plots of seismic reflection or subbottom profiler data when the trace signals are both positive or negative.

Mbphotomosaic: Fixed priority-heading option that allows image prioritization on the basis of camera heading.

Mbphotomosaic: Added options to detect and correct dark images (for when strobe lights partially drop out), to ignore dark images, and to allow image prioritization on the basis of camera heading.

SEGY format data: Changed MB-System SEGY traceheader to include a sensordepthtime float value in bytes 216-219. This will be used to hold the two-way traveltime in seconds corresponding to the source depth assuming a 1500 m/sec water sound speed. This value can be used as a trace start delay time in plotting to account for the source location of subbottom profiler data collected from submerged platforms like AUVs and ROVs. The MB-System programs mbsegygrid and mbm_grdplot use the source depth value in meters, but some external packages need the delay time.

SEGY format data: MB-System now recognizes file suffixes *.sgy and *.SGY in addition to *.segy *.SEGY *.seg and *.SEG

Mbsegyinfo: Fixed calculation and reporting of trace minimum and maximum values.

Mbextractsegy: Now allows output of subbottom analytic data as well as envelope data. Use of the -S4 command will output three separate segy files, one with the envelope function, one with the subbottom correlate, and one with the correlate conjugant (i.e. the Hilbert transform of the correlate). The section plot script generated now will create plots of all three trace types.

Mbtrnpp: The optional Terrain Relative Navigation (TRN) software has been augmented with code to utilize realtime format 58 (Kongsberg *.all) format multibeam accessed through a serial stream.

5.8.1beta09 (March 22, 2024)

Format 16 (MBF_SBSIOSWB): Fixed bug that became evident when processing old Scripps SeaBeam Classic data in format 16 on a MacOS Sonoma machine. This turned out to be a poorly formed preprocessor macro for rounding floating point values in code dating from 1992.

Formats 58 (MBF_EM710RAW) and 59 (MBF_EM710MBA): Fixed bug in which some bathymetry edits were applied to the wrong pings. Third generation Kongsberg multibeamers produce two cross profiles with each ping cycle, but represent these as two separate pings with the same ping time. MB-System distinguishes between pings using the timestamps rather than ping numbers (because not all sonars produce ping numbers), so pings with the same timestamp confuse the beam flag handling code. The solution is to add a small amount of time to the timestamp of the second ping in each pair. The bug was that the amount of time added by mbpreprocess was 33 microseconds, but the datagrams in Kongsberg *.all files specify timestamps only to the millisecond level, and so the added time was not large enough to be recorded differently in the output files.

Mbgrid: Improved output to shell so that it shows the min max values from each contributing input file whether verbose is specified or not.

5.8.1beta08 (March 10, 2024)

mbm_grdplot: Added colortable 10, which runs from blue to red and can be used for plots of seismic reflection or subbottom profiler data when the trace signals are both positive or negative.

SEGY format data: Changed MB-System SEGY traceheader to include a sensordepthtime float value in bytes 216-219. This will be used to hold the two-way travelttime in seconds corresponding to the source depth assuming a 1500 m/sec water sound speed. This value can be used as a trace start delay time in plotting to account for the source location of subbottom profiler data collected from submerged platforms like AUVs and ROVs. The MB-System programs mbseggrid and mbm_grdplot use the source depth value in meters, but some external packages need the delay time.

SEGY format data: MB-System now recognizes file suffixes *.sgy and *.SGY in addition to *.seg *.SEG *.seg and *.SEG

Mbseginfo: Fixed calculation and reporting of trace minimum and maximum values.

Mbextractseg: Now allows output of subbottom analytic data as well as envelope data. Use of the -S4 command will output three separate segy files, one with the envelope function, one with the subbottom correlate, and one with the correlate conjugant (i.e. the Hilbert transform of the correlate). The section plot script generated now will create plots of all three trace types.

Mbpreprocess and mbprocess: Now support merging navigation and attitude from Schmidt Ocean Institute RVDAS format ROV navigation.

Mbpreprocess and format MBF_EM710RAW (58): The command --kluge-auv-sentry-sensordepth now works for format 58 files (3rd generation Kongsberg multibeam data in *.all files) such that available sensordepth values are embedded in the output format MBF_EM710MBA (59) files.

5.8.1beta07 (February 24, 2024)

CMake build system: Fixed ability to set OTPS location in cmake build system.

CMake build system: Added installation of header files required for external programs to utilize MB-System libraries.

5.8.1beta04 (February 16, 2024)

Format 261 (MBF_KEMKMALL): Updated support for Kongsberg Kmall format to match updated specification J.

5.8.1beta03 (February 8, 2024)

Mbphotomosaic: Fixed priority-heading option that allows image prioritization on the basis of camera heading.

5.8.1beta02 (February 7, 2024)

Mbphotomosaic: Added options to detect and correct dark images (for when strobe lights partially drop out), to ignore dark images, and to allow image prioritization on the basis of camera heading.

5.8.1beta01 (February 1, 2024)

Mbpreprocess: Now checks for successive pings/scans with the same timestamp, and adds enough time to the second timestamp (0.0000033 seconds) that these pings/scans are seen as different by the beam edit flag handling code. For dual head sensors this logic only compares timestamps

for the same subsensor, so simultaneous operation of the two subsensors (sonar or lidar heads) is allowed.

Mbvoxelclean: Fixed bug in which previously beamflags from previously existing esf files were ignored. Also fixed a non-initialized pointer bug that produced occasional crashes.

5.8.0 (January 22, 2024)

Version 5.8.0 is now the current release of MB-System.

The source code distribution can be downloaded from the MB-System Github repository at:

<https://github.com/dwcaress/MB-System/archive/refs/tags/5.8.0.tar.gz>

In addition to many bug fixes, the changes of 5.8.0 relative to the prior major release (5.7.8) include:

New build system:

MB-System is now built and installed using the CMake package, rather than GNU Autotools. The old build system is still present and can be used to install MB-System on old operating systems (e.g. Ubuntu 18.04), but all support for building on recent, current and future operating systems will be for use of CMake. See the Download and Install (<https://www.mbari.org/technology/mb-system/installation/>) instructions page for details.

Global ties to reference grids in MBnavadjust:

MBnavadjust is a toolset used adjust navigation of submerged platform (e.g. AUV or ROV) surveys so that features match where swaths overlap and cross. The primary information comes from measuring the navigation offsets required to match features using cross correlation of the bathymetry data. MBnavadjust now also allows the survey navigation to be tied to reference bathymetry models, typically from GPS-navigated hull mounted surveys, so that the navigation can be tied to the world frame of reference.

Realtime Terrain Relative Navigation:

MB-System now includes a Terrain Relative Navigation (TRN) codebase developed at Stanford and MBARI that uses realtime topography information to where a platform is located on a pre-existing topography map. The MB-System tool mbtrnpp implements TRN in the case of an AUV or ROV equipped with a multibeam sonar.

Photomosaicing tools available:

Tools for generating photomosaics from sets of still seafloor photographs are

now built as part of MB-System. Documentation and examples are being developed but are not available at the time of this release.

MB-System Version 5.7 Releases and Release Notes:

- Version 5.7.9beta72 January 14, 2024
- Version 5.7.9beta71 January 3, 2024
- Version 5.7.9beta70 January 2, 2024
- Version 5.7.9beta69 December 17, 2023
- Version 5.7.9beta68 November 30, 2023
- Version 5.7.9beta66 November 18, 2023
- Version 5.7.9beta65 November 17, 2023
- Version 5.7.9beta64 November 16, 2023
- Version 5.7.9beta63 November 10, 2023
- Version 5.7.9beta62 November 3, 2023
- Version 5.7.9beta61 November 2, 2023
- Version 5.7.9beta60 October 22, 2023
- Version 5.7.9beta59 September 19, 2023
- Version 5.7.9beta58 August 30, 2023
- Version 5.7.9beta57 June 27, 2023
- Version 5.7.9beta53 June 15, 2023
- Version 5.7.9beta52 March 9, 2023
- Version 5.7.9beta51 February 14, 2023
- Version 5.7.9beta50 February 12, 2023
- Version 5.7.9beta49 January 22, 2023
- Version 5.7.9beta48 December 16, 2022
- Version 5.7.9beta47 November 15, 2022
- Version 5.7.9beta46 November 11, 2022
- Version 5.7.9beta45 November 6, 2022
- Version 5.7.9beta44 August 9, 2022
- Version 5.7.9beta43 July 29, 2022
- Version 5.7.9beta42 June 26, 2022
- Version 5.7.9beta41 June 22, 2022
- Version 5.7.9beta40 June 18, 2022
- Version 5.7.9beta38 June 18, 2022
- Version 5.7.9beta37 June 17, 2022
- Version 5.7.9beta36 June 15, 2022
- Version 5.7.9beta35 June 13, 2022
- Version 5.7.9beta34 June 5, 2022
- Version 5.7.9beta33 June 5, 2022
- Version 5.7.9beta32 June 4, 2022
- Version 5.7.9beta30 June 4, 2022

- Version 5.7.9beta29 May 13, 2022
- Version 5.7.9beta28 March 21, 2022
- Version 5.7.9beta27 February 28, 2022
- Version 5.7.9beta26 January 2, 2022
- Version 5.7.9beta25 December 29, 2021
- Version 5.7.9beta24 December 27, 2021
- Version 5.7.9beta23 December 18, 2021
- Version 5.7.9beta22 December 5, 2021
- Version 5.7.9beta21 December 4, 2021
- Version 5.7.9beta20 December 1, 2021
- Version 5.7.9beta19 November 6, 2021
- Version 5.7.9beta18 October 31, 2021
- Version 5.7.9beta17 October 16, 2021
- Version 5.7.9beta16 August 27, 2021
- Version 5.7.9beta15 August 26, 2021
- Version 5.7.9beta14 July 25, 2021
- Version 5.7.9beta13 July 18, 2021
- Version 5.7.9beta12 July 4, 2021
- Version 5.7.9beta11 June 26, 2021
- Version 5.7.9beta10 June 16, 2021
- Version 5.7.9beta09 June 8, 2021
- Version 5.7.9beta07 May 7, 2021
- Version 5.7.9beta06 March 24, 2021
- Version 5.7.9beta05 March 8, 2021
- Version 5.7.9beta04 February 21, 2021
- Version 5.7.9beta03 February 7, 2021
- Version 5.7.9beta02 January 27, 2021
- Version 5.7.9beta01 January 18, 2021
- **Version 5.7.8 January 17, 2021**
- Version 5.7.7 January 17, 2021 (flawed, quickly superceded)
- Version 5.7.7beta09 January 17, 2021
- Version 5.7.7beta08 January 6, 2021
- Version 5.7.7beta06 December 30, 2020
- Version 5.7.7beta05 December 28, 2020
- Version 5.7.7beta04 October 28, 2020
- Version 5.7.7beta03 October 27, 2020
- Version 5.7.7beta02 October 8, 2020
- Version 5.7.7beta01 October 7, 2020
- **Version 5.7.6 October 5, 2020**
- Version 5.7.6beta56 September 28, 2020
- Version 5.7.6beta55 September 16, 2020
- Version 5.7.6beta54 September 14, 2020
- Version 5.7.6beta53 September 13, 2020

- Version 5.7.6beta52 September 9, 2020
- Version 5.7.6beta51 September 4, 2020
- Version 5.7.6beta50 September 2, 2020
- Version 5.7.6beta49 September 2, 2020
- Version 5.7.6beta48 September 1, 2020
- Version 5.7.6beta47 September 1, 2020
- Version 5.7.6beta46 August 31, 2020
- Version 5.7.6beta45 August 26, 2020
- Version 5.7.6beta44 August 24, 2020
- Version 5.7.6beta43 July 23, 2020
- Version 5.7.6beta42 July 21, 2020
- Version 5.7.6beta41 July 12, 2020
- Version 5.7.6beta40 July 7, 2020
- Version 5.7.6beta38 June 8, 2020
- Version 5.7.6beta37 May 26, 2020
- Version 5.7.6beta36 May 17, 2020
- Version 5.7.6beta34 May 14, 2020
- Version 5.7.6beta33 May 5, 2020
- Version 5.7.6beta32 April 22, 2020
- Version 5.7.6beta31 March 2, 2020
- Version 5.7.6beta30 February 20, 2020
- Version 5.7.6beta29 February 17, 2020
- Version 5.7.6beta28 February 13, 2020
- Version 5.7.6beta27 February 3, 2020
- Version 5.7.6beta26 February 2, 2020
- Version 5.7.6beta25 January 20, 2020
- Version 5.7.6beta24 January 16, 2020
- Version 5.7.6beta23 January 11, 2020
- Version 5.7.6beta21 December 12, 2019
- Version 5.7.6beta20 November 26, 2019
- Version 5.7.6beta19 November 22, 2019
- Version 5.7.6beta18 November 21, 2019
- Version 5.7.6beta17 November 15, 2019
- Version 5.7.6beta16 October 29, 2019
- Version 5.7.6beta15 October 21, 2019
- Version 5.7.6beta14 October 8, 2019
- Version 5.7.6beta12 September 20, 2019
- Version 5.7.6beta10 September 18, 2019
- Version 5.7.6beta8 September 9, 2019
- Version 5.7.6beta6 August 26, 2019
- Version 5.7.6beta5 August 6, 2019
- Version 5.7.6beta4 August 2, 2019
- Version 5.7.6beta2 July 25, 2019

- Version 5.7.6beta1 July 6, 2019
- **Version 5.7.5 June 26, 2019**
- Version 5.7.5beta12 June 24, 2019
- Version 5.7.5beta11 June 16, 2019
- Version 5.7.5beta10 June 9, 2019
- Version 5.7.5beta9 June 8, 2019
- Version 5.7.5beta8 April 11, 2019
- Version 5.7.5beta7 March 28, 2019
- Version 5.7.5beta6 March 26, 2019
- Version 5.7.5beta5 March 22, 2019
- Version 5.7.5beta4 March 21, 2019
- Version 5.7.5beta3 March 14, 2019
- Version 5.7.5beta2 March 4, 2019
- Version 5.7.5beta1 February 26, 2019
- Version 5.7.5beta0 February 25, 2019
- **Version 5.7.4 February 12, 2019**
- **Version 5.7.3 February 8, 2019**
- Version 5.7.2 February 4, 2019
- **Version 5.7.1 December 19, 2018**



5.7.9beta72 (January 13, 2024)

Build Systems: Made building and installing deprecated programs optional for both the CMake and Autoconf build systems.

Man pages: Restructured the web page versions of the manual pages installed with MB-System. Recast the postscript versions of the manual pages into Pdf files.

Mbgrdviz: Generated a new version of the MB-System Route files.

mbm_route2mission: Now works with both old and new format route files.

5.7.9beta71 (January 3, 2024)

CMake build system: Fixed creating the levitus.h header file used by mblevitus and mbconfig to define the location of the Levitus database and the OTPS installation, thereby making mblevitus and mbconfig work properly.

5.7.9beta70 (January 2, 2024)

Mblist: Added capability to output beam travel times, angles and other values needed to recalculate bathymetry by raytracing.

Format 261 (MBF_KEMKMALL): Fixed recalculation of bathymetry by raytracing - the problem was that the interpolation of attitude data onto the beam receive time was faulty, so an incorrect roll value was used in calculating the beam raytracing takeoff angles.

5.7.9beta69 (December 17, 2023)

Format 192 (MBF_IMAGEMBA): Fixed correction of beam amplitude values (previously corrected values were not successfully inserted into the data structure).

Mbauvloglist: Program altered so that time and utcTime fields are printed by default in format %17.6f and %12.6f, respectively, even though the MBARI Dorado AUV log files have default formats of %8.8e instead. Now by default the timestamps are printed usefully with precision to microseconds.

Mbbackangle: Fixed bug in which mbbackangle did not process sidescan or amplitude data from files in formats that support variable numbers of beams and pixels.

Mbsslayout: Fixed bug in which a command to swap the starboard and port sidescan channels was ignored.

5.7.9beta68 (November 30, 2023)

CMake build system: It turns out that the GSF i/o module was not getting built and used by default. The build system has been fixed so that the GSF format i/o module is built and linked unless the cmake command includes -DbuildGSF=OFF, as in: cmake -DbuildGSF=OFF ..

Mbnavadjustmerge: Added options to shift global ties singly or all together.

Mbtrnpp: Fixed use of covariances from TRN: to get x y z covariances use covariance[2], covariance[0], covariance[5] rather than 0, 1, and 2.

5.7.9beta66 (November 18, 2023)

Mbdata1ist: Fixed an uninitialized string causing intermittent failure.

5.7.9beta65 (November 17, 2023)

Mbinfo and mblist: Fixed bug introduced with the alternate navigation capability that caused mbinfo and mblist to fail when running on single files rather than through datalists.

Mbnavadjust: Improved handling of reference grids. The list of reference grids now starts with an option "" that will cause loading a section with a global tie set to also load the reference grid (if any) loaded when the tie was created. If a specific reference grid is selected from the reference grid list, then that reference grid will be loaded when any section is loaded, regardless of whether a prior global tie already exists.

Mbtrnpp: Fixed bug identified by Kent Headley that caused divide by zeros when calculating swath width filtering of soundings.

CMake build system: Fixed the unit testing, and enabled building unit tests by default. After "make all" is run, the unit tests can be run with "make test".

5.7.9beta64 (November 16, 2023)

Reading GMT grids: Fixed a very significant bug that caused GMT grids to be read into memory incorrectly by `mb_read_gmt_grd()` in `src/mbaux/mb_readwritgrd.c`. The problem was that the GMT default padding of grids by 2 grid cells around all edges was applied incorrectly, with a result that the topography (or other data) in the grid was shifted two grid cell widths north. The creation of grids by `mbgrid` or `mbmosaic` was correct; the problem came when the grids were read in by `mbgrdviz`, `mbanglecorrect`, `mbprocess`, and `mbnavadjust`.

5.7.9beta63 (November 10, 2023)

Further fixes to the CMake build system, which now actually builds all components of MB-System on MacOS Ventura, Debian 11 and 12, and Ubuntu 20 and 22.

Moved the MB-System version tag and version date variables from the build system files `CMakeLists.txt` and `configure.ac` into `src/mbio/mb_define.h` so that there is only one place to edit the versioning.

5.7.9beta62 (November 3, 2023)

Fixed the Cmake build system so that all components of the current MB-System source can be built, installed, and run on MacOS using CMake.

Updated the copyright notices in the several hundred source files.

5.7.9beta61 (November 2, 2023)

Read functions `mb_get_all()`, `mb_get()`, `mb_read()`: Fixed bug in handling the vertical dimension while applying alternate navigation. Bathymetry were being corrected wrongly for changes in the `sensordepth`.

Datalists: Fixed problem in which processed files would not be read when the raw files do not conform to MB-System suffix conventions.

Mbbackangle: Changed to not set parameter files when the swath files do not contain the expected amplitude and/or sidescan data.

Mbgrd2gltf: Added `"#include "` to `src/mbgrd2gltf/bathymetry.cpp` to enable compiling on CentOS 7.

Configure.ac and Configure: Modified to find Proj on CentOS 7 systems.

5.7.9beta60 (October 22, 2023)

Mbnavadjust: Added an application or use mode to MBnavadjust projects. Projects can now be primary, secondary, or tertiary, with the setting found in the Controls dialog brought up via the Options menu. A primary project behaves as MBnavadjust projects have always behaved, so that applying the navigation model writes the adjusted navigation model to `*.na0` files parallel to the swath files and sets the `*.par` parameter files so that `mbprocess` merges the adjusted navigation as it generates the processed swath files. In a secondary project, applying the adjusted navigation model writes `*.na1` files parallel to the processed swath files (not the raw swath files), and in a tertiary project the output is in `*.na2` files. The purpose for this change is to allow the existence of multiple navigation adjustment models for the same swath data, generally because there may be reasons to have different vertical adjustments. The secondary and tertiary navigation models are termed alternative navigation models. A specific example is for repeated surveys of an active volcano experiencing deformation - one may want to adjust surveys so that vertical offsets over time are removed to allow a seamless topographic map, and to also adjust surveys so that the vertical changes between surveys are revealed by differencing the topographic models. The MBnavadjust project file version has been updated to 3.15 with the addition of the `USEMODE` parameters (`primary=0`, `secondary=1`, `tertiary=2`). MBnavadjust will read all old format projects but only write out the current format.

Mbgrid, mbmosaic, and mblist: These programs are now capable of accessing alternative navigation for processed swath data if such files exist and a datalist structure is set to enable use of the alternative navigation, as described above. The internal changes made to enable this capability are described below.

Datalists and a mechanism for alternative navigation: A new specialized datalist tag has been implemented to allow use of the alternative navigation files (*.na1 and *.na2) introduced above. Adding this tag to a datalist is the only way to access alternative navigation when reading swath files. If the following line appears in a datalist: \$ALTNAVSUFFIX:.na1 then following this tag the new datalist parsing function will look for a *.na1 file parallel to each processed file, and return a flag and the path to that file. This functionality works recursively, as all things do in datalist structures - a top level use of this tag sets the behavior for all datalist parsing down through a recursive datalist file structure. To use this functionality, a program must use a new function mb_datalist_read3() in place of mb_datalist_read() or mb_datalist_read2():

```
int mb\_datalist\_read(int verbose, void *datalist\_ptr, int *format, double *weight, int *error);

int mb\_datalist\_read2(int verbose, void *datalist\_ptr, int *format, char *ppath, char *dpath, int *format, double *weight, int *error);

int mb\_datalist\_read3(int verbose, void *datalist\_ptr, int *format, char *ppath, int *astatus, char *apath, char *dpath, int *format, double *weight, int *error);
```

Here the new astatus is a boolean indicating that an alternative navigation file exists for this swath file, and apath is a string containing the path for that alternative navigation file. In order to have the MBIO library calls actually use the alternative navigation in place of the navigation embedded in processed swath files, the program must use another new function mb_read_init_altnav() to initialize reading (instead of mb_read_init()) - here the change is to pass in the astatus and apath values obtained from mb_datalist_read3().

```

int mb\_read\_init(int verbose, char *file, int format, int
                  double bounds[4], int btime\_i[7], i
                  double speedmin, double timegap, voi
                  double *btime\_d, double *etime\_d,
                  int *beams\_amp, int *pixels\_ss, ir

int mb\_read\_init\_altnav(int verbose, char *file, int form
                        int lonflip, double bounds[4], int btime\_
                        double speedmin, double timegap, int astat
                        void **mbio\_ptr, double *btime\_d, double
                        int *beams\_bath, int *beams\_amp, int *pi

```

If `mb_read_init_altnav()` is used, `astatus` is true, and `apath` is a valid alternative navigation file, then calls to `mb_get_all()`, `mb_get()`, and `mb_read()` will return survey records with the alternative navigation merged in place of the embedded navigation.

The only programs utilizing this capability are `mbgrid`, `mbmosaic`, and `mblist` - this allows generating data products utilizing the alternative navigation.

We have chosen to implement these features using new MBIO functions rather than the simpler approach of modifying the original functions. This choice is to avoid breaking the MBIO API for existing other programs at this time. We will likely simplify the API at some point in the future when the consequences of an API change are understood and manageable.

5.7.9beta59 (September 19, 2023)

`Mbnavadjustmerge`: Made copying of `mbnavadjust` projects more efficient.

`Mbnavadjustmerge`: Add `--remove-short-sections` option to eliminate undesirably short sections by merging them with their prior section.

`Mbnavadjustmerge`: Add `--remove-file` option to remove a file from an `mbnavadjust` project.

`Mbcontour`: Fixed drawing of survey tracklines - restored to generate thin lines.

5.7.9beta58 (August 30, 2023)

`mbm_route2mission`: Modifications to accomodate changes to Dorado AUV vehicle software.

`Mbinfo`: Added `-Q` option which causes `mbinfo` to read statistics from existing `*.inf` files rather than to read the actual swath files. Variances, record types,

nonfatal error messages and mask output cannot be generated with this option.

Mbnavadjustmerge: Fixed bug in merging projects.

Docker: Added a lightweight (945 MB) MB-System Dockerfile build based on alpine Linux distribution. The image contains full MB-System, including TRN and graphical tools. Runs on MacOS 12 (Monterey) and Ubuntu 22.04.

TRN tools: Minor changes to .gitignore (add binaries) and mbtrn/utls/tbinx.cpp (add signal handler, reconnect timing, bug fix).

Mblist: Added option to merge data from a secondary file and allow printing those secondary data values. The secondary file is columnar text in which the first column holds the time stamp in epoch or unix time (seconds since 1/1/1970), and up to 19 following columns hold other data collected during the survey (e.g. temperature or salinity measured on a CTD sensor).

Mbeditviz: The scale widget controlling grid cell size now changes it's range if either the minimum or maximum values are selected (halving or doubling, respectively).

Mbnavadjustmerge: Copying mbnavadjust projects is much more efficient due to use of a fast file copy function replacing a shell call of the program cp.

5.7.9beta57 (June 27, 2023)

mbm_route2mission: Added -T option to embed use of Terrain Relative Navigation in MBARI Mapping AUV missions.

Format 89 (MBF_RESON7K3): Fixed too small buffer size for broadcast Teledyne s7k data records, which caused mbtrnpp to crash by seg fault. This was 32K and is now 600K.

Mbnavadjust: Fixed bug in the inversion algorithm.

5.7.9beta53 (June 15, 2023)

Rewrote the CMake build system based on the work of both Tom O'Reilly and Josch. This build system now works on MacOS Ventura. We will continue to augment and test using cmake so that this build system also works on Ubuntu and Debian Linux.

Mbtrnpp and related TRN code: Many updates and improvements from Kent Headley

Mbcontour: The navigation line width and color can now be set using the -W argument

Format SOIUSBLN (275): Supports USBL tracking data from R/V Falkor (too) as format 275.

Format SOIROVN (276): Supports ROV SuBastian INS navigation data as format 276.

mbm_route2mission: Added a depth limit parameter to the -D argument.

Mbgrdviz: Fixed display of vector data.

General: Fixed automated handling of asynchronous nav and attitude data when reading Kongsberg or Teledyne multibeam data that have not been preprocessed. Changes are in mbio/mb_navint.c

Format RESON7K3 (89): Fixed counting of valid records in the file catalog.

Mbgetphotocorrection, mbphotomosaic, mbphotogrammetry: Fixed to properly handle embedding of parameters within recursive imagelist structures, allowing mixing of photographs taken with difference camera systems or perhaps different camera calibrations.

Mbgetphotocorrection, mbphotogrammetry: enabled multi-threading.

Mbauvloglist: Allow merging attitude data from a separate file. Allow decimation of input.

Mbmosaic: Augmented azimuth priority mode so that the azimuth alone can be specified, in which case the azimuth priority factor is one.

Mbpreprocess: Now outputs integrated navigation for all sensors producing mapping data.

Formats 56 (MBF_EM300RAW) and 57 (MBF_EM300MBA): Fixed catastrophic bug introduced in 5.7.9beta50 that treated many signed values (like acrosstrack distance) as unsigned.

5.7.9beta52 (March 9, 2023)

Formats 56 (MBF_EM300RAW) and 57 (MBF_EM300MBA): Fixed catastrophic bug introduced in 5.7.9beta50 that treated many signed values (like acrosstrack distance) as unsigned.

MBgrdviz: Added ability to export routes as TECDIS LST files for display in a variety of marine chart display software.

Autotools build system: Altered Makefile.am files in third_party/googlemock and third_party/googletest to eliminate benign but alarming error messages during make install and make clean commands.

mbm_route2mission: Added ability to insert a magnetometer calibration maneuver into an AUV mission spiral descent using the -Naltitude/mode command, where altitude is the spiral descent termination altitude and mode = 0 for no start survey behavior, 1 for start survey behavior alone, and 2 for start survey plus a magnetometer calibration maneuver.

5.7.9beta51 (February 14, 2023)

Format 89 (MBF_RESON7k3): Removed debug message inadvertently left active in 5.7.9beta50.

5.7.9beta50 (February 12, 2023)

General: Changed many sprintf() calls to snprintf() calls.

General: Fixed many compiler warnings having to do with unused variables, uninitialized variables, and possible string overflows.

MBnavadjust: Fixed interface issues for importing multiple reference grids and selecting those while making global ties.

Format 261 (MBF_KEMKMALL): Added code to detect and handle gracefully some instances of corruption of MRZ datagrams, particularly due to missing bytes.

Format 201 (MBF_HYSWEEP1): Fixed reading of Hysweep multibeam in which beam angles are stored in spherical coordinates but are not corrected for roll and pitch. Updated support to handle multibeam data with angles in spherical coordinates that have not been corrected for roll and pitch, and to be consistent with the most recent Hypack users manual released February 2023.

5.7.9beta49 (January 22, 2023)

mbm_grdplot, mbm_grd3dplot, mbm_histplot, mbm_plot, mbm_xyplot: Made evince one of the default Postscript viewers because it is commonly installed on Ubuntu machines.

General: Addressed compiler warnings due to uninitialized variables, inconsistent variable typing, and other minor issues.

Mbnavadjust: Changed the solution algorithm so that the final stage of LSQR matrix inversion is done in several steps. As before, the first three stages are to construct an initial model by interpolating any global ties, then solve for and apply average offsets for each survey, then conduct an iterative relaxation towards an additional perturbation solution. Each stage produces a perturbation solution, that is, a solution to fit the navigation offsets remaining after applying the existing navigation model. Each perturbation is added to the navigation model, which is then the starting point for the next stage. These three stages build up an approximate navigation solution that solves most of the original mismatch between overlapping and crossing swathes. The final stage is to build and solve an overdetermined least squares matrix problem constrained by all crossing and global times, by any surveys with fixed navigation, and also constrained by a penalty against first and second derivatives of the perturbation. Now, for multi-survey projects the matrix solution stage consists of first solving the full matrix problem, then solving for a perturbation to satisfy the remaining misfit for each of the individual surveys in turn, and finally redoing the full matrix problem. Again, after each solution step the resulting perturbation is added to the navigation solution.

Mbnavadjust: Added two new list options for sorted crossing ties. Now the sorted crossing tie list can be limited to the top 5% or 1% of ties.

Format MBF_MBARIROV (165): Added recognition for new filenames conventions for MBARI ROV navigation files.

5.7.9beta48 (December 16, 2022)

Mbmosaic: Fixed parsing of the -Ypriority_source option when priority_source is a filename.

mbm_grdplot: Fixed handling of image file min max when color_mode == 6.

Mbnavadjust: Added controls allowing the mode of global ties to be changed interactively.

Mbnavadjust: Changed project file format, adding the the id of the source reference grid used for each global tie.

Mbview library: Fixed problem where mbview did not render the last row and column of a grid (the easternmost and northernmost data). Also attempted to make picking more robust.

Mbnavadjust: Fixed interpolation of global ties to create the starting navigation model during inversions. Fixed several actions in section and reference grid mode.

5.7.9beta47 (November 15, 2022)

Mbnavadjust: Individual survey grids are now sized to the region of those surveys rather than the entire project. When the individual surveys are visualized, only the navigation for that survey are loaded into the mbview 2D/3D map instance. Also fixed picking of section navigation in both crossing and section (vs reference grid) modes.

Mbnavadjustmerge: Added options set the mode (XYZ vs XY vs Z) of all global ties.

5.7.9beta46 (November 11, 2022)

Mbnavadjust: Added ability to import and use multiple reference grids for picking global ties of individual swath data sections.

5.7.9beta45 (November 6, 2022)

FNV files: The fast navigation or *.fnv files are created as ancillary files allowing navigation to be read without reading the full swath files. The *.fnv files are in the MBF_MBPRONAV (166) format. Format 166 has always supported comment records as lines beginning with the '#' character, but fnv files have always been created without any comment records. Many MB-System programs read fnv files directly without using the MBF_MBPRONAV i/o module. Now all format 166 files will be written with a first record documenting the contents of the file:

```
fprintf(mb\io\_ptr->mbfp, "## <yyyy mm dd hh mm ss.ssssss>  
    "<longitude (deg)> <latitude (deg)> <heading (deg)>  
    "<draft (m)> <roll (deg)> <pitch (deg)> <heave (m)>  
    "<portlat (deg)> <stbdlon (deg)> <stbdlat (deg)>
```

whether they are written by the MBF_MBPRONAV i/o module or by functions in applications like mbprocess or mbpreprocess. All instances reading these files will ignore these file header records.

Mbgrdviz: augmented and corrected the headers of route and site files output by mbgrdviz, better self documenting the formats of these files.

Mbnavadjust: Added ability to import a reference bathymetry grid that can be used to define global ties. Also modified so that when the main display list

mode limits what is shown to "with selected survey" or other modifiers, these constraints also limit what navigation is shown in the project visualization. So, if one selects a survey and then sets the list mode to show only the selected survey, then the visualization will also only display the navigation from that survey, the crossing ties or global ties from that survey, and only allow picking on that survey's navigation.

Mbareaclean: Fixed issue in which mbareaclean does not apply filters for files without pre-existing *.esf files.

Mbackangle: Plots of the backscatter vs grazing angle distribution are no longer histogram equalized.

Mbprocess: Modified the threaded processing function process_file() so that each instance carries a thread id that can be checked during debugging.

5.7.9beta44 (August 9, 2022)

Mbphotomosaic: Fixed problem in which an image correction model from mbgetphotocorrection was read but not applied.

Mbeditviz: Fixed display of beam info when picking in info mode in the 3D soundings display.

5.7.9beta43 (July 29, 2022)

Mblist and mbnavlist: Fixed failure to deallocate proj object.

Mbtrnpp: Added UTM projection to top level using Proj, but this is not used yet. The UTM projection used within the TRN codebase remains defined in the very old GCTP package, which is embedded with TRN.

TRN execution and plotting scripts (e.g. src/mbtrn/tools/mbtrnpp-plot/trnucli-plot.sh): Changed the shebang call from #!/usr/local/bin/bash to #!/usr/bin/env bash for portability.

Mbnavadjust: Recast global ties to utilize a full 3D covariance model just like the crossing ties, in preparation for allowing graphical picking of global ties relative to a reference bathymetry model.

Mbnavadjustmerge: Added ability to remove discontinuities in mbnavadjust projects. Recast global ties to utilize a full 3D covariance model just like the crossing ties, in preparation for allowing graphical picking of global ties relative to a reference bathymetry model.

mbm_trnplot: Added mission names to mbtrnpp result plots.

Cmake Build System: Incorporates an initial attempt at a cmake based build system that will provide an alternative to the existing AutoTools based build system. Updated documentation for both build systems is not included yet.

5.7.9beta42 (June 26, 2022)

Format 261 (MBF_KEMKMALL): Fixed bug in handling beam amplitude data from null beams.

Mbtrnpp: Fixed trnu logging.

Mbnavadjust: Altered the navigation adjustment inversion algorithm to apply linear interpolation of global ties to create a starting model for the inversion. Fixed picking on tie offsets in the modelplot window.

5.7.9beta41 (June 22, 2022)

mbm_makedatalist: Fixed to work with *.kmall files, and added -Bsize option to impose a size threshold for files included in the output datalist.

TRN: Several fixes to the TRN (terrain relative navigation) capability.

5.7.9beta40 (June 18, 2022)

Mbtrnpp: Fixed decimation algorithm more so it doesn't crash in Linux.

5.7.9beta38 (June 18, 2022)

Mbtrnpp: Added option --auv-sentry-em2040 to configuration file and command line options in order to enable use of the special pressure depth encoding in EM2040 data collected on AUV Sentry. Previously this option was hard coded in mbtrnpp.c. By default this option is disabled, so in order for mbtrnpp to work with Sentry EM2040 multibeam either in realtime or playback modes this option must now be specified.

5.7.9beta37 (June 17, 2022)

Mbtrnpp: Fixed decimation algorithm.

Mbgrdtilemaker: Fixed building of this new tool.

5.7.9beta36 (June 15, 2022)

Mbgrdviz: Fixed export of Risi survey scripts from routes.

mbm_trnplot: Fixed plotting macro to work when the users path does not include the current directory.

Mbgrdtilemaker: Now copies the source background grid into the directory containing the octree tiles with the name source_grid.grd.

5.7.9beta35 (June 13, 2022)

Mbtrnpp: Added options to set the TRN search area on the command line and in cfg files. Fixed wrapper script mbtrnpp.sh so that the number of cycles to be used is set correction.

mbm_trnplot: Fixed plotting macro to work with the current mbtrnpp output.

Mbgrd2octree: Recast program that translates a topography grid in a projected coordinate system (like UTM) into a TRN octree model. This program now used MB-System-like arguments, e.g. mbgrd2octree --input=grid --output=octree

Mbgrdtilemaker: Added new program to generate a tileset of octrees for TRN from a reference grid in a projected coordinate system (like UTM). This tileset can be used by mbtrnpp.

5.7.9beta34 (June 5, 2022)

Mbtrnpp and other elements of the Terrain Relative Navigation infrastructure: Augment mbtrnpp command set to include new commands for forced TRN resets with specified starting navigation offsets and particle filter spread size.

5.7.9beta33 (June 5, 2022)

Mbtrnpp and other elements of the Terrain Relative Navigation infrastructure: Test tools and mbtrnpp command set augmented to enable using TRN in an ROV context with realtime bathymetry available via LCM - this development is not complete.

5.7.9beta32 (June 4, 2022)

Fixes to src/mbtrnav/Makefile.am to allow successful build of TRN tools on Mac Homebrew.

5.7.9beta30 (June 4, 2022)

Fixes to the Autotools build system allowing MB-System to be built in full on Arm architecture Mac computers running the Monterey OS and fixing the build of the TRN tools on Linux.

MBnavadjust: Incremental changes towards handling global ties relative to a reference grid - defined a single section naverr mode but don't have it working yet.

5.7.9beta29 (May 13, 2022)

Fixes to the Autotools build system allowing MB-System to be built in full on Arm architecture Mac computers running the Monterey OS and fixing the build of the TRN tools on Linux.

5.7.9beta28 (March 21, 2022)

mbm_trnplot: Added --display option that immediately displays the plots.

General: Reduced the internal maximum file path name length from 4096 to 1024 characters.

Format MBF_RESON7K3 (89): Fixed reading/writing of the PingMotion (7012), Beamformed (7018), and FileCatalog (7300) records.

Mbnavadjust: Changed default range for z-offsets in calculating the 3D misfit from +/- 5 m to +/- 1 m. Made progress towards allowing interactive picking of global ties relative to a reference topography grid.

5.7.9beta27 (February 28, 2022)

Mbtrnpp: Improved TRN result logging, including having all log files from a session placed in the same directory named according to the start time. Also added automated plotting of the TRN results using a new plot macro mbm_trnplot.

mbm_trnplot: New plotting macro that generates two map views of the results from an mbtrnpp session.

Mbeditviz: Supports selective editing or ignoring of multipick soundings.

mbm_route2mission: Added new battery behavior that turns off the mapping sonars after data logging has been turned off at the end of the survey, before ascent to the surface.

Mbvoxelclean: fixed memory management fault.

General: Increased the size of MB_PATH_MAX to 4096 bytes to allow for longer file paths - this now conforms to the common file path maximum for Linux distributions.

Terrain Relative Navigation: Many changes to mbrnpp and TRN related code by Kent Headley

Mbphotomosaic: Fixed further issues with specifying options within the imagelist.

Mbnavadjust: Changed inversion - the relaxation stage now terminates if it starts to diverge, a mod that reduces the tendency of the inversion to blow up.

Mbmakeplatform: Fixed header file array definition issue that caused compile failures when testing cmake based builds.

5.7.9beta26 (January 2, 2022)

Mbphotomosaic: Augmented available commands that can be specified in imagelist files with --priority-weight and section-length-max. The --priority-weight allows one to up-weight or down-weight sets of images in a photomosaic. The --section-length-max command allows one to exclude groups of pixels that are projected into too large of an extent when projected onto the seafloor topography model.

mbm_makeimagelist: Augmented to comment out the first five image pairs in each image survey directory, as the first three or four images are usually quite dark.

5.7.9beta25 (December 29, 2021)

Mbphotomosaic: Fixed problem specifying the image correction table file in an imagelist structure.

Mbphotomosaic and mbgetphotocorrection: Altered the image correction table file generated by mbgetphotocorrection and read by mbphotomosaic to include correction tables for color as well as intensity. Since we are using the YCbCr color space this means generating tables of average chroma (color) difference in red and blue as well as a 3D table of average luma (intensity). If RGB and YCbCr values have ranges 0-255, then:

$$Y = 0.299R + 0.587G + 0.114B$$
 (Luminance, intensity, B/W signal)

$$Cb = 0.564(B - Y) + 128 \text{ (blue color difference)}$$

$$Cr = 0.713(R - Y) + 128 \text{ (red color difference)}$$

and

$$B = (Y + 1.773 * (Cb - 128));$$

$$G = (Y - 0.714 * (Cr - 128) - 0.344 * (Cb - 128));$$

$$R = (Y + 1.403 * (Cr - 128));$$

If the specified color correction file includes the Cr and Cb tables, then the --correct-color command will cause mbphotomosaic to use those tables to correct for color. Each source image pixel being corrected has a lateral location within the source image and a standoff (altitude) relative to the seafloor; these 3D positions correspond to locations in the 3D correction tables. As with the intensity, the Cr and Cb corrections are a multiplicative factor calculated to map the the value in the relevant location in the table to a reference value. The reference value may be the average central values in the correction tables or a value specified by the user with the --reference-intensity=intensity and --reference-crcb=cr/cb commands.

5.7.9beta24 (December 27, 2021)

Mbphotomosaic and mbgetphotocorrection: Altered the image correction table file generated by mbgetphotocorrection and read by mbphotomosaic to include the reference gain and exposure settings used by mbgetphotocorrection. This means that these settings no longer have to be explicitly set in the mbphotomosaic command.

Mbphotomosaic: Added an option --reference-intensity=intensity that sets the reference intensity used by mbphotomosaic when mbgetphotocorrection image correction tables are being used. The algorithm now works as follows: Before correction the pixel values are transformed from BGR colorspace into the YCbCr color space, that is from blue, green, red triples into Y (intensity), Cb (blue difference chroma), Cr (red difference chroma) triples. The correction involved changing the intensity, and then the YCbCr triples are transformed back into BGR triples for use in the photomosaic. The correction applied to each source pixel (or section) is a value that is multiplied by the source pixel intensity - a value of 1.0 will leave the source pixel unchanged, a value > 1.0 will make the pixel lighter, and a value < 1.0 will make the pixel darker. Each source pixel or section has an x-y location in the source image and a vertical standoff relative to the seafloor topographic model - these coordinates specify a location in the image correction table for the relevant camera. The value in the lookup table at that spot is the average intensity of

all pixels with that location. The correction value is calculated as the multiplier that would transform the lookup table value to a desired reference intensity: $C = \text{reference_intensity} / \text{table_intensity}$

5.7.9beta23 (December 18, 2021)

Mbphotomosaic and mbgetphotocorrection: Another iteration trying to get image gain and exposure correction to work correctly. Altered the imagelist file format to include camera gain and exposure settings. These can be extracted from the metadata embedded into images written by the MBARI Prosilica driver code (adapted from URI/WHOI/UM).

mbm_makeimagelist: Altered the imagelist file format to include camera gain and exposure settings. These can be extracted from the metadata embedded into images written by the MBARI Prosilica driver code (adapted from URI/WHOI/UM). Added --check-bayer option to allow checking the bayer images for the original camera gain and exposure settings when those are not carried over to the derived color images.

5.7.9beta22 (December 5, 2021)

Mbphotomosaic and mbgetphotocorrection: Another iteration trying to get image gain and exposure correction to work correctly.

5.7.9beta21 (December 4, 2021)

Mbphotomosaic, mbgetphotocorrection, mbphotogrammetry, mbm_makeimagelist: Altered imagelist file format and functions reading recursive imagelist structures. Now each stereo rig dataset has a single imagelist that can include both stereo pairs and single images (when one photo from a stereo pair is missing). Also, the imagelists created by mbm_makeimagelist now include the camera gain and exposure settings.

Mbphotomosaic, mbgetphotocorrection: Now can correct for image gain and exposure settings.

5.7.9beta20 (December 1, 2021)

Mblist: Added K and k options to the output, where K prints the fraction of non-null beams that are good (unflagged) and k prints the fraction of all possible beams that are good. These fractions are by definition bounded by 0 and 1.

Mbphotomosaic, mbgetphotocorrection, mbphotogrammetry: Added capability to load a time series of image quality values through new options:

- --image-quality-file=file
- --image-quality-threshold=value
- --image-quality-filter-length=value

5.7.9beta19 (November 7, 2021)

Format 89 (MBF_RESON7K3): Increased the maximum possible number of beams from 512 to 1024.

5.7.9beta18 (October 31, 2021)

Mbgrid: Enabled shifting of output grid bounds using a new -Yshiftx/shifty option.

Mbtrnpp: Fixed build issue TRN libraries.

5.7.9beta17 (October 16, 2021)

Mbgrid and mbmosaic: Fixed setting output grid format with the -G option. The definition and parsing of the options is now consistent with GMT 6.

Mbnavadjust: Added option to unset skipped crossings.

Mbnavadjust: Changed vertical scaling of the time series model plot and the tie plots so that these are centered on the midpoint values rather than zero.

Mbgrdviz: Changed how routes are output as Risi survey scripts - now the lateral positions of waypoints are relative east and north meters in UTM rather than local x,y calculated using mtodeglon and mtodeglat from a simple spheroid.

mbm_grdplot: Fixed so that it does not crash if the input grid has either no valid values (all are NaN) or all valid values are the same.

5.7.9beta16 (August 27, 2021)

Mbnavadjust: Made listing of survey vs survey blocks much faster.

5.7.9beta15 (August 26, 2021)

Mbnavadjust: Speeded up model tie plots and insured that changes to projects will be saved when users quit.

Mbview (mbgrdviz, mbeditviz, mbnavadjust): Addressed a number of code style issues particularly using bool rather than int for true/false values.

mbm_route2mission: added acoustic modem status signal to MBARI AUV missions immediately at the end of the "start survey" behavior.

5.7.9beta14 (July 25, 2021)

Most programs: Fixed possible overflow associated with code that sets user, host, and date information to be included in output files. This functionality has been concentrated into a function mb_user_host_date() found in src/mbio/mb_defaults.c

Many programs and i/o modules: Increased use of assert() to prevent overflow conditions when using sprintf to construct strings.

5.7.9beta13 (July 18, 2021)

Mbextractseg - fixed plotting so that the last plot is correct.

TRN: updated TRN documentation.

5.7.9beta12 (July 4, 2021)

Build system: Fixed location of RPC and XDR headers for Ubuntu 21.

TRN: updated TRN documentation.

5.7.9beta11 (June 26, 2021)

Build system: The configure script and the resulting Makefiles are generated using GNU Autotools 2.71 instead of 2.69.

Mbnavadjustmerge: Enabled new options --set-global-tie-relative which allows setting a global navigation tie with offsets calculated relative to the current navigation adjustment model.

Mbphotomosaic: Improved algorithm for mapping the imagery from the source images to the destination image. Now the code loops over all destination pixels in each quadrilateral of interest and obtains the corresponding source image pixels. Therefore no gaps are left in the destination image due to a resolution and sampling mismatch between the source and destination images.

mbm_grdplot, mbm_grd3dplot, mbm_grdcut, mbm_grdinfo, mbm_grdtiff:
Fixed the macros to work with the new gmt grdinfo output that changed for
GMT 6.2.0.

5.7.9beta10 (June 16, 2021)

Mbnavadjust: Fixed importation of swath files, which was failing. Fixed crash
that happened when a navigation inversion was performed in the same
session as swath data importation.

Mbauvloglist: Fixed parsing of short values in MBARI Dorado AUV MVC log
files.

mbm_grdplot: Fixed histogram equalization in cases where grdhisteq returns
an incomplete or short equalized color table.

5.7.9beta09 (June 8, 2021)

Mb_rt raytracing functions: Added tracking of travel times in arrays returned
by mb_rt() for plotting raypaths. This adds a parameter to the mb_rt()
function call, which is used by utilities/mb_process.cc and mbvelocitytool/
mbvelocity_prog.c.

mbm_grdplot: If `\B-MGL\PIF\PI` is given in conjunction with `\B-`
`MGL\PI\scalebar\PI` then the map scale will be surrounded by a white filled,
black bounded box on top of the map.

mbm_grdplot: Chooses more reasonable easting/northing annotation
intervals when plotting maps in projected coordinate systems like UTM.

mbm_grd2arc: Fixed so that the call to gmt convert is actually made.

mbm_grdtiff: Fixed so that the temporary GMT defaults are actually applied
to the output image. By default this enforces a white background on the
output GeoTiff image, which enables the new tool mbtiff2png to set the white
areas to transparent when it converts a GeoTiff image to a PNG image for
import into GIS.

Mbeditviz: Fixed sparse filtering functions, which were inadvertently broken a
few months ago.

Mbgetphotocorrection: Made multithreaded.

Mbphotomosaic: (1) Made multithreaded. (2) Added ability to map blocks of
pixels from source images to the destination image instead of mapping
individual pixels. The size of the square blocks is specified using --

section=sizeInPixels. (3) Added PNG format image output, which allows no data regions to be transparent. PNG images cannot have geodetics embedded, and so depend on a *.pgw world file to be importable into GIS. (4) Added image correction modes based on source pixel range or standoff.

Mbtiff2png: New tool that converts GeoTiff images to PNG images while setting no data regions transparent on the basis of being white, lighter than a specified threshold, black, or darker than a specified threshold.

Mbvoxelclean: Fixed application of acrosstrack and range filters.

5.7.9beta07 (May 7, 2021)

mbm_histplot: Fixed the use of the -C option to specify cellwidth for the histogram to be plotted.

Formats 232 (MBF_3DWISSLR) and 233 (MBF_3DWISSLP): Changed so that MB_FLAG_SECONDARY is no longer used for multiple picks per laser pulse.

MBnavadjust and MBnavadjustmerge: Restructured the code so that more capability of mbnadjust can be duplicated in the command line tool mbnadjust merge. Working to add ability to reimport surveys into a project.

MBvoxelclean: Added --neighborhood option and fixed amplitude range options.

Mblast: Fixed function of the -O%fnv and -O%FNV commands to produce *.fnv files.

5.7.9beta06 (March 24, 2021)

Mbpreprocess: Fixed to work with the old s7k format (88) MBF_RESON7KR.

Format 88 (MBF_RESON7KR): Fixed to not recognize collections of ping records that are mission bathymetry and/or travel time records as complete.

Mbnadjust: When importing files, only export navigation records to the *.mb166 files in the project directory for ping records (previously data were output for input navigation records as well).

5.7.9beta05 (March 8, 2021)

Mbauvloglist: Added available output field of speed calculated from the velocity vector in the kearfott.log log file, with tag calcKSpeed. Also added new -C option: in the case that navigation is being merged from an external

file specified with the -N option, the -C option suppresses output of records with timestamps from before or after the time bounds of the navigation data. The default remains to output those records with zero values for the merged navigation outside the time bounds.

General: Changed code that deletes temporary files from using a system() call to using the stdio function remove(). Affects src/mbio/mb_process.c, src/utilities/mbdatalist.cc, and src/mbvelocitytool/mbvelocity_prog.c.

TRN: Updates to src/mbtrn, src/mbtrnav, src/mbtrnutils from Kent Headley.

mbm_grdplot, mbm_3dgrdplot, mbm_grdtiff, mbm_grdinfo: Changed "-r" tests for file readability to "-e" tests for file existence. This is to accommodate filesystems that use ACL rather than old style unix file modes - the old stat based readability test in Perl fails on ACL filesystems.

5.7.9beta04 (February 21, 2021)

Mbpreprocess: Fixed handling of data formats that do not have specially defined preprocessing functions. This fix was prompted by problems with SeaBeam 2112 data in format 41 (MBF_SB2100RW).

General changes: More work to achieve thread safety for mbprocess: removed use of static variables in several components of MBIO.

Mbgrid: Fixed error handling so that if the program is shut down by an error, the exit code is nonzero.

MBIO: Added extraction function mb_extract_lonlat(), which returns swath data similar to mb_extract() but with beam and pixel positions defined in longitude and latitude rather than acrosstrack and alongtrack distances relative to the reference point.

Mbareaclean: Fixed memory management bug causing crashes.

5.7.9beta03 (February 7, 2021)

General changes: Replacing use of strtok() function with strtok_r(). Strtok() is intrinsically not thread safe or reentrant and is considered poor use under all circumstances. Source files with this change include: src/mbio/mbr_edgjstar.c src/mbio/mbr_hypc8101.c src/mbio/mbr_hysweep1.c src/mbio/mb_format.c src/mbio/mb_get_value.c src/bsio/mbbs_tm.c src/utilities/mblevitus.cc src/mbvelocitytool/mbvelocity_callbacks.c src/mbnavedit/mbnavedit_callbacks.c src/mbnavadjust/mbnavadjust_callbacks.c

General changes: Replace atof() with strtod() for thread safety. Source files with this change include: src/gmt/mbgrdtifforg.c src/bsio/mbbs_tm.c src/mbio/mb_navint.c src/mbio/mbr_edgistar.c src/mbnavadjust/mbnavadjust_fine.c

General changes: Replace atoi() with strtol() for thread safety. Source files with this change include: src/gmt/mbcontour.c src/gmt/mbgrdtifforg.c src/gmt/mbswath.c src/gsf/gsf.c src/utilities/mbgrid.cc src/utilities/mbprocess.cc

General changes: Protect against overflows copying comments in all of the mbsys_XXX_extract() and mbsys_XXX_insert() functions the in the source files mbsys_XXX.c

MBnavadjust: Fixed bug that failed to save new navigation ties if the program was closed without solving for a new model. Now closing the program will always save any unsaved ties.

MBeditviz and MBview: Removed unneeded functions from mbview/mb3dsoundings_callbacks.c that were breaking test Cmake builds.

5.7.9beta02 (January 27, 2021)

Fixed bug in format 58 and 59 support for bathymetry recalculation. The per beam heave values were being calculated incorrectly when bathymetry was recalculated by raytracing.

Fixed bug in format 57 in which reprocessing did not trigger recalculation of multibeam pseudosidescan.

These bugs were introduced during the 2020 code modernization.

5.7.9beta01 (January 18, 2021)

Mbedit and mbnavedit: Use extern for Widget definitions in mbedit_creation.h and mbnavedit_creation.h to avoid duplicate symbol link errors when building code according to current C / C++ standards. The other graphical utilities already use this construct.

5.7.8 (January 17, 2021)

Version 5.7.8 is now the current release of MB-System. Changes since the 5.7.6 release include:

Configure: Fixed handling of X11 libraries and header files in the autotools build system in order to circumvent more changes to dependencies installed on Macs using the Homebrew package manager. The first attempt at this

turned out to cause X11 runtime failures on Linux systems, and so release 5.7.7 was rapidly superceded by this 5.7.8 release.

mbdatalist: Fixed memory leak in src/mbio/mb_check_info.c that could occur when parsing *.inf files.

Formats 88 (MBF_RESON7KR) and 89 (MBF_RESON7K3): Fixed bug in handling of PingMotion data records (7012) that caused memory overruns and seg faults.

Mbclean: Fixed two bugs. The first involved setting the left/right bounds of flagging by across-track distance using the -Y option, and the other resulted in slope flagging being applied when not requested when the -Y option was used alone.

Mbpreprocess: Added option to set directory where output files are written instead of writing the output files parallel to the input swath files.

Format 121 (MBF_GSFGENMB): Modified handling of multibeam snippet backscatter so that samples associated with beams flagged as bad are nulled, and so that modified backscatter is written to the output file by mbprocess.

Mbeditviz: Modified 3D sounding view so that the depth buffering is actually used.

mbm_makedatalist: Now ignores the most recent file when the -L option is used.

Mbprocess: Fixed raytracking library used by mbprocess so that it is thread safe. The relevant code is in mbsystem/src/mbaux/mb_rt.c

Format 261 (MBF_KEMKMALL): Fixed bug in handling version 0 MWC datagrams.

Mbphotomosaic: Fixed bug in pixel processing that occasionally produced overflows leading to seg faults.

Mbphotomosaic: Fixed bug in imagelist processing that prevented use of images taken with the right camera of a stereo pair.

Mbimagecorrect: New program that performs some simple brightness and contrast corrections using standard OpenCV algorithms.

Mbprocess: Recast the program to process files in parallel using separate threads. This was implemented in the C++ main code using the C++11 standard thread API. The default is to use a single processing thread and

therefore to process the files serially; the new -Cthreads option enables the use of multiple threads. For now, the built-in record keeping of memory allocation/deallocation is disabled for mbprocess because this functionality is not thread-safe.

Mbnavadjust: The navigation adjustment inversion has been improved by tuning the parameters used for the overdetermined least squares solution.

Mbswath2las: Shell for not-yet-working program to export soundings from swath data to some variant of the LAS format used for point cloud data.

Mbvoxelclean: Added option to filter based on beam amplitude minimum and maximum values.

Mbeditviz: Fixed coloring of soundings using beam amplitude values (colormap was applied incorrectly).

Mbeditviz: Added option to display the selected sounding point cloud with soundings colored according to associated amplitude value. Also added the sounding amplitude value to the information listed when soundings are selected in the "info" mode.

Mbedit: Added the sounding amplitude value to the information listed when soundings are selected in the "info" mode.

Mbnavadjust: Previously autopicking of crossings skipped crossings including short sections where short was defined as less than 0.25 times the length of the first section of the associated file. This is problematic when the survey platform is stationary at the beginning of a file, resulting in a first section with a short track length (sections are terminated either on track length or total number of soundings). Now short is defined as less than 0.25 times the current desired section length for the project.

Format 58 (MBF_EM710RAW): This format supports third generation Kongsberg multibeam data as recorded in *.all files; the augmented format 59 (MBF_EM710MBA) is used for processing. Data are translated from format 58 to 59 using mbpreprocess. Data have been collected using a partially nonfunctional EM122 such that most of the backscatter snippet records are missing. The existing code treats pings for which the snippet records are missing as incomplete and drops them. The format 58 i/o module has been modified so that if a special flag is set, any snippet records will be ignored and all pings will be treated as having an empty but existing snippet record. Users can set this flag with a special --kluge-ignore-snippets argument to mbpreprocess.

Mbpreprocess and i/o modules with defined preprocessing functions: All existing preprocess functions have been augmented so that a call with a null pointer to the data structure will trigger an option to set i/o flags after reading from a file is initialized but before any data are read. The only case at present where this is used is format 58 (MBF_EM710RAW), where the mbpreprocess option --kluge-ignore-snippets causes the reading code to treat pings with bathymetry as complete whether snippet records exist or not, and to zero the snippet information for those pings.

mbm_makedatalist: Added -L option which will omit the last file found from the output datalist. The intent of this option is to exclude the most recent file in an actively data logging context, since the most recent file is still being logged. This presumes that filenames sort in time order as listed by the ls command, an assumption that does not hold for all file naming conditions or if the -T option has been used to disable time ordering. Also added a behavior particular to Kongsberg multibeam data as originally logged - files named "9999.all" are now ignored.

Mbotps: Modified mbotps to place temporary files in the user's home directory instead of the current working directory when the latter case results in file paths greater than 80 characters long. This is because OTPS has its filename variables defined as 80 character strings.

Format 88 (MBF_RESON7KR): Fixed handling of the various attitude data record types by function mb_extract_nnav(), which in turn allows mbnolist to work correction with format 88 data when keyed to those data record types.

Mblast: Added output option 'n' for survey line number. This value is only defined for SEGY format data files (format 160).

5.7.8beta01 (January 17, 2021)

The autoconf build system had been changed so that libXt and libX11 come before libXm in the link commands. This fixes runtime errors in all of the graphical utilities on Linux systems. This problem probably relates more directly to the use of the gcc compiler system.

5.7.7 (January 17, 2021)

The version 5.7.7 was fatally flawed in that the graphical tools would not run on Linux (or more probably, when built using gcc rather than llvm). The problem was that the autoconf build system had been changed in order to fix build failures in the Homebrew package manager, and these changes inadvertently including changing the library link order so that libXt and libX11

came before libXm. This problem was fixed rapidly and a new major release 5.7.8 put the same day.

5.7.7beta09 (January 17, 2021)

mbdatalist: Fixed memory leak in src/mbio/mb_check_info.c that could occur when parsing *.inf files.

Configure: Fixed handling of X11 libraries and header files in the autotools build system in order to circumvent more changes to dependencies installed on Macs using the Homebrew package manager.

5.7.7beta08 (January 6, 2021)

Formats 88 (MBF_RESON7KR) and 89 (MBF_RESON7K3): Fixed bug in handling of PingMotion data records (7012) that caused memory overruns and seg faults.

Mbclean: Fixed two bugs. The first involved setting the left/right bounds of flagging by across-track distance using the -Y option, and the other resulted in slope flagging being applied when not requested when the -Y option was used alone.

Mbpreprocess: Added option to set directory where output files are written instead of writing the output files parallel to the input swath files.

Format 121 (MBF_GSFGENMB): Modified handling of multibeam snippet backscatter so that samples associated with beams flagged as bad are nulled, and so that modified backscatter is written to the output file by mbprocess.

Mbeditviz: Modified 3D sounding view so that the depth buffering is actually used.

mbm_makedatalist: Now ignores the most recent file when the -L option is used.

5.7.7beta06 (December 30, 2020)

Mbprocess: Fixed raytracking library used by mbprocess so that it is thread safe. The relevant code is in mbsystem/src/mbaux/mb_rt.c

5.7.7beta05 (December 28, 2020)

Format 261 (MBF_KEMKMALL): Fixed bug in handling version 0 MWC datagrams.

Mbphotomosaic: Fixed bug in pixel processing that occasionally produced overflows leading to seg faults.

Mbphotomosaic: Fixed bug in imagelist processing that prevented use of images taken with the right camera of a stereo pair.

Mbimagecorrect: New program that performs some simple brightness and contrast corrections using standard OpenCV algorithms.

Mbprocess: Recast the program to process files in parallel using separate threads. This was implemented in the C++ main code using the C++11 standard thread API. The default is to use a single processing thread and therefore to process the files serially; the new -Cthreads option enables the use of multiple threads. For now, the built-in record keeping of memory allocation/deallocation is disabled for mbprocess because this functionality is not thread-safe.

Mbnavadjust: The navigation adjustment inversion has been improved by tuning the parameters used for the overdetermined least squares solution.

Mbswath2las: Shell for not-yet-working program to export soundings from swath data to some variant of the LAS format used for point cloud data.

5.7.7beta04 (October 28, 2020)

Mbvoxelclean: Added option to filter based on beam amplitude minimum and maximum values.

Mbeditviz: Fixed coloring of soundings using beam amplitude values (colormap was applied incorrectly).

5.7.7beta03 (October 27, 2020)

Mbeditviz: Added option to display the selected sounding point cloud with soundings colored according to associated amplitude value. Also added the sounding amplitude value to the information listed when soundings are selected in the "info" mode.

Mbedit: Added the sounding amplitude value to the information listed when soundings are selected in the "info" mode.

Mbnavadjust: Previously autopicking of crossings skipped crossings including short sections where short was defined as less than 0.25 times the length of the first section of the associated file. This is problematic when the survey platform is stationary at the beginning of a file, resulting in a first section with a short track length (sections are terminated either on track length or total number of soundings). Now short is defined as less than 0.25 times the current desired section length for the project.

Format 58 (MBF_EM710RAW): This format supports third generation Kongsberg multibeam data as recorded in *.all files; the augmented format 59 (MBF_EM710MBA) is used for processing. Data are translated from format 58 to 59 using mbpreprocess. Data have been collected using a partially nonfunctional EM122 such that most of the backscatter snippet records are missing. The existing code treats pings for which the snippet records are missing as incomplete and drops them. The format 58 i/o module has been modified so that if a special flag is set, any snippet records will be ignored and all pings will be treated as having an empty but existing snippet record. Users can set this flag with a special --kluge-ignore-snippets argument to mbpreprocess.

Mbpreprocess and i/o modules with defined preprocessing functions: All existing preprocess functions have been augmented so that a call with a null pointer to the data structure will trigger an option to set i/o flags after reading from a file is initialized but before any data are read. The only case at present where this is used is format 58 (MBF_EM710RAW), where the mbpreprocess option --kluge-ignore-snippets causes the reading code to treat pings with bathymetry as complete whether snippet records exist or not, and to zero the snippet information for those pings.

mbm_makedatalist: Added -L option which will omit the last file found from the output datalist. The intent of this option is to exclude the most recent file in an actively data logging context, since the most recent file is still being logged. This presumes that filenames sort in time order as listed by the ls command, an assumption that does not hold for all file naming conditions or if the -T option has been used to disable time ordering. Also added a behavior particular to Kongsberg multibeam data as originally logged - files named "9999.all" are now ignored.

5.7.7beta02 (October 8, 2020)

Mbotps: Modified mbotps to place temporary files in the user's home directory instead of the current working directory when the latter case results in file paths greater than 80 characters long. This is because OTPS has its filename variables defined as 80 character strings.

5.7.7beta01 (October 7, 2020)

Format 88 (MBF_RESON7KR): Fixed handling of the various attitude data record types by function `mb_extract_nnav()`, which in turn allows `mbnavlist` to work correction with format 88 data when keyed to those data record types.

Mblist: Added output option 'n' for survey line number. This value is only defined for SEG-Y format data files (format 160).

5.7.6 (October 5, 2020)

Version 5.7.6 is now the current release of MB-System. Changes since the 5.7.5 release include:

Many bug fixes to programs and data format i/o modules.

New programs in optional photomosaicing section:

- `mbgrd2obj`
- `mbphotomosaic`
- `mbgetphotocorrection`
- `mbphotogrammetry`
- `mbgrd2octree`
- `mbm_makeimagelist`

New program in optional Terrain Relative Navigation section: `mbtrnpp`

Continuous Integration testing: Continuous integration testing has been implemented using the Travis CI service integrated with Github. The tests are performed by running `make check` and are executed automatically whenever commits are made to the Github repository.

Partial migration to C++: The source code for programs in the `src/utilities` directory has been migrated to C++. Also, much of the C and C++ code has been updated to be consistent with the C11 and C++11 standards.

Deprecated programs: Several programs that are no longer part of the current data processing approach have been declared deprecated and have been moved from `src/utilities` to a new directory `src/deprecated`. These programs are:

- `mb7k2jstar`
- `mb7k2ss`
- `mb7kpreprocess`
- `mbauvnavusbl`

- mbhsdump
- mbhysweeppreprocess
- mbinsreprocess
- mbkongsbergpreprocess
- mbneptune2esf
- mbrollbias
- mbrphsbias
- mbstripnan
- mbswplspreprocess

The deprecated programs have also been converted to C++ and are still built and installed as part of MB-System. We tentatively plan to remove these programs entirely from MB-System distributions at the time of the 6.0 release.

5.7.6preparation (October 4, 2020)

Mbnavlist: Fixed bug in parsing -O option that sometimes resulting in the output of undesired values.

mbm_makeimagelist: New macro that constructs imagelist files of stereo photograph pairs as collected by MBARI's low altitude survey system. This is the first Python3 macro in MB-System.

Format 88 (MBF_RESON7KR): Fixed calculation of speed when using the mb_extract_nav() function for navigation records.

Mbpreprocess: Fixed problems with the --kluge-time-jumps option for fixing jumps in timestamps.

Mbsslayout: Add blanking interval to option --altitude-bottompick-threshold=threshold[/blank] so that when picking the bottom return in the sidescan time series, nearfield backscatter can be ignored out to the time interval in seconds given by the value blank.

5.7.6beta56 (September 28, 2020)

Mbsegylst: Add print option of 'l' for the line number contained in the segy file header.

Format 132 (MBF_EDGJSTAR): Edgetech Jstar format. The i/o module has been modified to handle broken records gracefully by searching byte by byte for the next valid start of record.

Mbnavadjust: Reinstated use of both first and second derivative penalty function in the final stage of inversion for a navigation adjustment model.

Mbnavadjustmerge: Now copies triangle files along with section swath files when copying a project. This means these triangle files will not need to be remade in the new project.

5.7.6beta55 (September 16, 2020)

Mbtrnpp: Fix potential variable overflow and incorrect metrics value assignment in netif code.

5.7.6beta54 (September 14, 2020)

Mbnavadjust: Changed "Zero All Z Offsets" action to apply to only the crossings or ties currently displayed in the list, not literally all set ties.

Mbtrnpp: Fixed TRN content of TRN updates when TRN processing fails due to insufficient or inconsistent data.

Mbtrnpp: Add support for trnu client reset callback (does reset using best offset) and supporting metrics, add file swap event to reinit plot

5.7.6beta53 (September 13, 2020)

Format 261 (MBF_KEMKMALL): Fix to AUV Sentry mode for kmall format - zero heave in processed ping records (XMT) when platform is an AUV.

Mbnavedit: fixed handling of interpolation/extrapolation when timestamps are repeated.

TRN plotting scripts - changed hard coded bash location to /usr/local/bash

5.7.6beta52 (September 9, 2020)

mbtrnpp: Added tide model correction. Added metrics covering non-survey data publishing.

Mbnavadjust: Now ignores pings with zero navigation values on import.

Format 261 (MBF_KEMKMALL): Fixed embedding of changed navigation and sensordepth values by mbprocess - these values needed to be changed in both MRZ and XMT records.

5.7.6beta51 (September 4, 2020)

mbtrnpp: Added time stamp and position to TRN status messages generated for pings with no valid soundings. Bug fix: stats and cycle exec time metrics get incorrect values on some platforms, because of mixed reference to real time and precision clocks; now use consistent references

5.7.6beta50 (September 2, 2020)

mbtrnpp: Now outputs TRN status messages even when the input data do not include valid soundings and so do not get processed by TRN. Also reduced the debug level of the network interface code.

5.7.6beta49 (September 2, 2020)

mbtrnpp: Fixed bugs in parsing commands and also in management shellscript mbtrnpp.sh

5.7.6beta48 (September 1, 2020)

mbtrnpp: Fixed bug that opened a new log file at each reinitialization without closing the old log file, eventually using up all of the available file descriptors and crashing. Added some diagnostic output. Updated related test clients and servers used to demonstrate socket based i/o to and from mbtrnpp.

5.7.6beta47 (September 1, 2020)

mbtrnpp: Modified the socket based TRN output packet and the related internal representation.

5.7.6beta46 (August 31, 2020)

mbtrnpp: Now reinitializes the Terrain Relative Navigation (TRN) filter using the best available position rather than the last estimated navigation offset. If no good convergence has been reached, then the center of the particle filter cloud will be offset from the current navigation by zero. If a good convergence has been found at some point, the most recent good convergence offset value will be used to center the new particle filter cloud. Good convergence is not defined by the convergence criteria within the TRN filter code, but is instead defined by mbtrnpp according to a maximum standard deviation magnitude (by default 5.0 meters) and a minimum number of successive iterations that achieve better than that threshold (by default 200)

Format 261 (MBF_KEMKMALL): Added hook to allow a program (currently on mbtrnpp) to set a flag that enables a correction specific to EM2040 data collected on AUV Sentry. The sensor depth value is recorded in a nonstandard location within the *.kmall data on AUV Sentry. In post processing this is handled with a special kluge option to mbpreprocess. The program mbtrnpp can now force the i/o module to make this same correction when reading raw *.kmall data.

Format 72 (MBF_MBARIMB1): Fixed bug in handling sensordepth values.

5.7.6beta45 (August 26, 2020)

Mbtrnpp: Changed most shell output from stdout to stderr. Altered logic for triggering TRN reinit.

Formats 12 (MBF_SBSIOCEN), 13 (MBF_SBSIOLSI), 14 (MBF_SBURICEN), 15 (MBF_SBURIVAX): Fixed string overrun while writing long comment records.

5.7.6beta44 (August 24, 2020)

Format 89 (MBF_RESON7K3): Fixed handling and processing of backscatter data, which had a variety of problems. Now, the pseudo-sidescan reported by MB-System as sidescan can be recalculated by mbprocess from the desired backscatter source. The default is to use the best source of backscatter available, with the order of "bestness" being:

1. Calibrated snippets
2. Snippets
3. Calibrated sidescan
4. Sidescan

You can force mbpreprocess to use a desired backscatter source with the --multibeam-sidescan-source option, where:

- --multibeam-sidescan-source=C ==> Calibrated snippet records
- --multibeam-sidescan-source=S ==> Snippet records
- --multibeam-sidescan-source=W ==> Calibrated sidescan records
- --multibeam-sidescan-source=B ==> Sidescan records

Format 89 (MBF_RESON7K3): Added support for additional informational data records.

Mbsegylst: Fixed formatting time strings.

Mbnavlist: Fixed formatting time strings.

Mbextractsegy: Fixed embedding the seafloor depth value correctly into output segy trace headers when the data are being extracted from Edgetech Jstar format data (MBIO format 132).

Mbnavadjust: Changed the inversion control parameters such that the second phase of the navigation adjustment solution, a coarse progressive relaxation intended to achieve large scale shifts between surveys, now has a maximum iteration count of 10000 (previously 1000) and a convergence criteria of 0.00001 (previously 0.0001).

Mbgrd2octree: New program to translate a GMT bathymetry grid to an octree representation in the form used by the Stanford/MBARI Terrain Relative Navigation software. The octree files have a suffix convention of *.ob for octree binary. The input bathymetry grids are assumed to be in UTM coordinates with square cells.

Mbtrnpp: Made the --platform-target-sensor option functional. Added options --reinit-qain --reinit-xyoffset=max --reinit-zoffset=min/max

Mbeditviz: Now outputs error message to shell when a file can't be imported because it lacks an *.inf file.

5.7.6beta43 (July 23, 2020)

Mbsvplist: Added capability to extract sound velocity profile (SVP) models from MB_DATA_CTD type records as well as MB_DATA_SOUND_VELOCITY_PROFILE type records (which is the default). This is controlled with the -A option: -AS specifies use of SVP records, and -AC specifies use of CTD records. At present, the only relevant data formats are the old Reson (88) and current Teledyne (89) *.s7k formats.

Mbvelocitytool: Fixed the -B and -E options to specify the allowed begin and end times of swath data used for modeling; previously these options were ignored. Also fixed a memory leak involving the display SVP profiles.

Mbgetphotocorrection: The --show-images option now uses the OpenCV imshow() function to briefly display the images being read and processed.

Mbphotomosaic: The --show-images option now uses the OpenCV imshow() function to briefly display the images being read and processed.

Mbphotogrammetry: The --show-images option now uses the OpenCV imshow() function to briefly display stereo pairs being read and processed, along with the disparity function calculated for the image pair.

5.7.6beta42 (July 21, 2020)

Mbtrn and mbtrnav: Updates and bug fixes to replay-trn_server.

Mbphotomosaic, mbgetphotocorrection, mbphotogrammetry: Added image quality value to the parameters returned by function mb_imagelist_read(), and augmented the definition of an imagelist entry to optionally include a quality column that has values in the range 0.0 to 1.0. Augmented mbphotogrammetry to output an imagelist of all image pairs it processes, and to populate the new quality field with the fraction of all possible bathymetry values that are successfully calculated, a number $0.0 \leq \text{quality} \leq 1.0$. Also augmented mbphotomosaic and mbgetphotocorrection with new options "--image-quality-threshold=value" that set a threshold quality value (by default 0.0) below which images or image pairs are ignored.

Format 89 (MBF_RESON7K3): Fixed calculation and use of azimuthal beam angles in RawDetection and SegmentedRawDetection records. This bug resulted in bathymetry recalculated by raytracing in mbprocess having the acrosstrack and alongtrack distances transposed. To fix the problems caused by this bug mbpreprocess and then mbprocess should be rerun.

5.7.6beta41 (July 12, 2020)

Mblist: Fixed bug in which output in the CDL format was broken, which in turn broke output in netCDF.

Mbphotomosaic: Fixed generation of photomosaics in projected coordinate systems (e.g. UTM).

Mbphotomosaic, mbgetphotocorrection, mbphotogrammetry: Changed source file names from the *.cpp suffix to the *.cc suffix to be consistent with other C++ source files in MB-System.

5.7.6beta40 (July 7, 2020)

Mbphotomosaic, mbgetphotocorrection, mbphotogrammetry: Added three programs used for processing seafloor photography collected during seafloor mapping surveys (i.e. from a survey platform with navigation and attitude data). These programs depend on the OpenCV version 4 package, and so add a large and complex dependency to MB-System. The source files are in the new directory src/photo. These programs are not currently built by default - the configure script must be run with a --enable-opencv option in order to enable building the photo tools. No documentation exists at this point for these tools. A key aspect is that the photography data are referenced through recursive imagelist structures (introduced in 5.7.6beta32)

analogous to the datalists used for sonar and lidar data. The photomosaicing and photo correction tools will work with both single and stereo camera datasets. The photogrammetry tools works only with stereo pair data. These tools also depend on camera calibrations - the tool(s) for that are not yet included in MB-System.

Qt based tool prototypes: Improved the build system handling of Qt5 and OpenGL programs. The test libraries and programs enabled by running configure with the --enable-qt option are now located in four directories: src/qt-mbgui, src/qt-mbgrdviz-1, src/qt-mbgrdviz-2, and src/qt-mbgrdviz-3.

GMT integration: The GMT 6.1.0 release contains a change to the API that broke the build of the GMT module mbswath. It also contained changes to the module initialization code that caused mbswath, mbcontour, and mbgrdtiff to crash. The code has been modified with (more) preprocessor directives determined by the installed GMT version to build with GMT versions 5.2, 5.4, 6.0, 6.1, and the current master that will become 6.2. For GMT versions ≥ 6.0 the MB-System code no longer depends on either the gmt/src/gmt_mb.h header file or the obsolete gmt_begin_module() function.

5.7.6beta38 (June 8, 2020)

Mblist: Fixed problem in which the centermost (nadir) beam was generally set to 0.

Format MBF_KEMKMALL (261): Brought reading and writing of *.kmall files up to revision G of the Kongsberg data format specification. Also fixed problems in the logic relating calculated depths as stored in the format to the depth values reported by the MB-System API functions, and with the beam angles calculated for use in recalculating bathymetry through raytracing. However, problems remain with extracting the installation bias parameters and time latencies that must be applied to the asynchronous ancillary data in order to properly calculate these values. At present, recalculation of bathymetry by raytracing still does not work correctly with this format - in some cases additional attitude biases and time latencies must be applied, and in others the result is simply not right.

Formats MBF_EM710RAW (58) and MBF_EM710MBA (59): Added allowed sonar models

- unexpectedly we are seeing *.all files from some current generation sonar installations, so we have to allow EM304 and EM712 sonar models with the obsolete format.

5.7.6beta37 (May 26, 2020)

Mbnavadjust: Fixed problems in the inversion algorithm. The complexity of this algorithm results from the tendency of overdetermined least squares solutions to work best at providing uniform scale, zero mean solutions. Consequently we construct the solution in three steps. First we solve for the average offsets between continuous surveys, and make this the starting model for the second step. Then we solve for a coarse ("chunk") perturbation model in which each chunk is a dataset consisting of about five sections worth of continuous survey data. This is done through an iterative damped relaxation procedure, and the resulting perturbation model is added to the starting model for the third and final step. The final step is to solve for a perturbation satisfying all of the navigation ties at full resolution. The problem is set up as an overdetermined least squares matrix problem and is solved using LSQR. The regularization is just penalizing the first derivative of the perturbation at present - we are not currently penalizing the second derivative.

Mbnavadjust: Fixed crash on Linux when executing the Auto Set Vertical Offset function (didn't dimension arrays large enough).

Writing GMT grids: Fixed crash reported by Joaquim Luis on Windows when writing GMT grids - the problem was a function call that caused GDAL to allocate a string but then it allowing that pointer to be freed in GMT functions. The solution is to ensure that memory allocated with GMT or GDAL libraries is freed from those same libraries. I also had to alter the configure.ac to add a conditional HAVE_GDAL that mimics one used in the GMT build system so that GDAL related headers are included by gmt_dev.h. The relevant code is only used if GDAL is available. If GMT version is $\geq 6.1.1$ then the function gmt_strdup_noquote() is called to allocate a PROJ4 string stored in the grid header; otherwise strdup() is called. Building on Windows will now require GMT 6.1.1 or later.

Mblevitus: Fixed errors that had been inadvertently created as part of commit #448. Thanks to Joaquim Luis for finding and fixing this.

5.7.6beta36 (May 17, 2020)

Mbgrd2obj: Had to add #ifdef's on GMT version because the number of parameters passed to gmt_init_module() changes between GMT 5.3 through 6.0 and 6.1.

Mbnavadjust: Changed calculation of overlap for a crossing so that the value is not small in the case that a small section (by area) is entirely inside the bounds of a much larger section. This case happens when adjusting

navigation from surveys at at two very different scales (e.g. AUV survey with ship hull mounted survey, or ROV survey with AUV survey).

Mbnavadjustmerge: Added function to merge two adjacent surveys into one with an internal discontinuity.

5.7.6beta34 (May 14, 2020)

Mbgrd2obj: New GMT module that converts GMT topographic grids to OBJ format 3D model files that can be imported to visualization software or printed on 3D printers.

Mbset and mbmakeplatform: Joaquim Luis reports that these programs will not compile on Windows Visual Studio "because of the too many nested if-else problem." I have attempted to fix this problem two ways. In mbset.cc I now use a switch

statement instead of many if {} else if {} statements to find the meanings of all the input options. In mbmakeplatform I now have many separate if {} statements testing the input arguments, but each first also tests a bool that indicates if a prior if {} statement matched the argument. We will find out from Joaquim if either, neither, or both methods work.

Tests: The Travis-CI tests of new checkins to the repository are failing for one of the many builds - the Ubuntu Xenial (16.04) build. The failures are occurring on all programs that call GMT grid io, but the existing logs do not tell me why. I have added print statements to the tests in mbsystem/test/utilities/mbbackangle_test.py and mbsystem/test/utilities/mbgrid_test.py. I don't know how to get that output into the log that Travis-CI makes available.

TRN tools: Kent Headley have added a config file mechanism to mbtrnpp, and fixed a number of other issues in a series of commits. These changes are in src/mbtrn, src/mbtrnav, and src/mbtrnutils.

5.7.6beta33 (May 5, 2020)

Mbnavadjust: Changed handling of fixed surveys when updating the project grid or applying the solution. Previously the files of fixed surveys were ignored, even if they previously had been adjusted before being set to fixed. Now, the unchanged *.na0 file will be output and the navadjust state will be updated so that mbprocess will apply the unchanged navigation.

Mbcopy: A compile failure occurs for src/utilities/mbcopy.cc on Windows as reported by Joaquim Luis. The issue is that under Visual Studio C++ some external symbols referenced in the mbsys_simrad.h header file are not available to the C++ code in mbcopy.cc. This is not true for clang or gcc. The

symbols in question are double arrays holding the beam angles for different operation modes of the Simrad multibeam supported by this i/o module. The solution attempted here is to move the array definitions to `mbsys_simrad.c` and to provide a non-standard function to access pointers to those arrays. By non-standard I mean this does not fit with the normal set of MBIO API functions, and does not exist for i/o modules generally. The function `mbsys_simrad_beamangles()` has been added to `mbsys_simrad.c` and the prototype in `mbsys_simrad.h` is wrapped with `extern "C"` so it can be called from `mbcopy.cc`.

Mbcopy: The current processing model for old Simrad multibeam data in format 51 is to first use `mbcopy` to translate it the extended second generation Kongsberg format 57, and then process it as one would more modern data. It was discovered that this translation was failing to properly copy navigation records. This was fixed.

Format MBF_EMOLDRAW (51): Because the compile error referenced above involved 1990's era Simrad multibeam data in format 51, it was necessary to test processing of such data. This revealed that recent changes to program logic from using MB_YES/MB_NO/MB_MAYBE values to bool variables (true/false) had broken the basic data record reading logic for the MBF_EMOLDRAW i/o module. This has been fixed.

Build system for Qt5 based tools: Improved the build system handling of Qt5 programs. The test program enabled by running `configure` with the `--enable-qt` option has been renamed `mbgrdvizqt`, but still resides in `src/qttest`. The approach now is to do the following: (1) The `configure` script creates the Qt project file `src/qttest/mbgrdvizqt.pro` and then modifies the values of variables specifying the required MB-System and GMT libraries and headers. (2) The `configure` script runs `qmake` in `src/qttest` to generate a Makefile named `src/qttest/Makefile.qmake` (3) The `configure` script generates a Makefile in `src/qttest` that in turn will run `make` itself using `Makefile.qmake` for targets `all`, `install`, `uninstall`, and `clean`. This approach now works on a Mac. It's time to test on Linux.

5.7.6beta32 (April 22, 2020)

Mbgrid: Fixed failure of the two gridding algorithm using beam footprints in which the footprint size blows up at low grazing angles. The fix is to not use soundings for which the grazing angle is less than five degrees.

Mbgrid and mbmosaic: Replaced `int` values with `bool` values where appropriate.

Build system: Added option to enable building tools based on Qt5 to the autotools build system. If the configure script is given the `--enable-qt` option, it checks if Qt5 has been installed, and if so, determines the compiler and linker flags required to build tools using Qt5. At present, the only Qt5 based code is in the directory `src/qttest`, and this code does not successfully compile and run. Therefore it is not recommended to run configure with the `--enable-qt` option. However, the build system is now ready to support Qt5 based tools as they are developed.

Mbgrdtiff: Paul Wessel contributed a new version of mbgrdtiff that constructs the image by a direct call to the `grdimage` module. This version will only build and work with GMT 6.1 and later. The original code included code building the image, duplicating functionality in `grdimage`. The new version is now `mbsystem/src/gmt/mbgrdtiff.c` and the original version `mbsystem/src/gmt/mbgrdtifforg.c`. The build system has been augmented to check the GMT version and build mbgrdtiff from the original when that is <6.1 and the new file when that is ≥ 6.1 .

General (`mb_define.h`, `mb_format.c`, `mb_format.h`): Added definition of `format=-2` as recursive imagelists. Analogous to datalists, this construct supports timestamped lists of single or stereo photographs. Like datalists, the imagelists can be recursive. This is a precursor to bringing into MB-System tools for processing seafloor photography collected during surveys, particularly for photomosaicing.

Mbsslayout and future photomosaicing: The parameters use to define convergence when intersecting a vector with a topography model in `mb_intersectgrid.c` have been improved, yielding more accurate intersection locations for backscatter samples or source image pixels when laying out sidescan or photography data.

Mbnavedit: Changed minimum range of draft (`sensordepth`) plot to be ± 0.05 meters.

Mbeditviz: Fixed problem with preserving changes to edits that are recorded in `*.esf` files.

Mbtrnpp: merged recent changes by Kent Headley to the source files in `src/mbtrn`, `src/mbtrnav`, and `src/mbtrnutils`.

Mbset: changed output to clearly indicate when parameter files are created (or not) or modified (or not). This involved adding a function `mb_pr_compare()` to `mb_process.c` that can be used in `mbset.c` to check whether the modified process parameter structure actually differs from the original structure.

Formats MBF_OICGEODA (141) and MBF_OICMBARI (142): Fixed support for old OIC format DSL120 interferometric sonar data. Processing of these data now works with mbpreprocess and mbprocess again. The sidescan data were compromised by treating unsigned amplitude values as signed, and treating null samples as valid.

Testing: Reinstated OSX test build as part of the Travis CI runs triggered by commits to the Github repository.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices and adding build tests. The improvements included in this beta release include work on mbview and programs using mbview, the auxilliary library in src/mbaux, particularly including mb_cheb.c, mb_intersectgrid.c, and mb_zgrid.c, and on mbedit.

Code style: Tom O'Reilly and David Caress added README.md files in each of the subdirectories under src/.

5.7.6beta31 (March 2, 2020)

Mbvoxelclean: Fixed memory leak. Added --acrosstrack-minimum and --acrosstrack-maximum filters. Cleaned up shell informational output.

Mbeditviz: The program now keeps only a limited number of esf (edit save file) files open for writing rather than opening esf files for all loaded swath files. The program was failing when the total number of open files exceeded the operating system maximum (1024 on MacOS and CentOS). The default maximum number of open esf files is now 25.

Mbeditviz: Colorized flagged soundings the same as for mbedit (filtered == blue, manually edited == red).

Format 233 (MBF_WISSLR): Corrected use of ev_offset and az_offset (across and alongtrack distance offsets at the optical head) in preprocessing. Also added a capability to apply Snell's law type tweak to the lidar pulse angles through mbpreprocess (--kluge-beam-tweak=value).

Code style: Kurt Schwehr is systematically altering the code to conform to best practices and adding build tests. The improvements included in this beta release include work on mbview and programs using mbview.

Code style: Github user abnj contributed some code cleanup by removing \$Id tags used when the code was in a Subversion repository.

5.7.6beta30 (February 20, 2020)

Mbprocess, mbfilter, mbvoxelclean, mbclean, mbinfo, mbdatalist: Fixed bugs in handling of status values returned by functions that caused early program termination.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices and adding build tests. The improvements included in this beta release include work on mbview and programs using mbview.

5.7.6beta29 (February 17, 2020)

Mbnavadjust: Fixed bugs in mbnavadjust creating by modifying the handling of function status returns.

Mbcopy: Fixed bug in parsing the end time values specified with the -E option.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices and adding build tests. The improvements included in this beta release include work on mbview and programs using mbview: mbgrdviz, mbeditviz, mbnavadjust.

5.7.6beta28 (February 13, 2020)

Format 89 (MBF_RESON7K3): Added support for data record type 7058. Also added ability to handle s7k data files missing the file header record.

Format 233 (MBF_WISSLR): Embedded fix for timing glitch in early WISSLR data.

Mbotps: Discovered that the path length for the temporary files written by mbotps must be less than 100 characters or the OTPS program predict_tide will fail. Altered the filenames used for these temporary files to be as short as possible.

mbvoxelclean: Fixed datalist reading logic.

mbprocess: Fixed bug introduced in 5.7.6beta27 that caused mbprocess to exit in the middle of processing files referenced by a datalist.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices and adding build tests. The improvements included in this beta release include work on mbedit, mbnavedit, and mbnavadjust.

5.7.6beta27 (February 3, 2020)

mbpreprocess: Corrected prior fix to error in calculating lever arms, which didn't include all of the sign changes needed in mb_platform.c.

mbgrid: Fixed flaw in min or max weighted mean algorithm that produced array overflows in mbgrid.

5.7.6beta26 (February 2, 2020)

Format 181 (MBF_SAMESURF): Fixed compiler warnings, including warnings from a mismatch of 32 bit and 64 bit integer pointers due to the early 1990's vintage of this contributed library.

mbpreprocess: Fixed error in calculating lever arms that resulted in incorrect static offsets to bathymetry calculated at the preprocess stage using platform models. Fixes are in src/mbio/mb_platform.c.

mbopts: The tidal correction program has been recast to use the current global atlas tidal model from the Oregon State University Tide Group. This model is called tpxo9_atlas - the model files must be obtained from OSU now as they are no longer available for anonymous download. When the MB-System documentation is updated to include the steps required to obtain and install the tidal model, we will output a formal 5.7.6.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices and adding build tests. The improvements included in this beta release include cleaning up the SURF format library, work on mbedit, mbnadjust, and the GMT modules mbswath, mbcontour, and mbgrdtiff.

5.7.6beta25 (January 20, 2020)

Info files: The top level information files README, ChangeLog, and GPL have been removed. The Markdown format versions (README.md, ChangeLog.md, GPL.md) remain and have been updated.

Mbeditviz: Fixed a bug recently introduced (inadvertently) that caused a crash when bringing up the sounding 3D cloud.

mbm_grd2arc: Fixed failure with GMT 6. Basically, there is a GMT module grdconvert that accomplishes exactly the same task, so this macro is unnecessary. It has been recast to simply call gmt grdconvert. It will be listed as deprecated, but left in the distribution to maintain the viability of old processing scripts.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices and adding build tests. The tests are performed by running make check and are executed automatically by the Travis CI service integrated with Github whenever commits are made to the Github repository. The current changes mostly consist of cleaning up the code of the graphical utilities such as mbedit, mbnavedit, mbnadjust.

5.7.6beta24 (January 16, 2020)

Build system: The configure.ac file now uses the `AX_CXX_COMPILE_STDCXX(11)` macro to require that the code conform to the C++11 standard. Some preprocessor directives have been added to `src/utilities/mbprocess.cc` to handle the case of building with gcc 4.8.1 through 4.8.5, which has errors in implementing structure constructors consistent with this standard. Also, instances of `isnan()` calls throughout the codebase have been changed to `std::isnan()`, and in these cases the `"#include <math.h>"` has been replaced by `"#include <cmath>"`. The order of libraries in `src/mbtrn/Makefile.am` has been changed so that `libmframe.la` is installed before `libr7kr.la` (which depends on `libmframe.la`). With respect to `libproj`, `configure.ac` now checks for Proj 4 vs Proj 6 using `proj_normalize_for_visualization()` for the Proj 6 API and `pj_init_plus()` for the Proj 4 api. Since `proj_normalize_for_visualization()` did not get added to the Proj 6 API until release 6.1.0, this means that the deprecated Proj 4 api will continue to be used when building with Proj releases 5.0 through 6.0. In practice, the build system sets preprocessor values that determine at compile time which Proj API is used by the functions in `src/mbio/mb_proj.c`.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices and adding build tests. The tests are performed by running make check and are executed automatically by the Travis CI service integrated with Github whenever commits are made to the Github repository.

5.7.6beta23 (January 11, 2020)

`MBprocess`, `mbpreprocess`, `mb_make_info()`: Altered `mbprocess` and `mbpreprocess` so that both run about half as slow (twice as fast) as before. This optimization is accomplished by having `mbprocess` and `mbpreprocess` generate `fbt` and `fnt` files directly rather than by `system()` calls to `mbcopy` and `mblist`, and by having the `system()` call to `mbinfo` include the overall area bounds so that `mbinfo` only reads the output file once while generating info files (instead of reading the data twice).

MBnavadjust: Added GUI elements related to defining a reference bathymetry model. In the future, it will be possible to tie swath files to a reference bathymetry imported from a grid file.

MBackangle: Fixed error in datalist read logic that was preventing it reading more than the first file (problem created by changing the handling of status and error values from MBIO calls).

MBextractseg: Fixed error in the milliseconds of traceheader timestamps.

MBlist: Improved calculation and handling of swath bounds values.

MBinfo: Augmented the -M data mask option to allow pre-definition of the file's area bounds. Previously, the data mask has been requested using -Mmask_nx/mask_ny where mask_nx/mask_ny are the dimensions of the mask. In this case, the file is read twice - first to get the area bounds of all data while getting the other data statistics output by mbinfo, and second to populate the data mask defined by the area bounds and the dimensions mask_nx and mask_ny. Now, if the option is given by -Mmask_nx/mask_ny/lonmin/lonmax/latmin/latmax, then the last four values define the area bounds and the data need only be read once. Mbprocess now calls mbinfo in this way, allowing a speedup of the mbprocess execution.

MBgrid: Added data min max values to the per file shell output when verbose > 0

MBsvpselect: This program depends on geodesic calculations that are now part of the Proj software package (from version 6 onwards). Previously the src/utilities directory had included the files geodetic.h and geodetic.c to provide this capability; those are now not included. Consequently, if MB-System is built with Proj versions 4 or 5, then mbsvpselect will not be built.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices and adding build tests. The tests are performed by running make check and are executed automatically by the Travis CI service integrated with Github whenever commits are made to the Github repository.

src/utilities: All programs in src/utilities have been migrated to C++.

Deprecated programs: Several programs that are no longer part of the current data processing approach have been declared deprecated and have been moved from src/utilities to a new directory src/deprecated. These programs are:

- mb7k2jstar
- mb7k2ss

- mb7kpreprocess
- mbauvnavusbl
- mbhsdump
- mbhysweeppreprocess
- mbinsreprocess
- mbkongsbergpreprocess
- mbneptune2esf
- mbrollbias
- mbrphsbias
- mbstripnan
- mbswplspreprocess

The deprecated programs have also been converted to C++ and are still built and installed as part of MB-System. We tentatively plan to remove these programs entirely from MB-System distributions at the time of the 6.0 release.

5.7.6beta21 (December 12, 2019)

GMT modules (mbcontour, mbswath, mbgrdtiff): modified the `#ifdefs` to allow building with GMT 6.1 and later.

MBnavadjustmerge: augmented `--set-tie` option to allow changing the z-offset value of an existing tie.

MBprocess: Change behavior when reading grid files for backscatter correction fails - the functions in `mb_readwritegrd.c` used to wait 1 millisecond before trying to read again; now the code waits for 25 milliseconds.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices

5.7.6beta20 (November 26, 2019)

Mbprocess: Fix to handle temporary failures to read GMT `grd` files. The GMT grid reading code will now return with an error rather than causing the program to exit. This allows the code to keep trying to read the grid file until it succeeds.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices. Current changes include replacing `MB_YES/`

MB_NO with boolean true and false, and changing the type of the associated variables from int to bool.

mbtrnpp: Changes by Kent Headley to mbtrnpp in src/mbtrnutils and supporting source directories src/mbtrn and src/mbtrnav.

5.7.6beta19 (November 22, 2019)

Mbprocess: Attempting to fix processing of format 71 files within an mbnavadjust project.

5.7.6beta18 (November 21, 2019)

Everything: Now fully compatible with PROJ 6.X. The configure script will detect the presence or absence of PROJ 6 or later - if the PROJ installation predates PROJ 6 then the old header files and API are used. PROJ 6 and later include a comprehensive database of coordinate reference systems (e.g. projected coordinate systems and/or datums), making the projected coordinate system list kept in the file src/share/Projections.dat unnecessary. For now this file will continue to be part of the MB-System distribution to support installation with obsolete versions of PROJ.

mbtrnpp: Removed some unnecessary test data and code from the src/mbtrnav/gctp/ directory.

mbtrnpp: Fixed a number for formatting and type issues hampering building the TRN code on MacOS.

5.7.6beta17 (November 15, 2019)

MBeditviz: Added option to display 3D soundings colored according to the map's coloring (including selected colortabel and any histogram equalization).

MBeditviz: Added GUI elements to support multiple modes of gridding.

mbm_route2mission: Modified to output waypoint_bottom behaviors with the current suite of options specified.

Format 72 (MBF_MBARIMB1): Fixed handling of heading (degrees not radians).

Code style: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices. Current changes include replacing MB_YES/

MB_NO with boolean true and false, and changing the type of the associated variables from int to bool.

mbtrnpp: Many changes by Kent Headley to this in src/mbtrnutils and supporting source directories src/mbtrn and src/mbtrnav.

5.7.6beta16 (October 29, 2019)

MBnavadjust: Fixed bug in calculating the range of contour values and the size of the memory allocation for contours.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices. Current changes include replacing MB_YES/MB_NO with boolean true and false, and changing the type of the associated variables from int to bool.

5.7.6beta15 (October 21, 2019)

Format 261 (MBF_KEMKMALL): Fixed preprocessing of Kongsberg multibeam data in the kmall format, particularly with regard to merging WHOI-NDSF processed navigation for surveys by AUV Sentry and ROV Jason.

Format 72 (MBF_MBARIMB1): Added support for a format used to store filtered and decimated multibeam bathymetry as generated by mbtrnpp for use by the terrain relative navigation module.

Mbpreprocess: Added an option named --kluge-auv-sentry-sensordepth that causes mbpreprocess to replace the sensor depth value with the antenna height recorded in the position record. This allows processing of AUV Sentry Kongsberg EM2020 using the embedded navigation, attitude, and sensor depth. At this time the Kongsberg EM2040 is not accepting the input depth datagrams, and so the sensor depth field is populated with incorrect values. Once a post-processed navigation, attitude, and sensor depth model is available for merging, this kluge option is no longer needed.

Terrain Aided Navigation (TRN) tools: Working towards supporting realtime UDP based reading of Kongsberg kmall format data into program mbtrnpp. Removed test data from the gctp projection package embedded within the TRN server source tree.

mbtrnpp: Augmented this tool to acquire realtime Kongsberg multibeam data over a UDP port. Note that configure must be invoked with the --enable-mbtrn and --enable-mbtrnav options for the terrain relative navigation tools to

be built. We do encourage general users to avoid building with these options
- the TRN tools are experimental, changing rapidly, and for now specific to MBARI AUVs.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices. Current changes include replacing MB_YES/MB_NO with boolean true and false, and changing the type of the associated variables from int to bool.

5.7.6beta14 (October 8, 2019)

MBnavadjustmerge: Added options --unset-short-section-ties=min_length and --skip-short-section-crossings=min_length that allow the deletion or prevention of ties made using short sections of data. This increases the reliability of the autopicking of ties. The track length threshold is specified with the command.

MBnavadjust: Restrict autopicking of ties incorporating short sections of data. The track length threshold is 1/4 of the target segment track length specified in the options dialog.

Format 88 (MBF_RESON7KR) and Format 89 (MBF_RESON7K3):
Corrected handling of reverse-mounted receive and/or transmit arrays.

MBpreprocess: Fixed handling of --filter-apply-nav option.

MBclean: Added flagging/unflagging by beam angle as part of the -Y option
-Yangle_left/angle_right/3 to flag outside angle_left to angle_right
-Yangle_left/angle_right/4 to unflag outside angle_left to angle_right

Terrain Aided Navigation (TRN) tools: The TRN related code has been refactored and reorganized by Kent Headley. There are now three related directories under src: src/mbtrn src/mbtrnav src/mbtrnutils. The former program mbtrnpreprocess is now mbtrnpp. The source for mbtrnpp is now in src/mbtrnutils rather than src/utilities.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices.

5.7.6beta12 (September 20, 2019)

Mbset: Fix to mbset so that the mbp_navadj_mode is set to MBP_NAVADJ_OFF instead of MBP_NAV_OFF and MBP_NAVADJ_LLZ instead of MBP_NAV_ON.

Mbminirovnav: Fix so that variations in the NAV* and CTD* files are handled properly.

Mbnavadjustmerge: Fixed handling of --unset-skipped-crossings-by-block=survey1/survey2 commands.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices.

5.7.6beta10 (September 18, 2019)

Mbnavadjust: Changed the contouring displayed during analysis of crossings to be based on a triangular mesh representation of the bathymetry data for each section. The Delauney set of triangles used for each section is saved to a file in the project directory. These can be made the first time each section is displayed by mbnavadjust, or they can be made offline using the program mbnavadjustmerge.

Mbnavadjustmerge: Added options to pre-generate the triangular mesh files for each section in an mbnavadjust project (--triangulate, --triangulate-all, --triangulate-section=file:section, and --triangulate-scale=scale).

Mbtrn library: Updated to current code written by Kent Headley.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices.

5.7.6beta8 (September 9, 2019)

MBIO library beam flagging and detect types: The handling of multi-pick soundings has been modified. This refers to sensors that can report more than one sounding per beam, including both multibeam sonars and lidars. At present the relevant data format are MBF_RESON7K3 (89), MBF_3DWISSLR (232), and MBF_3DWISSLP (233). There are two major changes. First, the detects array returned by mb_detects() now packs two parameters into the 32-bit values: the detect type uses bits 0-7 and the detect priority uses bits 8-11. The priority value will be 0 except when a sensor is reporting multiple sounding per beam (sonar) or pulse (lidar); in

that case the primary (best) sounding will have a priority of 0, and other secondary soundings (less than best) will have priorities > 0. If the sensor ranks the soundings then the priorities will reflect the ranking order with lower = better. Second, all secondary soundings will initially be assigned beamflags with a new value indicating that status (MB_FLAG_FLAG + MB_FLAG_SECONDARY). At this time, the bathymetry editing programs mbedit, mbeditviz, and mbclean will treat secondary soundings as not-to-be-used, which means those soundings will not be displayed or available for unflagging. Eventually these editors will be enabled to optionally display and unflag secondary soundings.

Mblist: The output of beam flag values now includes secondary soundings. The possible output characters representing the beam flags are now: '-'=null, 'G'=good, 'M'=manual, 'F'=filter, 'S'=sonar, 'N'=secondary (multi-pick), and 'I'=interpolated.

Mbminirovnav: Rewritten to handle the actual variability of MBARI MiniROV raw navigation, attitude, depth, and DVL data logs.

Formats MBF_3DWISSLR (232) and MBF_3DWISSLP (233): Augmented to handle a new version of the 3D at Depth RAA swath file format generated by the WISSL (wide swath subsea lidar).

Mbnavadjust: The navigation adjustment optimization algorithm has been modified. The problem is to find a perturbation (adjustment) to the original navigation that matches features in overlapping and crossing swath bathymetry data. The first stage of the inversion is to solve for the average position offsets between different surveys, and then remove that signal out of the navigation offset observations. The second stage of the inversion involves an iterative relaxation towards a coarse navigation adjustment model. The third stage is to obtain a full resolution perturbation model by solving a large, sparse, overdetermined least squares problem that satisfies the remaining navigation offset signal. The algorithm change is that the coarse stage 2 solution is linearly interpolated over the gaps between directly constrained navigation points before proceeding to the third stage. This reduces the tendency of the overall solution to trend towards zero adjustment along unconstrained sections of survey lines.

Mbtrn library: Updated to current code written by Kent Headley.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices.

5.7.6beta6 (August 26, 2019)

mbm_route2mission: AUV spiral descent option now includes a behavior to disable DVL aiding of the INS during the descent.

Formats MBF_3DWISSLR (232) and MBF_3DWISSLP (233): these i/o modules have been updated to handle both a new version (1.3) of the 3D at Depth Wide Swath Lidar (WiSSL) *.raa format data.

Mbtrn library: Updated to current code written by Kent Headley.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices.

5.7.6beta5 (August 6, 2019)

Integration with PROJ: Reverted to use of deprecated PROJ4 API due to problems with use of projections by the mbview library. This will get fixed, but it's more complicated than first thought.

Mbtrn library: Updated to current code written by Kent Headley.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices.

5.7.6beta4 (August 2, 2019)

Format MBF_GSFGENMB (format 121, Generic Sensor Format, GSF): The version of libgsf used to read and write Generic Sensor Format (GSF) files has been updated to version 3.0.9. The libgsf library code is released by Leidos under a LGPL2.1 license, and is included directly into the MB-System source code with minor changes. For 3.0.9 the only changes required are to avoid redefinition of several key system functions (e.g. fseek); these redefinitions are avoided using a preprocessor command that is only activated in the MB-System build system. The command mbformat -F121 now outputs the version of the GSF library embedded in MB-System as a part of the format description.

Integration with PROJ: The API for the PROJ coordinate transformation library libproj has changed with the release of version 6. The build system now tests which version of PROJ is installed and builds MB-System using the available API.g

Mbgrid: Mbgrid had an undocumented ability to set the interpolation tension using a third argument to the -C option. This has been removed. The tension value is set with the -T option, consistent with the documentation.

Mbgrid and mbmosaic: The functions used by mbgrid and mbmosaic to integrate with GMT's i/o capabilities to write the output grids have been augmented to embed the geographic coordinates in the fashion supported by GDAL and many software packages that utilize it.

Mbcontour, mbswath, mbgrdtiff: The preprocessor commands in the source files for the GMT modules in MB-System have been updated to handle the existence of versions 5.0 through 6.0+.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices.

5.7.6beta2 (July 25, 2019)

Formats MBF_3DWISSLR (232) and MBF_3DWISSLP (233): these i/o modules have been updated to handle both the original (v1.1) and updated (v1.2) 3D at Depth Wide Swath Lidar (WiSSL) *.raa format data.

Code style: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices.

5.7.6beta1 (July 6, 2019)

MBnavadjust: Fixed bug that resulted in Naverr window contours not being displayed when the difference between the minimum and maximum depth of a section is less than one meter.

Formats MBF_3DWISSLR (232) and MBF_3DWISSLP (233): working towards the code successfully reading and writing the 3D at Depth WiSSL *.raa format version 1.2.

5.7.5 (June 26, 2019)

Version: Set for release 5.7.5

Code style: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices.

mb_platform.c: Fixed problem introduced in code style changes

mbpreprocess: Fixed problem introduced in code style changes

mbfilter: update man page

5.7.5beta12 (June 24, 2019)

Code stye: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices.

5.7.5beta11 (June 16, 2019)

Format 89 (MBF_RESON7K3): Fixed bug in support of the Teledyne 7k version 3 format that caused mbpreprocess to crash.

Mbnavadjustmerge: Fixed bug due to failure to initialize new project structures.

Code stye: Kurt Schwehr is systematically altering the code to conform to best practices regarding header inclusion and reduced variable scope, particularly for loop indices.

5.7.5beta10 (June 9, 2019)

Build system: Set Autotools build system to force use of standard C (i.e. C99).

5.7.5beta9 (June 8, 2019)

Format 89 (MBF_RESON7K3): The Teledyne 7k version 3 format is now supported as format 89. This format is used for all multibeam sonars built by Teledyne, including Reson, Blueview, and Hydrosweep. By default, MB-System now treats files with the *.s7k suffix as format 89 rather than 88. However, old Reson data, specifically Reson data that does not store the bathymetry soundings in 7028 RawDetection records, should still be processed using format 88.

Format 261 (MBF_KEMKMALL): Support for Kongsberg multibeam data in the kmall format is functional excepting for the recalculation of bathymetry by raytracing.

Mbprocess: Fixed problem with backscatter correction of sidescan and amplitude data

General: Incorporates a large number of changes by Kurt Schwehr that nudge this codebase towards some level of compliance with software development best practices.

Unit testing: Incorporates code contributed by Kurt Schwehr in the directories mbsystem/test, mbsystem/third-party, and mbsystem/travis that will achieve automated build testing and unit testing.

Build system: Added enable-test option to configure.ac so that the default configure command does not try to compile the unit test code contributed by Kurt.

Mbvelocitytool: Fixed memory leak.

5.7.5beta8 (April 11, 2019)

Format 89 (MBF_RESON7K3): Progress towards support of Teledyne 7k version 3 format. The i/o module builds but is not fully functional yet. Most records parse correctly but the bathymetry calculation is incomplete.

Format 261 (MBF_KEMKMALL): We are close to complete with support for the new Kongsberg kmall format. Testing and debugging continues.

5.7.5beta7 (March 28, 2019)

Windows compatibility: A number of changes from Joaquim Luis that allow building under Windows.

Reson 7k version 3 support: Mods to mbsys_reson7k3.c and mbsys_reson7k3.h from Christian Ferreira working towards new i/o module supporting version of the 7k format from Teledyne now used for Teledyne Reson and Teledyne Atlas multibeam.

5.7.5beta6 (March 26, 2019)

Build system: Modified configure.ac to fix a problem building with the new Proj 6.0.0. MB-System uses a longstanding Proj API that is deprecated in Proj 6. The relevant header file is proj_api.h, which can only be used if compiled with the preprocessor macro ACCEPT_USE_OF_DEPRECATED_PROJ_API_H set. This compiler flag has been added to the autoconf test for usability of this header file.

5.7.5beta5 (March 22, 2019)

mbm_grdplot, mbm_grd3dplot, mbm_grdtiff, mbm_histplot, mbm_plot, mbm_xyplot: Set these plot macros to use "open" on Macs and on Linux to

use "gio open" if available, "xdg-open" if "gio" is not available. Also got rid of another instance of orphan file creation by the plotting shellscrips (e.g. `gmt.conf$$`).

5.7.5beta4 (March 21, 2019)

`mbm_grid`: Fixed problem in which execution of `mbm_grid` left behind an orphaned datalist file. Also changed this macro to output a bash shellscrip rather than a csh shellscrip.

`mbm_bpr`: Added support for various variants of Sonardyne AMT pressure data.

`mbm_grdtiff`: Changed this macro to output a bash shellscrip rather than a csh shellscrip.

`mbm_route2mission`: Fixed handling of the user specified time to first waypoint in the output MBARI AUV mission scrip.

`Mbextractseg`: Recast output section plot generation scrip to call `mbm_grdplot` using the arguments `-MIE300 -MITg` that cause that macro to render the output postscript files into 300 dpi png image files.

`mbm_grdplot`, `mbm_grd3dplot`, `mbm_grdtiff`, `mbm_histplot`, `mbm_plot`, `mbm_xyplot`: These plot macros now embed the user, computer, and time of creation associated with the output plot generation shellscrip.

5.7.5beta3 (March 14, 2019)

`Mbcopy`: Fixed problem with fbt file generation by `mbcopy` that was introduced with 5.7.5beta2

5.7.5beta2 (March 4, 2019)

Format 261 (MBF_KEMKMALL): There is progress towards support for the new Kongsberg kmall format. Only EM2040 data supplied by Kongsberg is being used for testing with `mbinfo`, `mbcopy`, and `mbprocess`, so far. The memory management faults are fixed, but it isn't all working yet.

`Mbcopy`: Changed logic so that in a full copy all data records are passed on to the output even if they generate nonfatal errors (e.g. out of time or location bounds).

5.7.5beta1 (February 27, 2019)

mbm_bpr: Augmented to work with Sonardyne AMT pressure data using PRS data records in addition to PR2 records.

Mbotps: Fixed some issues with applying a tide station correction to time models.

5.7.5beta0 (February 25, 2019)

Format 261 (MBF_KEMKMALL): Added support for new Kongsberg kmall format with MBIO id 261 and name MBF_KEMKMALL. At this point the support has memory management problems resulting in sporadic and inconsistent crashing.

5.7.4 (February 12, 2019)

Plotting macros (mbm_grdplot, mbm_grd3dplot, mbm_plot, mbm_xyplot, mbm_histplot): Fixed problem with plotting macro mbm_plot that caused failure of the plotting shellscript.

5.7.3 (February 8, 2019)

Plotting macros (mbm_grdplot, mbm_grd3dplot, mbm_plot, mbm_xyplot, mbm_histplot): This version changes how automatically displaying the Postscript plot is handled. Previously these plotting macros written in perl hard coded the user defined Postscript viewer program into the plot generation csh shellscripts they generate, where the Postscript viewer was defined by mbdefaults or by an environment variable. Now the plot macros write plot generation shellscripts using bash rather than csh, and code is embedded that executes a Postscript viewer defined at run time. This Postscript viewer can still be defined by the user's mbdefaults or environment variables, but otherwise will be the default application for viewing Postscript files on that computer, determined by the programs xdg-open (Linux, OpenBSD), open (Mac), or cygstart (Cygwin). Thus, the Postscript viewer program is determined at runtime by the plot generation shellscript rather than at the time the shellscript is generated.

Formats 58 (MBF_EM710RAW) and 59 (MBF_EM710MBA): Fixed bug reported by Steve Roberts in which some beams that have NaN values for depth in the original *.all files are treated as null during the first read, but are reset to valid but NaN during preprocessing. This fix works with data already processed through prior versions of MB-System as well as data newly processed from *.all files.

5.7.2 (February 4, 2019)

All files: Updated copyright to 2019.

Mbdumpesf: Fixed the application of the ignore options, applying fixes provided by Povl Abrahamsen of the British Antarctic Survey in October 2017 (!)

Mbclean: Fixed problem with heading-change-rate based flagging.

mbm_grdplot: supported generating plots of images (ie. Geotiffs) in addition to grids. Added two plot modes: -G6 will plot the image using the embedded georeferencing, and -G7 will plot the image using the bounds specified with the -R option as the bounds of the image.

Format 56/57 (MBF_EM300RAW MBF_EM300MBA): Fixed crashing with some EM122 data by disabling attempted parsing of "extraparameters" datagrams, which appear to not conform to the format specification.

Mbdefaults, mbm_* plotting macros: Changed the definition of the programs used to view Postscript plots generated through the mbm_* plotting macros and for images (e.g. geotiffs generated using mbgrdtiff). Previously, the programs used by MB-System to view postscript files and images were explicitly defined using mbdefaults. Defining the viewing programs is still possible with mbdefaults, but the default is now to use the operating system's command line program that automatically opens a specified file using the user's default application for that kind of file. On Linux systems, this program is "xdg-open". On MacOS, this program is "open". On Cygwin systems, this program is "cygstart".

5.7.1 (December 19, 2018)

Initiated use of version tagging in Git.

MB-System Version 5.6 Releases and Release Notes:

- Version 5.6.20181218 December 18, 2018
- **Version 5.6.20181217 December 17, 2018**
- Version 5.6.20181214 December 14, 2018
- Version 5.6.20181129 November 29, 2018
- Version 5.6.20181016 October 16, 2018
- Version 5.6.002 September 14, 2018
- Version 5.6.002 September 11, 2018

5.6.20181218 (December 18, 2018)

Generated release package using github

mbm_vrefcheck: Removed, never completed, never worked.

mbm_dslnavfix: Removed, obsolete.

5.6.20181217 (December 17, 2018)

Memory management: Fixed memory leak associated with allocation and deallocation of edit save file (*.esf) data.

5.6.20181214 (December 14, 2018)

Format 121 (MBF_GSFGENMB): Changed GSFLib version to 3.08. MB-System also now builds and installs the program dump_gsf. Fixed several array overruns in the GSFLib source code distributed by Leidos.

MBgrid: Added two new gridding algorithms, minimum weighted mean and maximum weighted mean. These are both implementations of Gaussian weighted mean in which only valid soundings that are close to the minimum (or maximum) value in each grid cell are used. A threshold value in meters defines what close means; only soundings no further from the minimum (or maximum) than the threshold are used. These algorithms are useful when bathymetry data include areas that are not truly representable with a 2D grid because of vertical walls or multiple values (e.g. overhangs). These algorithms allow one to choose to follow the shallowest or deepest surfaces in the gridded model. These algorithms were specifically added to handle subsea lidar data that maps animals as well as the seafloor.

5.6.20181129 (November 29, 2018)

MBgrdtiff, mbm_grdtiff: Added -Nnudge_x/nudge_y option to apply a positional offset in meters relative to the input grid or mosaic.

MBgrdviz, mbeditviz: Changed mechanism by which files selected from navigation in mbgrdviz are opened into mbeditviz. Previously the selection of too many files in mbgrdviz would cause a crash when the pulldown menu item to open those into mbeditviz was selected (too many == something like >10). Now an arbitrarily large number of files can be selected because a temporary datalist is written by mbgrdviz and then opened into mbeditviz.

MBpreprocess: Added options --head1-offsets=x/y/z/heading/roll/pitch and heading2-offsets=x/y/z/heading/roll/pitch which allow one to set the positional and angular offsets between the separate heads on a dual head

MB-System Version 5.5 Releases and Release Notes:

- Version 5.5.2350 September 6, 2018
- Version 5.5.2348 August 20, 2018
- Version 5.5.2347 August 17, 2018
- Version 5.5.2346 August 13, 2018
- Version 5.5.2345 August 10, 2018
- Version 5.5.2344 August 3, 2018
- Version 5.5.2343 July 10, 2018
- **Version 5.5.2342 June 29, 2018**
- Version 5.5.2340 June 26, 2018
- Version 5.5.2339 June 25, 2018
- **Version 5.5.2336 June 6, 2018**
- Version 5.5.2335 May 6, 2018
- Version 5.5.2334 April 18, 2018
- Version 5.5.2333 April 18, 2018
- Version 5.5.2332 April 17, 2018
- Version 5.5.2331 April 10, 2018
- Version 5.5.2330 March 7, 2018
- Version 5.5.2329 February 12, 2018
- Version 5.5.2328 January 31, 2018
- **Version 5.5.2327 January 23, 2018**
- Version 5.5.2324 January 18, 2018
- Version 5.5.2323 December 7, 2017
- Version 5.5.2322 November 25, 2017
- **Version 5.5.2321 October 26, 2017**
- Version 5.5.2320 October 18, 2017
- **Version 5.5.2319 October 16, 2017**
- **Version 5.5.2318 September 29, 2017**
- **Version 5.5.2314 August 24, 2017**
- **Version 5.5.2313 August 9, 2017**
- Version 5.5.2312 July 14, 2017
- Version 5.5.2311 June 20, 2017
- **Version 5.5.2309 June 4, 2017**
- Version 5.5.2306 May 27, 2017
- Version 5.5.2305 May 13, 2017
- Version 5.5.2304 May 6, 2017
- Version 5.5.2303 April 28, 2017
- Version 5.5.2302 April 20, 2017
- Version 5.5.2301 April 17, 2017
- Version 5.5.2300 April 15, 2017
- Version 5.5.2299 April 10, 2017

- Version 5.5.2297 April 5, 2017
- Version 5.5.2296 March 31, 2017
- Version 5.5.2295 March 26, 2017
- Version 5.5.2294 March 21, 2017
- Version 5.5.2293 March 6, 2017
- Version 5.5.2290 January 2, 2017
- Version 5.5.2289 December 2, 2016
- Version 5.5.2287 November 29, 2016
- Version 5.5.2286 November 8, 2016
- Version 5.5.2285 November 3, 2016
- **Version 5.5.2284 October 23, 2016**
- Version 5.5.2282 August 25, 2016
- Version 5.5.2281 August 7, 2016
- **Version 5.5.2279 July 8, 2016**
- **Version 5.5.2278 July 1, 2016**
- Version 5.5.2277 June 25, 2016
- Version 5.5.2275 May 17, 2016
- **Version 5.5.2274 May 5, 2016**
- Version 5.5.2271 April 1, 2016
- **Version 5.5.2270 March 24, 2016**
- Version 5.5.2268 March 14, 2016
- **Version 5.5.2267 February 11, 2016**
- Version 5.5.2265 February 11, 2016
- Version 5.5.2264 February 2, 2016
- **Version 5.5.2263 January 7, 2016**
- Version 5.5.2260 December 22, 2015
- Version 5.5.2259 October 27, 2015
- Version 5.5.2258 October 5, 2015
- Version 5.5.2257 September 1, 2015
- Version 5.5.2256 August 24, 2015
- Version 5.5.2255 August 11, 2015
- Version 5.5.2254 July 23, 2015
- **Version 5.5.2252 July 1, 2015**
- **Version 5.5.2251 June 30, 2015**
- Version 5.5.2250 June 29, 2015
- Version 5.5.2249 June 26, 2015
- **Version 5.5.2248 May 31, 2015**
- Version 5.5.2247 May 29, 2015
- **Version 5.5.2246 May 27, 2015**
- **Version 5.5.2243 May 22, 2015**
- **Version 5.5.2242 May 16, 2015**
- Version 5.5.2241 May 12, 2015
- Version 5.5.2240 May 8, 2015

- Version 5.5.2239 May 6, 2015
- Version 5.5.2238 April 14, 2015
- Version 5.5.2237 March 23, 2015
- Version 5.5.2234 March 5, 2015
- **Version 5.5.2233 February 23, 2015**
- Version 5.5.2232 February 21, 2015
- Version 5.5.2231 February 20, 2015
- Version 5.5.2230 February 18, 2015
- Version 5.5.2229 February 14, 2015
- Version 5.5.2228 February 6, 2015

5.5.2350 (September 6, 2018)

Mbnavadjust: Added a sorted ties list view for which the list of ties is ordered from largest misfit magnitude to smallest where the misfit is measured between the tie offset and the offset of the most recent inversion. This allows one to easily inspect the most poorly fit ties. Also augmented stored information about global ties. Also made some changes to the inversion algorithm.

5.5.2348 (August 20, 2018)

Reson 7k V3 support: Added files mbr_reson7k3.c mbsys_reson7k3.c mbsys_reson7k3.h while working towards support of version 3 7k data (by Christian Ferreira).

5.5.2347 (August 17, 2018)

Mbtrnpreprocess: precruise update of mbtrnpreprocess and related tools used for optional install of AUV terrain relative navigation. Excepting for a few debug print statement changes, this matches the 20180814 mbtrnpreprocess installation of Kent Headly on MBARI Mapping AUV 2.

5.5.2346 (August 13, 2018)

Mbauvloglist: augmented dimensioning of fields array to allow up to 500 data fields.

Mbnavadjust: Changed output of project so a single navigation offset model file is output that can be parsed to get x, y, and z offset components for plotting etc.

Format MBF_SBURIVAX (format id 15): Augmented the i/o module to handle negative longitude values (the format should use unsigned shorts but clearly data exist using signed values).

5.5.2345 (August 10, 2018)

Mbmakeplatform: Fixed segmentation fault when modifications to the platform model are specified before a command that initializes the platform.

Mbcopy and Format 88 (MBF_RESON7KR): Added hook to mbcopy so that it can output bathymetry only records when copying format 88 (*.s7k) data. This option is enabled by using the -N argument twice, and is used to generate data files that mimic the minimal data record stream requested by mbtrnpreprocess.

Mbnavadjust: Undid the modification of 5.5.2340 that stores only valid, unflagged soundings in the section files, which are format 71. This turned out to be a very bad idea because it sometimes breaks the contouring used for display of the navigation crossings.

Mbnavadjust: Changed so that sensordepth values are included in the navigation points stored in the project file (*.nvh file).

5.5.2344 (August 3, 2018)

Mbcontour, mbswath, mbgrdtiff, mbbackangle, mbprocess, mbgrid, mbmosaic, libmbaux, mbgrdviz, mbeditviz, mbnavadjust, libmbview: Implemented a number of low level changes suggested by Paul Wessel and Joaquim Luis in order to maintain compatibility with GMT versions >= 5.5.4 and achieve compatibility with the coming GMT6.

Format 88 (MBF_RESON7KR): Fixed handling data from a Reson 7125 installation with the receive head mounted backwards (this is something one might do in an AUV context in order to achieve a desired cable run).

Mbtrnpreprocess: Changes from Kent Headley (this program is being actively developed).

src/mbtrn: Changes from Kent Headley (these tools and library are being actively developed).

5.5.2342 (June 29, 2018)

Mbgpstide: New program contributed by Gordon Keith. This program generates tide files from the height above ellipsoid data in the 'h' datagrams of Simrad files. There is an option to include fixed offsets and geoid

differences. This development was funded by Geoscience Australia with the understanding that the code would be made available to the general MB-System distribution.

5.5.2340 (June 26, 2018)

Autoconf build system: Restructured to build successfully with the mbtrn capability enabled using the --enable-mbtrn option of the configure script.

Mb_input_init() in src/mbio/mb_read_init.c: Allows calling program to initialize arbitrary input method by supplying functions to open, read bytes, and close the input. This capability is used by mbtrnpreprocess to read multibeam data over a socket directly from a sonar.

Binary file i/o functions in src/mbio/mb_fileio.c: Can now read from an arbitrary input method defined by the mb_input_init() function.

Mbtrnpreprocess: moved from src/mbtrn to src/utilities.

Mbnavadjust: now stores only valid, unflagged soundings in the section files, which are format 71. Previously all soundings, including null and flagged, were stored.

5.5.2339 (June 25, 2018)

Mbgrid: Modified to use correct gridding algorithm when reading fbt files lacking the sonar type value.

Mbcopy: Modified to ensure that the sonar type value is embedded in fbt files written by mbcopy.

Format MBF_LDEOIH (MBIO format id 71): I/O module modified to ensure the sonar type value is embedded in fbt files.

mbm_bpr: added generic data input format

src/mbtrn: added directory under src named mbtrn that contains code to enable terrain relative navigation (TRN) on autonomous underwater vehicle (AUV) platforms. These programs and library, particularly including mbtrnpreprocess, are built optionally providing the configure script is run with the --enable-mbtrn option.

Mbtrnpreprocess: Program to read multibeam data from a Reson 7K sonar in realtime, decimate and filter the bathymetry data, and provide the data to a terrain relative navigation (TRN) client that localizes the AUV position relative to a pre-existing map using the current bathymetry data.

5.5.2336 (June 6, 2018)

Mbpreprocess and format MBF_3DWISLR (232): Add option --kluge-fix-wissl-timestamps to fix a timestamp problem with the initial version of the 3D at Depth WiSSL (wide swath lidar).

Mbbackangle and mbprocess: Lidar intensity correction calculations now appropriate for linear data instead of log-scaled data.

src/mbaux/mb_intersectgrid.c: Added function mb_topogrid_bounds() that returns the lon-lat bounds of a topography grid previously loaded using the mb_topogrid_init() function.

5.5.2335 (May 6, 2018)

mbm_bpr: Added ability to parse pressure data from Sonardyne AMT beacons. Also added optional smoothing of the BPR depth data used to calculate tides.

Mbotps: Made the options -Ctidestationformat, -Ntidestationfile, and -Utidestationlon/tidestationlat introduced last month actually work. One can now use nearby tide station data to correct tide models calculated for the location and time of survey data.

mbm_route2mission: Altered to reflect the increased mission duration possible for MBARI Mapping AUVs.

Format 88 (MBF_RESON7KR): Fixed handling of beams when using the version 2 raw detection data records.

5.5.2334 (April 18, 2018)

Mbprocess, mbareaclean, mbclean, mbedit, mbeditviz, mbrphsbias, mbneptune2esf: Reset MB_ESF_MAXTIMEDIFF_X10 value in mb_process.h to 0.0011 to handle old beamflags with millisecond truncated timetags.

Mbareaclean, mbclean, mbrphsbias: Fixed the previous fixes .

5.5.2333 (April 18, 2018)

Mbprocess, mbareaclean, mbclean, mbedit, mbeditviz, mbrphsbias, mbneptune2esf: Decreased time range where multiplicity of pings will consider close records as the same from 100 to 1 microsecond.

5.5.2332 (April 17, 2018)

Mbprocess, mbareaclean, mbclean, mbedit, mbeditviz, mbrphsbias, mbneptune2esf: Fixed problem recognizing multiplicity of pings when ping times are close to but not exactly the same. This problem was recognized in XSE data from a SeaBeam 3020 multibeam, but could potentially have impacted data from other sensors.

5.5.2331 (April 10, 2018)

mbm_makedatalist: Fixed problem with use of perl sort function when handling Kongsberg multibeam data. Also fixed problem with specifying a directory using the -l option.

Mbotps: Added new options -Ctidestationformat, -Ntidestationfile, and -Utidestationlon/tidestationlat. Together these commands allow users to input observations from a tide station; these observations can be used to calculate corrections to tidal model values in the vicinity of the tide station. If tide station data are specified, then MBotps calculates the difference between the observed and modeled tide at that station for each data point in the input tide station data. This difference time series is then used as a correction to the output tide models, whether at a location specified with the -Rlon/lat option or for swath data specified with the -ldatalist option.

Mbmakeplatform: Fixed initialization of the organization and documentation_url fields.

Mbtrnpreprocess: Continued development of this new tool, particularly adding interprocess communication via TCP-IP sockets.

5.5.2330 (March 7, 2018)

Proj: Removed the embedded Proj source package from the MB-System archive and distribution. From now on Proj is strictly a prerequisite for building MB-System.

Mbtrnpreprocess: Added initial version of new tool for real-time multibeam data filtering as part of the implementation of terrain aided navigation on MBARI AUVs. Specifically, mbtrnpreprocess accesses realtime s7k data from a Reson 7125 multibeam sonar, decimates and filters the bathymetry, and then passes the decimated and filtered soundings on to an application that attempts to locate the AUV in real time relative to a pre-existing multibeam bathymetry survey. This allows repeat AUV surveys to execute exactly the desired survey tracks.

Format MBF_3DWISSLP (233): Many fixes to the code supporting WiSSL lidar data.

5.5.2329 (February 12, 2018)

Format MBF_3DWISSLP (233): Rewrote the processing format for the 3D at Depth wide swath lidar (WiSSL) system delivered to MBARI in December 2017. The new version of the format is more compact and is read and written much faster.

Edit Save Files (*.esf) and mbedit, mbclean, mbareaclean, mbeditviz: Fixed problem in which flags were sometimes not applied to all soundings in pings that are less than 0.1 milliseconds earlier or later than another ping or scan.

MBeditviz: Replaced use of the global edit files (*.gef*) by *mbeditviz* with use of new edit files called reverse edit save files (*.resf*). The *.gef files were generated by mbpreprocess using mbgetesf. The *.resf files are generated by mbprocess.

mbm_route2mission: Fixed generation of Dorado AUV missions with waypoint_bottom behaviours.

5.5.2328 (January 31, 2018)

Edit Save Files (*.esf): The edit save file format has been augmented to include a mode value that can include implicitly setting all soundings not set by a beamflag in the file to a null value (mode == 1) or a valid value (mode = 2). The default remains to change sounding beamflag values only for beams explicitly set by an edit event. The only means to create ESF files with implicit beamflag modes is using mbgetesf with -M4 or -M5, and the only use of implicit beamflag modes is in the MBeditviz *.gef files. The new ESF files have a version 3 tag; old ESF files will continue to work fine.

MBgetesf: Augmented to output edit save files in two new modes. If -M4 is specified, the beamflags of null beams will not be output, but the ESF mode is set so that the beamflags of any soundings not specified will be set null. If -M5 is specified, the beamflags of valid beams will not be output, but the ESF mode is set so that the beamflags of any soundings not specified will be set valid.

MBpreprocess: Generates *.gef files using mbgetesf with the -M4 rather than -M2 option.

MBinfo: Fixed memory allocation problem that led to crashes reading data in formats MBF_3DWISSLR (232) and MBF_3DWISSLP (233).

5.5.2327 (January 23, 2018)

Build system: Restructure the use of the mb_config.h file so that compiling on Ubuntu 17 succeeds (issue related to stdint.h includes)

5.5.2325 (January 23, 2018)

MBinfo: Fixed bug in JSON output (Christian Ferreira)

5.5.2324 (January 18, 2018)

MBpreprocess: Added support for the 3D at Depth wide swath lidar (WiSSL) system delivered to MBARI in December 2017.

Formats MBF_3DWISSLR (232) and MBF_3DWISSLP (233): Added support for the 3D at Depth wide swath lidar (WiSSL) system delivered to MBARI in December 2017.

mbm_route2mission: Fixed implementation of inserting surfacing events into missions at line start and end waypoints.

Many source files: Changes to variable names in GMT grid header and CPT structures for GMT 6.

5.5.2323 (December 7, 2017)

MBnavadjust: fixed crashes that happened when files or surveys are held fixed.

5.5.2322 (November 25, 2017)

Mbpreprocess: Now set so that input Imagenex DeltaT data in the vendor format MBF_IMAGE83P (191) will be output in the processing format MBF_IMAGEMBA (192) after pre-processing.

Mb7k2jstar: Now outputs in the current jstar format rather than a >10 year old variant.

Formats MBF_EDGJSTAR (132) and MBF_EDGJSTR2 (133) supporting Edgetech Jstar (*.jsf) files: Changed code to support recent and current versions of Jstar format files. The code should recognize and convert older variants, particularly those written by past versions of MB-System.

Various source files (mk_cheby.c, geod_for.c, mbsys_xse.c, mbsys_sb2100.c, mbsys_elacmk2.c, mbsys_elac.c, mbr_xtfr8101.c, mbbs_defines.h): Added curly brackets, changed beamflag setting

calculations, and reformatted some lines in order to silence compiler warnings.

5.5.2321 (October 26, 2017)

Mbgrdviz: fixed bug in displaying overlays.

Mbpreprocess: Added some kluge fixes to time jumps in ancillary data. New commands are --kluge-ancillary-time-jumps and --kluge-mbaripressure-time-jumps.

Mbextractseg: fixed bug in the output plotting script.

Format 88 (MBF_RESON7KR): Fixed confusion between Depth and Height s7k data records.

5.5.2320 (October 18, 2017)

Mbgrdviz: Now, when overlays are displayed in mbgrdviz, the only areas rendered are those where both the primary and overlay grids are defined.

5.5.2319 (October 16, 2017)

Mbprocess: Fixed bug that caused mbprocess to (sometimes) never finish while continuing to write to the output file.

5.5.2318 (September 29, 2017)

Mbnavadjust: Fixed bug that often, but not always, caused the inversion to blow up and crash the program.

General: Fixed problem with data record type informational messages

General: Fixed problem with time gap nonfatal error detection

MBpreprocess: Added --skip-existing option that causes MBpreprocess to skip preprocessing of files referenced in the input datalist that have already been preprocessed. This allows efficiently adding new files to a survey, particularly in a shipboard context where one is trying to process new data as they are collected.

MBotps: Added -S option that causes MBotps to skip calculating a tidal correction model for files referenced in the input datalist that already have models calculated by mbotps. The skipped files will not be viewed as out-of-date by mbprocess, and thus will not be reprocessed if mbprocess or mbm_multiprocess are run. This allows efficiently adding new files to a

survey, particularly in a shipboard context where one is trying to process new data as they are collected.

MBgrdviz: Added capability to output site data as Winfrog waypoint (*.WPT) files.

MBeditviz: Added capability to optimize an additional bias parameter (sort of...) in the 3D sounding view. The new parameter is a "snell correction", referring to adjusting the receive beam angles of multibeam data by applying a Snell's law correction equivalent to changing the speed of sound used for beam forming. This parameter is expressed as a ratio of the new to original sound speed, so that a snell correction value of 1.00 corresponds to no change, a value of 0.995 corresponds to a slight reduction in the sound speed, and a value 1.005 corresponds to a slight increase in the sound speed. This correction is intended for near-bottom surveys from submerged platforms (ROVs or AUVs) where sound speed is calculated from CTD data (and values may plausibly be slightly erroneous) and where errors due to raytracing through an incorrect model of the water column sound speed are unlikely to be significant. This correction is generally not useful for multibeam data collected from a surface vessel.

MBminirovnav: Added new program that processes raw MBARI MiniROV data logs to produce standard MBARI ROV navigation files (format MBF_MBARIROV) MBpreprocess: Add option to skip preprocessing files in the input datalist that have already been fully preprocessed.

MBsegygrid: Added a trace mode=2 to the -Smode[/start/end[/schan/echan]] command for which start and end refer to shot numbers and all traces within that range of shot numbers are plotted. Effectively the channel numbers are ignored by setting all trace channels to 0 and plotting channel 0.

MBsslayout: Changed arguments to have '-' rather than '_' characters between words in multiword commands (e.g. --topo_grid_file is now --topo-grid-file). Also now have code identifying the fileroot of the input file and using that in the construction of output file names so that the input format suffix is not embedded in the middle of the output filename. Also improved the swathplotting script generated by mbsslayout.

Formats 132 (MBF_EDGJSTAR) and 133 (MBF_EDGJSR2): Fixed preprocessing function in the i/o module so that altitude values read in by mbpreprocess are actually applied in the output file.

Format 160 (MBF_SEGYSEGY): Added recognition of this format by file suffixes *.SEG and *.seg (in addition to *.SEGY and *.seggy).

mbm_makedatalist and Formats 56, 57, 58 59 (MBF_EM300RAW, MBF_EM300MBA, MBF_EM710RAW, MBF_EM710MBA): The mbm_makedatalist macro will now attempt to sort Kongsberg data into time order based on filenames when the file suffixes follow the MB-System convention (*.mb56, *.mb57, *.mb58, *.mb59). Previously this functionality was only applied to files with the *.all suffix. This capability is applied by default but can be disabled with the -T option.

5.5.2314 (August 24, 2017)

Mbprocess: Fixed bug in which mbprocess sometimes crashed for files that have not had bathymetry edited or filtered.

Mbprocess: Code used to read GMT grid files modified so that if the GMT API call to read a grid fails, that call will be repeated every 0.1 seconds for 10 seconds until it succeeds. This should allow multiple instances of mbprocess to read the same grid files used for processing without interfering (the current GMT libraries have problems with multiple simultaneous reading of a grid file over some network mounted filesystems).

Format 88 (MBF_RESON7KR): Augmented the preprocess function to properly implement a correction to the sound speed value used for beamforming, with consequential changes to the recalculated bathymetry.

Mbpreprocess: Changed so that ancillary data is specified to be read from external file(s) but one of those files does not exist, the program terminates with an error message.

5.5.2313 (August 9, 2017)

Format 88 (MBF_RESON7KR): Fixed problem handling Reson data preprocessed or processed using a version older than 5.3.2004 which in some cases causes the alongtrack and acrosstrack values to be swapped.

5.5.2312 (July 14, 2017)

MBedit: Added togglebutton to the View menu that allows to control whether flagged soundings are displayed (previously flagged but valid soundings were always displayed).

MBauvloglist: Added ability to recalculate MBARI Mapping AUV CTD data using corrected calibration coefficients. This allows one to output a corrected time series of sound speed.

Proj: Removed the embedded Proj library from MB-System. One must now have Proj installed separately in order to build MB-System (which is always the case anyway).

MBpreprocess: Added several new options.

MBgrdtiff, mbcontour, mbswath, mbps: Changed defines in *.c files to reflect the versioning of GMT 6

5.5.2311 (June 20, 2017)

MBnavadjust: Fixed bug that preventing importing data into a new project.

5.5.2309 (June 4, 2017)

Applied reformatting to all *.c and *.h files using the tool clang-format as suggested by Joaquim Luis.

Updated copyright statements to 2017.

Updated mbotps to use the current best OSU tidal model (atlas_tpxo8_1).

5.5.2306 (May 27, 2017)

Format 88 (MBF_RESON7KR): Fixed a couple of bugs in the i/o module identified by Kurt Schwehr.

Format 121 (MBF_GSFGENMB): Fixed handling of attitude records.

5.5.2305 (May 13, 2017)

MBdatalist: Fixed bug involving operating on datalist files other than the default datalist.mb-1.

MBpreprocess: Added option --kluge-soundspeed-tweak=factor that applies a multiplicative correction to the water sound speed at the sonar arrays. This both changes the beam angles by a Snell's law correction and affects the calculation of bathymetry using the travel times.

MBconfig: Added options to print out the installation location, the compile flags needed to compile code using MB-System libraries, and the linker flags needed to link programs that call functions in MB-System libraries.

MBextractseggy: Force jpeg renderings of the section plots to be portrait style.

MBinfo: Fix bug in XML output disabling output of minimum good beam counts in some cases.

5.5.2304 (May 6, 2017)

MBpreprocess: Fixed generation of *.baa, *.bsa, and *.bah files so they include only data relevant to the associated swath file, which means samples from 10 seconds before the first survey data through 10 seconds after the last survey data. The program now removes any pre-existing *.ata, *.sta, *.ath, *.baa, *.bsa, and *.bah files.

MBconfig: New program to provide command line access to the ### MB-System Version and the locations of the Levitus database and the OTPS tide prediction software.

MBlevitus: The variable storing the location of the Levitus database file has been changed from "ifile" to "levitusfile".

Datalist parsing: The mb_datalist_read() function changed with the 5.5.2299 revision, including adding a new argument. The old version of that function is now available within the API as mb_datalist_readorg().

5.5.2303 (April 28, 2017)

MBpreprocess and MBeditviz: Changed the ancillary files used to store the asynchronous attitude and heading data used by MBeditviz for time latency modeling from text to binary. The text *.ata, *.sta, and *.ath files generated by mbpreprocess (and formerly by mb7kpreprocess and mbkongsbergpreprocess) are replaced by *.baa, *.bsa, and *.bah files respectively. The size of the the binary files is about half of the previous text files; the i/o speed for loading data is improved as well.

Configure script: Fixed problems with specifying the location of the netCDF, GDAL, and GMT config programs.

MBswath: Fixed bug that caused occasional crashes.

5.5.2302 (April 20, 2017)

Formats 56 and 57 (MBF_EM300RAW and MBF_EM300MBA): Fixed handling of sensordepth and heave data by mbpreprocess and mbprocess. Tide correction and recalculation by raytracing work correctly again. Added preprocessing function to the i/o module. Users should now use mbpreprocess for preprocessing old Kongsberg multibeam data so that navigation is properly interpolated and beam flagging works correctly.

mbm_plot, mbm_grdplot, mbm_xyplot: The plotting macros now handle negative scaled (reverse) axes properly (e.g. sound speed plots with depth increasing downwards).

Mbdatalist: Now supports long command line options (old short options are deprecated but still work).

5.5.2301 (April 17, 2017)

Mbpreprocess and Format 88 (MBF_RESON7KR): Fixed application of kluge-beam-tweak option for Reson 7k (format 88) data.

5.5.2300 (April 15, 2017)

Formats 58 and 59 (MBF_EM710RAW and MBF_EM710MBA): Fixed memory leak.

Formats 59 (MBF_EM710MBA): Fixed calculation of interpolated heave when recalculating bathymetry by raytracing.

Format 88 (MBF_RESON7KR): Fixed memory leaks.

mbm_arc2grd: Rewritten to use GMT modules grdconvert and grdedit.

5.5.2299 (April 10, 2017)

Formats 58 and 59 (MBF_EM710RAW and MBF_EM710MBA): Fixed handling of sensordepth and heave data during preprocessing. Program mbkongsbergpreprocess is now deprecated and will be removed from the distribution soon. Users should now use mbpreprocess for preprocessing Kongsberg multibeam data.

Format 88 (MBF_RESON7KR): Fixed bug in handling of TVG data records.

Mbdatalist: Added a new option -D that causes mbdatalist to list the unique datalist files referenced as a recursive datalist structure is parsed. The recursion level of each datalist file is indicated in the listing.

Mblist and mbnavlist: Augmented the -Zsegmenttag option for printing out segment start lines in the output. Normally the string segmenttag is a single character that is recognized by GMT as a segment beginning when parsing tabular data. Now, if segmenttag == "swathfile" the segment start lines will consist of the character '#' followed by the path to the source swath file, and if segmenttag == "datalist" the segment start lines will consist of the character '#' followed by the path to the source datalist file

5.5.2297 (April 5, 2017)

All i/o modules: Added sensordepth_source to the arguments of the mbr_info_XXXXXXXX() functions in the i/o modules.

Mbpreprocess: Added ability to define default sources (in terms of data record types) for the various asynchronous ancillary data types in Kongsberg and Reson data.

Formats 58 (MBF_EM710RAW) and 59 (MBF_EM710MBA): Kongsberg reports some bathymetry bottom picks that are interpolated or extrapolated from valid soundings. Until now MB-System has treated these interpolated soundings as valid but flagged. MB-System now recognizes interpolated soundings as a different type, neither valid nor null. These soundings can no longer be seen or edited with MBedit or MBeditviz.

mbm_makedatalist: Added option to suppress processed files (e.g. *p.mb88) from inclusion in the output datalist.

5.5.2296 (March 31, 2017)

mbm_makedatalist: Major capability augmentation for this tool, preparing for automated setup of the processing environment. This macro will now construct datalists from files matching a user specified filename suffix, and will attempt to sort raw Kongsberg multibeam data files into time order.

Formats 58 (MBF_EM710RAW) and 59 (MBF_EM710MBA): Fixed to handle EM712 data and other Kongsberg multibeams now generating more than 512 beams.

mbm_grd2arc: Fix provided by Monica Schwehr for compatibility to *.grd files generated with the current GMT.

5.5.2295 (March 26, 2017)

mbm_plot, mbm_grdplot, mbm_xyplot, mbm_3dgrdplot: Changes to the manual pages to reflect the new syntax for map scales (the -MGL option in the MB-System plot macros) in GMT 5.3.X

Mbnavadjust: Fixed bug in calling scripts within the project directory for users that do not include "." in their path environment variable. Problem identified by Monica Schwehr.

Mbpreprocess: Added functionality to handle specialized, format-specific preprocessing tasks and to handle changes to data timestamps. Currently set to work with generic data, Reson 7k data (format 88), and 3DatDepth

Lidar data (format 231). Code written for mbpreprocess to work with Kongsberg data, but not yet tested.

Format 88 (MBF_RESON7KR) and Mb7kpreprocess: Mb7kpreprocess is deprecated, with preprocessing of Reson 7k data to be done by mbpreprocess.

Format 121 (MBF_GSFGENMB): Integrated latest release of GSF from Leidos (3.07)

5.5.2294 (March 21, 2017)

Mbsvpselect: Fixes by Ammar Aljuhne and Christian Ferreira of MARUM.

5.5.2293 (March 6, 2017)

Mb7kpreprocess: Fixed bug in handling old MBARI Mapping AUV with navigation and attitude data in deprecated "Bluefin" records.

Mbnavlist: Added ability to output positions in a projected coordinate system.

Mblist: Use ping count as ping number when the data format does not include ping or shot number.

Format 21 (MBF_HSATLRAW): Fixed bug in handling zero length comments.

Format 231 (MBF_3DDEPTH): Fixed bug in handling angular offset values in preprocessing.

5.5.2292 (January 30, 2017)

Mblist: Added ability to output positions in a projected coordinate system, to output positions of the sensor instead of soundings or pixels, or to output positions relative to the sensor in the world frame.

mbm_route2mission: Fixed handling of waypoint spacing for constant depth segments of missions.

Mbnavadjust: Now outputs the altered project less frequently (every tenth new tie instead of every tie).

5.5.2291 (January 12, 2017)

Mbnavedit: interpolation of selected navigation values now also flags the original values so they are not used in calculating a navigation model.

General: fixed a number of memory leaks by switching all remaining `mb_malloc()`, `mb_realloc()`, and `mb_free()` calls to `mb_mallocd()`, `mb_reallocd()`, and `mb_freed()`.

Mbnavadjust: prevent occasional corruption of the mbnavadjust project by not allowing excessively large offset values to result from unstable inversions.

5.5.2290 (January 2, 2017)

Mbinfo: applied fixes from Suzanne O'Hara to JSON output from mbinfo.

Mbnavadjust: Fixed problem in which tie snav times became incorrect - these values are now reset when the project is read.

Mbgrid and mbmosaic: added code to mbaux/mb_readwritegrd.c that will enable use of new GMT5 grid mode flags, solving the problem of creating geographic grids that can be directly read into ESRI ArcGIS. These modes will appear in GMT 5.3.2 sometime early in 2017. Thanks to Paul Wessel for diagnosing and fixing this longstanding issue.

Mbgrid and mbmosaic: implemented suggestion by Paul Wessel that the calculation of grid dimensions be done with a `lrint()` rounding call rather than implicit truncation. This will change the behavior of the `-Edx/dy/units` option, but the resulting grid dimensions will be more consistent with users expectations.

5.5.2289 (December 2, 2016)

Mbnavadjust: Fixed auto set vertical level function to use the same block inversion now used for the first stage of the main inversion. Also set this function so that for z offset changes less than a threshold (currently 0.10 m) the x and y offsets are not repicked.

Mbnavadjustmerge: Fixed import and export of tie lists to allow moving ties between projects.

5.5.2287 (November 29, 2016)

mbm_makesvp: added capability to extract sound speed values from survey data records as well as ctd data records, and to optionally produce sound speed models extending to the surface and the deep ocean even if the data are available only for a limited depth range.

Mbnavadjust: Modified the inversion algorithm to once again have a first stage solution for "block" (survey) average offsets followed by the main inversion to satisfy all of the navigation tie offsets in detail.

Mbnavadjust: updated the documentation of the inversion algorithm.

Mbprocess: fixed rare singularity in the raytracing code.

5.5.2286 (November 8, 2016)

Mbsvplist: Added -R command to set longitude-latitude bounds within which the -S option will cause ssv values to be output.

Mbgrdviz: Added start5 and end5 waypoint types to routes.

5.5.2285 (November 3, 2016)

Mbnavadjust: Added a first step in the inversion in which mbnavadjust solves for average offsets for each survey ("block"). The offsets associated with this average model are removed from the tie offsets before the full inversion. The smoothing penalty is thus applied to deviations from the average model rather than the full navigation adjustment model.

5.5.2284 (October 23, 2016)

Fixed some typos preparing for full release.

5.5.2283 (October 23, 2016)

mbmakeplatform: fixed bug that caused core dumps when built with gcc.

mbaux/mb_cheb.c: Added open source least squares solver LSQR by Michael A. Saunders (in C version translated from Fortran by Michael P. Friedlander),

Mbnavadjust: Switch navigation matrix solution algorithm to LSQR.

Mbnavadjust: Fixed bug that reset the z-offset-width value to 5-m every time a project was read.

Mb7kpreprocess: Now will use complete platform description when reading older Reson 7k data.

Mb7kpreprocess: Now allows users to specify the the sources of asynchronous ancillary data (position, sensor depth, heading, attitude) to be merged with the survey data.

Mbgrdviz, mbeditviz, mbnavadjust: pick actions will now print out positions to the shell in both decimal degrees and degrees + minutes.

Mbextractseg: Now uses psconvert from GMT instead of convert from imagemagick.

mbm_grdplot: Once again handles section plots from mbextractseg properly.

mbm_arc2grd, mbm_dslnavfix, mbm_grd2arc, mbm_grd2geovml, mbm_grd3dplot, mbm_grdcut, mbm_grdinfo, mbm_grdplo, mbm_grdtiff, mbm_grid, mbm_histplot, mbm_plot, mbm_utm, mbm_xyplot: Modified to work properly with GMT 5.3

mbprocess: fixed correction of sidescan and amplitude data using topographic grid so that the correction is actually calculated and applied.

5.5.2282 (August 25, 2016)

Mbnavadjustmerge: Added --set-ties-xyonly-by-time=timethreshold option.

Mbnavadjust: Improved program behavior with respect to generating the grid used for the project visualization view.

Mbedit: Changed behavior so that using the slider to change the number of pings viewed also changes the number of pings to step proportionately.

5.5.2281 (August 7, 2016)

Mbnavadjustmerge: Added --unset-skipped-crossings-by-block=survey1/survey2 and --unset-skipped-crossings-between-surveys options, and made the --import-tie-list=filename and --export-tie-list=filename options work correctly.

Mbclean: Added option to flag outer beams and/or unflag inner beams by across-track distance (-Y option).

5.5.2279 (July 8, 2016)

Bathymetry editing (mbedit, mbeditviz, mbclean, mbareaclean): fixed problem in which mbprocess failed to successfully apply new edits generated using mbeditviz on files with existing, old esf (edit save files) files. Yet another consequence of adapting to very short ping intervals... Existing edit save files can now be fixed using mbclean -T0.0011.

mbm_grdtiff: Added support for image display program feh.

5.5.2278 (July 1, 2016)

Mbkongsbergpreprocess (Formats 58 & 59): Fixed modification of png_xducer_depth value to not include lever arms or heave, as SIS records sensor depth value in height datagrams that are already compensated for lever arms and heave.

5.5.2277 (June 25, 2016)

mbm_xyplot, mbm_grdplot: fixed problem generating plots using linear axes. Recent changes to GMT cause gmt mapproject to generate an error when passed non-map (e.g. non lon lat) values with a linear projection (after three decades of working just fine....). Created a workaround by treating linear plots as a special case.

Mbeditviz, mbedit, mbclean: Fixed problem with edit save files in which old format *.esf files were generated by mbeditviz. This does not work well with data where separate ping timestamps differ by less than 10 milliseconds (e.g. current generation Kongsberg multibeam data reporting fore and aft pings from each ping cycle and 3DatDepth lidar data).

Mbkongsbergpreprocess (Formats 58 & 59): Fixed handling of sonar depth and heave values in Kongsberg multibeam data logged using SIS on a submerged platform.

Format 201 (MBF_HYSWEEP1): Changed handling of file header data to enable the extraction of platform definition data by the program mbmakeplatform.

MBmakeplatform: Now capable of extracting the list of sensors and the associated offsets from Hypack HSX files, and outputting an MB-System platform file.

MBhysweepprocess: Now allows for sensor offsets to be defined by an MB-System platform file, which can be extracted from HSX data files with mbmakeplatform, and can be modified and augmented using the same program.

MBeditviz: Added a new sounding filter mode that calculates the sounding density for a 3D "voxel" representation of the selected volume, and then flags soundings in voxels containing less than a threshold of soundings. This algorithm flags isolated soundings, an approach that is particularly useful for submarine lidar data. This filter is accessible from the "action" menu of the 3D sounding window.

5.5.2276 (May 31, 2016)

MBeditviz: Added algorithm to flag isolated soundings by analyzing the 3D distribution of currently selected soundings. Soundings are flagged in voxels containing less than a desired threshold of soundings. This option is accessed from the menu of the 3D sounding view.

Format 201 (MBF_HYSWEEP1) and mbhysweepprocess: Fixed handling of data that have beam takeoff angles calculated without attitude correction. Changed the default heave sign convention.

Format 231 (MBF_3DDEPTH): Now handles files with broken data records a bit more gracefully.

5.5.2275 (May 17, 2016)

MBnavadjust: Fixed display of navigation in visualization view. Fixed overwriting of zoffsetwidth value when projects are read in. Fixed autopicking when view mode is survey-vs-survey blocks.

MBkongsbergprocess: Added capability to merge sonardepth from a separate ascii file consisting of Unix time and sonardepth pairs.

Makefiles and mbr_gsfgenmb.c: Fixed typos noted by Joaquim Luis.

General: Fixed several warnings generated by the new gcc version in Ubuntu 16.

5.5.2274 (May 5, 2016)

Configure.cmd and "How to Get" web page: Updated with instructions for installing in Ubuntu, including Ubuntu 16.04.

MBgrdviz, MBeditviz: New radiobox in the Controls->Projections dialog allows user to change interactive pick annotations so that longitude and latitude values are shown as degrees + decimal minutes or decimal degrees, as desired

MBeditviz: Fixed bug involving some isnan calls according to suggestion by Gordon Keith - MB-System now builds on Ubuntu 16.04.

Mbswath: Fixed bug in handling format for single input files, as suggested by Joaquim Luis.

Mbnavadjustmerge: Added commands to set the mode of all ties as XYZ, XY only, or Z only.

Many source files: Added a number of `#ifdef` preprocessor statements to handle building on Windows, generally following suggestions by Joaquim Luis.

Many source files: Fixed a number of warnings related to typing and prototyping issues.

5.5.2271 (April 1, 2016)

MBnavadjust: Added numbers of crossings and ties to the table listing of survey-vs-survey blocks.

Formats 58 and 59 (MBF_EM710RAW & MBF_EM710MBA): added EM850 to supported third generation Kongsberg multibeam.

5.5.2270 (March 24, 2016)

MBnavadjust: Now plots ties within missions (surveys) in dark blue and ties between mission in light blue in the bathymetry visualization.

mbm_route2mission: Calculates AUV ascent time with a 1.5 safety factor instead of a 1.2 safety factor to ensure the new Mapping AUV always makes it to the surface before timing out.

5.5.2269 (March 23, 2016)

MBkongsbergpreprocess, and formats 58 (MBF_EM710RAW) and 59 (MBF_EM710MBA) for current generation Kongsberg multibeam data: Changed so that the default source for attitude data used in recalculating bathymetry from travel times and angles is the "active" source originally used by the sonar rather than always being motion sensor 1.

MBnavadjust: Fixed creation of bathymetry grid (gridding scripts were not being set executable). Removed data from fixed files from the bathymetry grid.

MBkongsbergpreprocess: Now by default uses the same attitude data stream used by the sonar in realtime, as opposed to using data from "motion sensor 1" regardless of whether that was the active realtime sensor.

Bathymetry editing programs (MBedit, MBeditviz, MBareaclean, MBclean): fixed beam edit code so that no attempt is made to sort zero length arrays of beam flags.

5.5.2268 (March 14, 2016)

Mbnavadjust: Added integrated mbgrdviz-style visualization of the bathymetry in an Mbnavadjust project. Users can select crossings or ties by clicking on the navigation in the map view. If two selected sections do not already have a defined crossing, a crossing can be created and analyzed. The new version of mbnavadjust will upgrade old projects to include the bathymetry grid. The new GUI commands include under the menu, and under the menu. The documentation, such as it is, does not yet cover these new features.

mbm_multicopy and mbm_multidatalist: Fixed bugs identified (along with fixes) by Martin Ernst of HafenCity University in Hamburg, Germany.

Mbswath, mbcontour, mbgrdtiff: added #ifdefs for compatibility with the upcoming GMT 5.3 release. A number of GMT functions called by the MB-System GMT modules are being renamed.

Format 21 (MBF_HSATLRAW): Added some logic to handle problems in a very old HSDS dataset collected on the R/V Ewing and available at the archive formally known as NGDC.

5.5.2267 (February 11, 2016)

Mbeditviz: Added capability to do automated optimization for bias parameters from the 3D soundings view. Optimization options are accessed from the "Action" menu.

Mb7kpreprocess: Added capability to tweak beam angles through a Snell's law type correction (kluge mode 9).

Mbgetesf, mbdumpesf, mbedit, mbeditviz, mbareaclean, mbclean, mbprocess: Fixed problem handling certain old ESF files (edit save files) that had timestamps truncated to milliseconds instead of microseconds. New ESF files now have a header indicating the version and time of creation. Version 2 ESF files are presumed to have timestamps consistent with datafiles to a +/-1 microsecond precision.

Documentation: Corrected instructions for building MB-System on Ubuntu machines.

5.5.2264 (February 4, 2016)

Mbgrid, mbm_dslnavfix, mbm_grd2arc, mbm_grd3dplot, mbm_grdplot, mbm_grdtiff, mbm_histplot, mgm_plot, mbm_utm, mbm_xyplot: Replaced

call to "grdinfo" with call to "gmt grdinfo" for compatibility with GMT5 installations that do not include soft links to the old GMT4 programs.

Mbauvloglist: Added ability to calculate and output potential temperature when parsing an MBARI Dorado AUV CTD log. Includes adding a potential temperature calculation function to src/mbio/mb_absorption.c

Mbpreprocess: Fixed problem with application of changes to roll and pitch values.

MBnavadjustmerge: Enabled exporting and importing lists of ties.

5.5.2263 (January 7, 2016)

Formats 58 (MBF_EM710RAW) and 59 (MBF_EM710MBA) for current generation Kongsberg multibeam data: Fixed problems handling tide correction and applying heave when recalculating bathymetry through raytracing.

Format 59 (MBF_EM710MBA): Worked on preprocessing function called by mbpreprocess. Not done yet...

Format 88 (MBF_RESON7KR): Worked on preprocessing function called by mbpreprocess. Not done yet...

mbio/mb_access.c: Added explicitly setting the target sensor id to the mb_preprocess() function call.

mbm_grdtiff: Fixed bug in grdinfo call.

GMT integration: Removed GMT header files from mbsystem/gmt because GMT 5.2.1 now installs full development headers. MB-System is now not compatible with any version of GMT prior to 5.2.1.

Configure build system: Now uses built in configuration tools in GMT and netCDF so that command line arguments to the configure script specifying GMT and netCDF library locations are no longer necessary.

mbio/mb_io.h and mbio/mb_platform.c: Added fields to platform structure: mb_longname documentation_url; double start_time_d; double end_time_d; int start_time_i[7]; int end_time_i[7];

Mbmakeplatform: Added commands: --platform-documentation-url=string --platform-start-time=yyyy/mm/dd/hh/mm/ss.ssssss --platform-end-time=yyyy/mm/dd/hh/mm/ss.ssssss

5.5.2259 (October 27, 2015)

Mbpreprocess: Now called format-specific preprocess function if available and applied generic preprocessing otherwise. The first format specific preprocessing to be defined is for Reson 7k data (MBIO format 88).

Mb7kpreprocess: Modified optional fixing of multibeam ping times assuming a specified constant ping interval.

Mbmakembplatform: Added manual page.

mbio/mb_navint.c: Added MBIO API functions mb_apply_time_latency() and mb_apply_time_filter().

Mbeditviz: Fixed application of time latency to sonardepth.

5.5.2258 (October 5, 2015)

Mbnavadjust: Added output of route files including all unfixed ties for each survey and all crossings for each survey.

Mbmakeplatform: Added new program to create or modify platform files.

Format 58 (MBF_EM710RAW): Added functions needed for mbmakeplatform to automatically extract a platform model with sensor offsets.

Format 59 (MBF_EM710MBA): Added functions needed for mbmakeplatform to automatically extract a platform model with sensor offsets.

Format 88 (MBF_RESON7KR): Added functions needed for mbmakeplatform to automatically extract a platform model with sensor offsets.

Mb7kpreprocess: Added kluge mode (-K6) to fix a time stamp problem with recent MBARI Mapping AUV data. Specifically, due to the application of time disciplining to the Reson computer clock using two occasionally inconsistent time sources, sometimes there are abrupt shifts in the ping time stamps for one to three pings. This mode detects and corrects these time tears.

5.5.2257 (September 1, 2015)

Mbpreprocess: Using platform functions to handle sensor offsets. Read platform file or command line offsets and calculate sensor offsets. Updated bathymetry calculations.

General: Added functions `mb_platform_orientation` and `mb_platform_orientation_target` on `mbio/mb_platform`. Cleaned `mb_platform_orientation_offset`. Change all `MB_PLATFORM_MATH*` functions to DEEGREES inputs/outputs on `mbio/mb_platform_math`. Fixed bug on `mb_platform_lever`.

5.5.2256 (August 24, 2015)

Mbeditviz: Improved the way to handle sensor offsets. Improved `mbeditviz_apply_timelag` the way to handle angles corrections. Cleaned `mbeditviz_beam_position` to make it more clear.

`mbio/mb_platform_math.c`: Added new math functions `mb_platform_math_attitude_offset_corrected_by_nav` and `mb_platform_math_attitude_rotate_beam` to handle sensor offset corrections.

5.5.2255 (August 11, 2015)

Mbnavadjust: Set limits on application of smoothing via penalizing the first and second derivatives of the navigation perturbation (particularly the second derivative) in the inversion algorithm. This change has been implemented to prevent the inversion from becoming unstable as the smoothing parameter is made larger.

Mbprocess: Fixed problem with handling of sensor depth changes due to tide correction or lever arm correction.

5.5.2254 (July 23, 2015)

Autotools build system: Disabled `dist` and `distclean` targets in the makefiles produced by the configure script. We do not use the autotools system to generate production distributions, so the existence of these targets defined by default caused some confusion.

Mbset and mbprocess: Added `NAVSHIFTX` and `NAVSHIFTY` options to the `mbprocess` parameter file definition.

Mbgrid: Fixed the `-Kbackground` option for the case of producing grids in projected coordinate systems.

General: Improved the way to handle sensor offsets on `mbio/mb_platform.c` and changed the way is currently used in `mb7kpreprocess`. Added `mbio/mb_platform_math.c` to the archive. This source file includes math functions to calculate angular offsets.

5.5.2252 (July 1, 2015)

Mbedit, mbnavedit, mbnavadjust, mbvelocitytool: Fix X11 font initialization problem created in the 2251 commit.

5.5.2251 (June 30, 2015)

Mblist, mbnavlist, mbctdlist: Changed time outputs so that decimal second values will be formatted according to the locale (e.g. decimal delineation by commas in Europe).

Mbedit, mbnavedit, mbnavadjust, mbvelocitytool, mbgrdviz, mbeditviz: Set up preprocessor defines to allow fonts to be defined using the CFLAGS environment variable.

5.5.2250 (June 29, 2015)

Mbedit, mbnavedit, mbvelocitytool, mbgrdviz, mbeditviz: Removed call to X11 function XtSetLanguageProc() in all graphical tools. This call apparently causes the program locale to be reset according system defaults, even if the program implicitly begins in the standard C locale. If the system locale uses "," rather than "." as the decimal point marker (e.g. a normal European locale), then a GMT 5 initialization will probably fail on reading fonts, at least on many if not all Linux distributions. Thanks to Giancarlo Troni for figuring this one out.

General: Added mbio/mb_platform.c to the archive. This source file includes the functions to read, write, and use platform, sensor, and sensor offset definitions. At this time the mb_platform_*() functions are only used in mb7kpreprocess, but they will soon be used in mbprocess and all the preprocess programs.

Mbprocess: changed application of tide corrections so that these corrections are applied to the platform depth values rather than the bathymetry values. The result is the same, but now the navigation (or trajectory) of the processed files is corrected in addition to the bathymetry.

5.5.2249 (June 26, 2015)

Format 121 (MBF_GSFGENMB): Kluge added to the GSF format i/o module to handle beam angles incorrectly constructed so that angles from vertical are negative for port side beams when all azimuthal angles are uniformly zero (=starboard).

General: Added platform, sensor, and sensor offset definitions to mb_io.h for use in flexibly defining a platform consisting of many sensors with relative positional and angular offsets. Also added functions to read and write platform files using these definitions. Have not completed the function to perform lever arm calculations using this platform definition. Initially these functions will be used in mb7kpreprocess, but ultimately these will be used generally in MB-System.

Mb7kpreprocess: initial implementation using the new platform file and structure definitions.

5.5.2248 (May 31, 2015)

Mbgrdviz and mbview: Fixed casts between int and pointer that seem to be responsible for mbgrdviz crashes.

5.5.2247 (May 29, 2015)

General: Cleaned up missing function prototypes through much of the codebase (excepting externally written libraries gsf, sapi, bsio) in an effort to fix crashes of mbgrdviz and other programs.

5.5.2246 (May 27, 2015)

Mbswath, mbcontour, mbgrdtiff: Updated GMT5 header files in src/gmt to enable building on Ubuntu Linux, CentOS Linux, and CygWin while maintaining compatibility with GMT 5.1.2.

Mbedit, mbnavedit, mbvelocitytool, mbgrdviz, mbeditviz: Incomplete tweaks to font handling to enable use of fonts other than Helvetica, Times, and Courier.

5.5.2243 (May 22, 2015)

Rewrote the configure.ac file to fix logic flaws in the configure script.

5.5.2242 (May 16, 2015)

Mbswath, mbcontour, mbgrdtiff: Updated files in src/gmt for compatibility with GMT 5.1.2.

5.5.2241 (May 12, 2015)

Format 59 (MBF_EM710MBA): Fixed flag causing erroneous warning that beam flags are not supported for this format (beam flags are supported).

Many source files: further changes to precompiler directives suggested by Joaquim Luis in order to enable building under Windows.

5.5.2240 (May 8, 2015)

Format 241 (MBF_WASSPENL): Fixed recognition of *.nwsf suffix.

Mbclean: fixed bug in beam position calculation identified by Joaquim Luis.

5.5.2239 (May 6, 2015)

Format 241 (MBF_WASSPENL): Now supports WASSP multibeam data conforming to the WASSP ICD 2.4. MB-System is storing beam flags in unused bytes in the existing CORBATHY data records (specifically the "empty" field in the CORBATHY beam data specified in ICD 2.4).

Many source files: changes to precompiler directives suggested by Joaquim Luis in order to enable building under Windows.

Mbnavadjust: Modified the inversion to separate the vertical and lateral covariance so that lateral offsets do not bleed into the vertical offset model.

Mb7kpreprocess: Fixed bug that treated null soundings as good for datasets without detection records.

Mbdumpesf: Added capability to output in the edit save file format in addition to ASCII text, and to ignore specified types of edit events (e.g. copy an esf file while removing all beam null events).

Build system: Fixed bug that caused configure to fail if netCDF has a pkg-config installation while GMT5 is in a specified but nonstandard location.

5.5.2238 (April 15, 2015)

Mbnavadjust: Recast and improved the inversion. Added a "perturbation" model display which does not include the average offsets between the individual surveys in projects involving multiple surveys.

Mbcontour, mbswath, mbgrdtiff: Included fixes suggested by Joaquim Luis for compatibility with the next GMT5 release.

Mbclean: Removed -M3 and -M4 options that previously caused the program to null (or zero) rather than flag bad soundings. This is an obsolete feature that only made sense prior to existence of mbprocess.

Mbackangle: Fixed mbm_grdplot call to no longer use an obsolete option.

5.5.2237 (March 23, 2015)

Mbnavadjust, mbnavedit: Removed references to GMT and netCDF in the Makefile.am file in both source directories.

5.5.2236 (March 23, 2015)

Mbnavadjust, mbnavadjustmerge: Added a new type of constraint referred to as a global tie. Each data section can have one of its navigation points tied to the fixed global frame of reference with a specified x, y, z offset (or just x and y, or just z) and x, y, and z uncertainties in the offset values. These global ties are set using mbnavadjustmerge. The relevant mbnavadjustmerge commands are: `--set-global-tie=file:section[:snav]/xoffset/yoffset/zoffset[/xsigma/ysigma/zsigma] --set-global-tie-xyz=file:section[:snav] --set-global-tie-xyonly=file:section[:snav] --set-global-tie-zonly=file:section[:snav]`

Mbnavadjustmerge: Added ability to unset (delete) global ties and crossing ties. The relevant mbnavadjustmerge commands are: `--unset-global-tie=file:section --unset-tie=file1:section1/file2:section2`

Mbnavadjust, mbnavadjustmerge: Explicitly added references to libgmt and libpsl in the src/mbnavadjust/Makefile.am file so that the mbnavadjust and mbnavadjustmerge executables are linked to those libraries. This is to solve a mysterious dependency of mbnavadjust on libgmt on CentOS6 - the program was failing due inability to find libgmt.so.5 even though the code does not reference any GMT or GMT5 function or header file. Presumably this change will go away when the mystery is solved.

Mbsslayout: fixed automatically generated plottin script.

mbm_route2mission: Added multibeam maximum range value.

5.5.2234 (March 5, 2015)

Plot macros (mbm_grdplot, mbm_grd3dplot, mbm_grdtiff, mbm_histplot, mbm_plot, mbm_xyplot): Now generate plotting scripts that will not attempt to display the plot on the screen if invoked with a "-N" command line argument.

Format 64 (MBF_MR1PRVR2): Added include of `<sys/time.h>` in mbbs_defines.h to facilitate building under cygwin.

Multi-macros (mbm_multiprocess, mbm_multicopy, mbm_multidatalist):
Changed to use datalist.mb-1 as default input and to use 4 as the default number of CPUs.

Mbedit: Added fast scroll through a file if the forward or back mouse buttons are held down more than 2 seconds.

Mbextractseg, mbsslayout: Changed output section/line plotting script so that it will not attempt to display the plot on the screen if invoked with a "-N" command line argument.

Mbprocess: Reduced informational output when not in verbose mode to make the output from use of mbm_multiprocess cleaner.

5.5.2233 (February 23, 2015)

Release 5.5.2233

mbm_grdplot, mbm_grdtiff: Generated plot scripts now set foreground and background colors based on the -D option.

Mbmroute2mission: Now allows the maximum planned climb rate of the AUV to be specified with the -U option

5.5.2232 (February 21, 2015)

mbm_plot, mbm_grdplot, mbm_grd3dplot, mbhistplot: Changed handling of gmt defaults so that any local gmt.conf file is deleted before any gmtset calls are made, and the resulting gmt.conf file is deleted before the plot script ends.

Mbswath: fixed calculation of beam or pixel footprints in mode requesting real footprint plotting.

5.5.2231 (February 20, 2015)

Mb7kpreprocess: Switched beam angle calculation to the mb_beaudoin() function already used by mbkongsbergpreprocess (contributed by Jonathan Beaudoin).

mbm_bpr: Made compatible with GMT5.

5.5.2230 (February 18, 2015)

Mbgrdtiff: Fixed ordering of rows and columns in the output image.

mbm_route2mission: Added output of a mission altitude profile plot.

Mbauvloglist: Added capability of binary output.

Mb7kpreprocess: Fixed so that bathymetry calculation uses roll merged at the bottom detect time for all of the possible combinations of Reson 7k data record types.

Mbpreprocess: Fixed to exclude zero longitude or latitude values from the tables used for interpolation onto ping times.

Mbrolltimelag: Fixed automatically generated roll-slope correlation plot.

5.5.2229 (February 14, 2015)

Format 121 (MBF_GSFGENMB): The i/o module will now allocate and initialize arrays of beamflags and alongtrack distance when those are not included in the input file.

Mbfilter: removed failing check for existence of sidescan data.

Mbsegygrid: flipped grid convention for compatibility with GMT5.

mbm_plot, mbm_grdplot, mbm_grd3dplot, mbm_histplot: further changes for compatibility with GMT5.

mbm_route2mission: Compatibility with GMT5.

Mbcontour, mbswath: More changes for compatibility with GMT5.

5.5.2228 (February 6, 2015)

Install_makefiles: the old install_makefiles build system no longer functions and has been removed.

Mbgrid: When using the two-step weighted footprint slope algorithm, mbgrid only reads files on the second pass through the input datalist that contained useful data in the first pass.

Major changes made to integrate MB-System with GMT5: The code will no longer compile or work with GMT4.5. Changes include: -updating functions in libmbaux that read and write GMT grids -deletion of src/mbaux/mb_pslibface.c -changes to all programs that read or write GMT grids, -the former programs mbcontour, mbswath, and mbgrdtiff are now GMT5 modules built as part of a shared library. -changes to all of the plot macros (e.g. mbm_grdplot) that make use of GMT

Format 88 (MBF_RESON7KR): Update Reson 7k i/o module to handle TVG records.

////////////////////////////////////

MB-System Version 5.4 Releases and Release Notes:

////////////////////////////////////

- **Version 5.4.2220 January 22, 2015 (Last GMT4-compatible archive revision)**
- Version 5.4.2219 December 11, 2014
- Version 5.4.2218 December 4, 2014
- Version 5.4.2217 December 1, 2014
- **Version 5.4.2213 November 13, 2014**
- Version 5.4.2210 November 10, 2014
- **Version 5.4.2209 November 4, 2014**
- **Version 5.4.2208 October 29, 2014**
- Version 5.4.2204 September 5, 2014
- **Version 5.4.2202 August 25, 2014**
- Version 5.4.2201 August 20, 2014
- **Version 5.4.2200 July 24, 2014**
- **Version 5.4.2199 July 19, 2014**
- Version 5.4.2196 July 14, 2014
- Version 5.4.2195 July 9, 2014
- Version 5.4.2194 July 8, 2014
- **Version 5.4.2191 June 4, 2014**
- **Version 5.4.2188 May 31, 2014**
- Version 5.4.2187 May 28, 2014
- Version 5.4.2186 May 26, 2014
- Version 5.4.2185 May 11, 2014
- **Version 5.4.2183 April 16, 2014**
- Version 5.4.2182 April 8, 2014
- Version 5.4.2181 April 4, 2014
- **Version 5.4.2176 March 18, 2014**
- **Version 5.4.2168 February 19, 2014**
- **Version 5.4.2163 January 31, 2014**
- Version 5.4.2162 January 24, 2014
- **Version 5.4.2159 January 18, 2014**
- Version 5.4.2158 January 18, 2014
- **Version 5.4.2157 October 14, 2013**
- Version 5.4.2155 October 13, 2013
- Version 5.4.2154 September 26, 2013
- Version 5.4.2153 September 22, 2013
- **Version 5.4.2152 September 16, 2013**
- Version 5.4.2151 September 12, 2013

- Version 5.4.2149 September 2, 2013
- Version 5.4.2148 August 28, 2013
- Version 5.4.2147 August 27, 2013
- Version 5.4.2144 August 26, 2013
- Version 5.4.2143 August 24, 2013
- Version 5.4.2141 August 24, 2013
- Version 5.4.2139 August 19, 2013
- Version 5.4.2138 August 18, 2013
- Version 5.4.2137 August 9, 2013
- Version 5.4.2136 August 8, 2013
- **Version 5.4.2135 August 7, 2013**
- Version 5.4.2133 July 29, 2013
- Version 5.4.2132 July 26, 2013
- Version 5.4.2130 July 20, 2013
- Version 5.4.2129 July 8, 2013
- Version 5.4.2128 June 18, 2013
- Version 5.4.2123 June 10, 2013
- Version 5.4.2082 May 24, 2013

////////////////////////////////////

5.4.2219 (December 11, 2014)

Mbnavadjust: Fixed fixed memory management issue related to fbt files.

Mb7kpreprocess: Moved toward correct handling of sensor offsets.

Mbpreprocess: Moved toward correct handling of sensor offsets.

5.4.2218 (December 4, 2014)

Mbinfo: Fixed JSON format output to file (previously missed final closing bracket).

5.4.2217 (December 1, 2014)

Mbclean: Implemented additional flagging tests contributed by Suzanne O'Hara, including speed range (-Pspeed_min/speed_max), ping navigation bounds (-Rwest/east/south/north), and zero longitude and latitude values (-Z). Also, a minimum depth at nadir test embedded by Dana Yoerger for all data (circa 2010) has been recast into a minimum range test option (-Krange_min).

Format 71 (MBF_MBLDEOIH) and fbt files: fixed a problem with the i/o module as updated in 5.4.2216.

5.4.2216 (November 30, 2014)

Format 251 (MBF_PHOTGRAM): We have added a new data format and associated data system supporting photogrammetric topography calculated from stereo pair photographs. This format includes navigation and attitude data. Each 2D group of bathymetry values is derived with a single stereo pair. A file consists of a sequence of stereo pair bathymetry, each set of which has a timestamp, navigation and attitude as well as bathymetry values. The format 251 files are generated from stereo pairs (and navigation and attitude data) by a set of tools that are not currently in MB-System, but which will be added to MB-System in the future.

Mbeditviz and Mbgrdviz: Now allow selection of a single navigation point.

Mbeditviz and mbgrid: Now handle point topography data (e.g. xyz soundings, lidar soundings, photogrammetry topography) differently than multibeam soundings even when the footprint algorithm is specified. Point data are now treated as such, and no longer are associated with nonsensical beam footprints.

Format 71 (MBF_MBLDEOIH) and fbt files: We have defined a new data record header (version 5) that represents the number of bathymetry beams, amplitude beams, and sidescan pixels as four-byte int values rather than two-byte short values. This supports data constructs that have more than 32768 bathymetry values, as can be the case for dense photogrammetry data derived from stereo-pair photography. The i/o module only uses the version 5 header when there are more than 32768 bathymetry values in the associated sonar ping, lidar scan, or photographic stereo pair. Otherwise, the previously existing version 4 header is used. Consequently, for all previously supported data types there will be no change to the MBF_MBLDEOIH format or to fbt files.

General: MB-System now defines several types of bathymetry data:

MB_TOPOGRAPHY_TYPE_UNKNOWN 0

MB_TOPOGRAPHY_TYPE_ECHOSOUNDER 1

MB_TOPOGRAPHY_TYPE_MULTIBEAM 2

MB_TOPOGRAPHY_TYPE_SIDESCAN 3

MB_TOPOGRAPHY_TYPE_INTERFEROMETRIC 4

MB_TOPOGRAPHY_TYPE_LIDAR 5 MB_TOPOGRAPHY_TYPE_CAMERA

6 MB_TOPOGRAPHY_TYPE_GRID 7 MB_TOPOGRAPHY_TYPE_POINT 8

The immediate utility of differentiating between data types is to allow gridding algorithms to handle data appropriately. As discussed above, the footprint gridding algorithms are now only applied by mbgrid or mbeditviz to

multibeam bathymetry. Other differences in data processing will be added in the future.

General: The sort function and related comparison function declarations in MB-System have been corrected to be consistent with `qsort()` from `stdlib`.

5.4.2213 (November 13, 2014)

Mbkongsbergpreprocess: Added `-E` option to allow specification of offsets between the depth sensor and the sonar. This is relevant only to submerged platforms such as AUVs or ROVs. Also added `-P` option to enable filtering of pressure depth data.

Format 59 (MBF_EM710MBA): Set the navigation and attitude source records to be survey data so that `mbnavedit` and `mbnavlist` work by default with values from the survey records rather than asynchronous raw sensor data. The navigation and attitude sources for format 58 (MBF_EM710RAW) remain the asynchronous records.

Mbnavedit: Strictly define the font definitions for pushbutton widgets (some X11 environments are making bad choices when given latitude).

5.4.2210 (November 10, 2014)

Mbkongsbergpreprocess: Changed handling of water column records. The default behavior is now to not write water column records to the output format 59 files. Users can specify `-W1` to have the water column records written in the output files.

Format 41 (MBF_SB2100RW): Bug fix for Seabeam format 41 so the code handles records without the maximum number of beams. Contributed by Bob Covill.

Mbprocess: Added ability to apply static bathymetry corrections defined according to beam angle in addition to corrections according to beam number. Contributed by Bob Covill.

Mbvelocitytool: When loading a swath file, `mbvelocitytool` will now also read in and apply an associated `*.esf` (edit save file) if it exists. This prevents soundings that have been identified as bad from biasing the calculations. Contributed by Bob Covill.

mbm_grdcut: Fix to the manual page. Contributed by Jenny Paduan.

5.4.2209 (November 4, 2014)

MBnavadjustmerge: Completed the manual page for this new program that allows one to merge and manipulate MBnavadjust projects.

Formats 58 (MBF_EM710RAW) and 59 (MBF_EM710MBA): Recast the i/o architecture to handle the full variability of multibeam data in these formats.

5.4.2208 (October 29, 2014)

Mbkongsbergpreprocess: Fixed calculation of beam takeoff angles for raytracing from the raw range and angle data records by including code made available by Jonathan Beaudoin. Recalculation of bathymetry in current generation Kongsberg multibeam data appears to work now.

Formats 58 (MBF_EM710RAW) and 59 (MBF_EM710MBA): Support Mesotech M3 multibeam data recorded in *.all files.

Formats 58 (MBF_EM710RAW) and 59 (MBF_EM710MBA): Fixed calculation of beam takeoff angles for raytracing from the raw range and angle data records by including code made available by Jonathan Beaudoin. Recalculation of bathymetry in current generation Kongsberg multibeam data appears to work now.

5.4.2204 (September 5, 2014)

Mb7kpreprocess: Changed handling of roll, pitch, and heave compensation to deal with deep water Reson 7150 data.

Format 88 (MBF_RESON7KR): Changed handling of roll, pitch, and heave compensation to deal with deep water Reson 7150 data.

Mbdefaults: Added control of default color and shading settings for mbgrdviz and mbeditviz.

Format 231 (MBF_3DDEPTH): Fixed the mbsys_3datdepthlidar_insert_nav() function to apply changes to all pulses.

Mbgrdviz and Mbeditviz: Default color and shading settings now can be set using mbdefaults.

5.4.2202 (August 25, 2014)

Format 88 (MBF_RESON7KR): Enlarged the maximum number of beams to 1024 in order to handle 7150 data with >800 beams.

Format 21 (MBF_HSATLRAW): Augmented to trim trailing blank space at the end of lines before parsing - this allows reading Hydrosweep DS data in the form held by NIO.

5.4.2201 (August 20, 2014)

mbm_grdplot: Added two "sealevel" color palletes that use Haxby colors for negative values (e.g. topography below sea level) and either greens or browns for positive values (e.g. topography above sea level). The Sealevel 2 palette was contributed by Jenny Paduan.

Mbeditviz: Changed default illumination parameters to magnitude=1.0 and elevation=5.0.

Mbgrdviz: Changed default illumination parameters to magnitude=1.0 and elevation=5.0.

Mbnavadjust: Added views for 10% coverage crossings.

Mb7kpreprocess: Added kluge function to "tweak" the beam angles as if the speed of sound used for beamforming had been wrong.

5.4.2200 (July 24, 2014)

Format 121 (MBF_GSFGENMB): Fixed bug in which null sensor depth and altitude values are handled incorrectly.

5.4.2199 (July 20, 2014)

Format 121 (MBF_GSFGENMB): Modified GSF 3.06 source files gsf.c gsf_idx.c to disable recasting of fundamental file io functions (fopen(), fseek(), ftell(), stat()) when the compile flag -DUSE_DEFAULT_FILE_FUNCTIONS is defined. This allows MB-System builds to just use the normal file functions without changing the build behavior of the code in other contexts. The issue is that Leidos is supporting 64-bit file i/o in binaries for 32-bit architectures. The consequence of this change in MB-System is that MB-System will not support GSF files that are 2 GB or larger when built on or for 32-bit systems.

mbpreprocess: Fixed bug in merging of asynchronous attitude data. This program is not ready for general use.

5.4.2196 (July 14, 2014)

mbotps: Added -P option to specify the location of the OTPS package.

mbsslayout: Made to work (again) with Reson 7k data with embedded Edgetech sidescan and subbottom data.

mb7kpreprocess: Made to work (again) with Reson 7k data with embedded Edgetech sidescan and subbottom data.

mbextractseg: Made to work (again) with Reson 7k data with embedded Edgetech sidescan and subbottom data.

5.4.2195 (July 9, 2014)

Format 88 (MBF_RESON7KR): Fixed bug in mbsys_reson7k_extract_altitude().

Format 132 (MBF_EDGJSTAR): Added mbsys_jstar_insert_altitude() to support mbpreprocess and mbsslayout. Fixed handling of heading on extract and insert.

mbm_route2mission: Removed confusing juxtaposition of estimated AUV mission time with actual AUV mission termination time in the output AUV mission script.

mbpreprocess: Added ability to merge altitude data. Tested successfully with raw Edgetech sidescan data collected without embedded navigation, attitude, or anything really.

mbsslayout: A new program to lay out raw sidescan onto the seafloor, most often on a 3D seafloor topographic model. Achieved functionality, at least for use with Edgetech sidescan data in Jstar format.

5.4.2194 (July 8, 2014)

Format 121 (MBF_GSFGENMB): Updated source files in src/gsf/ to GSF release 3.06.

Format 121 (MBF_GSFGENMB): Fixed scaling of array values in GSF files to allow depth and distance resolutions better than 1 cm.

Formats 58 (MBF_EM710RAW) and 59 (MBF_EM710MBA) to support EM2040D data, in which dual sonars ping simultaneously.

5.4.2191 (June 4, 2014)

Install_makefiles: Fixed old build system so that it successfully compiles and links the new, unfinished program mbsslayout.

5.4.2189 (June 4, 2014)

Format 121 (MBF_GSFGENMB): Fixed bug that caused programs reading GSF data to hang when the GSF file ends with a partial or corrupted data record.

MBeditviz: Added capability to set the color of selected soundings (e.g. soundings associated with a particular file or particular section of trackline).

Format 88 (MBF_RESON7KR): Added support for pitch stabilization.

MB7kpreprocess: Added support for pitch stabilization in Reson 7k data.

5.4.2188 (May 31, 2014)

Format 121 (MBF_GSFGENMB): Fixed bug that caused crashes when the GSF file contains a zero length comment.

Format 64 (MBF_MR1PRVR2): Fixed bug that caused crashes when copying data from MR1 file to an fbt file when comments are longer than supported in fbt files.

MBnavadjust: Fixed bug that reset the selected survey while doing autopicks.

5.4.2187 (May 28, 2014)

Format 201 (MBF_HYSWEEP1): Added code to ignore bad RMB records found in some NOAA HSX data.

Format 88 (MBF_RESON7KR): Support for calibrated snippet records (contributed by David Finlayson).

MB7kpreprocess: Support for calibrated snippet records (contributed by David Finlayson).

MBnavadjustmerge: Fixed to handle projects not in the current working directory.

5.4.2186 (May 26, 2014)

MBeditviz: Fixed interactive application of pitch bias and heading bias changes.

MBnavadjustmerge: New program to merge two existing MBnavadjust projects.

5.4.2185 (May 17, 2014)

MBrolltimelag: Now checks for case when all beams are flagged.

MBlist: Added beamflag values to those that can be printed ('F' or 'f').

Bathymetry editing: Fixed bug that prevented successful flagging of some beams when files include simultaneous pings with different numbers of beams.

GSF library: Updated to new release 03.05. This release is licensed using LGPL 2.1.

5.4.2185 (May 11, 2014)

Several programs: Fixed formatting error in printing system time_tm.tv_sec values.

MBsvpselect: Fixed sscanf format warning.

MBcopy: Fixed array dimensioning bug that occasionally caused buffer overflows.

MBnavadjust: Moved some declarations from mbnadjust_prog.c to mbnadjust.h in preparation for breaking project i/o out into a separate source file to be shared with the new program mbnadjustmerge.

MBsslayout: Added shell of program under development to read sidescan in raw time series form, lay the sidescan out regularly sampled on a specified topography model, and output the sidescan to format 71 (MBF_MBLDEOIH) files.

HSDDS formats (MBF_HSATLRAW, MBF_HSLDEDMB, MBF_HSURIVAX, MBF_HSURICEN): Fixed bug in handling of system gain arrays (16 rather than 59 values).

MBsegygrid: Attempted to incorporate actual nonvertical geometry into the subbottom sections - not satisfactory yet.

MBrolltimelag: Fixed bug regarding the default roll source. The program will now work with roll values derived from survey records by default.

Format 88 (MBF_RESON7KR): Cleaned up some debug print statements.

MBinsreprocess: Incomplete new MB6 program to reprocess INS data of various sorts to improve on realtime Kalman filtered navigation and attitude data.

MBsslayout: Incomplete new MB6 program to perform layout of time series sidescan onto a 3D topography model. This will replace mb7k2ss and extend the functionality to conventional sidescan data in several data formats.

mbm_route2mission: Fixed output AUV mission script to have "\r\n" line ends on all lines.

Format 222 (MBF_SWPLSSXP): Revised implementation of SEA SwathPlus SXP data format (format id 222) contributed by David Finlayson.

Format 121 (MBF_GSFGENMB): Changed the source for the internally supplied GSF library to be the new 3.05 release. This includes for the first time a proper open source license (LGPL 2.1).

5.4.2184 (April 22, 2014)

src/bsio/Makefile.in: Added to archive (previously mistakenly left out).

5.4.2183 (April 16, 2014)

Many programs: Fixed handling of system time character string provided by function ctime() to prevent occasional overflows.

Format 222 (MBF_SWPLSSXP): Revised implementation of SEA SwathPlus SXP data format (format id 222) contributed by David Finlayson.

MBswplspreprocess: Preprocess program for SEA SwathPlus SXP data format (format id 222) contributed by David Finlayson. This was formerly known as mbsxppreprocess.

5.4.2182 (April 8, 2014)

Format 231 (MBF_3DDEPTH): Added new raw Lidar record to be used by 3DatDepth.

Format 201 (): Corrected bug in handling of navigation in projected coordinate systems.

mbio/mb_navint.c and mbio/mb_define.h: Added a new function mb_navint_prjinterp() that interpolates navigation and speed from internal runnings lists assuming the navigation is in eastings and northings rather than longitude and latitude.

5.4.2181 (April 4, 2014)

Release 5.4.2181

htmlsrc/mbsystem_home.html & htmlsrc/mbsystem_faq.html: Actually committed pictures of Christian Ferreira and Krystle Anderson to the archive

5.4.2180 (April 2, 2014)

htmlsrc/mbsystem_home.html & htmlsrc/mbsystem_faq.html: Updated references to the MB-System team in the html documentation to include Christian Ferreira and Krystle Anderson.

htmlsrc/mbsystem_how_to_get.html: Updated installation instructions in the html documentation.

MB7kpreprocess: recoded the application of time domain filtering of pressure depth data to be much more efficient.

Format 132 (MBF_EDGJSTAR): Supported obsolete sidescan records with 80 byte traceheaders.

MBextractseg: Now works with Edgetech Jstar files.

MBauvloglist: reset default printing of timestamp values.

Mbset: modified so that when mbset is used to turn off a mode that implies use of an external file, the associated filename is also erased. For example mbset -PSVPMODE:0 will now also erase (null) the filename set by -PSVPFILE.

mbm_grd3dplot, mbm_grdplot, mbm_histplot, mbm_plot, mbm_xyplot: added support for the evince postscript viewer.

Format 172 (MBF_HIR2RNAV) and format 173 (MBF_MGD77TXT): fixed segmentation faults while handling comment records.

MBlist: The 'N' output option will now use actual ping numbers if those are available (instead of ping count in the file).

MBroutetime: Now exits with error message if no start line or end line waypoints are read from the input route file.

5.4.2176 (March 18, 2014)

Release 5.4.2176

5.4.2175 (March 18, 2014)

Configure.ac: Removed reference to src/mbsvptool (src/mbsvptool/mbsvptool.c was moved to src/utilities/mbsvpselect.c for 5.4.2173).

MBnavadjust: The program generates route files of crossings and ties that can be viewed in mbgrdviz. The coloring of the crossings and ties when displayed in mbgrdviz has changed. The route files generated are: True Crossings (unfixed) >50% Crossings (unfixed) >25% && <50% Crossings (unfixed) <25% Crossings (unfixed) Ties (unfixed) Ties (fixed) For the crossing files, individual crossings are colored as: Unset - Red Skipped - Yellow Set - Green For the tie files, individual ties are colored as: Ties (unfixed) - Blue-Green Ties (fixed) - Purple

All source files: Updated copyright notices to 2014.

5.4.2173 (March 17, 2014)

MBsvpselect: Added program contributed by Ammar Aljuhne and Christian Ferreira of MARUM (University of Bremen). This program chooses and implements the best available sound speed model for each swath file in a survey. The user provides a list of the available sound speed models and specifies the criteria used for model selection. The program uses mbset to turn on bathymetry recalculation by raytracing through the sound speed model selected for each swath file.

MBsvplist: The SVP files output by mbsvplist now include a header line that is recognized by mbsvpselect. This header line includes the time stamp and position associated with the SVP record's location in the swath file.

MBpreprocess: Added an incomplete manual page for this incomplete MB-System 6 program.

5.4.2172 (March 14, 2014)

MBmosaic: Added option to apply priorities based on the platform heading.

Format 64 (MBF_MR1PRVR2): Hawaii Mapping Research Group (HMRG) data format updated to use the current library and thereby support post-2005 data. Removed old HMRG mr1pr library from mbsystem/src and added current bsio library.

MBgrdviz: Modified handling of routes so that if a route header contains a line like: ## ROUTEEDITMODE:0 then the route cannot be changed in MBgrdviz.

MBnavadjust: Changed so that when a project is output, mbnavadjust writes out five different route files in which each tie point or crossing is a two point route consisting of the connected snav points

- route files of ties (fixed and unfixed separate) represent each tie as a two point route consisting of the connected snav points
- route files of crossings (<25%, >= 25% && < 50%, >= 50%, true crossings) represent each crossing as a two point route consisting of the central snav points for each of the two sections.

Mbvelocitytool: made all filename and command strings type mb_path, which is a 1024 byte char array.

Format 173 (MBF_MGD77TXT): Added format to read and write MGD77 format underway geophysical data files with "\n" characters at the ends of the data records.

Format 174 (MBF_MGD77TAB): Added format to read and write MGD77T format underway geophysical data files with tab delimiters and "\n" characters at the ends of the data records.

5.4.2168 (February 19, 2014)

Mbinfo: Fixed bug in variance calculation (memory overwrites of the relevant arrays).

5.4.2165 (February 18, 2014)

Format 241 (MBF_WASSPENL): Made format suffix ".000" recognizable as format 241.

5.4.2164 (February 15, 2014)

Format 241 (MBF_WASSPENL): added new format for WASSP multibeam sonar.

Format 151 (MBF_OMGHDCSJ): applied patch supplied by Bob Covill.

Mbrolltimelag: fixed so that the program works with data formats for which the roll source is the survey records.

Mbauvloglist: added capability to merge navigation from external files.

5.4.2163 (January 31, 2014)

Format 71 (MBF_MBLDEOIH): fixed a recently introduced error in scaling of bathymetry values. This error impacts the fbt files, and consequently will mess up bathymetry gridding and plotting. It's important to update installations to 5.4.2163.

MBextractseg: Fixed so correct navigation is inserted in both the source and group position fields in the segy traceheader.

5.4.2162 (January 24, 2014)

Format 88 (MBF_RESON7KR): fixed crash when generating sidescan from pings with no valid beams.

Format 201 (MBF_HYSWEEP1): fixed crash when generating sidescan from pings with no valid beams.

Build system: Altered so the configure script works with standard options.

5.4.2161 (January 21, 2014)

MBedit: fixed use of beamflag setting macros that were messed up yesterday.

5.4.2160 (January 20, 2014)

General: fixed many compiler warnings.

General: implemented changes suggested by Joaquim Luis in order to enable building MB-System on Windows systems.

5.4.2159 (January 18, 2014)

Release 5.4.2159.

5.4.2158 (January 18, 2014)

Many changes, including:

- Support for new format of lidar data
- Fixes to support swath data with sub-cm lateral resolution
- Fix so that mbnadjust works when built with shared libraries.
 - this involved changes to the contouring code in the mbaux library.
- Augmentation of the AUV mission planning capability
- Improvement to mbm_grdplot output for maps of small areas

- Fixes to the configure build system
 - now allows MB-System to be built using an externally installed libproj or the proj library bundled with MB-System
 - using --disable-gsf now works properly to build without any use of or entanglement with libgsf.

5.4.2157 (October 14, 2013)

mbm_makesvp: New macro to extract sound speed and depth data from a datalist of swath files, and generate a sound velocity profile model from averages of the sound speed values in regular depth ranges. This macro uses mbctdlist to extract the sound speed values embedded in swath data files is intended for use with mapping data from submerged platforms (e.g. ROVs and AUVs) carrying CTD or sound speed sensors.

5.4.2155 (October 13, 2013)

MBvelocitytool: Fixed problems with bad calculations after loading more than one swath data.

MBgrdtiff, mbm_grdtiff: Added capability to output a *.tfw "world" file parallel to the GeoTiff image. Some software does not recognize the coordinate system information embedded in the GeoTiff file.

MBsegygrid: Added capability for simple time domain low-pass filtering.

MBrphsbias: Added incomplete new program that will, when complete, use a brute force multidimensional search obtain optimized estimates for bias parameters from a specified dataset. There is no documentation yet as the program currently does nothing but compile and read data.

5.4.2154 (September 26, 2013)

MBkongsbergpreprocess, MB7kpreprocess, MBhysweepprocess, mbprocess: Fixed errors in navigation interpolation introduced in 5.4.2152.

Format 84 (MBF_XTFR8101): Fixed initialization of the storage data structure.

Committed from CCGS Sir Wilfrid Laurier at 116d 04.4876' W, 68d 57.30' N.

5.4.2153 (September 22, 2013)

Format 201 (Hysweep HSX): fixed sign error in handling of pitch values.

5.4.2152 (September 16, 2013)

Formats 58 (Kongsberg raw), 59 (Kongsberg extended), 88 (Reson 7k): Fixed problem with interpolation of heading for Kongsberg and Reson data. Eliminated possibility of negative headings being inserted into the storage data structure.

Format 222: Inserted initial implementation of SEA SwathPlus sxp data format (format id 222) contributed by David Finlayson with minor changes. This format support is still developmental.

Build system: Applied patch contributed by Frank Delahoyde with additional fixes to configure.ac and the src/*/Makefile.am files.

5.4.2151 (September 12, 2013)

Many *.c files: hundreds of small changes to eliminate compiler warning messages on various types of systems.

Build system: Changes to configure.ac, autogen.sh, and src/*/Makefile.am files based on suggestions from Frank Delahoyde of SIO and Kurt Schwehr of Google.

5.4.2149 (September 2, 2013)

Src directories src/mbio and src/utilities: Fixed a number of debug print statements that treated pointer values as %ul rather than %p.

5.4.2148 (August 28, 2013)

Buildsystem: More tweaking of configure.ac file, including making the comments output more sensible.

5.4.2147 (August 27, 2013)

Buildsystem: More tweaking of configure.in file trying to get MB-System to build on Ubuntu 12.04.02LTS. Moved configure.in to configure.ac to conform to current autoconf file naming conventions.

5.4.2144 (August 26, 2013)

Buildsystem: Added src/mbgrdviz/Makefile.in and src/mbeditviz/Makefile.in to the subversion source archive.

Format 201 (Hysweep HSX): Changed mbr_rt_hysweep1() in mbr_hysweep1.c so that survey records without navigation and/or attitude

data do not have an error set. This means that data missing nav and/or attitude will still be processable.

Format 121 (GSF): Now recognizes and appropriately treats null values for position, attitude, speed, and sonar depth.

5.4.2143 (August 24, 2013)

MBsxppreprocess: Added nonfunctional stub for program mbsxppreprocess to be developed by David Finlayson.

5.4.2141 (August 24, 2013)

Build system, MBgrdviz, MBeditviz, MBview: Moved source files for MBgrdviz and MBeditviz from src/mbview to src/mbgrdviz and src/mbeditviz, respectively. This move separates the application source files for MBgrdviz and MBeditviz from the source files of the mbview library.

5.4.2139 (August 19, 2013)

Build system: Further modification to the src/mbview/Makefile.am file.

5.4.2138 (August 18, 2013)

Build system: Further modifications to the Makefile.am files.

MBopts: Now allows users to specify the tide model used by OTPS. Also now works with all three variants of the OTPS package.

MBareaclean: Fixed memory allocations problems.

MBgrdviz: Added capability to launch mbnavedit and mbvelocitytool on selected swath data (contributed by Christian Ferreira).

5.4.2137 (August 9, 2013)

Build system: Still attempting to fix problems with the autoconf build system on Ubuntu machines. Change mbsystem/src/opts/Makefile.am so that building this utility does not depend on GMT libraries (since it doesn't).

5.4.2136 (August 8, 2013)

Build system: Attempted to fix problems with the autoconf build system on Ubuntu machines. Reset the automake version to 2.65 from 2.69 as specified in the mbsystem/configure.in file. Also added a conditional

reference to libmbgsf to the requirements for mbcopy in mbsystem/src/
utilities/Makefile.am.

5.4.2135 (August 7, 2013)

Mbdatalist: Fixed generation of old-format fbt files.

Web page documentation: Updated basic web pages included in the
distribution.

5.4.2134 (July 31, 2013)

Heading and nav interpolation (src/mbaux/mb_spline.c): Fixed function
mb_linear_interp_degrees() so that negative latitude values are allowed.

Mbkongsbergpreprocess: Added checking so that interpolated heading and
navigation are in the correct domains.

5.4.2133 (July 29, 2013)

Heading and nav interpolation (src/mbaux/mb_spline.c): Modified function
mb_linear_interp_degrees() so that return values must be in the range $0.0 \leq \text{value} < 360.0$ to fix bad heading values near due north.

Mbclean: added -Ttolerance option which will recast the timestamps of edit
events read from edit save files to match the pingtimes, where the tolerance
value in seconds defines how close the timestamps must be to be
considered the same. This is used to override timestamp differences greater
than 0.0011 seconds that can arise when edits are extracted from one set of
files (perhaps processed using software other than MB-System) using
mbgetesf and then applied to a different set of files (presumably as part of
MB-System processing).

5.4.2132 (July 26, 2013)

Format 88 (Reson s7k): Fixed layout of snippet backscatter into sidescan in
the near-nadir region.

Format 88 (Reson s7k): Mbprocess now routinely recreates multibeam
sidescan during processing. This allows backscatter from beams flagged as
bad to be excluded from the multibeam sidescan.

Mbinfo: Fixes to XML output from mbinfo (Christian Ferreira)

Format 201 (Hysweep): Substantially changed i/o logic to handle the many different variants of data logged through Hysweep.

Format 201 (Hysweep): Augmented to handle sidescan data in conjunction with multibeam bathymetry. The i/o module will lay the raw sidescan out on the bathymetry to generate "processed" sidescan. That will be included in any output file as MSS records (an MB-System extension to the HSX format), which can be corrected and filtered in the usual way.

Format 88 (Reson s7k): Fixed bug in which sidescan generated from backscatter records was flipped port to starboard. Also fixed layout of backscatter in the near-nadir region.

5.4.2129 (July 8, 2013)

Build system: Attempted to implement changes to the build system suggested by Kurt Schwehr and Hamish Bowman.

Mbrolltimelag: Augmented to allow specification of the time lag interval used in correlation calculations with arbitrary start and end times.

Mbnavlist: Fixed problems with outputting attitude data from some variants of Kongsberg data.

Mbgrid: Changed the convergence criteria for the zgrid interpolation algorithm to simply be that the largest change in the grid value is no more than 1 mm.

Formats 56 and 57: Augmented handling of Kongsberg EM1002 data to recognize and fix erroneous transmit and receive beamwidth values.

Mbprocess and mbvelocitytool: Augmented raytracing code to handle high angle rays without rounding errors producing a square root of a negative number. This fixed problems with sample EM1002 data.

5.4.2128 (June 18, 2013)

Mblist: Fixed bug that flagged as bad all sidescan pixels with negative values.

src/mbio/projections.h and src/utilities/levitus.h: Removed from svn version control as these are created during the build process.

Build system: Implemented changes to the build system contributed by Kurt Schwehr that enable building MB-System without support for GSF or inclusion of the GSF source code from SAIC. This optional removal of GSF

support addresses the lack of a proper open source or free software license for the GSF source code distribution from SAIC. MB-System distributions that include GSF code or require the GSF library cannot be included in official open source package collections such as Debian.

Mbgrid: Changed the usage of the zgrid interpolation by mbgrid. Release 5.3.1989 included changes to speed up interpolation by calculating a smooth model for a low resolution grid and then resampling this onto the full resolution grid. This approach has the problem that the low resolution interpolation can work poorly near data. Mbgrid still does low resolution interpolation as part of the slope estimation stage of algorithms 5 and 6 and as part of background interpolation, but once again does the primary interpolation stage at full resolution.

5.4.2123 (June 10, 2013)

Many changes implementing fixes to the new build system from Bob Covill, Hamish Bowman, and Christian Ferreira. Moved key auto-generated header file from mbsystem/src/mbsystem_config.h to mbsystem/src/mbio/mb_config.h.

mbm_route2mission: added support for more than one type of survey behavior in an AUV mission as controlled by waypoint type in the route files exported from mbgrdviz.

Moved program hsdump to mbhsdump.

Fixed some potential buffer overflows and other errors identified by Hamish Bowman.

Changed the header of the mbm_* perl macros to #!/usr/bin/env perl as suggested by Hamish Bowman and Kurt Schwehr.

5.4.2082 (May 24, 2013)

Configure.cmd: Added -DBYTESWAPPED to the recommended pre-options for the configure script on Macs.

MBF_EM710RAW (format 58) and MBF_EM710MBA (format 59): Added EM2045 to the list of supported Kongsberg multibeam sonars (also known as the EM2040D).

5.4.2081 (May 23, 2013)

Build System: Have implemented an autotools-based build system with a configure script, following on the initial work by Bob Covill and others. The

man page and web page documentation have been moved into the source tree. The old install_makefiles build system has been updated to still work.

MB-System Version 5.3 Releases and Release Notes:

- Version 5.3.2053 April 4, 2013
- Version 5.3.2051 March 20, 2013
- Version 5.3.2042 March 12, 2013
- **Version 5.3.2017 March 3, 2013**
- **Version 5.3.2013 January 29, 2013**
- **Version 5.3.2012 January 25, 2013**
- **Version 5.3.2011 January 17, 2013**
- Version 5.3.2010 January 14, 2013
- **Version 5.3.2009 January 10, 2013**
- **Version 5.3.2008 January 6, 2013**
- Version 5.3.2007 January 5, 2013
- Version 5.3.2006 January 4, 2013
- Version 5.3.2005 December 31, 2012
- Version 5.3.2004 December 12, 2012
- Version 5.3.2000 November 14, 2012
- Version 5.3.1999 November 13, 2012
- Version 5.3.1998 November 6, 2012
- Version 5.3.1994 October 27, 2012
- Version 5.3.1988 September 29, 2012
- Version 5.3.1986 September 12, 2012
- **Version 5.3.1982 August 15, 2012**
- Version 5.3.1981 August 2, 2012
- **Version 5.3.1980 July 13, 2012**
- **Version 5.3.1955 May 16, 2012**
- Version 5.3.1941 March 6, 2012
- **Version 5.3.1917 January 10, 2012**
- **Version 5.3.1912 November 19, 2011**
- **Version 5.3.1909 November 16, 2011**
- **Version 5.3.1907 November 9, 2011**
- **Version 5.3.1906 September 28, 2011**

5.3.2062 (May 17, 2013)

Mbprocess: Fixed a couple more mistakes on lines 5659 and 5662 in mbprocess.c.

5.3.2061 (May 16, 2013)

Perl macros: Renamed all perl source files in mbsystem/src/macros by removing the *.pl suffix. This is another change to allow use of the GNU autotools for building MB-System. The easy way for automake to handle executable scripts is to just copy them to the bin directory; renaming the scripts is harder to set up.

5.3.2060 (May 14, 2013)

Mbsvplist: Added -N option to limit the number of SVP profiles that can be output. (contributed by Suzanne O'Hara)

5.3.2059 (May 14, 2013)

Mbprocess: Fixed bug in mbprocess in which angle rotation calculations mixed degrees and radians when attitude is merged as part of an external navigation stream. (Contributed by Bob Covill)

Mbsvplist: Added -T option to output CSV delimited table (contributed by Suzanne O'Hara)

5.3.2056 (May 7, 2013)

Formats 221 and 222: Added empty i/o module files to ultimately support two new formats, both handling data from SEA SWATHplus interferometric sonars: MBF_SWPLSSXI - 221 MBF_SWPLSSXP - 222 The new files include: mbio/mbsys_swathplus.c mbio/mbsys_swathplus.h mbio/mbr_swplssxi.c mbio/mbr_swplssxp.c

5.3.2055 (May 7, 2013)

Many files: fixed issues that result in compiler warnings.

Mb7k2ss: Fixed problem that overwrote the first extracted sidescan line.

Mbgrid: Added gridding algorithm 6, called footprint weighted mean. This differs from algorithm 5, called footprint slope weighted mean, in that it omits the use of the local slope, and thus requires only a single pass through the data.

Format 121 (GSF): Added fix from Christian Ferreira to reset the depth_corrector value to zero if necessary

5.3.2053 (April 4, 2013)

Mb7k2ss: Fixed line breakouts so that the first line is output separate from the second.

Formats 162, 163, 168, 169 (text xyz variants): Fixed i/o modules to handle files with leading white space before the first column.

Mbset: Added -N option to turn off merging of navigation from MBnavadjust and also remove the *.na0 files.

Mbgrid, mbmosaic, mbm_grid: Fixed documentation descriptions of the options controlling the spline interpolation, particularly the tension.

mbm_grdtiff: Fixed the image display program called in the tiff-creating script created by mbm_grdtiff.

Mbdatalist: Recast the output format for the -S option. One now gets a single line of output for each file unless the -V option is also specified.

5.3.2051 (March 20, 2013)

Formats 58 and 59 (mbf): The calculation of "sidescan" from raw backscatter samples has been improved. The sidescan can now be successfully recalculated by mbprocess following application of bathymetry edits.

Mbprocess: Recalculation of Konsberg multibeam sidescan now enabled for formats 58 (mbf_em710raw) and 59 (mbf_em710mba) with command mbset -PSSRECALCMODE:1.

Mbedit: soundings originally flagged by the sonar now return to that state if they are unflagged and then reflagged interactively.

Mbgrdviz: Disabled "goaway" buttons in dialogs to minimize crashes.

Mbeditviz: Disabled "goaway" buttons in dialogs to minimize crashes.

mbm_grdplot: Updated macros to derive system defaults from mbdefaults.

mbm_grdtiff: Updated macros to derive system defaults from mbdefaults.

mbm_histplot: Updated macros to derive system defaults from mbdefaults.

mbm_grd3dplot: Updated macros to derive system defaults from mbdefaults.

mbm_vrefcheck: Updated macros to derive system defaults from mbdefaults.

mbm_plot: Updated macros to derive system defaults from mbdefaults.

5.3.2042 (March 12, 2013)

MBkongsbergpreprocess: Fixed calculation of transmit time for sector subpings.

Format 58 (mbf_em710raw): Improved translation of bottom pick parameters to beam flags.

MBgrdviz: Added export of routes to Hypack Inw format and to degrees + decimal minutes format.

5.3.2017 (March 3, 2013)

Mb7k2ss: Program exits if topography grid specified but reading the file fails.

5.3.2016 (March 2, 2013)

Mb7k2ss: Fixed plotting correlation functions.

mbm_xyplot: Fixed handling of NaN values in input data - no longer includes NaN inputs in sorting to determine min max.

5.3.2015 (March 1, 2013)

Format 88 (mbf_reson7kr): Fixed some debugging print statements of hexadecimal values.

mbm_route2mission: Added command line control of multibeam sonar settings.

Mbprocess: Fixed handling of tide data with just one value.

Mbeditviz: Fixed calculation of corrected attitude and position for pings at start and end of files. Previously badly mislocated pings happened unpredictably.

Mbfilter: Fixed handling of nonfatal read errors.

Format 94 (mbf_l3xseraw): Made storage available for sound speed profiles much larger to handle some ridiculous data samples.

Mbauvloglist: Added code to output readable date and time values if desired.

mbm_xbt: Fixed code to more generally handle actual headers in Sippican MK12 data.

mbox/mb_spline.c: Fixed extrapolation error in linear interpolation code.

Formats 162, 163, 168, 169 (xyz, yxz, xyt, yxt): Augmented code to handle text triples with NaN values.

Mbotps: made /usr/local/otps the default location for the OSU Tidal Prediction Software (OTPS)

Format 21 (mbf_hsatlraw): Fixed failure to initialize the internal storage structure.

5.3.2013 (January 29, 2013)

Format 94 (mbf_l3xseraw): Fixed bug causing memory faults in Linux when data with large svp records are encountered. SVP records can now have as many as 8192 entries.

5.3.2012 (January 25, 2013)

Mbkongsbergpreprocess: Fixed bug causing seg faults on Linux

5.3.2011 (January 17, 2013)

Format 88 (mbf_reson7kr): Removed debug messages left in by mistake

5.3.2010 (January 14, 2013)

Format 88 (mbf_reson7kr): Fixed reporting of angular beam widths, particularly for pre-2009 data in which the alongtrack value was reported incorrectly.

Mbgrid: Changed the weighted footprint algorithm to correctly use the beamwidth scaling parameter set with the -W option.

5.3.2009 (January 10, 2013)

Format 88 (mbf_reson7kr): Fixed a bug introduced at 5.3.2004 in first-time parsing of current Reson 7k data that caused erroneous flagging of some beams.

5.3.2008 (January 6, 2013)

5.3.2007 (January 5, 2013)

Mbkongsbergpreprocess: Fixed -O option to direct all output to a single file.
Mb7kpreprocess: Fixed -O option to direct all output to a single file.

5.3.2006 (January 4, 2013)

Mbkongsbergpreprocess: Fixed -D option to put output files in the specified directory.

5.3.2005 (December 31, 2012)

Mbsvplist: Added -M option to control SVP printing. If mode=0 (the default), then the first SVP of each file will be output, plus any SVP that is different from the previous SVP. If mode=1, then only the first instance of each unique SVP will be output, even through multiple files referenced through a datalist structure. If mode=2, then all SVPs will be output even if they are duplicates (equivalent to the -D option). The -D option is retained for compatibility.

Format 88 (mbf_reson7kr): MB-System now recognizes files with a *.7k suffix as Reson multibeam data in format 88. Usually Reson data are logged to files with a *.s7k suffix.

mbm_route2mission: Updated the calculation of the number of photos to be taken during a Dorado-class AUV bottom photography mission.

Formats 58 (mbf_em710raw) and 59 (mbf_em710mba): Added support for the "Extraparameters" datagram.

Formats 58 (mbf_em710raw) and 59 (mbf_em710mba): Changed the encoding of binary values in the format 58 and 59 files written by MB-System to be little-endian (Intel byte order). The Kongsberg format specification allows byte encoding to be little or big-endian, and previously MB-System has consistently used big-endian.

Mblist: Fixed bug regarding the output of transmit pulse length values.

Mbprocess: Altered mbprocess so that input SVP files are checked for zero thickness layers.

5.3.2004 (December 12, 2012)

Mbsvplist: Added -S option to output surface sound speed from survey data rather

Mb7kpreprocess: Changed lever arm correction specified with the -D option to involve three dimensions rather than just two.

Format 88 (mbf_reson7kr): Fixed so that mbctdlist and mbsvplist can output surface sound speed values from Reson 7k data.

Format 88 (mbf_reson7kr): Fixed so that the storage of bathymetry across track and along track distance values in bathymetry (7006) records is correct. MB-System has output incorrect 7006 records since the Reson 7k format (88) was first supported. The error was that the across track and along track distance values were transposed relative to the format specification and the data output by the PDS2000 datalogger (a reality that only became apparent when I finally had access to a sample of PDS2000-logged data). The format 88 i/o module has been augmented to detect if data being read derives from pre-fix versions of MB-System, and to fix the data if necessary. The existence of this error and its fix should be invisible to users, except that data written by pre-fix MB-System will probably import to other software packages with the across track and along track distances switched.

Mbmosaic: Fixed azimuthal priority weighting so that directional mosaicing is more reliable.

5.3.2000 (November 14, 2012)

Mbinfo: Changed mbinfo to gracefully handle the situation of reading a file that has no data records while the -P option is specified (gracefully means not seg faulting).

Mbmosaic: fixed bug in the use of the azimuth weighting factor.

5.3.1999 (November 13, 2012)

mbm_route2mission: Added multibeam pulse length as a command line argument.

Mbnavadjust: Added capability to solve for a z-offset model in which each survey has a uniform or constant z-offset, and then reset all ties automatically using those z-offsets.

Format 88 (mbf_reson7kr): Fixed bug that caused seg faults with pings that have no valid soundings.

5.3.1998 (November 6, 2012)

Mb7kpreprocess: Added -C option to apply roll bias and pitch bias during preprocessing. Fixed rotation calculations so that side-looking and up looking mapping data can be handled properly.

Mbmosaic: added checks for valid topography grid file.

Mbprocess: Fixed rotation calculations so that side-looking and up looking mapping data can be handled properly.

mbm_route2mission: added handling of third specified altitude value in AUV missions.

Mbeditviz: Fixed rotation calculations so that side-looking and up looking mapping data can be handled properly.

Formats 56 (mbf_em300raw) and 57 (mbf_em300mba): added support for asynchronous attitude output, in particular by mbnavlist -K18.

5.3.1995 (October 27, 2012)

5.3.1994 (October 27, 2012)

Mbfilter: when filtering sidescan the output file now includes any bathymetry available in the original file. The bathymetry can be used by mbmosaic for calculating apparent grazing angles and data priorities.

Mbmosaic: substantially rewrote the calculation of apparent grazing angle for sidescan data to be more reliable and to optionally use a topographic model supplied by a topography grid (specified with the -T option).

Mb7k2ss: removed functions associated with laying out sidescan on a 3D topographic model. These functions are now found in src/mbaux/mb_intersectgrid.c.

Format 88 (mbf_reson7kr) and mb7kpreprocess: added support for multibeam sidescan derived from either the backscatter records or the snippet records. The snippets are generally better, and are the default source when . The program mb7kpreprocess can be set to generate the multibeam sidescan from either record type. The multibeam sidescan is stored using MB-System-only "processed sidescan" records as an MB-System-specific extension to the 7k format.

libmbaux: added functions to the mbaux library that locate the intersection of arbitrary vectors from a sonar platform with a topographic grid. This code is located in src/mbaux/mb_intersectgrid.c, and includes functions formerly found in src/utilities/mb7k2ss.c. These functions are now used to lay sidescan out on a seafloor topographic model and to calculate the apparent grazing angles needed for angle-based priority calculation in mbmosaic.

Mbgrid: fixed -Cclip[/mode] option so that -C0/3 will in fact fully interpolate the resulting grid.

Format 88 (mbf_reson7kr): fixed travel time and angle calculation for current generation data using v2detectionsetup data records.

Mbgrid and mbmosaic: Added -Rfactor option that will allow users to specify that the output grid extent will be the data extent expanded by a multiplicative factor. For instance, specifying factor = 1.1 means the grid is expanded 5% to the west, east, south and north for a total expansion of 0.1 or 10%.

5.3.1989 (October 4, 2012)

mbm_grdplot & mbm_grdtiff: Fixed application of strict color table bounds in mbm_grdplot and mbm_grdtiff.

mb7k2ss: Added -Q option so that sidescan lines can be constructed based on the times starting and ending waypoints were reached.

Format 71 (mbf_mbldeoih): Fixed scaling of sidescan values to handle data with small values.

Mbgrid and mbmosaic: Fixed the zgrid interpolation code, and also changed the usage so that the interpolation stages will proceed much more rapidly. This is now accomplished for large grids by iteratively calculating a smooth Laplacian model for a low resolution grid and then resampling this onto the desired full resolution grid using bilinear interpolation.

5.3.1988 (September 29, 2012)

Format 71 (mbf_mbldeoih): Implemented automatic scaling of sidescan values to improve fidelity of stored values to the original values.

MBeditviz: Fixed region selection to include topography min and max within that region.

Reson 7k data (format 88, mbf_reson7kr): fixed calculation of beam angles from 7026 7k Detection records.

MBnavadjust: the tie (or block) view now honors the "With Selected Survey" and "With Selected File" display modes.

MB7kpreprocess: Added control for the use or nonuse of attitude sensor time delay data embedded in MBARI "Bluefin Navigation" records.

MB7k2ss: Added option to define sidescan line start and end points using a list of times generated using mbrousetime (duplicating an option of mbextractseg).

MB7k2ss: When extracting sidescan data from 7k data files to separate format 71 files, use navigation, heading, sonar depth, and attitude data from multibeam data records in the 7k data file (previously these values derived from asynchronous navigation, heading, attitude, etc, records).

5.3.1986 (September 12, 2012)

MBnavadjust now treats data from interferometric sonars different than data from other sonars. When interferometric bathymetry is imported, the many soundings are binned and averaged into 1-degree wide "pseudo-beams" to allow reasonable (both visually and computationally) contouring.

Added MBIO function `mb_sonartype()` that returns the type of sonar associated with some data, using the definitions:

- `#define MB_SONARTYPE_UNKNOWN 0`
- `#define MB_SONARTYPE_ECHOSOUNDER 1`
- `#define MB_SONARTYPE_MULTIBEAM 2`
- `#define MB_SONARTYPE_SIDESCAN 3`
- `#define MB_SONARTYPE_INTERFEROMETRIC 4`

Added function to `mbnavadjust` that will estimate vertical offset between surveys and then set relevant ties accordingly.

Fixed some plotting defaults for `mbm_histplot`.

Added `-MXexcludepercent` option to `mblist` to exclude a user defined percentage of outer beams from `mblist` output. (contributed by Suzanne O'Hara)

5.3.1982 (August 15, 2012)

Fixed significant issue in `mb7kpreprocess` and in Reson 7k format support in general. The code was not handling the current raw detection data records correctly.

Fixed `mbotps` so that it handles requests for sound speed models on locations that are dry land in the Topex models more gracefully.

Fixed minor info printing issue with `mbnavadjust` (now doesn't report failure to invert unless there is a failure to invert).

Improved performance of navigation and attitude merging for both `mb7kpreprocess` and `mbkongsbergpreprocess`

Added new functionality to mbkongsbergpreprocess (contributed by Suzanne O'Hara):

- Added -D argument to allow users to set new directory for output files; original code always created output in input directory. This is a problem where users should not be modifying original directories. Using this flag allows the user to use the datalist option and is easier than copying the original mb58 data to a different directory or to using a script that loops through all the data using the -D option
- Added -C flag to output counts. Current code always outputs many rows of information that can be confusing. The default now is to work silently unless there is a problem.

5.3.1981 (August 2, 2012)

Fixed problem with mbprocess in which the heading was unexpectedly replaced by course-made-good. Now this can only happen with HEADINGMODE:1 or HEADINGMODE:2 in the parameter file.

Fixed error in the definition of the OMG HDCS format in mbf_omghdcsj.h
This fix provided by Bob Covill.

5.3.1980 (July 13, 2012)

Augmented support for L3 XSE format (94) so that data from recent SeaBeam 3000 and SeaBeam 3050 multibeam can be processed.

Added option to mbinfo to generate output in XML (contributed by Christian Ferreira)

Augmented the i/o module for Reson 7k data to work with data files that do not include the 7006 bathymetry records but instead include the raw detection 7027 records.

Altered mbnavlist so that longitude and latitude values are output with a precision about equivalent to 0.1 mm, the same as mblist and mbinfo.

Altered mbprocess so that navigation shifts and offsets are applied to merged navigation. Navigation derived from mbnadjust is not affected.

Added new program mbkongsbergpreprocess, which reads data from a third generation Kongsberg multibeam sonar (e.g. EM122, EM302, EM710), interpolates the asynchronous navigation, heading, and attitude onto the multibeam data, and writes a new file with that information correctly embedded in the multibeam survey data. The input files may be in the

vendor format MBF_EM710RAW (format id 58) or the MB-System extended format MBF_EM710MBA (format id 59); the output files will always be in the MB-System extended format MBF_EM710MBA (format id 59).

Updated GSF library to new release 3.04 from SAIC.

Removed local(\$!) = 0 initializations from all perl macros for compatibility with the current version of perl (some macros were missed when this was done before 5.3.1955).

Fixed problem with mbprocess in which merged roll and pitch data were not applied to the bathymetry unless the bathymetry was being recalculated by raytracing.

Added ability to change the read and write buffers for file i/o, initially just for Reson 7k and Kongsberg current generation data. This allows one to tune for the highest throughput file i/o for a given situation (e.g. 10 MB buffers achieve 5-10% faster throughput on the MBARI network).

Altered i/o module mbr_image83p.c for Imagenex DeltaT data so that if no roll or pitch data are stored, the sonar is treated as if it is pointed down rather than horizontal. Also fixed the module so that the profile tile angle parameter is used correctly.

5.3.1955 (May 16, 2012)

Removed (\$!) = 0 initializations from all perl macros for compatibility with the current version of perl.

Updated PROJ4 to the 4.8.0 release.

Added code for a new i/o module reading (but not yet writing) Benthos 1624 sidescan data in the XTF format. This read-only i/o module has a format id of 211. This code has been contributed by Jens Renken (MARUM/University of Bremen). The intent is to complete the i/o module to allow full processing of the Benthos 1624 data.

Added a new macro, mbm_bpr, to translate pressure data from a Seabird SBE53 pressure sensor used as a Bottom Pressure Recorder (BPR) into tidal data that can be used to correct swath bathymetry data.

Changed default Postscript viewer for Linux or Mac to be gv rather than Ghostview.

Added option to mbinfo (-X1) to generate output in the json format. If the -O option is used to make metadata files, then the addition of -X1 will cause the

output files to be named "*_inf.json*" rather than ".inf". Suzanne O'Hara (LDEO) contributed this improvement.

Augmented mbsvplist with option -C which causes the program to output the number of unique SVPs in each file to stdout. Suzanne O'Hara (LDEO) contributed this improvement.

Fixed multiple problems with mbcontour and the underlying contouring library that were producing crashes in many circumstances.

Updated the MBARI AUV mission generator mbm_route2mission to reflect current operational parameters for the MBARI Mapping AUV.

Applied fixes to the Marine Sonics sidescan i/o module (mbr_mstiffss.c) contributed by Val Schmidt of UNH/CCOM.

Changed the color table in mbnadjust to eliminate yellow contours, which are difficult to see.

Added output of potential temperature to mbctdlist.

Altered subbottom section plots generated by mbextractseg. The first cut plots generated when mbextractseg is used to extract subbottom data into segy files are broken into multiple section plots for long files (representing survey lines if extracted according to a route file). Previously, all section plots for a given line had a time sweep encompassing the data for the entire line. Now, if the total sweep exceeds 1 second, then the sections plots will be generated using only the sweep required for each section alone.

Improved the robustness of calculating longitude latitude bounds for segy data using mbseginfo.

Added capability to mbseggrid to grid and plot subbottom sections based on distance between the end points of a survey line. This approach to plotting subbottom sections removes the impact of speed variations and deemphasizes data where the sonar platform moved slowly or stopped.

5.3.1941 (March 6, 2012)

Fixed sidescan filtering with mbfilter. The filtered sidescan output in format 71 files had incorrect acrosstrack locations.

Fixed problems with sidescan generation for current generation Kongsberg data (formats 58 and 59). The code previously tended to choose too small of a pixel size, resulting in a sidescan swath narrower than the real swath width.

Fixed swath contouring and track plotting by mbcontour and mbm_plot. Subtle changes in the GMT pslib resulted in contours and tracks only partly plotting in some Postscript devices. The MB-System code now explicitly chooses when to call stroke operations in the Postscript, rather than leaving that up to pslib.

Fixed format 24 (mbf_hsldeoih) so that certain old files with extra bytes in some comment records can be read correctly.

Added output of raw values from current generation Kongsberg data (formats 58 and 59) to mblist.

5.3.1937

Changed the resolution of navigation in fbt (format 71) files and fnv files to be 1e-9 degrees, equivalent to about 0.1 mm. Similarly change the navigation resolution in the output of mbinfo, and thus in inf files. This affects mbr_mbldeoih.c, mbsys_ldeoih.c mbsys_ldeoih.h in src/mbio, and mbinfo.c and mblist.c in src/utilities.

Add importing and display of "vector" data in mbview and mbgrdviz. The vector files are GMT-style segmented files of lon, lat, topography value triples. These are displayed as lines colored according to the value. Controls for setting the color tables still have to be added.

Changed mbgrid so that any background (option -K) is calculated first, before significant memory is allocated. This avoids crashes due to attempted forks that overrun available memory.

Fixed beamwidth calculation for Reson 7k data. Fix in mbr_reson7kr.c and mbsys_reson7k.c.

Fixed overflow during iterative search for beam angle values in mbr_em710raw.c

Added capability to mbauvloglist to output angle values in degrees rather than radians.

Added code to mbnadjust to detect when the uncertainty ellipsoid of one or more ties contains a zero value that will cause the inversion to fail. In this case, the program prints out which ties are problematic, and declines to calculate the inversion.

Fixed beamwidth values stored in fbt files.

Added JSON output option to mbinfo. This addition provided by Suzanne O'Hara of LDEO/IEDA.

Added graceful exit to mbm_grdplot when a call to grdinfo fails. Fix provided by Hamish Bowman of the University of Otago.

Bug fixes to mbr_mstiffss.c related to reading Marine Sonics sidescan data. This fix provided by Val Schmidt of CCOM/JHC at University of New Hampshire.

5.3.1917 (January 10, 2012)

Added preliminary support for HYSWEEP HSX format as MBIO format 201. Added program mbhysweeppreprocess to preprocess the HSX data.

Fixed bug in mb_lever() function in mb_angle.c.

GSF 3.03 update.

5.3.1912 (November 19, 2011)

Formats 58 and 59 (third generation Kongsberg multibeam data): Augmented code to handle bathymetry data in which beams are reported as having valid soundings but actually have zero ranges and NaN bathymetry, across-track distance, and along-track distance values.

Formats 58 and 59 (third generation Kongsberg multibeam data): Fixes to the handling of attitude records, particularly with regard to writing the records.

5.3.1909 (November 16, 2011)

Program mbnolist: Fixed attitude record output so that use of -K18, -K55, -K56, or -K57 results in output lines for all attitude records, even when position or heading data are not available for interpolation.

Formats 58 and 59 (third generation Kongsberg multibeam data): Fixed the i/o modules to successfully output attitude and netattitude records identified as MB_DATA_ATTITUDE1, MB_DATA_ATTITUDE2, or MB_DATA_ATTITUDE3.

5.3.1907 (November 9, 2011)

Program mblist: Added output of beam bottom detection algorithm (amplitude or phase) to mblist. One can now use Q and q as valid output values that can be included in the arguments to the -O option.

Program mbnavlist: Added ability to output navigation data keyed to primary or ancillary attitude data. For instance, use of the -K18 option will cause the mbnavlist output to occur for all attitude samples in the primary attitude data stream. The timestamps will be those of the attitude records, and any position, speed, or sonar depth values requested will be interpolated onto the attitude timestamps.

Program mbm_route2mission: Enabled the generation of AUV missions in which multibeam beamformed data ("water column") are recorded in addition to bathymetry and backscatter.

Program mb7kpreprocess: Fixed integration of MBARI AUV INS log data into the processing of Reson 7k data.

Program mbrolltimelag: Fixed a bug that rarely produced a failure of time lag correlation calculation.

Third generation Kongsberg data (formats 58 & 59: Fixed handling of different attitude records, in that the code now recognizes multiple sources of roll, pitch, and heave when they appear in a datastream. The data records identified as the primary attitude source are identified as type MB_DATA_ATTITUDE (18) while ancillary records will be identified as MB_DATA_ATTITUDE1 (55), MB_DATA_ATTITUDE2 (56), or MB_DATA_ATTITUDE3(57).

5.3.1906 (September 28, 2011)

Program mbnavadjust: Added -D option to invert foreground (normally black) and background (normally white) colors in the interactive plots

Format 88 MBF_RESON7KR (Reson 7k multibeam data): Fixed deallocation of MBF_RESON7KR data structures.

Program mb7kpreprocess: Fixed some filtering code in mb7kpreprocess.

Program mbrolltimelag: Added -K option to mbrolltimelag - this duplicates the new -K option in mbnavlist and is used when mbrolltimelag calls mbnavlist to extract the roll time series.

Program mbnavlist: Augmented mbnavlist to allow extraction of data keyed to data records other than navigation or survey data. A new -Kkind option allows users to specify output at the times of attitude, heading, or other record types.

Programs mbedit, mbeditviz, mbnavedit, mbclean, mbprocess: Added ability to disable file locking using the program mbdefaults and the .mbio_defaults

file in the user's home directory. If a user disables file locking by running `mbdefaults -U0` then the programs `mbedit`, `mbeditviz`, `mbnavedit`, `mbclean`, and `mbprocess` will not set new file locks and will ignore any existing file locks. In short, a user can disable the entire file locking mechanism in MB-System.

New macros `mbm_multicopy`, `mbm_multidatalist`, `mbm_multiprocess`: Added three new macros authored by Christian Ferreira. These are `mbm_multicopy`, `mbm_multidatalist`, and `mbm_multiprocess`. All three are used to execute tasks on large numbers of swath files by starting multiple processes in parallel. The `mbm_multicopy` macro accomplishes copying of files from one format to another. The `mbm_multidatalist` macro accomplishes the creation of ancillary files. The `mbm_multiprocess` macro accomplishes processing with `mbprocess`. These all require the Parallel-Forkmanager Perl module available from www.cpan.org.

Program `mbclean`: Added flagging by across-track distance to `mbclean`. Also added `esf` file locking for compatibility with `mbedit` and `mbeditviz`, and fixed handling of old edits.

Program `mbgrid`: Fixed a problem with the footprint algorithm of `mbgrid` that sometimes left holes that could not be filled by interpolation.

Macro `mbm_route2mission`: Added ability to mix constant altitude and constant depth behaviors within a single AUV mission to `mbm_route2mission`.

Format 88 MBF_RESON7KR (Reson 7k multibeam data): Fixes to handling of asynchronous attitude data in format 88 (Reson s7k) and calculation of time lag estimates.

Program `mbextractseg`: Adjustments to the default plots of `seg` data by `mbextractseg`.

Macro `mbm_route2mission`: Fixes to generation of MBARI AUV missions by `mbm_route2mission`.

Format 88 MBF_RESON7KR (Reson 7k multibeam data): Fixed extraction of raw, asynchronous attitude data from Reson 7k data using `rollpitchheave` records (e.g. from the MARUM AUV), which in turn fixes the calculation of attitude time lag estimates using `mbrolltimelag`.

Program `mb7kpreprocess`: Fixed application of time lag model by `mb7kpreprocess` for the case of Reson 7k data using `rollpitchheave` records (e.g. from the MARUM AUV).

Program mblist: Added -UN option to mblist that ignores output of lines associated with zero longitude or latitude values. This option will be used by mbdatalist to create *.fnv files.

Format 71 MBF_LDEOIH (generic swath): Provided a means to continue using the old definition of swath format MBF_LDEOIH (format 71) for fbt files. Users can now use mbdefaults to set the format 71 version that will be generated when fbt files are created by mbdatalist and mbprocess. If mbdefaults -Fold is executed, the .mbio_defaults file in the user's home directory will be altered so that all new fbt files are in the old format. The purpose of this backwards compatibility is to allow users to take advantage of the Fledermaus capability for editing bathymetry in MB-System processing environments. This involved changes to mbcopy as well as to the MBF_LDEOIH i/o module.

Program mbnadjust: Changed the swath data import code so that sections will be created even when all beams have been flagged as bad. This is to allow surveys to remain intact, with no breaks, because the concept of a continuous survey is increasingly important in MBnavadjust. Also altered the status displays and listings to show survey id along with file and section id's.

Format 71 MBF_LDEOIH (generic swath): Updated the definition of swath format MBF_LDEOIH (format 71), which is used for the "fast bathymetry" or *.fbt files in MB-System processing environments. The previous form of *.fbt files had a serious limitation in that bathymetry from multibeam operated near the seafloor in deep water did not represent the full numerical resolution of those data. The updated format allows for depth and distance resolution to 0.001 m even in the deep ocean. Old *.fbt files are read transparently, but newly written files will be in the new form. IMPORTANT: In order to avoid compatibility issues, all users operating on the same projects should upgrade to this version or higher once one user upgrades.

Format 88 MBF_RESON7KR (Reson 7k multibeam data): Updated support for Reson 7k data to include the "1022" record. We still don't know what this is, but the code now reads and writes it without complaint.

Program mbinfo: Fixed mbinfo handling of swath files with no good data (Thanks Suzanne O'Hara)

MBIO function mb_get_format(): Changed mb_get_format() function in mb_format.c so that formats are inferred from parameter files if they exist.

Program mbnadjust: Supplemented informational output to stdout from MBnavadjust.

Format 71 MBF_LDEOIH (generic swath): Started development of new version of format 71 (mbf_ldeoih).

Program mb7kpreprocess: Fixed translation of beam quality values into MB-System beam flags by mb7kpreprocess.

Program mbextractseg: Fixed calculation of line breaks by mbextractseg.

MBIO function mb_get_format(): Augmented mb_get_format() in mb_format.c to look for the format id value in mbprocess parameter files before trying to make sense of file suffixes.

Program mbedit: Fixed MBedit's handling of files not conforming to the MB-System filename suffix convention.

Macro mbm_xyplot: Allow users of mbm_xyplot to specify both axis annotation with the -B option and axis labeling with the -L option.

Program mbeditviz: Implemented workaround for MBeditviz crash problem on Poseidon Linux. MBeditviz would shut down whenever a second map view was requested with an Xserver error named GLXBadContextTag. Previously, the OpenGL rendering within X11/Motif widgets has been implemented with the graphics calls always sent through the X11 window server. I have now set the code to allow direct rendering through hardware when that is possible. For reasons I do not understand, this change results in MBeditviz no longer crashing on my Poseidon Linux test machine.

Programs mbedit, mbnavedit, mbeditviz: Fixed font issue for MBedit, MBnavedit, and MBeditviz by using courier rather than monaco as a fixed-width font for the available file list widgets.

Program mbprocess: Added support for the "Rolling Deck to Repository" (R2R) navigation format as both an MB-System format (format id 172) and an mbprocess navigation merging format (NAVFORMAT=10)

Macros mbm_grdplot and mbm_grdtiff: Modified mbm_grdplot and mbm_grdtiff so that the -Y option strictly enforces the colormap min max bounds set with the -Z option.

Formats 132 MBF_EDGJSTAR and 133 MBF_EDGJSTR2 (Edgetech Jstar): Fixed support for Edgetech Jstar files (formats 132 and 133) so that the output of mb7k2jstar and mbprocess are compatible with Edgetech programs.

Programs mbedit, mbeditviz, and mbnavedit: Added file locking to mbedit, mbeditviz, and mbnavedit. All three programs can now load datalists and display lists of files available for editing. These lists show whether the file

has been previously edited and if the file is locked. Locked files cannot be loaded or edited. As before, mbprocess also locks files during processing and skips files that are locked by other programs. The program mbdatalist can be used to detect (-S) and remove (-Y) orphan file locks in files referenced by datalist structures.

Program mbprocess: Fixed bug in mbprocess.c involving parsing of NMEA GGA strings when reading in navigation for merging with survey data.

Program mbnadjust: Changed MBnavadjust to allow more file modes, in turn allowing more control over which data has the most influence over the navigation solutions. In addition to the previously existing modes (Fixed, Good, Poor), surveys can now be set to FixedXY and FixedZ modes where the navigation of the files so identified will have the specified coordinates fixed (unadjusted) and the other coordinate(s) treated as Good. In particular, this allowed us to simultaneously adjust navigation from overlapping MBARI Mapping AUV and ABE surveys in which the Mapping AUV pressure depth was clearly more accurate than the ABE vehicle depths. By setting the MBARI data to mode FixedZ, we were able to force the solution to adjust the ABE navigation to match the Mapping AUV vertical reference, while still allowing lateral (XY) adjustments of all the AUV navigation.

Program mbnadjust: Changed MBnavadjust to output user, cpu, and time of changes to project files and as comments to the adjusted navigation files. Also changed mbprocess to handle comments in adjusted navigation files.

Program mbm_copy: Fixed -C option of mbm_copy.

Format 192 MBF_IMAGEMBA (Imagenex DeltaT): Fixed i/o module for extended format Imagenex DeltaT data (format 192) by removing code that recalculated bathymetry unnecessarily.

Program mbdatalist: Added -Y option to mbdatalist to remove any leftover lock files.

Parsing *.inf files: Fixed bug in parsing file start and end times in *.inf files.

MBIO functions mb_defaults(), mb_env(), and mb_lonflip(): Changed mb_defaults(), mb_env(), and mb_lonflip() functions to always return MB_SUCCESS status even when ~/.mbio_defaults file does not exist. Working with system defaults should not be an error.

Program mbeditviz: Changed mbeditviz_import_file() function in mbeditviz_prog.c to reset global status to MB_SUCCESS on entry.

Program mbclean: Incomplete implementation of Dana Yoerger's changes to mbclean. Not yet tested.

Program mbnavedit: Increased verbosity of mbnavedit for -X option.

MB-System Version 5.2 Releases and Release Notes:

- **Version 5.2.1880 December 30, 2010**

--

5.2.1880 (December 30, 2010)

Augmented mbotps to output tide in both time_d tide and year month day hour minute seconds tide using a -Atideformat command line option.

Added new kluge processing option to mb7kpreprocess (-K2) that zeros alongtrack angles. This fixes some recent sample Reson 7k data.

Recast lever arm calculation due to roll and pitch rotations in mb_angle.c.

More changes to the handling of current generation Kongsberg data in mbr_em710raw.c.

Fixed handling of beam alongtrack distance values during bathymetry recalculation by raytracing.

Improved beam info display in mbeditviz.

Fixed mbnadjust recalculation of the 3D cross-correlation function after changing the vertical offset.

Changed mbr_image83p.c, mbr_imagemba.c, and mbsys_ima83p.c so that calculation of beam angles happens during the first read of the data.

Replaced strsep() with strtok() in mbr_edgjstar.c. This is to allow MB-System to be more easily built on Solaris systems.

Fixed mbset so that it recognizes sidescan cutting commands (SSCUTNUMBER, SSCUTDISTANCE, SSCUTSPEED).

MB-System Version 5.1 Releases and Release Notes:

- **Version 5.1.3beta1875 November 23, 2010**

- Version 5.1.3beta1874 November 7, 2010
- Version 5.1.3beta1862 June 7, 2010
- Version 5.1.3beta1858 May 18, 2010
- Version 5.1.3beta1855 May 4, 2010
- Version 5.1.3beta1851 April 14, 2010
- Version 5.1.3beta1844 March 30, 2010
- Version 5.1.3beta1843 March 29, 2010
- Version 5.1.3beta1829 February 5, 2010
- **Version 5.1.2 December 31, 2009**
- Version 5.1.2beta15 December 30, 2009
- Version 5.1.2beta14 December 28, 2009
- Version 5.1.2beta13 December 28, 2009
- Version 5.1.2beta12 December 26, 2009
- Version 5.1.2beta11 August 26, 2009
- Version 5.1.2beta10 August 12, 2009
- Version 5.1.2beta09 August 7, 2009
- Version 5.1.2beta08 August 5, 2009
- Version 5.1.2beta06 July 2, 2009
- Version 5.1.2beta05 June 14, 2009
- Version 5.1.2beta02 March 13, 2009
- Version 5.1.2beta01 March 9, 2009
- **Version 5.1.1 December 31, 2008**
- Version 5.1.1beta26 November 18, 2008
- Version 5.1.1beta25 September 28, 2008
- Version 5.1.1beta23 September 19, 2008
- Version 5.1.1beta21 July 20, 2008
- Version 5.1.1beta20 July 10, 2008
- Version 5.1.1beta19 June 6, 2008
- Version 5.1.1beta18 May 16, 2008
- Version 5.1.1beta17 March 21, 2008
- Version 5.1.1beta16 March 14, 2008
- Version 5.1.1beta15 February 8, 2008
- Version 5.1.1beta14 January 15, 2008
- Version 5.1.1beta13 November 16, 2007
- Version 5.1.1beta12 November 2, 2007
- Version 5.1.1beta11 October 17, 2007
- Version 5.1.1beta10 October 8, 2007
- Version 5.1.1beta5 July 5, 2007
- **Version 5.1.0 November 26, 2006**
- Version 5.1.0beta4 October 5, 2006
- Version 5.1.0beta3 September 11, 2006
- Version 5.1.0beta2 August 9, 2006
- Version 5.1.0beta July 5, 2006

5.1.3beta1875

Altered -P option in mbsvplist. Previously this option (which turns on bathymetry recalculation by raytracing in mbprocess using the water sound speed models extracted from the data files) set the raytracing to correct the takeoff angles for the difference between the sound speed used for beamforming (surface sound velocity or SSV) and the sound speed at the sonar depth in the water sound speed model. Now, mbsvplist sets mbprocess to leave the takeoff angles unchanged. This is more consistent with the expectation that raytracing through the original sound speed model should yield values matching the original bathymetry.

Altered mbprocess bathymetry recalculation by raytracing to better handle cases where large heave values bring the sonar array above the nominal water line. In this case, a static heave offset is calculated, raytracing is done from the top of the water sound speed model, and the heave offset is added to the raytracing result.

Improved the autopicking function of mbnadjust.

Fixed a bug in handling the per-beam heave values in current generation Kongsberg data (formats 58 & 59).

Changed mbm_route2mission to allow command line argument control of AUV speed during ascent/descent, survey lines, and transit lines. Also added control of the "deltaDepthRestart" value controlling how far up the AUV should float after an altitude abort before resuming the mission.

More changes to support of Kongsberg current generation multibeam data in formats 58 and 59. As previously noted, the angles used to recalculate bathymetry from raw travel times by raytracing are estimated by iteratively seeking to match the original bathymetry reported by the sonar. These angles are estimated when data are first read as format 58 and then embedded in format 59 data (presumably when mbcopy is used to translate format 58 files to format 59) for later use by mbprocess. The default algorithm matches the original bathymetry to within about 0.1% altitude by calculating an effective heave for each ping and takeoff angles for each beam. A second algorithm (which can only be activated by uncommenting an `#ifdef` statement in `mbr_em710raw.c`) matches the original bathymetry by modifying both the takeoff angles and the travel time measurement - this achieves matching of the original bathymetry to about 0.02% of altitude. Use of the second algorithm is not recommended because modifying the fundamental observations (travel times) to match the sonar's calculation is, well,

unsatisfying and wrong. The bad option is there because I took the time to code it to see how well it would work.

5.1.3beta1874

The function `mb_get_info()` now properly applies the `lonflip` value. This in turn allows `mbgrid` to infer correct bounds in situations where the `lonflip` is important (e.g. data across the ± 180 degree boundary when `lonflip` is -1 or 1).

Changed `MBnavadjust` so that an "Inversion Smoothing" value replaces a no-longer-used "Inversion Precision" value. This value, accessible under the Options dialog, sets the importance of smoothing in the adjusted navigation model. The default is 4.00, and possible ranges are 0.10 to 10.0, where the smoothing penalty weight applied to the first and second derivatives of the adjusted navigation perturbation is ten raised to this power.

Added support for Kongsberg EM2040 multibeam in formats 58 and 59.

Changed `MBnavadjust` so that default settings for section length and contour interval are appropriate for high resolution surveys such as those produced by AUV's equipped with >100 kHz multibeam.

Fixed plotting macros `mbm_plot`, `mbm_grdplot`, `mbm_xyplot`, `mbm_grd3dplot` so that the calls to display postscript graphics using `gv` in the output plotting scripts scale plots to fit on the screen.

Fixed `mbm_route2mission` to use proper camera control when generating mission scripts for the MBARI Benthic Imaging AUV.

Added `-W` option to set the desired swath width of sidescan output from `mb7k2ss`.

Updated the `i/o` module supporting OMG HDCS (the John Hughes Clarke format) to handle HDCS version 4. These mods contributed by Bob Covill.

Fixed `mb7kpreprocess` to check for and ignore repeated ancillary and survey data records.

Update GSF code to version 3.02, released 28 September 2010.

Set `MBeditviz` to resolve format id's in output parameter files when filenames do not follow known suffix conventions.

Added support for a number of new data records in the Reson 7k data format, following the 19 June 2009 addendum to the 7k format version 1.00 specification.

Changed `mb_malloc()` calls in `mb_format.c` and `mb_buffer.c` to `mb_mallocd()` calls for greater debugging capability.

Added some debugging statements to `mbprocess.c`.

Changed `mbm_grdplot` macro to use the variable names embedded in seismic section GMT grid files generated by `mbsegygrid`.

Improved autopicking in `MBnavadjust` to the point where it is actually useful. Also fixed bug that caused eventual seg faults when analyzing many crossings in a single session.

Fixes to Reson s7k (format 88) support allowing `mbnavlist` to use position records as navigation channel 3. This in turn allows `mbrolltimelag` to work with Reson 7k data collected by MARUM (University of Bremen).

Added file name and line output to debug messages in `mbr_l3xseraw.c` to aid in later work to fully support the current XSE data format.

Set `mbrolltimelag` to only attempt to generate a variable time lag model plot if more than one robust time lag values have been generated.

Updating in preparation for beta release version 5.1.3beta1874.

5.1.3beta1862

Moved `src/mbaux/mb_rt.c` to `src/mbio/mb_rt.c` and made this raytracing code part of `libmbio` rather than `libmbaux`.

Fixed deallocation of raytracing data in `mbprocess`.

Added source type flag (CW or chirp) definition to `src/mbio/mb_status.h`

Add `mb_io_pulses()` function definition to `src/mbio/mb_io.h` as a pointer for functions in i/o modules that extract source type (CW or chirp) for individual beams. Added `mb_pulses()` function calls to `src/mbio/mb_define.h` and `src/mbio/mb_access.c`.

Added `mbsys_simrad3_pulses()` function to i/o module for current generation Kongsberg (Simrad) data in `src/mbio/mbsys_simrad3_pulses()`.

Altered i/o module for current generation Kongsberg (Simrad) data so that bathymetry calculation using raytracing works correctly. This involves `src/mbio/mbr_em710raw.c` and `src/mbio/mbsys_simrad3.c`. The problem is that

the current raw beam and angle datagram stores travel times and angles uncorrected for motion and attitude. My attempts to properly calculate the attitude and motion compensation have not succeeded (as measured by succeeding in replicating the original bathymetry when used with the original sound speed model). This version achieves accurate estimation of the compensated angles for each sounding by finding a ray (through iteration) that replicates the original sounding position by raytracing through the original sound speed model. The depth difference is stored as a per-beam heave correction, and the angles are stored normally. This calculation is done only on the raw data format 58. When mbcopy is used to translate the data to the processing format 59, the compensated angles are stored in extended bathymetry datagrams. This scheme suffices to allow full processing of the data, but is not satisfying in that I clearly still do not fully understand the raw data format

Fixed issues with a number of manual pages.

5.1.3beta1860

Further changes to mbnavadjust:

- The inversion stops if it is diverging rather than converging on a navigation adjustment model solution.
- The program will insure that all crossings have the later section second by flipping the order of crossings if necessary while reading an old project.
- The program also resorts the crossings when it reads a project.

5.1.3beta1858

Slight modification to mbm_grdplot map annotation scheme (degrees + minutes for maps up to 4 degrees across where only degrees shown before for maps wider than 1 degree).

Changes to mbm_route2mission to accommodate new capability of MBARI Mapping AUV to record full water column data from the Reson 7125 multibeam.

Move mb_mergesort() function prototype from mb_esf.c to mb_define.h.

MBnavadjust augmented with capability to check for new crossings and to recalculate overlap coverage of existing crossings after inversions. Users can also toggle previously analyzed crossing to "unset" status.

MB7kpreprocess augmented to handle Reson 7111 data sample from NGDC.

Fixed incorrect listing MB_DATA defines in mb_status.h.

Added per-beam heave data to mbsys_simrad3 ping structure to support bathymetry recalculation for EM710, EM302, EM122 data. Defined new processed bathymetry record for use in format 59, and set code to transparently read the old record and write only the new record. Mostly fixed handling of attitude data in bathymetry recalculation. There still seems to be a problem with handling heading data.

5.1.3beta1855

Fixed error in beam angle calculation for third generation Simrad multibeam data (formats 58 and 59, EM710, EM302, EM122) that made bathymetry recalculation by raytracing badly wrong.

5.1.3beta1851

Fixed problem where mb7kpreprocess made beams that should have been null valid but flagged.

Fixed bug that caused mbclean to fail to actually flag some beams identified for flagging.

Added button to zero all z offsets on crossings for cases where tidal corrections have been made before data were imported into a mbnavaadjust project.

Fixed mbgetesf manual page.

Fixed mode control in mbgetesf so one can extract the complete beam flag state from a swath file. MBgetesf is now used by MBeditviz to get the original beam flag state of raw swath bathymetry when processed files are read.

Fixed sorting of beamflag edit events in edit save file data as used by MBedit, MBeditviz, MBclean, MBareaclean, and MBprocess. This fixes a problem wherein some edits performed by MBeditviz were dropped by MBprocess. Also, MBgetesf is now used by MBeditviz to get the original beam flag state of raw swath bathymetry when processed files are read.

5.1.3beta1844

Fixed yet another bug in MBnavadjust - this time getting the importation of old project files correct and, more importantly, getting the z-offset sign correct in the Naverr display.

5.1.3beta1843

Updated mb7k2ss man page.

Fixed bug in mbrolltimelag regarding popen/pclose use.

Fixed bug in mb_process.c file locking.

Fixed mbotps man page. Fixed bug in MBeditviz and added hot keys for editing (only partially successful because it's hard to reliably get the keyboard focus onto the rendering OpenGL widget).

Fixed mbotps man page.

Augmented MBnavadjust to allow referencing high resolution bathymetry (e.g. AUV surveys) to lower resolution bathymetry (e.g. hull mounted multibeam surveys). The navigation of specified files (typically the data collected from the surface where GPS is available) can be fixed so that everything else floats and is adjusted relative to those data.

mbprocess - improved error reporting to show why files are not being processed.

mbmosaic - fixed aspects of the footprint calculation, particularly fixing a bug that prevented footprints from being fully covered.

Added -S option to mbprocess for debugging file status values used to determine whether processed data files are "out of date".

Greatly improved mbnadjust by adding a interim solution for a smooth navigation adjustment model fitting ties to fixed (immovable) data and by making all of the internal crossing and tie conventions consistent.

MBnavadjust now outputs version 3.0 nvh project files, but will transparently read and translate earlier version nvh project files.

5.1.3beta1829

From now on beta releases will be named according to the corresponding source archive revision in the MB-System Subversion source code archive.

This will allow us (and users) to more precisely track code changes relative to the beta releases.

Fixed support of Reson 7k data (format 88) to work with MARUM AUV data. Includes changes to mb7kpreprocess.

Fixed 64 bit issues with Simrad, Reson 7k, and L3 XSE data (formats 58, 59, 88, 94).

Fixed 64 bit issues with mbnavedit, mbclean, and mbneptune2esf.

Added buttons to MBedit to immediately go to the start or end of the data.

Fixed sidescan beamwidths used by the Edgetech Jstar format i/o modules (formats 132 & 133).

Fixed memory management errors in MBgrdviz and mbfilter.

Fixed more 64 bit and memory management issues in MBeditviz and MBgrdviz.

Added a plot reset button and an ability to autoscale on unflagged soundings only in the MBeditviz 3D sounding cloud display.

Fixed handling of site and route points far from the display view in MBgrdviz.

Put actual (but still incomplete) text into the MBeditviz man page.

Changed print format for unsigned long values from %ld to %lu to avoid copious warning messages in Ubuntu.

--

MB-System Version 5.1.2 Release Notes:

--

Fixed pixel calculation algorithm in mbmosaic. Previously, sidescan data from each pixel were being treated as extending over a larger area than is correct.

Resurrected program mbfilter with an new implementation. Allows low pass, high pass, and contrast enhancement filtering of amplitude and sidescan data. Implemented so that filtered data are stored in ancillary files ending in *.ffa (amplitude) and *.ffs (sidescan). The data type selection options of mbswath, mbm_plot, and mbmosaic all now allow users to select filtered data.

Improved handling current generation Simrad multibeam data (e.g. EM710, EM122) through formats 58 (MBF_EM710RAW) and 59 (MBF_EM710MBA). There still seems to be a problem with calculating the takeoff angles for recalculating bathymetry by raytracing, probably due to a problem interpolating the correct roll and pitch values.

Changed processing kluge 004. Previously kluge 004 caused mbprocess to not output survey data with time stamps prior to the last good ping. Now the dropped data will have time stamps prior to or equal to that of the last good ping.

Fixed problem reading and writing format 16 (MBF_SBSIOSWB) data on little-endian systems.

Added support for new ROV Doc Ricketts navigation data as format 165.

Added a Gaussian mean smoothing algorithm to MBnavedit. This is primarily intended for smoothing USBL or LBL based navigation of submerged platforms (e.g. ROVs or submersibles).

Altered the install_makefiles perl script used to generate the makefiles during installation of MB-System. The install_makefiles script now automatically determines whether the local architecture is big or little "endian". Consequently, the "BYTESWAPPED" parameter no longer needs to be set in install_makefiles, and has been removed. The "GRAPHICAL" parameter has also been removed. Now, install_makefiles builds the graphical utilities only if the Motif libraries and header file location are specified with the MOTIFLIBs and MOTIFINCDIR parameters. Also, install_makefiles now allows users to specify the use of independent installations of the GSF and PROJ4 libraries. By default, the versions of these libraries distributed with MB-System will be built and used.

Fixed bug in mbedit in which the view mode switched spontaneously after loading a new file and advancing the view buffer.

Improved efficiency of attitude interpolation when reading Simrad multibeam data. This greatly improves the speed at which Simrad multibeam data files are read and processed.

Fixed bug in mbm_grdplot which sometimes produces broken color tables.

Updated GSF library code to GSF release 3.01.

Fixed bug in EM710 support (format 59) involving netattitude datagrams.

Changed licensing from GPL version 2 to GPL version 3.

5.1.2beta07

Fixed MB-System compatibility with GMT 4.5.0

Fixed mbps memory handling.

MBgrdviz now displays ping/shot numbers when navigation is picked.

MBextractseg now embeds line numbers into the output segy files.

5.1.2beta08

Fixed mbauvloglist to work with all MBARI AUV logs.

Fixed mbm_route2mission so that the AUV mission segment duration always corresponds to the actual mission segment length.

Added file locking to the mbprocess system. Now, when mbprocess starts working on a swath file, it creates a *.lck file parallel to the swath file and deletes the *.lck file when processing is complete. Other instances of mbprocess will skip a locked file. This allows users to run multiple instances of mbprocess on multiple machines on the same datalist structure. This crude sort of parallel processing can greatly speed up reprocessing of large datasets. This locking functionality will be extended to the processing tools mbedit, mbeditviz, and mbnavedit in the future.

5.1.2beta09

Fixed bug in SeaBeam 2112 support that misplaced some sidescan data on little-endian machines.

Fixed the mbview library so that MBgrdviz will enable display of routes, sites, and navigation on all open windows when such data is loaded into one of the windows.

Fixed cause of frequent MBgrdviz crashes when displaying multiple windows.

Implemented timed background plotting in MBgrdviz so that full resolution displays automatically appear within a few seconds of the end of mouse interactions. Previously one had to click the "Full" button to get a full resolution view. At this point, the redisplay fails to happen occasionally.

Greatly increased speed of reading third generation Simrad data (formats 58 & 59, EM710, EM302, EM122).

5.1.2beta11

Fixed mb7k2ss to avoid creating shadow zones in the extracted sidescan.

Fixed support for dual-head Simrad EM3002 data (formats 56 and 57).

Changed mbdatalist so that the -Z option (create datalistp.mb-1 datalist file referencing an input datalist with the \$PROCESSED tag set) can be executed in conjunction with creating ancillary files with the -O or -N options.

5.1.2beta12

Updated proj library to 4.7.0 release. If the installing user chooses to use the proj distributed with MB-System, then the programs proj and geod will now be built and installed in the bin directory.

Rooted through the entire codebase fixing obvious failure points for 64-bit compilation. Most of the issues identified so far relate to storing address values in variables declared as "int".

Completed moving the code base into subversion hosted at Lamont by first updating the subversion archive to 5.1.2beta11 and then committing the copious mods related to the 64-bit cleanup.

Changed the suffix of the Perl source files in src/macros from ".perl" to ".pl".

Changed the section name for the MB-System man pages from "I" to "1" for programs and "3" for libraries and functions. This is in line with common practice and follows a similar change by GMT.

Modified support for Edgetech JSTAR sidescan/subbottom files (formats 132 & 133) to work with a new data sample from GEOMAR. MB-System can now automatically distinguish between low frequency (132) and high frequency (133) sidescan data.

Modified support for Reson 7k multibeam (format 88) to work with a new data sample from GEOMAR. Altered interpretation of initial beam quality flags, improving initial beamflags.

Fixed problems with survey generation in mbgrdviz.

Improved read-only support for XTF format Reson 8XXX data (format 84 MBF_XTFR8101), but still don't have time stamping of attitude data correct.

Augmented edit save file format and beam flag handling in order to deal successfully with multiple head multibeam that produce multiple pings with

identical time stamps. This affects mbprocess, mbedit, mbeditviz, mbclean, and mbareaclean.

Added program mbotps to generate open ocean tidal models at specified times and locations using the Oregon State Tidal Prediction Software (OTPS) package. This program will build whether OTPS is installed or not, but will only work if the OTPS programs are installed and in the user's path. The OTPS predictions are based on global barotropic inverse tidal solutions obtained with OTIS and available for download at: <http://www.coas.oregonstate.edu/research/po/research/tide/>

Added program mbsegypsd to calculate sonograms from segy time series data. Sonograms are 2D displays of power spectral density (PSD) functions (y-axis) versus time (x-axis). One PSD is calculated for each trace in the segy file. This program requires linking with the FFTW (Fastest FFT in The West) package.

5.1.2beta13

Fixed many more issues relating to clean compiles on 64 bit machines. In particular, store GSF and netCDF data stream id's in their own int-size variables rather than a pointer-size FILE variable, and declare mbview instance parameters as size_t rather than int so that passing these values through Xt event notify function calls as pointer values is clean. Also changed casting of pointer values to long for debug printing so that the pointer values are now casted to size_t values. This should allow for compatibility with Windows 64 bit builds, as Windows 64 bit C has a different type model than the rest of the universe (e.g. long = 32 bit on Windows but long = 64 bit for gcc).

5.1.2beta14

Fixed a few more issues relating to clean compiles on 64 bit machines. We're iterating towards a working version by getting problem reports from people like Hamish Bowman, Bob Arko, and Bob Covill.

5.1.2beta15

Fixed EM3002 support to reliably detect whether data comes from a single or double head sonar (formats 56 & 57).

Fixed problem with EM710 support (formats 58 & 59).

5.1.2

Incorporates all changes listed above.

Fixed memory management bug for formats 56 and 57 (Simrad EM3002 etc).

MB-System Version 5.1.1 Release Notes:

Fixed longstanding error in src/mbio/mb_angle.c in the application of roll and pitch angles. Previously, the pitch rotation was applied first, which is incorrect, but only produced obvious errors with large pitch values. Now roll is applied first, and the translation between sonar coordinates and raytracing coordinates is correct.

Ping number, and more importantly for seismic data, shot number annotation of navigation tracks is now supported by mbm_grdplot.

Improved handling of navigation plotting and annotation by mbcontour, mbm_plot, and mbm_grdplot. It is now easier to specify time, ping number, and filename annotation of navigation tracks.

Major modifications have been made to MBnavadjust. MBnavadjust now picks offsets in z (depth) as well as x (longitude) and y (latitude). An autopicking algorithm has been implemented, and a display of the optimal navigation adjustment model added as well.

The acrosstrack view of MBedit now shows the real alongtrack positions of the soundings.

Fixed bug in mbsys_gsf.c that incorrectly calculated the alongtrack distance of sidescan samples in "snippet" sidescan data contained in GSF format (121) multibeam data. On occasion this bug produced egregiously wrong alongtrack values.

Fixed bug in mbgrid that caused failure to write Arc Ascii grids with option -G4.

Augmented i/o module for XSE format (94) to support current version of SeaBeam 2112 sonars on WHOI ships. This data format now has an MB-System extension to its multibeam records that includes interpolated navigation values. Previously only asynchronous navigation was handled.

Fixed bug in old Simrad i/o module regarding EM121A data.

Added prototype of MBeditviz, a tool that combines 3D bathymetry editing and patch test capability.

MBeditviz can be started from MBgrdviz. Any selected files (using navigation selection) will be loaded.

Fixed further issues with the XSE format i/o module.

Added swath file copy function to mbdatalist.

Fixed calculation of grazing angles in mblast by adding sonar depth to the calculation.

Added some additional large format page sizes to the plot macros mbm_plot, mbm_grdplot, mbm_grd3dplot, mbm_xyplot, and mbm_histplot.

Added mblast capability to output tables using column delimiters other than tabs (e.g. commas to make csv files).

Modified mbnavedit so that any nav points that repeat previous lon and lat values will be automatically flagged as bad.

Fixed footprint calculation in mbmosaic, correcting problems in sidescan mosaic creation.

Altered mbm_utm to work with comma delimited input data as well as white space delimited data.

Updated proj library to current version 4.5.0.

Updated gsf to the current version 2.07.

Sidescan extracted from MBARI Mapping AUV data can now be laid out on a topography grid rather than laid out with a flat bottom assumption (mb7k2ss).

The sidescan and amplitude correction scheme (mbbackangle & mbprocess) can now use a topography grid to calculate grazing angles.

Altered several programs so that sidescan data can have valid zero or negative values. Stopped applying a shift to Simrad sidescan and amplitude values to force them to be positive.

Added decimation feature to mblast, mbnavlist, and mbsegylst. Also added and/or fixed the delimiter, segment, and binary output features for all three listing programs.

Added mbcopy capability to merge bathymetry and beam flags from a third "merge" swath file. This is a Gordon Keith contribution.

MB-System programs will now recognize filename suffixes of the form ".MB****" as well as ".mb****". Capitalized versions of many vendor format suffixes are also supported.

Fixed error in mblist manual page.

Fixed mbswath handling of time gap errors that made plotting of single beam data problematic.

Fixed problem with processing mgd77 data. Can now use mbedit to process single beam echosounder bathymetry.

Made checking for data min maxes and bounds more robust to improve parsing through large databases.

Added some generic gain values to mblist as part of the "raw" list. To do this, added mb_gains() function to MBIO. This is currently defined for SeaBeam 2112, Simrad, and Reson 7k multibeam.

Added new program mbabsorption to calculate the sound absorption of seawater as a function of salinity, pH, temperature, depth, and frequency.

Changed macro mbm_grdplot so that the -T option causes the coastline to be drawn without grayscale filling of dry areas. To obtain the previously default behavior, add -MTG128.

Added support for newer Simrad multibeam data (e.g. EM710) in vendor format MBF_EM710RAW (format id 58) and processing format MBF_EM710MBA (format id 59)

Updated format MBF_OMGHDCSJ (151), which supports the John Hughes Clark HDCS (SwathEd) format, to handle all of John's "version 3" data. John's "version 4" format is not yet supported.

Added calculation and use of three dimensional covariance in the xyz nav offsets used by mbnavadjust.

Added processing kluge006 to mbprocess. This "kluge" allows users to change the sonar draft value without changing the calculated bathymetry. This fixes a problem in which Atalante Simard data were exported by Caris into GSF with an incorrect sonar draft.

Added program mbtime to allow command line conversion between calendar times and unix time values.

Fixed mbprocess so that changes to the sonar depth/draft derived from mbnadjust are output to the processed data. Previously the bathymetry was corrected, but not the sonar depth/draft.

Fixed formats 58/59 to support EM302, EM122 in addition to EM710. Also supported "network attitude" datagram as source of attitude.

Changed mbnadjust inversion to use simplistic iterative relaxation rather than a full matrix solver. This targeted solver is faster and avoids some bad behavior around survey starts and ends.

Fixed mbedit scaling for swath widths less than 6 m.

Added formats 191 and 192 to support Imagenex Delta T multibeam. Format 191 supports the 83P vendor format and format 192 is an extended processing format. This format also supports data from the Odom ES3 multibeam sonar.

Lengthened filename char arrays in mbedit, mbnadjust, and mbvelocitytool to prevent possible overflows with large paths.

Updated the GSF code to new GSF version 2.09

Fixed support of UNB OMG HDCS format 151 to handle situation where ancillary sidescan files are missing.

Added new program mbctdlist to allow mblist style text output of CTD data from swath files. Initially relevant only to Reson 7k format data.

Applied patches to mbgrid and mbmosaic to handle lonflipping of bounds in projected coordinates.

Added format 26 to support Hydrosweep DS data format used by SOPAC.

Fixed support for EM302 sonars.

Augmented mbgrid footprint gridding algorithm. When used with the -F5 option, mbgrid now does a first pass, low resolution grid to provide a local slope estimate. During the second pass, final gridding, individual beam footprints are tilted to reflect the local slope, increasing the high-resolution fidelity of the resulting topographic model.

Enhanced the patch test capability of mbeditviz. MBeditviz can now be used to model time lag as well as roll, pitch, and heading bias. In order to use the time lag function, users must place files parallel to each swath file containing time series of attitude, heading, and sonardepth. These files contain the full asynchronous times series for heading, sonardepth, roll, and pitch and the

synchronous time series for roll and pitch (asynchronous means the raw sensor data sampled more frequently than the sonar ping rate, and synchronous means the sensor data sampled at ping times). Each time series file uses epoch times in seconds as the first column. These files are:
*.ath - asynchronous heading - time heading *.ats - asynchronous sonardepth - time sonardepth *.ata - asynchronous attitude - time roll pitch *.sta - synchronous attitude - time roll pitch Asynchronous data are not available in all formats. When available, the asynchronous data can be extracted using mbnavlist. The synchronous attitude can be extracted using mblist.

Added support for EM12D data in the Caraibes netcdf form as format 76.
Contributed by Gordon Keith.

Removed a number of obsolete programs and macros from the distribution. The following are no longer distributed with MB-System: mbanglecorrect mbbbackangleold mbbath mbcleanold mbeditold mbfilter mbgetmask mbmask mbmerge mbm_dslnavfix.perl mbm_fmtvel.perl mbm_vrefcheck.perl mbm_rollererror.perl mbnaveditold mbsmooth mbtide mbunclean

MB-System Version 5.1.0 Release Notes:

The version 5.1.0 release of MB-System contains both bug fixes and new capabilities relative to the 5.0.9 release.

A typo in the mbgrid man page was fixed.

A catastrophic error in the i/o module for the MBF_ASCIIYXZ format was fixed.

The proj library was updated to use code from the Proj 4.4.9 release.

The proj and GSF libraries internal to MB-System have been renamed libmbproj and libmbgsf to avoid name conflicts with proj and gsf in package managers like fink for MacOSX.

Fixed mbprocess problem with per-beam heave values when applying rotational bathymetry correction - previously did not initialize heave values for non-null but flagged beams.

A minor change to mbbbackangle to output the slope correction status (-Q) in the comments in the output file.

Altered mbackangle so that it outputs at least one table, even if there are no survey pings in a file. This prevents mbprocess from failing on data files with no survey pings.

Also altered mbackangle so that it outputs a single global correction table based on all of the input data. This can be used for uniform correction of sidescan and amplitude data.s

A new program mbrolltimelag calculates the cross-correlation between roll data and the difference between the seafloor slope and the roll. If there is a time lag in the roll data, then the two series should have a cross correlation maximum at a nonzero time lag.

New macro mbm_histplot for simple histogram plots.

MBgrdviz now has a profile display capability. Profiles can be displayed and exported from two point picks, selected routes, and selected navigation. The profile view is enabled from the view menu.

Fixed problems with output of ESRI ARC ascii grids from mbgrid and mbmosiac.

Added interactive control over the target of precision of the navigation inversion in MBnavadjust.

Added output of Winfrog pts file to mbm_route2mission.

Added output of Winfrog pts file to mbgrdviz.

MBedit now automatically chooses appropriate acrosstrack and vertical annotation intervals when files are opened.

MBextractseggy now will extract subbottom data to segy files in sequential line files based on waypoints in a route file. The program generates a plotting shellscript that will in turn generate profile plots of the segy data. Long lines will be broken up into multiple plots.

Updated manual page for mbm_route2mission.

A bug in mbgrdtiff has been fixed that mislocated the geoTIFF images by 1/2 pixel, thanks to Gordon Keith.

The plotting macros mbm_plot, mbm_grdplot, mbm_xyplot, mbm_3dgrdplot, and mbm_histplot all now use the current GMT default parameter PLOT_DEGREE_FORMAT rather than the old DEGREE_FORMAT.

Upgraded the mbsystem/gsf code to GSF version 2.0.4. Since the libgsf code now has #ifdef statements allowing compilation under MacOSX, the

code contained in MB-System no longer has modifications relative to the generic GSF releases.

Added support for Simrad EM710 data in formats 56 and 57.

Fixed byte count problem with comment records in format 94 (XSE data).

Added GMT_end() calls to all programs calling gmtlib and pslib functions so that GMT "advisory file locking" does not system() calls to GMT programs.

Put (void *) casts into qsort() calls to avoid compiler warnings.

The macro mbm_grdplot now handles calls for a linear plot with decreasing x values (e.g. using -Jx-0.01/20 to specify the projection).

A new edit mode called "grab" has been added to MBedit. In this mode, the user drags a rectangle on the ping display. When the mouse is released, all unflagged beams within that rectangle are flagged.

All MB-System programs that read or write grids have been altered so that they will work with GMT 4.1.3 built in the default fashion (i.e. GMT built with "advisory file locking" enabled).

Fixed mbgrdtiff so that it creates geographic GeoTIFF images with the longitude bounds consistent with the user's default or specified lonflip value.

MBlist can now print out values associated with the port-most and starboard-most non-null beams and pixels. Use the special '=' or '+' characters in the -O option.

Support was added for a new MBARI ROV navigation format (format id 170)

Support was added for SEGY seismic data as single beam format (id = 160). Heading values are stored in an unused space in the trace header - this is an MB-System specific modification that will only be found in segy files generated by mbextractseg.

Ping number, and more importantly for seismic data, shot number annotation of navigation tracks is now supported by mbcontour and mbm_plot.

Fixed problem reading some Simrad multibeam data with slightly broken bathymetry records.

////////////////////////////////////

MB-System Version 5.0 Releases and Release Notes:

////////////////////////////////////

- **Version 5.0.9 February 20, 2006**

- **Version 5.0.8 February 8, 2006**
- Version 5.0.8beta5 February 3, 2006
- Version 5.0.8beta4 February 1, 2006
- Version 5.0.8beta3 February 1, 2006
- Version 5.0.8beta2 January 27, 2006
- Version 5.0.8beta January 24, 2006
- **Version 5.0.7 April 7, 2005**
- **Version 5.0.6 February 19, 2005**
- **Version 5.0.5 October 6, 2004**
- **Version 5.0.4 May 22, 2004**
- **Version 5.0.3 February 27, 2004**
- **Version 5.0.2 December 24, 2003**
- **Version 5.0.1 December 12, 2003**
- **Version 5.0.0 December 5, 2003**
- Version 5.0.beta31 April 29, 2003
- Version 5.0.beta30 April 25, 2003
- Version 5.0.beta29 March 10, 2003
- Version 5.0.beta28 January 14, 2003
- Version 5.0.beta27 November 13, 2002
- Version 5.0.beta26 November 3, 2002
- Version 5.0.beta25 October 15, 2002
- Version 5.0.beta24 October 4, 2002
- Version 5.0.beta23 September 20, 2002
- Version 5.0.beta22 August 30, 2002
- Version 5.0.beta21 July 25, 2002
- Version 5.0.beta20 July 20, 2002
- Version 5.0.beta18 May 31, 2002
- Version 5.0.beta17 May 1, 2002
- Version 5.0.beta16 April 5, 2002
- Version 5.0.beta15 March 26, 2002
- Version 5.0.beta14 February 25, 2002
- Version 5.0.beta13 February 22, 2002
- Version 5.0.beta12 January 2, 2002
- Version 5.0.beta11 December 20, 2001
- Version 5.0.beta10 November 20, 2001
- Version 5.0.beta09 November 6, 2001
- Version 5.0.beta08 October 19, 2001
- Version 5.0.beta07 August 10, 2001
- Version 5.0.beta06 July 30, 2001
- Version 5.0.beta05 July 23, 2001
- Version 5.0.beta04 July 20, 2001
- Version 5.0.beta03 July 19, 2001
- Version 5.0.beta02 June 30, 2001

- Version 5.0.beta01 June 8, 2001
- Version 5.0.beta00 April 6, 2001

MB-System Version 5.0.9 Release Notes:

The version 5.0.9 release of MB-System is purely a bug fix release, and includes only a few changes relative to the 5.0.8 release.

The macros `mbm_grdtiff`, `mbm_grd2arc`, `mbm_grd3dplot`, `mbm_grdinfo`, `mbm_grdtiff`, `mbm_grd2geovrml`, and `mbm_grdcut` have been fixed to work properly with the output of the GMT 4.1 version of `grdinfo`.

The code in `src/mbio/mb_swap.c` has been fixed so it will compile using the Solaris cc compiler.

MBprocess had been fixed so that it will read navigation formats using julian days properly.

MBnavedit has been altered so that speed and acceleration weighting values in the smooth inversion function can be less than 1.0.

MB-System Version 5.0.8 Release Notes:

The version 5.0.8 release of MB-System includes several changes relative to the 5.0.7 release.

MB-System 5.0.8 requires GMT 4.1 in order to build successfully.

The format 75 (`MBF_MBNETCDF`) i/o module has been altered to handle multiple pings with the same time stamp without breaking the beam edit (edit save file) scheme, which depends upon unique time stamps. When multiple pings with the same time stamp are encountered, the subsequent pings have multiples of 2 msec added so that each has a detectably unique time stamp. This issue relates to Thompson Seafalcon II multibeam data; this sonar collects five simultaneous across-track swathes. Since this is a deep water sonar, the maximum 10 msec time addition should not introduce excessive error in navigation or other aspects of the data.

The Edgetech Jstar format is now supported through the new MB-System formats 132 and 133. The Jstar format is relevant to Edgetech FSDW systems (and related sonar products). The FSDW systems include chirp subbottom profiler and dual frequency chirp sidescan sonar. Format 132

treats the low frequency sidescan as survey data, and format 133 treats the high frequency sidescan as survey data.

Incorrect trace scaling of subbottom and sidescan data in the Reson 7k format (format 88) has been fixed.

A new program called mb7k2jstar has been added that extracts Edgetech subbottom and sidescan data from Reson 7k format (88) files and writes that data in Edgetech Jstar (132/133) format files.

The comments in the install_makefiles script has been updated to show the correct parameters needed to build MB-System on a current Solaris system.

A feature to apply longitude and latitude offsets to navigation data has been added to MBnavedit.

The program mbextractsegy can now extract subbottom profiler data in segy format from both Reson 7k files (format 88) and Edgetech Jstar files (formats 132 and 133).

MBprocess kluge005 has been defined to cause survey data timestamps to be replaced by the timestamps of the corresponding merged navigation records. This allows timestamps fixed using MBnavedit to be inserted into processed data.

The program mbsegygrid can now apply a simple time-varying gain to traces before gridding. This gain may begin at either the start of each trace or at the seafloor arrival time. The user may also set the length of time the gain is applied; samples after the end of the gain window are zeroed.

The method for determining the best altitude value to be used in correcting amplitude and sidescan data has been improved in programs mbackangle and mbprocess.

The program mbgrid once again uses the Zgrid algorithm for thin plate spline interpolation. The code allows for the GMT Surface algorithm to be used instead by compiling with a -DUSESURFACE compile flag.

The macros mbm_grdplot and mbm_grd3dplot have been altered so that histogram equalization will work even if grdhisteq returns a smaller number of valid intervals than requested.

The capability of plotting amplitude vs. grazing angle histograms from mbackangle results has been fixed for sidescan data.

A further significant architectural change was implemented for release 5.0.8 in order to support data formats that have no explicit maximum number of

beams or pixels. The memory management of arrays used to hold bathymetry, amplitude, and sidescan data has been made dynamic. Now, when data records are encountered that include larger numbers of beams or pixels than will fit in the arrays previously allocated, those arrays are reallocated to the required size. This is handled automatically for all of the internal arrays used by MBIO functions. Of course, applications using MBIO must allocate arrays that are passed into functions like `mb_read`, `mb_get_all`, and `mb_get` to be populated by the desired data. In order for these arrays to be managed dynamically, the application must first register each array by passing the location of the array pointer to a new function called `mb_register_array`.

The program `MBgrdtiff` has been altered so that the geoTiff images produced are more generally portable.

A program called `mbrolltimelag` has been written to analyze attitude time lag. This macro extracts raw attitude and apparent slope values from multibeam data, and then calculates the cross correlation between roll and apparent slope over a specified range of time lags. If there is an attitude time lag, then the bathymetry collected over a planar bottom should be dominated by a jitter that is correlated, with a time lag, with the roll signal.

The format 56 (vendor Simrad multibeam format) i/o module has been altered to support data logged on byteswapped platforms (e.g. Windows Intel PC's.). The Simrad multibeam formats 56 and 57 now support recently introduced raw angle/range and water column imagery datagrams. These i/o modules also now handle cases where the beams listed in a sidescan datagram do not exactly match the beams listed in the corresponding bathymetry datagram differently than before. Previously the entire ping would have been dropped. Now, the ping is preserved but the raw sidescan samples are not used to generate binned sidescan.

The program `mbdatalist` has been augmented to allow users to easily identify some problems with swath data files and the processing parameters specified in parameter files. The `-n` and `-o` options are used to generate ancillary files for all swath files referenced through a recursive datalist structure. These options now invoke `mbinfo` with the `-n` option, causing the "inf" files to include listings of easily identified data problems. The `-q` option of `mbdatalist` now extracts and lists these data problems as well as problems with the processing parameters. The possible data problems include:

- No survey data found
- Zero longitude or latitude in survey data
- Instantaneous speed exceeds 25 km/hr
- Average speed exceeds 25 km/hr

- Sounding depth exceeds 11000 m
- Unsupported Simrad datagram

To populate the "inf" files of existing datalist structures with data problem notices, use mbdatalist with the -n option.

The program mbvelocitytool now allows users to interactively set the center as well as the range of the water sound speed model plot window.

Fixed mbm_plot so that it calculates reasonable plot bounds at high latitudes.

The program mbset now accepts '=' as well as ':' as separators between parameter names and values in -P option arguments (as suggested by Bob Covill).

The install_makefiles script has been altered so that the editable parameters are located towards the top of the file rather than below the documentation of example settings for different operating systems.

The program mbareaclean now incorporates a mean filter as well as a median filter (contributed by Gordon Keith).

The program mbmosaic will now mosaic grazing angle or acrosstrack slope as well as amplitude or sidescan data (contributed by Gordon Keith).

The program mblist will now output some format specific values from Simrad multibeam (formats 56 and 57). In particular, some system parameters, raw amplitude values, and raw sidescan samples may now be output (Contributed by Gordon Keith).

A new macro called mbm_makedatalist can easily generate a datalist referencing all identifiable swath files in a specified directory.

There is a known but not understood bug in MBnavedit. When built on SUSE 10 systems, use of the smooth inversion function causes the first line of the output edited navigation to have NaN values for the longitude and latitude.

//

MB-System Version 5.0.7 Release Notes:

//

The version 5.0.7 release of MB-System includes several changes relative to the 5.0.6 release.

MBprocess and MBset now support merging sonar depth (or draft) from separate time series files. This is controlled by the SONARDEPTHMODE, SONARDEPTHFILE, and SONARDEPTHFORMAT mbprocess parameters.

A bug in mbgrid has been fixed that affected the footprint gridding algorithm used with bathymetry from sonars on submerged platforms.

MBedit has new view options. The default is the the traditional waterfall view. Users may now also view the soundings from an alongtrack view perspective and an acrosstrack view perspective without static vertical offsets between pings. The view mode is controlled from the View menu and from keyboard macros (characters '2', '3', and '4').

The 5.0.6 release mistakenly left the code in mbr_em300raw.c in debug mode, causing copious stderr output when reading raw Simrad data (format 56). This has been corrected.

Problems with the output in debug mode of mbr_em300raw.c and mbr_em300mba.c have been fixed.

The handling of the tickinfo string in the plot macros mbm_plot, mbm_grdplot, mbm_grd3dplot, and mbm_xyplot have been fixed.

The orientation of the filename annotation by mbcontour has been fixed, and control over that orientation has been added to mbcontour and mbm_plot.

Fixed problem of uninitialized data in mbr_mbpronav.c.

Fixed problem with occasional incorrect scaling of sonar depth in mbldeoih format (71) data.

Fixed problem in which sonar depth could be calculated from implausible pressure values in some single beam or navigation formats.

Improved handling of interpolated asynchronous data, especially sonar depth, in Reson 7k data (format 88).

A capability to interpolate over repeated values was added to mbnavedit.

Fixed a problem with the beam footprint gridding algorithm in mbgrid that caused beam footprints to be miscalculated for submerged sonars.

Fixed MBgrdviz crashes related to route data by fixing problem with allocation and deallocation of route arrays in the mbview library.

Moved tide correction to end of processing tasks so that it doesn't mess up grazing angle calculations for amplitude and sidescan correction.

Added option to mbm_grdplot allowing the user to specify a separate grid file to be contoured. This code was contributed by Gordon Keith.

////////////////////////////////////

MB-System Version 5.0.6 Release Notes:

////////////////////////////////////

The version 5.0.6 release of MB-System includes several changes relative to the 5.0.5 release.

The man page for mbprocess has been updated with full documentation of the navigation formats supported for merging by mbprocess.

The merging of heading and attitude data from navigation files has been fixed.

The ability to merge attitude data from a separate file has been added to mbprocess, and the mbprocess and mbset man pages have been updated.

A problem producing ascii grids from mbgrid and mbmosaic has been identified, and a fix suggested by Gordon Keith adopted.

A problem with the -D option of mblist has been identified, and a fix suggested by Gordon Keith adopted.

A new program called mbneptune2esf has been contributed by Gordon Keith. MBneptune2esf imports manual data flagging performed using Simrad's NEPTUNE software and flags those beams in the corresponding MB-System files.

A new program called mbauvnavusbl has been added to the distribution. MBauvnavusbl reads a primary navigation file (usually from a submerged platform swath survey) and also reads secondary navigation (e.g. USBL fixes). The program calculates position offsets between the raw survey navigation and the secondary navigation every 3600 seconds (10 minutes), and then linearly interpolates and applies this adjustment vector for each primary navigation position. The adjusted navigation is output.

The ability to annotate tracklines on swath plots with the swath filenames has been added to mbm_plot and mbcontour. The annotation occurs at the beginning of the data associated with each file. This option can be used most simply by specifying -NF in mbm_plot. The suggestion and initial implementation were contributed by Gordon Keith.

A problem with setting file paths in parameter files in the different directories associated with recursive datalists has been fixed. The nature of and fix to this bug were determined by Gordon Keith.

Fixed makefiles to link libpsl.a with all programs making libgmt.a calls. This was necessitated by changes to the GMT4.0 release relative to the GMT4.0beta release.

Implemented latest GSF release (2.0.3).

Fixed, but not satisfactorily, a problem reading some older EM3000 data with the current format 56 i/o module.

Added release version of simple grid visualization demo mbgrdviz.

Improved the ability of mbgrid to embed background datasets.

MB-System Version 5.0.5 Release Notes:

The version 5.0.5 release of MB-System includes several changes relative to the 5.0.4 release.

The program mbgrid can now obtain background data from GMT grid files using grd2xyz as well as through raster databases using grdraster. See the -Kbackground option documentation in the mbgrid manual page.

The macro mbm_xbt has been substantially updated.

The -G option of mbinfo now avoids reporting zero starting positions (it always ignored zero positions for the reported data bounds).

Provides read-only support for Edgetech sidescan and subbottom profiler data in the new Reson 6046 format (format id 88).

A new program mbextractseggy allows for the extraction of subbottom profiler data into separate files in the SEG-Y format (this can apply only to data formats that incorporate subbottom data in with swath sonar data, and at present only supports format 88).

A new program mbseggyinfo is a utility for reading a segy format seismic data file and outputting some basic statistics. The table generated shows the filename, data counts, navigation totals, time and navigation of the first and last data records, minimum and maximum data values, and the geographic bounding box of the data.

A new program mbsegylist is a utility to output specified header values from segy seismic data files to stdout. The option -Ooutput_format is used to control the type and order of values output. By default, mbsegylist produces ASCII files in spreadsheet style, with data columns separated by tabs. Alternatively, the output can be binary, with each field represented as a double precision float (-A option).

A new program mbsegymgrid generates grids from subbottom profiler data (and seismic reflection data, and potentially other seismic data) in the SEG-Y format. These grids can then be displayed using GMT (through mbm_grdplot if desired).

The program mbm_plot now works properly when start and end times are specified using the -MMB and -MME options.

A bug involving the handling of edit save filenames by mbset and mbprocess has been fixed.

Errors in handling Simrad datagrams and edit save files on byteswapped machines (e.g. Intel or AMD processors) have been fixed.

The program mbdatalist has a new option -Z which causes a standard "datalist.mb-1" file to be created. This is a convenience file that applies the \$PROCESSED flag to be applied to the swath files referenced in a datalist named "datalist.mb-1".

Problems with the creation of amplitude vs. grazing angle correction tables using mbbackangle, and the use of those tables by mbprocess, have been fixed. The default settings for mbbackangle and amplitude vs. grazing angle correction by mbprocess have been changed.

The default angle mode for raytracing has been changed so that starting angles are adjusted using Snell's Law for the difference between the SSV and the initial depth in the SVP. This change affects mbvelocitytool, mbsvplist, mbset, and mbprocess.

The program mbsvplist now has an option -P that not only outputs SVPs in a swath file to individual ancillary SVP files (as with the -O option), but also sets the first SVP output file to be used by mbprocess to recalculate the bathymetry.

Problems with the MGD77 format i/o module have been fixed according to suggestions from Bob Covill.

--

MB-System Version 5.0.4 Release Notes:

The version 5.0.4 release of MB-System includes several changes relative to the 5.0.3 release.

All of the interactive tools (MBedit, MBnavedit, MBvelocitytool, MBnavadjust) have been changed to require linking with the Motif 2.0 or later library (or compatible open source versions such as OpenMotif or LessTif).

The MB-System distribution is now compatible with GMT 4.0b. There have been minor changes to the pslib and gmtlib APIs, so it is necessary to specify the linked version of GMT in the mbsystem/install_makefiles script. Set: `$GMTVERSION = "4.0"`; if you are using GMT 4.0b, or set: `$GMTVERSION = "3.4"`; if you are still using GMT 3.4

MBnavadjust has a significant new feature in which the contours displayed by the Nav Err window can be pre-generated. This greatly increases the speed with which the bathymetry crossings can be analyzed.

A "Flag View" feature has been added to MBedit, allowing users to flag all of the beams in the current display. Key macros have also been defined for both the "Flag View" and "Unflag View" buttons.

The raw Hydrosweep DS format (format 21) i/o module now estimates travel times from the bathymetry when data files lacking travel time records are read. This allows users to recalculate bathymetry by raytracing even if the travel times are not recorded.

MB-System Version 5.0.3 Release Notes:

The version 5.0.3 release of MB-System includes two bug fixes relative to the 5.0.2 release.

We have fixed a bug in the i/o modules for Simrad multibeam data (formats 56 and 57) that caused a failure to gracefully handle unsupported datagrams on byteswapped systems (e.g. Intel processors running Linux).

We have fixed a bug that caused edit save files to be incorrectly read on byteswapped systems (e.g. Intel processors running Linux).

We have fixed a bug in the i/o modules for binary SeaBeam 2100 data (formats 42 and 43) that caused data to be written incorrectly on byteswapped systems (e.g. Intel processors running Linux).

MB-System Version 5.0.2 Release Notes:

=====

The version 5.0.2 release of MB-System includes two bug fixes relative to the 5.0.1 release.

We have fixed a bug in the i/o module for Elac Bottomchart data in the XSE format (94) in which the sonar depth was added to bathymetry values when new data files were written.

We have also fixed problems related to reading and writing SeaBeam 2100 data in the binary formats 42 and 43.

=====

MB-System Version 5.0.1 Release Notes:

=====

The version 5.0.1 release of MB-System includes two bug fixes relative to the 5.0.0 release. The program mbgrid has been fixed so that it compiles correctly under Red Hat Linux. The program mbcopy has been fixed so that time and space bounds are successfully applied to pings with a time gap error.

Also, the distribution now has a top directory name of mbsystem-5.0.1 rather than just mbsystem. This will allow users to unpack the distribution in the target location without overwriting an existing older MB-System installation. Users can then rename the directory to mbsystem or create a soft link to mbsystem-5.0.1 named mbsystem (e.g. `ln -s mbsystem-5.0.1 mbsystem`).

=====

MB-System Version 5.0.0 Release Notes:

=====

The version 5.0 release of MB-System includes a number of changes and improvements relative to the version 4 releases. The most significant changes include:

A new approach to managing data processing.

- Many tools - one output file. In previous versions of MB-System, each processing program read an input swath data file and produced an output swath data file. This "serial" processing scheme generally produced a large number of intermediate data files. ### MB-System Version 5.0 features the integration of the editing and analysis tools with a single program, mbprocess, that outputs processed data files. The new "parallel" processing scheme covers bathymetry data processing,

but does not yet incorporate the sidescan processing capabilities. All of the old tools and capabilities are still part of the distribution.

- Recursive datalists. The lists of data files used by gridding and plotting programs can now be recursive, making it simpler to manage data from many different surveys.
- Automatic format identification. MB-System programs will now attempt to automatically identify the swath data format based on the filename suffix.
- Extended inf files. Users can generate inf files by directing the output of mbinfo to a file named by adding an ".inf" suffix to the swath data file name. Several programs can parse inf files, if they exist, to quickly obtain data locations or ranges. This feature speeds operations such as gridding, mosaicing, and automated plotting.

New tools.

- mbnadjust. This new tool allows users to adjust poorly navigated surveys by matching features in overlapping swathes. It is particularly useful for processing surveys conducted from submerged platforms.
- mbprocess. This new tool performs a variety of processing tasks and produces a single output processed swath data file. The program mbprocess can apply bathymetry edits from mbedit and mbclean, navigation edits from mbnedit, sound velocity profile changes from mbvelocitytool, and a variety of other corrections.
- mbset. This new tool allows users to create and modify the parameter files used to control the operation of mbprocess.
- mbdatalist. This new tool allows users to list the files referenced by a recursive datalist structure. It can also be used to create the ancillary ".inf", ".fvt", and ".fvt" files for all of the data files referenced in a recursive datalist structure.
- mbsvplist. This new tool lists water sound velocity profiles embedded in swath data files, creating secondary files that can be read into MBvelocitytool.
- mbareaclean. This new tool identifies and flags artifacts in swath sonar bathymetry data within a specified area of interest. The area is divided into a grid with square cells or bins, and the data are grouped according to these bins. Once all of data are read, statistical tests are applied to the soundings within each bin.

Improved bathymetry and navigation editors.

- MBedit and MBnedit now swallow data files whole rather than reading in limited size buffers.

- MBedit now outputs beam edit events rather than an entire swath file. The edits are applied by MBprocess.
- MBnavedit now outputs the edited navigation rather than an entire swath file. The edited navigation is merged using MBprocess.
- Both editors show the position of the currently displayed data within the entire data file.
- MBnavedit has two navigation modeling modes relevant to swath data collected using poorly navigated ROVs and towfishes. One mode applies a dead reckoning model with interactively set drifts, and the other involves inverting for an optimally smooth navigation by penalizing speed and acceleration.

Support for Projected Coordinate Systems

- MB-System now incorporates the source code for the PROJ.4 Cartographic Projections library, providing support for (apparently) all commonly used geodetic coordinate systems. PROJ.4 was developed by Gerald Evenden (then of the USGS), and was obtained from the www.remotesensing.org website.
- A large number of commonly used projected coordinate systems (e.g. UTM) are defined in a file (mbsystem/share/projections.dat) distributed with MB-System. These include all of the standard UTM zones, all of the standard state plate coordinate systems, and most of the European Petroleum Survey Group (EPSG) coordinate systems (also including UTM).
- MB-System can now handle swath data that is navigated in a supported projected coordinate system. In particular, data files that are navigated with UTM eastings and northings instead of longitude and latitude can now be plotted and processed with MB-System.
- The programs mbgrid and mbmosaic can now output grids and mosaics in any of the projected coordinate systems specified in mbsystem/share/projections.dat.
- The TIFF images generated with mbm_grdtiff and mbgrdtiff now fully conform to the GeoTIFF standard, providing that the source grids or mosaics were generated using mbgrid or mbmosaic in either Geographic coordinates, UTM coordinates, or any of the EPSG coordinate systems specified in the projections.dat file. This means, for instance, that GeoTIFF images generated with mbgrdtiff will be properly georeferenced when they are imported into ESRI ArcGIS or other GIS packages.

Restructuring the code.

- All of the C code now conforms to the ANSI C standard.

- The underlying input/output library (MBIO) has been substantially rewritten. The structure has been streamlined, simplifying both future development and support of the existing code. The MBIO API has been greatly modified.

Handling of old Simrad multibeam data.

- Vendor format data from the old Simrad multibeam (pre- 1997 sonars) are now supported by a single format id (51) rather than a separate format id for each sonar model. The old format id's are automatically aliased to 51, so existing shells scripts will continue to work.
- Sidescan data from old Simrad multibeam (pre-1997 sonars) are now handled in the same manner as data from the newer sonars (e.g. EM3000, EM3000, EM120). The raw samples in the vendor data format are binned, averaged, and interpolated into a 1024 pixel sidescan swath. This binned sidescan is not saved in the vendor format, so it is recommended that the data be copied to an extended format (57) that stores both bathymetry beam flags and processed sidescan. Format 57 is also used for processing data from the current Simrad multibeam sonars.

Streamlining of MB-System Default Parameters.

- Prior to version 5.0, the MB-System defaults set by mbdefaults included the format id, a control for ping averaging, longitude and latitude bounds for windowing by area, and begin and end times for windowing in time. These values are no longer set in the .mbio_defaults file or controlled by mbdefaults. As noted above, the format id is automatically identified from the filename when possible. When filenames do not match one of the recognized structures, users must specify the format using the relevant programs -Fformat option. The controls for ping averaging and windowing in time and space are rarely used, and must now be explicitly set in command line arguments.

New Data Formats

- Furuno HS10 multibeam bathymetry is supported as format 171.
- SeaBeam 2120 multibeam data in the L3 Communications XSE format are supported as format 94 (already used to support Elac Bottomchart MkII XSE data).
- Raw STN Atlas multibeam data generated by the upgraded Hydrosweep DS2 multibeam on the R/V Ewing are supported by read-only format 182. Processing is supported using the augmented read-write format 183.

- The IFREMER netCDF multibeam archiving data format is supported as format 75. Similarly, the IFREMER netCDF navigation archiving data format is supported as format 167.
- The STN Atlas processing data format SURF is supported as format 181. At present, SURF is supported as a read-only format. This allows plotting and gridding of the SURF data, but not processing. Writing or translating the SURF data to allow processing will be supported in a later version.
- The Hawaii Mapping Research Group's new MR1 format is supported as format 64. This format is used to disseminate data from both the HMRG interferometric sonars (e.g. MR1) and the WHOI DSL 120 deep-towed interferometric sonar. This format has been supported by including the code for the HMRG library libmr1pr in the MB-System library. Thanks to Roger Davis and HMRG for making the code available under the GPL.