## NAME

**mbm_multiprocess** − Macro to run mbprocess on the swath files referenced by a datalist using parallel processes.

## VERSION

Version 5.0

## SYNOPSIS

**mbm_multiprocess −I***datalist* [**−X***nprocesses* **−H −V**]

## DESCRIPTION

**mbm_multiprocess** is a macro used to efficiently process large numbers of swath data files by executing parallel instances of the program **mbprocess**. See the **mbprocess** manual page for a description of its operation.

The **−X***nprocesses* option sets the number of parallel processes that can be started by **mbm_multiprocess**. In general, the most efficient (fastest) execution of the overall command will be achieved when *nprocesses* equals the number of available CPUs or cores.

## MB-SYSTEM AUTHORSHIP

David W. Caress
Monterey Bay Aquarium Research Institute
Dale N. Chayes
Center for Coastal and Ocean Mapping
University of New Hampshire
Christian do Santos Ferreira
MARUM - Center for Marine Environmental Sciences
University of Bremen

## AUTHORSHIP OF THIS PROGRAM

Christian do Santos Ferreira
MARUM - Center for Marine Environmental Sciences
University of Bremen

## SIMPLE DESCRIPTION OF BASIC OPTIONS

**−H** This "help" flag cause the program to print out a description of its operation and then exit immediately.

**−I** *datalist*
Sets the input datalist filename. A datalist is an ascii file containing a list of the input swath sonar data files to be copied and their formats. In the *datalist* file, each swath data file should be followed by a data format identifier, e.g.:

```
datafile1 11
datafile2 24
```

As discussed in the **MB-System** manual page, datalists may reference other datalists, allowing users to construct recursive datalist structures. This program uses the **MBIO** library and will read or write any swath sonar format supported by **MBIO**. A list of the swath sonar data formats currently supported by **MBIO** and their identifier values is given in the **MBIO** manual page.

**−V** Causes **mbm_multiprocess** to operate in "verbose" mode so that it outputs more information than usual.

**−X** *nprocesses*
This option sets the number of parallel, simultaneous **mbprocess** processes that may be run. Default: *nprocesses* = 4.

## EXAMPLES

Suppose one has two format 88 Reson 7125 data files:

20110805_053612.mb88
20110805_054149.mb88

and that these files are ready to be processed with **mbprocess**. In order to execute the processing using multiple, parallel processes, use the macro mbm_multiprocess with a datalist file referencing the target swath files as input:

mbm_multiprocess −Idatalist.mb-1 −V −X2

The macro prints out the following as the processing proceeds:

```
Running mbm_multiprocess...

Program <mbprocess>

Program <mbprocess>
MB-system Version 5.3.1904
MB-system Version 5.3.1904

Program Operation:

Program Operation:
 Input file:     20110805_053612.mb88
 Input file:     20110805_054149.mb88
 Format:         88
 Format:         88
 Files processed only if out of date.
 Files processed only if out of date.
 Comments embedded in output.

 Comments embedded in output.

**: Data processed − out of date − unlocked:
        Input:  /Volumes/MappingAUVOps2011/test/20110805_054149.mb88
        Output: /Volumes/MappingAUVOps2011/test/20110805_054149p.mb88
**: Data processed − out of date − unlocked:
        Input:  /Volumes/MappingAUVOps2011/test/20110805_053612.mb88
        Output: /Volumes/MappingAUVOps2011/test/20110805_053612p.mb88
```

Note that the terminal messages from the two **mbprocess** instances are mixed because the processes are executed in parallel.

## SEE ALSO

**mbsystem**(1), **mbprocess**(1)

## BUGS

In insetos sao permitidos. Keine insekten hier gestattet ist.