NAME

mbformat − List information about swath sonar data formats supported by the **MBIO** library.

VERSION

Version 5.0

SYNOPSIS

mbformat
[--format=format_id {-Fformat_id}
--input=file {-Ifile}
--list-ids {-L}
--list-root {-K}
--verbose {-V}
--html {-W}
--help {-H}]

DESCRIPTION

mbformat is a utility which identifies the swath sonar data formats associated with **mbio** format id's. If no format id or input filename is specified, **mbformat** lists all of the currently supported formats along with short descriptions. If a format id is specified using the **−F** option, then **mbformat** prints a short description of that format. If a filename is specified using the **−I** option, then **mbformat** attempts to identify a valid format id for that file using swath data filename prefix and suffix conventions embedded in **MB-System**. The program also determines the filename "root", which is the filename minus whatever format-specific prefix or suffix has been recognized. In no prefix or suffix is recognized, then the root is simply the entire filename.

Normally, **mbformat** prints out a brief description of each identified format. If the **−L** option is used, **mbformat** simply prints out the valid format id number, or 0 if a file or format has been specified but no valid id can be identified. If the **−K** option is used, **mbformat** will print out the filename "root" followed by the format id number.

MB-SYSTEM AUTHORSHIP

David W. Caress
Monterey Bay Aquarium Research Institute
Dale N. Chayes
Center for Coastal and Ocean Mapping
University of New Hampshire
Christian do Santos Ferreira
MARUM - Center for Marine Environmental Sciences
University of Bremen

OPTIONS

−−format=format_id −Fformat_id

Sets the format id to be listed. If no format is given, all of the currently supported formats will be listed. A list of the swath sonar data formats currently supported by **MBIO** and their identifier values is given in the **MBIO** manual page.

−−help −H

This "help" flag cause the program to print out a description of its operation and then exit immediately.

−−input=file −Ifile
Sets the filename to be tested against known filename prefix and suffix conventions in order to identify the format id.

−−list−root −K
Causes the fileroot and the format id to be output. The fileroot is the filename with any format specific suffix removed.

−−list−ids −L
Causes the format descriptions to be omitted so that only the **MBIO** format id numbers are listed.

−−verbose −V
Normally, **mbformat** only prints out format descriptions. If the **−V** flag is given, then **mbformat** works in a "verbose" mode and also outputs the program version being used.

−−html −W
Output the list of formats as HTML.

EXAMPLES

Suppose one wishes to identify the swath sonar data format associated with a format id of 11. The following will suffice:

```
mbformat −F11
```

and the result will be this output:

```
MBIO data format id: 11
Format name:        MBF_SBSIOMRG
Informal Description: SIO merge Sea Beam
Attributes:         Sea Beam, bathymetry, 16 beams, binary, uncentered,
                    SIO.
```

Suppose one wishes to list all of the currently supported data formats. The following will suffice:

```
mbformat
```

Suppose one wants to find out what format is associated with a raw SeaBeam 2112 file named sb199811231045.rec:

```
mbformat −I sb199811231045.rec
```

This results in the output:

```
MBIO data format id: 41
Format name:        MBF_SB2100RW
Informal Description: SeaBeam 2100 series vender format
Attributes:         SeaBeam 2100, bathymetry, amplitude
                    and sidescan, 151 beams and 2000 pixels, ascii
                    with binary sidescan, SeaBeam Instruments.
```

Using the −K option:

```
mbformat −K −I sb199811231045.rec
```

will produce the following output:

```
sb199811231045 41
```

where the format id has been identified as 41 because of the ".rec" file suffix and the fileroot has been identified as "sb199811231045" by removing the suffix. Use of the −L option:

```
mbformat −L −I sb199811231045.rec
```

will produce output with just format id:

```
41
```

SEE ALSO

mbsystem(1), **mbio**(1)

BUGS

No known bugs.