

NAME

mbsystem – A set of utilities for the processing and display of seafloor mapping data, particularly bathymetry, amplitude, and sidescan data from multibeam, sidescan, and interferometric sonars.

VERSION

Version 5.8

MB-SYSTEM AUTHORSHIP

David W. Caress
Monterey Bay Aquarium Research Institute
Christian do Santos Ferreira
Center for Marine Environmental Sciences (MARUM)
University of Bremen
Dale N. Chayes
Center for Coastal and Ocean Mapping
University of New Hampshire

INTRODUCTION

MB-System is an open source software package for the processing and display of seafloor mapping data, particularly bathymetry and backscatter imagery data derived from multibeam, interferometry, and sidescan sonars. **MB-System** is freely available for download as source code that can be built and installed on Linux and OS-X computers. Documentation, tutorials, and FAQ are provided in this website. The **MB-System** discussion email lists allows users to engage with **MB-System** developers and other users from around the world.

MB-System was originally developed in 1993 at the Lamont-Doherty Earth Observatory (L-DEO) of Columbia University by David W. Caress and Dale N. Chayes with support from the Marine Geology and Geophysics program of the U.S. National Science Foundation (NSF).

MB-System is now a collaborative effort between the Monterey Bay Aquarium Research Institute (MBARI), the Center of Marine Environmental Science (MARUM) at Universität Bremen, and the Center for Coastal and Ocean Mapping (CCOM) at the University of New Hampshire. The David and Lucile Packard Foundation has provided the primary support for **MB-System** through MBARI since 1998. NSF supported **MB-System** development from its inception in 1993 through 2018.

WEBSITE AND SOURCE CODE REPOSITORY

The website for **MB-System** is hosted by MBARI, and serves as the primary source of information about this project and software:

<https://www.mbari.org/technology/mb-system/>

SOURCE CODE REPOSITORY

The source code repository for **MB-System** is at:

<https://github.com/dwcaress/MB-System>

COPYRIGHT

MB-System Copyright (C) 1993-2024 by

David W. Caress (caress@mbari.org)
Monterey Bay Aquarium Research Institute
Moss Landing, California, USA

Dale N. Chayes

Center for Coastal and Ocean Mapping
University of New Hampshire
Durham, New Hampshire, USA

Christian dos Santos Ferreira
Zentrum für Marine Umweltwissenschaften (MARUM) | Center of Marine Environmental Science (MARUM)
Universität Bremen | University of Bremen
Bremen, Deutschland | Bremen, Germany

LICENSING

The MB-System source code is distributed under the GNU General Public License, version 3, as formulated by the GNU Project. Early MB-System distributions were described as "public domain", which meant there was no restriction whatsoever on the use of the code. For over a decade we have adopted the more restrictive GNU GPL license in order to insure that anyone who distributes software based in whole or in part on MB-System also distributes their modified MB-System source code and any additional source code.

The file "GPL.md", located at the top of the MB-System source code distribution directory structure, contains the text of the GNU GPL version 3. This text and associated explanations are available at the GNU Project website <https://www.gnu.org/licenses/gpl-3.0.en.html>

The MB-System distribution includes some source code derived from packages that are distributed separately and have been authored by programmers other than the MB-System team. This includes:

The Generic Sensor Format (GSF) library source located in `mbsystem/src/gsf`

The GSF package is maintained and distributed by Leidos Corporation under contract to the United States Naval Oceanographic Office. The current source code can be downloaded from <https://www.leidos.com/products/ocean-marine> and is licensed using the LGPLv2.1 open source license.

The SURF API (SAPI) library source located in `mbsystem/src/surf` The SAPI package was released under the GNU General Public License by Atlas Hydrographic in 2001; Atlas Hydrographic has since been acquired by Teledyne Marine Technologies Inc.

The MR1PR library source located in `mbsystem/src/mr1pr` This package was primarily developed by Roger Davis of the Hawaii Mapping Research Group (HMRG) at the University of Hawaii. The MR1PR source code was released without restriction by HMRG in 2000. This code is licensed as part of MB-System under the GNU General Public License (version 3).

The `mb_beaudoin()` function found in `mbsystem/src/mbio/mb_angle.c` This important function that calculates beam angles for multibeam sonars was contributed by Jonathan Beaudoin of CCOM/JHC University of New Hampshire and John Hughes Clarke of the Ocean Mapping Group, University of New Brunswick. This code is licensed as part of MB-System under the GNU General Public License (version 3).

The `mb_mergesort()` function found in `mbsystem/src/mbio/mb_esf.c` This implementation of the merge sorting algorithm derives from the GNU-Darwin Distribution. This code is released under both the Apple Public Source License Version 1.1 and the BSD license, with original copyright by the Regents of the University of California.

The Terrain Relative Navigation (TRN) algorithm and related software The TRN software included in MB-System derives from software developed by Steve Rock of Stanford University, many of Steve Rock's graduate students from 2000 through 2020, and Rob McEwen, Rich Henthorn, and Kent Headley of MBARI. The integration of TRN into MB-System was done by Kent Headley and David Caress, and the relevant source files are found in `mbsystem/src/mbtrn`, `mbsystem/src/mbtrnav`, `mbsystem/src/mbtrnframe`, and

mbsystem/src/mbtrnutils. This code is licensed as part of MB-System under the GNU General Public License (version 3).

CAVEAT

The MB-System source code and any associated documentation does not come with any warranties, nor is it guaranteed to work on your computer or to do anything useful. The user assumes full responsibility for the use of this system. In particular, David W. Caress, the Monterey Bay Aquarium Research Institute, the Lamont-Doherty Earth Observatory of Columbia University, or any other individuals or organizations involved in the design and maintenance of the MB-System software package are NOT responsible for any damage that may follow from correct or incorrect use of these programs.

SEE ALSO

MB-System consists of many programs, some of which are graphical tools. The following libraries, programs and macros have separate manual pages:

mbsystem(1): This manual page for the **MB-System** software package.

mbio(3): The **MB-System** input-output (i/o) library supporting many seafloor mapping data formats.

Compiled programs:

mb7k2jstar(1): Extracts subbottom profiler and/or sidescan sonar data from Reson 7k format data files into Edgetech Jstar format data files.

mbabsorption(1): Calculates water sound absorption as a function of water properties.

mbareaclean(1): Identifies and flags bad beams in swath sonar bathymetry data within a specified area.

mbauvloglist(1): Generate arbitrary text lists of values from MBARI AUV mission log files.

mbbackangle(1): Generates corrections for sidescan and/or amplitude data by calculating average amplitudes as a function of the seafloor grazing angle.

mbclean(1): Identifies and flags bad beams in swath sonar bathymetry data.

mbconfig(1): Provides command line access to the MB-System version and to the locations of the levitus database and the OTPS tidal correction software.

mbcopy(1): Copy swath sonar data files.

mbctdlist(1): List CTD data in swath sonar data files.

mbdatalist(1): Parses recursive datalist files and outputs the complete list of data files and formats.

mbdefaults(1): Set or list default mbio parameters for reading and writing swath sonar data

mbdumpsf(1): mbdumpsf reads an MB-System edit save file and dumps the contents as an ascii table to stdout.

mbedit(1): Interactive editor used to flag bad beams in swath sonar bathymetry data.

mbeditviz(1): Interactive 3D visualization bathymetry editing and attitude bias patch test.

mbextractseg(1): Extract subbottom profiler or center beam reflection data to segy files.

mbfilter(1): Apply one or more simple filters to sidescan and/or beam amplitude data.

mbfnv2navlab(1): Converts an MB-System fast navigation (fnv) text file to a Kongsberg Navlab smoothed navigation binary file.

mbformat(1): List information about swath sonar data formats supported by the MBIO library.

mbgetesf(1): Extract bathymetry edits in edit save file format.

mbgetphotocorrection(1): Generates a 3D table of image correction values as a function of lateral position and standoff distance from a camera.

mbgpstide(1): Generate tide files from the height above ellipsoid data in the 'h' datagrams of Kongsberg multibeam data files

mbgrd2gltf(1): Convert bathymetric grid data to GLTF format with optional settings, including Draco compression.

mbgrd2octree(1): Translates a topography grid to a TRN octree topography model for use with the MB-System TRN (terrain relative navigation) tools.

mbgrdtilemaker(1): Creates a set of overlapping square grids (tiles) from an original topography grid.

mbgrdrviz(1): Visualize GMT grids.

mbgrid(1): Grid bathymetry, amplitude, and sidescan data from swath sonar data files.

mbhistogram(1): Obtain histogram of bathymetry, amplitude, or sidescan data from swath sonar data files.

mbimagecorrect(1): Applies brightness and contrast corrections to images using OpenCV algorithms.

mbimagelist(1): Parses recursive imagelist structures, performing one or more tasks on the image files referenced in the imagelist(s).

mbinfo(1): Output some basic statistics of swath sonar data files.

mblevitus(1): Create a water velocity profile which is representative of the mean annual water column for a specified 1 degree by 1 degree region.

mblist(1): List data in swath sonar data files.

mbmakedatalist(1): Generate a datalist of the swath files in a specified directory.

mbmakeplatform(1): Create or modify an MB-System platform file, which represents a survey system as a set of sensors with positional and angular offsets.

mbmapscale(1): Outputs the local scaling between geographic coordinates and meters east and north at a specified latitude.

mbmesh(1): Process swath bathymetry data and generate 3D point clouds and GLB models.

mbminirovnav(1): Merges MBARI MiniROV data logs and outputs the ROV navigation in the format used for other ROV navigation at MBARI (format 165, MBF_MBARIROV).

mbmosaic(1): Mosaic sidescan and amplitude data.

mbnavadjust(1): Package that solves for optimal navigation by matching bathymetry of overlapping swathes.

mbnavadjustmerge(1): Command line tool to create and modify MBnavadjust projects, including creating new projects, importing swath data, merging projects, and managing global and crossing navigation ties.

mbnavedit(1): Interactive editor used to fix problems with navigation in swath sonar data files.

mbnavlab2fnv(1): Converts a Kongsberg Navlab smoothed navigation binary file to an MB-System fast navigation (fnv) text file.

mbnavlist(1): List navigation data in swath sonar data files.

mbotps(1): Generate open ocean tidal model for specified time and location using the Oregon State Tidal Prediction Software (OTPS) package.

mbphotogrammetry(1): Generates bathymetry from stereo pair photographs taken from a submerged survey platform.

mbphotomosaic(1): Makes a mosaic of navigated downlooking photographs.

mbpreprocess(1): Perform preprocessing of the logged data comprising a survey, including applying lever arm corrections (if necessary) and setting up the MB-System processing environment.

mbprocess(1): Process swath sonar data files, including merging navigation, applying bathymetry edits, recalculating bathymetry by raytracing, and applying a variety of other corrections.

mbrolltimelag(1): Estimate attitude time lag by cross correlation of apparent bottom slope with the roll time series.

mbrouatetime(1): Outputs a list of the times when a survey passes the waypoints of a planned survey route.

mbsegygrid(1): Generate time vs. trace number grids of seismic data from segy files.

mbsegyinfo(1): Output some basic statistics of segy seismic data files.

mbsegylist(1): List selected header values in segy seismic data files.

mbsegypsd(1): Calculates the power spectral density function of each trace in a segy data file, outputting the results as a GMT grid file.

mbset(1): Create and modify parameter files used to control mbprocess.

mbsslayout(1): Translate time-based sidescan sonar data into backscatter laid out into a regular array of pixels on the seafloor by projecting onto a topographic model.

mbsvplist(1): Extract water sound velocity profiles (SVPs) from swath data files.

mbsvpselect(1): Select the best available sound speed model for each swath file in a survey according to user specified criteria.

mbswath2las(1): Exports swath bathymetry soundings to LAS 1.4 point cloud files.

mbtiff2png(1): Convert GeoTiff images to PNG format images setting no data regions to be transparent.

mbtime(1): Converts between calendar time and unix time.

mbtrnpp(1): Real-time preprocessor that reads multibeam sonar data, applies automated cleaning and down-sampling, and passes the resulting bathymetry to a terrain relative navigation (TRN) process.

mbusbl2fnv(1): Converts a USBL (ultra-short baseline) ROV tracking CSV file to an MB-System fast navigation (fnv) text file.

mbvelocitytool(1): Interactive program for modeling the affect of the water velocity profile on swath sonar bathymetry calculations.

mbvoxelclean(1): mbvoxelclean identifies and flags artifacts in swath bathymetry data using a 3D density filter.

Alphabetical List of GMT Modules:

MB-system also includes four plug-in modules for the GMT software package that are built as a shared library that can be called by GMT.

mbcontour(1): GMT plug-in that generates GMT Postscript color contour plots of swath bathymetry.

mbgrd2obj(1): GMT plug-in that translates a topography grid to an OBJ format 3D model file for visualization and 3D printing

mbgrdtiff(1): GMT plug-in that generates a GeoTIFF image from gridded data.

mbswath(1): GMT plug-in that generates GMT compatible Postscript color and color shaded relief plots of swath bathymetry and backscatter data.

Alphabetical List of Macros:

Macros are executable shellscrips which make use of programs from the MB-System and other software packages to accomplish common tasks easily. Some are written in Perl and others in Python3.

mbm_arc2grd(1): Convert an ArcView ASCII grid file to a GMT grid file.

mbm_bpr(1): Process data from a Seabird SBE53 pressure sensor into a tidal model for use by mbprocess.

mbm_copy(1): Translate groups of swath data files between formats.

mbm_grd2arc(1): Convert a GMT grid file to an ArcView ASCII grid file.

mbm_grd3dplot(1): Reads a GMT GRD grid file and writes a shellscript which will generate a GMT 3D perspective view of the data.

mbm_grdcut(1): Extract a subarea of a GMT grid file.

mbm_grdinfo(1): Get information regarding a GMT grd file when the region of interest is a subset of the area covered in the input file.

mbm_grdplot(1): Reads a GMT GRD grid file and writes a shellscript which will generate a GMT map of the data.

mbm_grdtiff(1): Reads a GMT GRD grid file and writes a shellscript which will generate a TIFF image of the data.

mbm_histplot(1): Create an executable shellscript which will generate a GMT histogram plot of a dataset.

mbm_makedatalist(1): Macro to generate a datalist of the swath files in a specified directory.

mbm_makeimagelist(1): Generates MB-System imagelist files within MBARI Low Altitude Survey System (LASS) stereo seafloor photography data directories.

mbm_makesvp(1): Generate a sound velocity profile model from sound speed and depth values in swath files.

mbm_multicopy(1): Translate groups of swath data files between formats using parallel processes.

mbm_multidatalist(1): Generates ancillary files used in data management using parallel processes.

mbm_multiprocess(1): Apply specified processing tasks to a swath data file using parallel processes.

mbm_phins2fnv(1): Translate processed Phins INS data to an fnv file for use in MB-System processing.

mbm_plot(1): Reads a swath sonar data file and writes a shellscript which will generate a swath and/or contour plot of the data.

mbm_rollererror(1): Reads a multibeam bathymetry file, calculates the noise in the vertical reference used by the sonar, and generates a file of roll corrections for use by mbprocess.

mbm_route2mission(1): Translate an mbgrdviz survey route file into an MBARI AUV mission script.

mbm_stat(1): Runs mbinfo on a swath sonar data file and extracts beam statistics from the output of mbinfo.

mbm_tmap(1): Macro to convert XYZ point clouds to 3D Tiles and generate a Cesium viewer.

mbm_trnplot(1): Plot map views of an mbtrnpp session.

mbm_utm(1): Performs forward and inverse UTM projections of ASCII data triples.

mbm_xbt(1): Processes a Sparton XBT data file and outputs a sound velocity profile file which can be used to process swath sonar data.

mbm_xyplot(1): Reads one or more xy data files and writes a shellscript which will generate GMT plot of the data.

mbpy_grd3dplot(1): Python/PyGMT-era replacement for mbm_grd3dplot; reads a GMT grid file and writes a GMT modern-mode shellscript which will generate a 3D perspective view of the data.

mbpy_grdplot(1): Python/PyGMT-era replacement for mbm_grdplot; reads a GMT grid file (or georeferenced image) and writes a GMT modern-mode shellscript which will generate a map of the data.

mbpy_histplot(1): Python/PyGMT-era replacement for mbm_histplot; creates a GMT modern-mode shellscript which will generate a frequency histogram plot of a dataset.

mbpy_xyplot(1): Python/PyGMT-era replacement for mbm_xyplot; reads one or more xy data files and writes a GMT modern-mode shellscript which will generate a plot of the data.

Deprecated Programs and Macros:

These are programs and macros that are no longer used, and are not built by default when MB-System is installed. If required, these can be built and installed with a special argument to the CMake build system.

mb7k2ss(1): mb7k2ss extracts Edgetech sidescan sonar data from Reson 7k format data, bins and lays the sidescan onto the seafloor, and outputs files in the MBF_MBLDEOIH formst (MBIO format id 71).

mb7kpreprocess(1): Preprocess Reson 7k data (format 88), including applying time lag and biases to attitude and navigation data.

mbauvnavusbl(1): Merge inertial and surface tracking navigation for submerged sonar platforms (e.g. ROVs and AUVs).

mbhsdump(1): List raw information contained in Hydrosweep DS data files (formats 21 and 24).

mbhysweepprocess(1): Preprocess Hysweep HSX data (format 201), including applying time lag and biases to attitude and navigation data.

mbinsreprocess(1): Reprocesses INS navigation data (e.g. from a Kearfott SeaDevil) by removing navigation tears from free-inertial periods via linear interpolation.

mbkongsbergpreprocess(1): performs preprocessing of data from third generation Kongsberg multibeam sonars (e.g. EM122, EM302, EM710).

mbneptune2esf(1): Extract bathymetry edits from Simrad Neptune software into edit save file format.

mbotpsold(1): Predicts tides using the OSU Tidal Prediction Software (OTPS) distribution.

mbrollbias(1): Evaluate the roll bias of a swath sonar system using two pieces of coincident bathymetry data collected with opposing ship headings.

mbrphsbias(1): Solves for roll-bias, pitch-bias, heading-bias, and array-water-sound-speed-bias parameters by a brute force multi-dimensional search minimizing the variance of unflagged bathymetry soundings.

mbstripnan(1): Filter to remove NaN nodes.

mbswplspreprocess(1): Preprocess SwathPlus SXP data (format 222), including applying time lag and biases to attitude and navigation data.

mbm_fmtvel(1): Scans a Hydrosweep swath sonar data file using the program mbhsdump and generates a list in columnar format with time, date, latitude, longitude, C-mean, and C-keel entries.

mbm_grd2geovrml(1): Create and execute commands which generate a TerraVision tileset and GeoVRML set of files that can be combined with other data and viewed in a web browser.

mbm_grid(1): Reads a swath sonar data file and writes a shellscript which will grid bathymetry data or mosaic sidescan (or amplitude) data using reasonable guesses at the appropriate grid bounds and bin size.

BUGS

It doesn't do everything we want it to yet, it doesn't work with every kind of seafloor mapping data ever collected, and sometimes it breaks.