Use LLMs to Build Repair Tools, Not Patch Generation: Cost-Effective Automated Program Repair

Anonymous submission

Abstract

Large language models (LLMs) repair buggy submissions to programming assignments well, but they are deployed *one query per submission*: every buggy program triggers a fresh model call, so cost, latency, and external dependence scale with enrollment and recur every term, while the specification-level reasoning being purchased is identical across a class — and caching or cheaper models shrink only the constant, not the structure. We propose CoEP, which moves the LLM from the marginal-cost to the fixed-cost column: *spend the model once per assignment, not once per submission*. An LLM agent reads the assignment and a clustered sample of worked (buggy $\rightarrow$ fixed) pairs and authors the assignment-specific layer of a local repair tool — AST rewrite rules named after the misconceptions they fix — atop a shared symbolic substrate of generic edits and reference-guided minimal-hunk transplant from the class's own correct solutions. Every candidate patch is validated against the instructor's tests before it is kept; the tool can never self-report success, and submissions it abstains on escalate to a conventional per-submission call, so coverage is never sacrificed. On the standard benchmark of this literature, the synthesized tool repairs *more* submissions with *smaller* patches than the strongest hand-built symbolic tool, on that tool's own corpus and metric — with the entire model spend collapsed into a one-off synthesis plus a small escalation tail, so everything repaired locally costs no model call at all, offline and deterministically. A price-invariant break-even analysis shows when amortization wins and why cheaper models and caching do not change the answer, and the artifact yields what a per-query API cannot: reproducible minimal patches and a per-class misconception profile.

Introduction

Timely, individualized feedback is the scarcest resource in programming education: introductory courses enroll hundreds of students on campus and tens of thousands online, each producing buggy submissions no instructor can examine one by one. Automated program repair (APR) has therefore long been proposed as a feedback engine for programming assignments: given a buggy submission and the assignment's test suite, produce a small patch that makes it correct while preserving the student's own approach (Yi et al. 2017; Gulwani, Radicek, and Zuleger 2018; Wang, Singh, and Su 2018; Hu et al. 2019; Ahmed et al. 2022).

Three generations of systems have pursued this goal. The first established the setting: test-driven repair of introductory assignments, with the requirement that a patch stay close to the student's program, since a correct but unrelated rewrite passes the tests and teaches nothing (Yi et al. 2017). The second exploited the structure of a *class*, mining the assignment's own solution space: CLARA clusters correct submissions, Sarfgen searches aligned examples, Refactory refactors correct solutions into a per-problem search space, and Verifix aligns the student's program to a reference under verified equivalence (Gulwani, Radicek, and Zuleger 2018; Wang, Singh, and Su 2018; Hu et al. 2019; Ahmed et al. 2022). These repair each submission cheaply, at two prices: an assignment must first accumulate a large pool of correct solutions, and repair proceeds by matching the student's control flow against one of them, so a submission whose structure diverges from every reference is out of reach (Orvalho, Janota, and Manquinho 2025). Both prices rise with task difficulty, which is why this generation is evaluated on novice-level assignments. The third removes both constraints at once: LLM-based repair needs neither a solution pool nor a structural match, and fixes the large majority of real student programs, up to 96.5% of buggy submissions in PyDex (Zhang et al. 2024), at modest per-bug prices (Xia and Zhang 2024, 2022; Liu et al. 2024; Yang et al. 2024).

What the third generation fixed in coverage, however, it broke in *cost structure*. Its deployment default is one model query per buggy submission, so spending scales linearly with enrollment and restarts every term — while the queries themselves are massively redundant. Assignment repair is a *many-instances, one-specification* regime: one handout is attempted by hundreds or thousands of students whose failures cluster into a handful of recurring misconceptions (Gulwani, Radicek, and Zuleger 2018; Hu et al. 2019); on the corpus we study, 77% of a repair prompt is byte-identical across submissions to the same assignment. Paying a model to rediscover the same off-by-one for the three-hundredth time is not intelligence at work; it is a billing artifact. The standard remedies do not change this shape: cheaper models and provider caching (Anthropic 2025; OpenAI 2024) shrink the *constant*, retrieval enriches the query (Dai et al. 2026), but

This is an anonymized submission for review purposes only. Distribution, citation, or public sharing of this manuscript is strictly prohibited. Copyright and publication details will appear in the final version if accepted.

every submission still triggers a frozen-model round trip, with the attendant marginal cost, latency, rate limits, nondeterminism, and shipping of student code to an external service. The question worth asking is not how much a call costs, but *where in the pipeline the LLM is invoked*.

Our answer moves the LLM from the marginal-cost column to the fixed-cost column: **spend the LLM once per assignment, not once per submission**. Agent research has shown that LLMs can author reusable code once and amortize it across many uses (Cai et al. 2024; Wang et al. 2024); classical program synthesis has even learned per-assignment fix rules from examples (Rolim et al. 2017). We instantiate this idea for assignment repair, under the discipline the setting demands — every patch validated against the instructor's tests, never trusted from generation. In CoEP (Cost-Effective Program repair), an LLM agent reads the specification, tests, and a clustered sample of worked (buggy $\rightarrow$ fixed) pairs, and authors the assignment-specific layer of a local repair tool: AST rewrite rules named after the misconceptions they fix. That layer runs on a shared symbolic substrate — a generic small-edit library and a reference-guided *minimal-hunk transplant* engine that adopts the smallest differing hunks from the structurally nearest correct solution, in the lineage of reference-reuse repair (Gulwani, Radicek, and Zuleger 2018; Wang, Singh, and Su 2018; Hu et al. 2019). Every candidate is executed against the visible tests before it is kept, and the builder loop refines the module against harness feedback; a tool can never self-report success. The frozen tool then repairs submissions locally, in about a second on a CPU, at *zero* marginal LLM cost, and the few it abstains on escalate to a conventional per-submission call, so the hybrid never sacrifices coverage.

The resulting artifact does not merely approximate the hand-built state of the art — it beats it on its own benchmark and its own metric. Against Refactory (Hu et al. 2019), CoEP's local repair covers more submissions at smaller patch size (97.8% vs. 90.8% repair rate, 0.326 vs. 0.40 mean relative patch size over 1,686 real student programs). We are explicit about attribution: the rule layer produces $\sim$13% of local fixes at near-minimal patch size (RPS $\approx$0.03), the transplant engine the rest — and a framework-only ablation shows the symbolic substrate alone already carries the coverage, so the LLM layer's measured contribution on this corpus is the *diagnosis* (misconception-labeled repairs) and the strategy-matched escalation path, not the headline number. The claim is therefore not that an LLM wrote a SOTA repairer; it is that the *invocation structure* — one cheap build plus a $\sim$2% fallback tail instead of an inference per submission — removes the per-submission model call for everything repaired locally, while the artifact it feeds exceeds the hand-built state of the art.

The stakes scale with where repair is deployed. In one CS1 offering the per-submission bill is dollars; on an online judge it is not: CodeNet aggregates 13.9M submissions to 4,053 problems, 46.4% of them failing their tests (Puri et al. 2021). At a representative frontier tier, one repair pass over that backlog is on the order of $18K of inference, re-paid as every new submission arrives — where the amortized route pays a fixed $\sim$$1K of one-off builds plus a $\sim$2% escalation tail, and the gap *widens* with every further submission. The comparison is also robust to pricing. If building a tool costs C_{build} and it locally resolves a fraction $(1-f)$ of submissions that would each have cost Δ, amortization wins once enrollment exceeds $N^* = C_{\text{build}}/(\Delta(1-f))$ — and when build and per-query spending are priced on the same token schedule, N^* is *invariant to token price*: "just use a cheaper model" shrinks both sides of the ledger and leaves the crossover untouched. Meanwhile the fixed-cost artifact carries properties per-submission inference cannot offer at any price, scoped to the locally repaired fraction: it assembles patches on the AST, so it cannot emit syntactically invalid code and splices minimal spans rather than regenerating files; it is deterministic and reproducible; it runs offline, so student code never leaves the institution and repair latency does not grow with enrollment; and its rule-fired repairs aggregate into a per-class misconception profile an API call never returns.

This paper makes the following contributions:

- **A cost-structure reformulation of assignment repair.** We move the LLM from per-submission marginal cost to per-assignment fixed cost, with a break-even analysis $N^* = C_{\text{build}}/(\Delta(1-f))$ that is price-invariant under a stated pricing assumption — amortization is a structural advantage, not a constant-factor one that cheaper models erase.
- **The CoEP system.** A builder agent synthesizes misconception-named AST rewrite rules through a generate–validate–refine loop (Madaan et al. 2023; Shinn et al. 2023), atop a shared substrate of generic edit rules and reference-guided minimal-hunk transplant with variable renaming; every patch is independently test-validated, so a tool can never self-report success, and abstentions escalate to a strategy-matched LLM fallback.
- **An empirical result on the baseline's own corpus and metric.** CoEP's local repair exceeds Refactory on both coverage and patch size at negligible one-off build cost, deterministic and offline at 1–2 s per submission, with an honest mechanism attribution (rule layer $\sim$13%, transplant $\sim$87%), a framework-only ablation isolating the LLM layer's contribution, and per-builder analyses across two commodity models.
- **Artifacts.** We release the harness, dataset-import pipeline, prompts, synthesized repairers, and all raw model outputs.[1]

The Cost Anatomy of Per-Submission Repair

Decomposing the per-submission prompt of our PyDex reproduction (and, mutatis mutandis, of ChatRepair-style systems (Zhang et al. 2024; Xia and Zhang 2024)) shows where the money goes. Averaged over the Refactory corpus, roughly three quarters of a query's input tokens — the assignment description, the visible tests, and the fixed instructions — are byte-identical across every submission to the same assignment; the buggy program is the only part that varies. Provider caching cannot even reach that redundancy: it discounts only a *leading* shared prefix, and PyDex's own prompt

[1] Anonymized repository submitted as supplementary material.




Figure 1: CoEP. LLM effort (blue) is spent once per assignment to synthesize a local repairer (red); at deployment, the large majority of submissions never touch a model.

layout places the buggy program first, so no shared prefix precedes the variable content at all — and even reordered, these prompts fall below the providers' cacheable minimums (1,024–4,096 tokens by model).

Two consequences follow. (1) *Caching is a discount, not a fix; here, not even a discount.* Prompt caching bills a shared prefix at $0.1\times$ after a $1.25\times$ write (Anthropic 2025); here it has nothing to bite on — the variable part leads the prompt and the whole prompt sits below the cacheable minimum — so the redundancy is real, but provider caching serves it at the wrong granularity. (2) *The redundancy is exactly the amortizable part.* What is constant per assignment, namely understanding the specification, the tests, and the space of likely mistakes, can be reified *once* into an executable artifact. That is the move CoEP makes, and the rest of the paper quantifies what it buys.

Approach

Problem Formulation

An *assignment* is a triple $A = (d, T, R)$: a natural-language description d, a test suite $T = \{(x_i, y_i)\}$ (function-entry or judge-style stdin/stdout), and the pool R of correct student solutions, which the setting assumes is available at feedback time — as every per-assignment system from CLARA to Refactory assumes (Gulwani, Radicek, and Zuleger 2018; Hu et al. 2019). A *repair* of a buggy submission b is a program p that passes all of T. Patch quality is measured, never gated: RPS, the tree-edit distance between the ASTs of b and p normalized by the size of b (computed with Refactory's reference implementation (Hu et al. 2019)), is reported for every repair, since a small patch is feedback on the *student's* program while a rewrite passes tests but teaches nothing (Yi et al. 2017).

Conventional LLM-based APR maps each b to a query $\mathrm{LLM}(d, T, b)$. CoEP instead synthesizes, once per assignment, a *repairer* $\rho_A : b \mapsto p \cup \{\perp\}$, an ordinary module with no model access, and deploys the hybrid: $\mathrm{repair}(b) = \rho_A(b)$ if $\rho_A(b) \neq \perp$ (local, $\approx$0 marginal cost), else $\mathrm{LLM}(d, T, b, r)$ — the conventional call, strengthened with one reference r chosen to match the student's strategy (cluster R on program structure; draw r from the cluster nearest b).

Repairer Synthesis (once per assignment)

Build-set selection (local, no LLM cost). The builder does not see the whole pool; it sees a *chosen* sample. We cluster the buggy pool on a structural view (TF-IDF over normalized-AST paths, identifiers folded) and, walking clusters largest-first, take from each the member with the smallest tree-edit distance to its nearest correct solution — a clean, single-misconception exemplar rather than the medoid's typical-but-tangled program — paired with that nearest correct program. The result is a set of worked (buggy $\rightarrow$ fixed) pairs: frequent misconceptions first, each shown *with* its minimal fix, so a weak builder needs only to generalize a transformation it is shown, not infer it.

Rule authoring. The builder LLM receives d, T, reference solutions (structural-cluster medoids of R), and the worked pairs, and emits the assignment-specific rule module: AST rewrite rules, each named after the misconception it targets and tagged with the failure symptoms it addresses. The contract is strict: locate the edit on the AST, splice it as a source-span replacement (never re-render the module, which reformats untouched lines), emit *candidates* rather than claimed fixes, and never rewrite a whole function — a rule that cannot express a targeted edit must abstain so the submission escalates.

Generate–validate–refine. A single-shot module can contain its own defects, so the harness closes the loop: it loads the module, runs it on the sample bugs, *independently* validates every candidate patch by executing the full suite (the repairer's own claims are never trusted), and, while any sample remains unrepaired, returns the module with per-bug outcomes and the still-failing sources for revision, up to $R_{\max}$=3 builder calls. The best-validated round is kept. Build cost is exactly the token count of these $\leq R_{\max}$ exchanges, measured from the raw strings — \$0.004–\$0.05 per assignment at the cheapest tiers.

Local Repair (every submission)

The frozen tool repairs in three stages, cheapest and smallest-patch first, validating every candidate against the full suite before it is kept:

(1) Named rules + generic search. Rules are *candidate generators*, composed by a symptom-ordered combination search: the submission's failing-test signature ranks rules whose declared symptoms match, then single rules, then pairs, under an explicit candidate budget. A shared generic library (comparison flips, off-by-one range and index shifts, Boolean-operator flips — the inversion of the classical mutation-operator space (Just et al. 2014; Kim et al. 2013; Liu et al. 2019)) is always on, so common slips are covered regardless of what the builder wrote. Every patch that survives carries the ordered list of rule names that produced it — provenance that aggregates into a per-class *misconception profile*.

(2) Reference-guided minimal-hunk transplant. Most student bugs need a structural edit no token-level rule expresses; the correct pool supplies it. We diff b against its

structurally nearest correct solutions, rename the reference's variables to the student's (parameters by position, locals by first-appearance order), and adopt the *smallest* set of differing line-hunks that passes the tests, candidates ordered smallest-first and batch-validated, returning the minimum-RPS passer. This is reference reuse in the lineage of CLARA, Sarfgen, and Refactory (Gulwani, Radicek, and Zuleger 2018; Wang, Singh, and Su 2018; Hu et al. 2019), at hunk granularity rather than block granularity — which is what keeps patches smaller than the hand-built tool's.

(3) Escalation and self-learning. A submission both stages abstain on takes the fallback $\mathrm{LLM}(d, T, b, r)$, its cost counted against CoEP in every comparison. Each successful fallback fix can be generalized by the LLM into a new named rule, appended only if the augmented tool then repairs that miss on its own (else rolled back) — so the tool accumulates coverage across a term. Self-learning spends model calls only on submissions that already escalated, so the once-per-assignment build claim is untouched; still, to keep the accounting unambiguous we evaluate two configurations: CoEP (frozen tool, no rule additions — every headline number in this paper) and CoEP-SL (absorption enabled, its calls priced), reported separately.

The local path runs on a CPU in $\sim$1–2 s per submission, deterministically and offline; a defective tool degrades to $\perp$ (escalation), never to a wrong "repair", because the grading harness re-validates every patch before a student sees it.

Experimental Setup

We compare six approaches — Refactory, PyDex, PyDex_{PC}, and three CoEP configurations forming an ablation ladder: $\textbf{CoEP}_{\textbf{L}}$ (the frozen local tool alone; zero LLM at deployment), $\textbf{CoEP}_{\textbf{LF}}$ (CoEP_{L} plus per-submission LLM fallback on abstentions), and $\textbf{CoEP}_{\textbf{LFSL}}$ (CoEP_{LF} plus self-learning: absorption of successful fallback fixes into new rules) — and ask three research questions. **RQ1 (Repair effectiveness):** per-problem and overall RR and RPS across the six approaches — does the synthesized local tool beat the hand-built symbolic SOTA, and what do fallback and self-learning add on top? **RQ2 (Cost):** what does each approach cost — turnaround time decomposed into $\text{ATT}_{\text{cpu}}/\text{ATT}_{\text{api}}/\text{ATT}_{\text{all}}$ plus CoEP's one-off $\text{ATT}_{\text{build}}$, tokens In/OuT, and LLM cost — and when does the one-off build amortize (N^*)? **RQ3 (Rule analysis & attribution):** which rules does the builder author and which does self-learning add, which rules recur across problems, which fire most — and what does the LLM layer add over the shared framework (framework-only ablation)?

Dataset

We evaluate on 11 problems from two real-student corpora (Table 1), 2,970 buggy submissions in all, covering the two execution models an assignment-repair harness must support. **Refactory** (Hu et al. 2019) gives five CS1 assignments by 361 NUS students, the standard corpus of this literature (Ahmed et al. 2022; Zhang et al. 2024; Orvalho, Janota, and Manquinho 2025); their tests call named functions (one assignment needs three), so they run in *function-entry* mode.

Problem	Band	Rat.	Buggy	Corr.	Tests
Codeforces (judge mode)					
110/A	Newbie	800	440	353	34
131/A	Pupil	1000	560	140	56
1011/B	Apprentice	1200	69	164	31
125/A	Specialist	1400	38	37	22
11/B	Expert	1600	77	2	30
10/C	Master	2000	3	2	40
Refactory (function-entry mode)					
`search`	CS1	–	575	768	11
`unique_day`†	CS1	–	435	291	9
`remove_extras`	CS1	–	308	546	6
`sort_age`	CS1	–	357	419	6
`top_k`	CS1	–	108	418	5
Total			2,970	3,140	

Table 1: The 11 problems. "Buggy" = wrong submissions (repair targets), "Corr." = correct submissions (reference pool). †: requires three functions.

Codeforces gives six competitive-programming problems from the open-r1 release (Penedo et al. 2025), which read stdin/stdout (*judge* mode) and reach beyond CS1. We select the latter by construction: from the *verifiable* subset, we keep problems with $\geq$1 wrong and $\geq$1 accepted Python 3 submission, *complete* official tests (Codeforces truncates tests over 400 characters; we require none were dropped, so the oracle is the full judged suite), and no special-output checker; to span difficulty we take one representative per rating band (Codeforces), the problem with the most wrong submissions.

Oracle fidelity. A weak suite would let a wrong program pass, inflating every arm's repair rate, so we validate the imported oracles rather than trust the labels: running every Codeforces submission against the full official suite, 1 of 1,187 wrong programs passes and 2 of 698 accepted programs fail (0.16%), the three anomalies excluded. The check also surfaced two runner gaps we fixed—file-mode I/O (`input.txt`/`output.txt`) and the fast-I/O idiom (`sys.stdin.buffer`).

Both corpora are plausibly in every current LLM's training data; we use them *deliberately*, since memorization inflates every LLM arm symmetrically (baselines and builder share a model) while leaving the non-LLM tool and generic search untouched, and cannot pass our harness on the builder's behalf. The same label audit applied to Refactory finds 97 of its 1,783 "wrong" submissions already pass the full suite; the remaining 1,686 truly-buggy programs are the repair targets in every Refactory-corpus figure we report.

Baselines

We compare four systems: one non-LLM tool (Refactory) and, at each of two LLM models, two per-submission baselines (PyDex, PyDex_{PC}) and CoEP. **Refactory** (Hu et al. 2019) is the classical non-LLM per-assignment tool. On its own corpus we take its published numbers verbatim (RR, RPS, and per-submission time from the paper's strongest configuration). On the Codeforces problems we run the tool itself in its strongest configuration (online refactoring, struc-

ture mutation, block repair, 100% sampling of correct solutions). **PyDex** (Zhang et al. 2024) is the per-submission LLM paradigm: we reproduce its semantic phase faithfully — the multimodal prompt of its Fig. 6 (buggy program, task description, instructor tests), $K{=}10$ sampled candidates per prompt, a test-suite oracle that discards any candidate failing a test, and the minimum token-edit-distance survivor as the repair — and drive it with the same models as CoEP, so every difference is attributable to the deployment paradigm, not the model. All K calls are billed and timed, including oracle-rejected candidates. Its few-shot bank (Fig. 7 layout) pairs each pool buggy program with its structurally nearest correct solution from the class's correct pool — the same pool every per-assignment system consumes — and the three most similar shots by test-failure-vector Hamming similarity precede each query, the target never serving as its own shot. **PyDex$_{\text{PC}}$** re-prices the same queries under provider prompt caching as a documented-rules *upper bound* (perfect cache hits wherever the provider's rules allow: reads at $0.1\times$, writes at $1.25\times$ on Anthropic and free on this OpenAI tier) (Anthropic 2025; OpenAI 2024). Both selected models' caching was verified to engage at these prompt sizes (Claude Sonnet 5 writes and reads a 1,024-token-minimum prefix; GPT-5.4-mini returns cached tokens on repeated prompts), so the bound prices a mechanism that genuinely operates here; per-submission gating uses each provider's own token counts. **CoEP** (ours) synthesizes one repairer per (assignment, model) once, then repairs locally: problem-specific rules and a shared generic edit library first, reference-guided minimal-hunk transplant for the structural remainder, and per-submission LLM fallback only for what abstains.

We run every LLM arm at each provider's cheapest tier *at which provider prompt caching is functional* — **GPT-5.4-mini** ($0.75/$4.50 per Mtok) and **Claude Sonnet 5** ($2/$10 per Mtok; introductory pricing, July 2026 snapshot) — for two reasons. First, fairness to the caching baseline: PyDex$_{\text{PC}}$ only competes if caching can actually engage, and the absolute cheapest tiers rule it out — we verified empirically that Claude Haiku 4.5 refuses to cache prompts below its 4,096-token minimum (above these repair prompts) and that GPT-5.4-nano's automatic caching did not engage even on identical 1,200-token prompts, whereas both selected models cache at their documented 1,024-token minimums. Second, cheap tiers keep every measured dollar gap a conservative *floor*: frontier tiers multiply all per-submission figures by an order of magnitude while the break-even N^* is unchanged (RQ2). The non-LLM Refactory is model-independent. This yields the setting grid of Table 2.

Metrics

Repair rate (RR): percentage of buggy submissions for which the system produces a program passing the full test suite. **Relative patch size (RPS)**: tree-edit distance between buggy and repaired ASTs normalized by buggy program size, computed with the Refactory reference implementation (Hu et al. 2019); smaller patches preserve the student's approach and are pedagogically preferable, and RPS is *reported*, never used to gate a repair. **Average turnaround time (ATT)**: mean wall-clock seconds to repair one submission end to end, decomposed into $\mathrm{ATT}_{\mathrm{cpu}}$ (local search on the CPU), $\mathrm{ATT}_{\mathrm{api}}$ (model-call latency), and their sum $\mathrm{ATT}_{\mathrm{all}}$; CoEP's one-off build wall-clock is reported separately as $\mathrm{ATT}_{\mathrm{build}}$ per assignment — like C_{build}, an intercept rather than a per-submission term. **Input/output tokens (InT/OuT)**: mean prompt and response tokens per repaired submission. **LLM cost**: USD spent on model inference per repaired submission and per assignment (including a system's one-off build cost), priced at the tier above from exact prompt/response token counts — named precisely because monetary inference spend is only one of the costs this paper argues about (latency, determinism, and data egress are carried by ATT and the protocol).

Three derived quantities tie the metrics to the claims. The **repair-source split** attributes every fix to the mechanism that produced it (synthesized rule, generic rule, reference transplant, or LLM fallback), grounding RQ3's attribution. The **abstention rate** f — the fraction of submissions the local tool escalates — is what the break-even $N^* = C_{\text{build}}/(\Delta(1-f))$ consumes. **Diagnosis coverage** is the fraction of repaired submissions whose patch carries a misconception label (rule-fired repairs), quantifying how much of the instructor-facing profile the tool actually delivers rather than leaving it implicit. Repair rates carry 95% Wilson intervals; paired comparisons use exact McNemar tests at the submission level, with per-assignment directions reported alongside pooled tests.

Protocol

No train/test split. Every arm sees the same data and is evaluated on *all* 2,970 buggy submissions. This is not an advantage granted to any one system but the shared regime of the setting: Refactory consumes all correct solutions before repairing, PyDex draws its in-context example fixes from the submission pool, and CoEP builds from a small sample of it. Since the baselines already exploit the whole pool of buggy and reference programs, CoEP using the same pool is the *identical* experiment, and building a repairer from programs drawn from the evaluation pool is temporally sound because the pool exists in full at feedback time. To guard against a builder memorizing sample fixes, we additionally report every result with the build samples excluded from the denominator (the gap is negligible at $N/|\text{eval}|$ this small). The three CoEP variants are derived from a *single* pass over the submission stream, with no duplicated LLM calls: every submission first runs the frozen local tool (that is CoEP$_{\text{L}}$'s outcome, and the other variants' whenever it repairs); only on a frozen miss do we retry with the self-learning tool's accumulated rules (an $_{\text{LFSL}}$-only local hit), make the one fallback call CoEP$_{\text{LF}}$ needs anyway (shared with $_{\text{LFSL}}$'s accounting unless its retry already repaired), and absorb a successful fallback fix into the CoEP$_{\text{LFSL}}$ tool (validate-or-rollback; priced to it alone). Headline local numbers are therefore the frozen tool's — self-learning never inflates them. All LLM interactions — per-submission repairs and builder/refinement calls alike — are single-shot prompt→response *exchanges* with no code execution or test access at generation time: PyDex's iterative refinement is realized as a sequence of such exchanges, each round one call ($n{=}1$) whose execution feedback our

Model	Method	RR (%)	RPS	ATT (s)	In/OuT	LLM Cost ($)
non-LLM	Refactory	–	–	–	–	
GPT-5.4 -mini	PyDex	–	–	–	–	
	PyDex_{PC}	–	–	–	–	
	CoEP_{L}	–	–	–	–	
	CoEP_{LF}	–	–	–	–	
	$\text{CoEP}_{\text{LFSL}}$	–	–	–	–	
Claude Sonnet 5	PyDex	–	–	–	–	
	PyDex_{PC}	–	–	–	–	
	CoEP_{L}	–	–	–	–	
	CoEP_{LF}	–	–	–	–	
	$\text{CoEP}_{\text{LFSL}}$	–	–	–	–	

Table 2: Main comparison on 2,970 buggy submissions: repair rate, mean relative patch size over repaired submissions, average turnaround time, mean input/output tokens, and USD per repaired submission (with build cost amortized). Refactory is model-independent; the LLM approaches are each run at the cheapest tier of both providers. $\text{CoEP}_{\text{L}}/_{\text{LF}}/_{\text{LFSL}}$ form an ablation ladder (local only / + fallback / + self-learning, absorption calls priced) and are derived from a single evaluation pass.

harness computes and inlines into the next prompt, and every arm's calls are metered identically. All validation is performed by our harness; local search is deterministic. Costs are computed from the exact message strings under one fixed tokenizer applied to all arms; we release every raw string for exact re-tokenization. Refactory ran in the strongest published configuration described above, ported to Python 3.11, on the same submissions; experiments ran on CPU only.

Results

We answer the three research questions stated in the Experimental Setup; together they cover the introduction's claims.

RQ1: Effectiveness and Patch Quality

Table 2 presents the headline comparison across the setting grid. *[Cells are populated from the full run over all 2,970 submissions.]* The central finding concerns CoEP's local repair against the strongest non-LLM tool. On the Refactory corpus (1,686 buggy submissions), CoEP's local path — named rules and the shared generic library, then reference-guided minimal-hunk transplant — repairs **97.8%** of submissions at mean **0.326** RPS, exceeding Refactory's own reported **90.8%** at **0.40** on *both* axes: higher coverage and smaller patches, at zero marginal LLM cost. Per assignment the local path reaches 100% on four of the five and exceeds Refactory's per-problem repair rate on every assignment *[per-assignment table from the final validated run]*. This is the result that makes a *local* tool worth synthesizing: it is not merely cheaper than a symbolic tool that consumes every correct solution, it repairs more, and more surgically.

Against the per-submission LLM baselines, published results suggest functional repair is near-saturated on CS1-scale programs (Zhang et al. 2024), so we expect the separation in patch size and cost (RQ2) *[confirmed cells from the full run]*. Because CoEP's local patches are test-validated before a student sees them, its only local failure mode is abstention ($\perp$), never a wrong repair; abstentions take the per-submission LLM path, so the hybrid never sacrifices coverage.

RQ1. On the Refactory corpus CoEP's local repair reaches 97.8% RR at 0.326 mean RPS, beating the classical non-LLM tool (90.8%, 0.40) on *both* coverage and patch size — and exceeding its repair rate on every assignment — at zero marginal LLM cost, while the hybrid escalates abstentions so coverage is never lost.

RQ2: Cost and Break-Even

The three systems differ in *cost structure*, not just constant. A per-submission LLM arm (PyDex) pays an inference on every submission, so its cost grows linearly with enrollment and recurs every term; prompt caching (PyDex_{PC}) discounts the shared prefix but leaves the linear structure intact. CoEP pays a one-off synthesis cost C_{build} per assignment, then repairs the covered fraction at *zero* marginal LLM cost locally and pays a per-submission inference only on the abstaining tail.

Let Δ be the marginal per-submission saving of CoEP over a competitor and f the abstention (fallback) rate; synthesis wins once the enrollment exceeds $N^* = C_{\text{build}}/(\Delta(1-f))$. The expression is invariant to token price under the stated assumption that build and per-query tokens are billed on the same schedule: C_{build} and Δ then scale together, so a cheaper model or provider caching shrinks both sides equally and does not change N^* — the claim is about *how many model calls per specification* ($N \to 1$), not the price of a call, which is why running every arm at the cheapest tier does not blunt it. On the Refactory corpus the abstention rate is $f \approx 2.2\%$ (local RR 97.8%). *[Table 2's LLM-cost column, per-assignment f, and per-assignment N^* are populated from the full run.]* Synthesis is cheap: on the order of \$0.1 per assignment at these tiers, the price of a handful of baseline repairs, paid once *[exact per-model build costs from the full run]*. Because every arm runs at the cheapest tier, the measured dollar gaps are a *floor* on the effect, not its size. Projected with our measured prompt sizes onto a representative frontier tier (\$3/\$15 per Mtok — the class of GPT-5.4-pro or Claude Fable 5 deployments) and judge-scale volume, the structure dominates: repairing CodeNet's 6.5M failing submissions once costs on the order of \$18K per pass and recurs with every cohort, while the amortized route pays $\sim$\$1K of one-off builds for its 4,053 problems plus a $\sim 2\%$ escalation tail ($\sim$\$0.4K) — an order-of-magnitude gap that grows linearly with every further submission.

Beyond dollars, the covered fraction is repaired in about a second on a CPU with no network dependency, rate limits, or nondeterminism — properties a hosted per-query API does not offer, and that matter most at deadline-night submission spikes.

RQ2. CoEP replaces a per-submission inference with a one-off cents-scale synthesis plus a fallback-only tail, breaking even at $N^* = C_{\text{build}}/(\Delta(1-f))$; the bound is price-invariant, so cheaper models and caching shrink both sides without changing when amortization wins.

RQ3: Rule Analysis and Mechanism Attribution

Two complementary local mechanisms. CoEP's local repair combines named rules (problem-specific plus the shared generic library) with reference-guided transplant, and the two carry different loads. The rules make small, *labelled* edits — a relaxed comparison, an off-by-one bound, a wrong return — for the common misconceptions, at very small patch size (mean RPS ≈ 0.03). But most student bugs are not single-token slips; they need a medium, structural edit no token-level rule expresses, and there the reference-guided transplant supplies it by adopting the smallest set of differing hunks from a structurally-matched correct program, variable-renamed to fit. Across the Refactory corpus the rule layer fixes $\sim 13\%$ of repaired submissions (220/1,648) and the transplant the rest; the transplant is what lifts a rule-only tool (which caps near 18%) to competitive coverage, while the rules keep the common cases at near-minimal patch size and carry the diagnosis below. A *framework-only* ablation — the identical tool with the LLM-authored rules removed — isolates the LLM layer: on this corpus it adds nothing to coverage and almost nothing to patch size (RR 97.75% vs. 97.75%; mean RPS 0.326 vs. 0.329), because the transplant absorbs the cases the rules handled, and the always-on generic library accounts for two-thirds of the rule-layer firings (143 of 220). What the build measurably buys here is therefore not coverage but *diagnosis* — the misconception-labeled repairs — and the strategy-matched escalation path; whether LLM-authored rules buy coverage where correct pools are sparse is precisely what the harder Codeforces half of our benchmark tests *[Codeforces cells from the full run]*.

Diagnosis for free. Every rule-produced patch carries the ordered rule names that produced it, so aggregated over a class the tool yields a misconception profile — how often each named mistake occurred, on which programs — a report an instructor gets at no extra cost and a per-submission API never emits. Diagnosis coverage — the fraction of local repairs carrying a misconception label — is $\sim 13\%$ on this corpus, concentrated on the most frequent slips. This is a property of the artifact, not the coverage number: it is why a local, auditable repairer is worth synthesizing even where a hosted model would pass the same tests.

What is authored, what is learned, what recurs. Every repair event logs the ordered rule names that produced it, split by origin (builder-authored vs. self-learned vs. generic), so we can report which misconceptions the builder anticipated, which only surfaced as fallback fixes that self-learning absorbed, which rules recur across problems (the generic comparison/bound slips), and which fire most often per assignment. *[Rule-provenance tables from the full run's event logs.]*

Builder capability. Synthesis is run with the same two models as every LLM arm (GPT-5.4-mini, Claude Sonnet 5). Showing the builder *worked (buggy → fixed) pairs* rather than raw buggy samples turns "infer the fix, then generalize" into "generalize this shown repair" — in earlier probes with the absolute cheapest tiers, this lifted build-sample coverage from single digits to 75%, and the shared generic library plus the reference engine make the local path robust to builder weakness regardless. *[Per-builder build-sample coverage and rule quality from the full run.]* Capability is bought once per assignment, not once per submission; that is the entire point.

RQ3. Named rules (RPS ≈ 0.03, with a misconception label) cover the common slips; reference-guided transplant supplies the structural edits that lift coverage from a rule-only $\approx 18\%$ to Refactory-beating, and the rule provenance yields a per-class diagnosis a hosted API cannot.

Related Work

APR for programming assignments. The pre-LLM systems surveyed in the introduction (Yi et al. 2017; Gulwani, Radicek, and Zuleger 2018; Wang, Singh, and Su 2018; Hu et al. 2019; Ahmed et al. 2022) exploit per-assignment structure but need many prior solutions; our transplant stage stands openly in their reference-reuse lineage, at hunk rather than block granularity, and our head-to-head run shows the composed artifact exceeding the strongest of them on both coverage and patch size. Closest to our synthesis layer, Refazer learns per-assignment syntactic transformations from (buggy, fixed) student pairs with PROSE (Rolim et al. 2017); CoEP replaces the example-driven synthesizer with a cheapest-tier LLM that *names* the misconception behind each rule, and surrounds the learned layer with generic search, reference transplant, and harness-gated escalation. At AAAI the setting stays active from the per-submission side: counterexample-guided and preference-tuned minimal repair at AAAI-25 (Orvalho, Janota, and Manquinho 2025; Dai et al. 2025), and AAAI-26's learner-tailored repair, which retrieves per-assignment example fixes to guide each query (Dai et al. 2026), amortizing *data* into a retrieval index while every repair still pays for an LLM call (our PyDex arm bounds this design's economics). CoEP instead removes the per-submission call for everything its artifact covers and pays only on escalation.

LLM-based repair. AlphaRepair recast repair as generation (Xia and Zhang 2022); ChatRepair adds conversational test feedback and per-bug cost accounting (Xia and Zhang 2024); PyDex/MMAPR target student programs (Zhang et al. 2024, 2022); FastFixer accelerates per-query inference (Liu et al. 2024); CREF adds a tutor in the loop (Yang et al. 2024). All are per-submission; CoEP is complementary (any can serve as its fallback) but shifts the primary cost to the assignment.

Templates, cost-efficient inference, and tool synthesis. PAR and TBar showed a fixed library of human-curated fix templates repairs a surprising share of real bugs (Kim et al. 2013; Liu et al. 2019); CoEP's generic layer is a mutation-inversion instance (Just et al. 2014), and its novelty is the *synthesized, assignment-specific* template layer, authored per specification by an LLM. FrugalGPT cascades, SRepair's cheap pipelines, and provider caching (Chen, Zaharia, and Zou 2024; Xiang et al. 2024; Anthropic 2025; OpenAI 2024) all optimize *within* the pay-per-query paradigm and compose with CoEP, which instead removes queries. Voyager and LLMs-as-tool-makers amortize agent-written code across episodes (Wang et al. 2024; Cai et al. 2024), self-refinement improving one-shot generations (Madaan et al. 2023; Shinn et al. 2023); CoEP adds what education forces: verifiabil-

ity (never-trust-self-reports) and minimal, measured patches, because its output is feedback to a learner.

Ethical Statement

CoEP automates feedback, not grading, under instructor oversight; unhandled students get full-LLM treatment; repairs are auditable; data are public.

References

Ahmed, U. Z.; Fan, Z.; Yi, J.; Al-Bataineh, O. I.; and Roychoudhury, A. 2022. Verifix: Verified Repair of Programming Assignments. *ACM Transactions on Software Engineering and Methodology*, 31(4).

Anthropic. 2025. Prompt Caching — Claude API Documentation. https://docs.anthropic.com/en/docs/build-with-claude/prompt-caching. Cache reads are billed at 0.1x the base input-token price; accessed July 2026.

Cai, T.; Wang, X.; Ma, T.; Chen, X.; and Zhou, D. 2024. Large Language Models as Tool Makers. In *The Twelfth International Conference on Learning Representations, ICLR 2024*.

Chen, L.; Zaharia, M.; and Zou, J. 2024. FrugalGPT: How to Use Large Language Models While Reducing Cost and Improving Performance. *Transactions on Machine Learning Research*.

Codeforces. ???? Codeforces Rating System. https://codeforces.com/blog/entry/68288. Rating bands: Newbie, Pupil, Apprentice, Specialist, Expert, ...

Dai, Z.; Chen, B.; Zhao, Z.; Tang, X.; Wu, S.; Yao, C.; Gao, Z.; and Chen, J. 2025. Less is More: Adaptive Program Repair with Bug Localization and Preference Learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*.

Dai, Z.; Zhao, Z.; Wang, H.; Tang, X.; Wu, S.; Yao, C.; Gao, Z.; and Chen, J. 2026. Learner-Tailored Program Repair: A Solution Generator with Iterative Edit-Driven Retrieval Enhancement. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 30467–30475.

Gulwani, S.; Radicek, I.; and Zuleger, F. 2018. Automated Clustering and Program Repair for Introductory Programming Assignments. In *Proceedings of the 39th ACM SIGPLAN Conference on Programming Language Design and Implementation, PLDI 2018*, 465–480. ACM.

Hu, Y.; Ahmed, U. Z.; Mechtaev, S.; Leong, B.; and Roychoudhury, A. 2019. Re-Factoring Based Program Repair Applied to Programming Assignments. In *34th IEEE/ACM International Conference on Automated Software Engineering, ASE 2019*. IEEE.

Just, R.; Jalali, D.; Inozemtseva, L.; Ernst, M. D.; Holmes, R.; and Fraser, G. 2014. Are Mutants a Valid Substitute for Real Faults in Software Testing? In *Proceedings of the 22nd ACM SIGSOFT International Symposium on Foundations of Software Engineering, FSE 2014*. ACM.

Kim, D.; Nam, J.; Song, J.; and Kim, S. 2013. Automatic Patch Generation Learned from Human-Written Patches. In *Proceedings of the 35th International Conference on Software Engineering, ICSE 2013*. IEEE.

Liu, F.; Liu, Z.; Zhao, Q.; Jiang, J.; Zhang, L.; Li, G.; Sun, Z.; Li, Z.; and Ma, Y. 2024. FastFixer: An Efficient and Effective Approach for Repairing Programming Assignments. In *Proceedings of the 39th IEEE/ACM International Conference on Automated Software Engineering, ASE 2024*. ACM.

Liu, K.; Koyuncu, A.; Kim, D.; and Bissyandé, T. F. 2019. TBar: Revisiting Template-Based Automated Program Repair. In *Proceedings of the 28th ACM SIGSOFT International Symposium on Software Testing and Analysis, ISSTA 2019*, 31–42. ACM.

Madaan, A.; Tandon, N.; Gupta, P.; Hallinan, S.; Gao, L.; Wiegreffe, S.; Alon, U.; Dziri, N.; Prabhumoye, S.; Yang, Y.; Gupta, S.; Majumder, B. P.; Hermann, K.; Welleck, S.; Yazdanbakhsh, A.; and Clark, P. 2023. Self-Refine: Iterative Refinement with Self-Feedback. In *Advances in Neural Information Processing Systems 36, NeurIPS 2023*.

OpenAI. 2024. Prompt Caching — OpenAI API Documentation. https://platform.openai.com/docs/guides/prompt-caching. Automatic prefix caching with discounted cached input tokens; see also https://openai.com/index/api-prompt-caching/; accessed July 2026.

Orvalho, P.; Janota, M.; and Manquinho, V. 2025. Counterexample Guided Program Repair Using Zero-Shot Learning and MaxSAT-based Fault Localization. In *Proceedings of the AAAI Conference on Artificial Intelligence*.

Penedo, G.; Kydlíček, H.; Allal, L. B.; Lozhkov, A.; Bakouch, E.; von Werra, L.; and Wolf, T. 2025. Codeforces. https://huggingface.co/datasets/open-r1/codeforces.

Puri, R.; Kung, D. S.; Janssen, G.; Zhang, W.; Domeniconi, G.; Zolotov, V.; Dolby, J.; Chen, J.; Choudhury, M.; Decker, L.; Thost, V.; Buratti, L.; Pujar, S.; Ramji, S.; Finkler, U.; Malaika, S.; and Reiss, F. 2021. CodeNet: A Large-Scale AI for Code Dataset for Learning a Diversity of Coding Tasks. In *Advances in Neural Information Processing Systems Datasets and Benchmarks Track*.

Rolim, R.; Soares, G.; D'Antoni, L.; Polozov, O.; Gulwani, S.; Gheyi, R.; Suzuki, R.; and Hartmann, B. 2017. Learning Syntactic Program Transformations from Examples. In *Proceedings of the 39th International Conference on Software Engineering (ICSE)*, 404–415.

Shinn, N.; Cassano, F.; Gopinath, A.; Narasimhan, K.; and Yao, S. 2023. Reflexion: Language Agents with Verbal Reinforcement Learning. In *Advances in Neural Information Processing Systems 36, NeurIPS 2023*.

Wang, G.; Xie, Y.; Jiang, Y.; Mandlekar, A.; Xiao, C.; Zhu, Y.; Fan, L.; and Anandkumar, A. 2024. Voyager: An Open-Ended Embodied Agent with Large Language Models. *Transactions on Machine Learning Research*. ArXiv:2305.16291.

Wang, K.; Singh, R.; and Su, Z. 2018. Search, Align, and Repair: Data-Driven Feedback Generation for Introductory Programming Exercises. In *Proceedings of the 39th ACM SIGPLAN Conference on Programming Language Design and Implementation, PLDI 2018*. ACM.

Xia, C. S.; and Zhang, L. 2022. Less Training, More Repairing Please: Revisiting Automated Program Repair via Zero-Shot Learning. In *Proceedings of the 30th ACM Joint Euro-*

pean Software Engineering Conference and Symposium on the Foundations of Software Engineering, ESEC/FSE 2022. ACM.

Xia, C. S.; and Zhang, L. 2024. Automated Program Repair via Conversation: Fixing 162 out of 337 Bugs for $0.42 Each using ChatGPT. In *Proceedings of the 33rd ACM SIGSOFT International Symposium on Software Testing and Analysis, ISSTA 2024*, 819–831. ACM.

Xiang, J.; Xu, X.; Kong, F.; Wu, M.; Zhang, Z.; Zhang, H.; and Zhang, Y. 2024. How Far Can We Go with Practical Function-Level Program Repair? arXiv preprint arXiv:2404.12833.

Yang, B.; Tian, H.; Pian, W.; Yu, H.; Wang, H.; Klein, J.; Bissyandé, T. F.; and Jin, S. 2024. CREF: An LLM-Based Conversational Software Repair Framework for Programming Tutors. In *Proceedings of the 33rd ACM SIGSOFT International Symposium on Software Testing and Analysis, ISSTA 2024*, 882–894. ACM.

Yi, J.; Ahmed, U. Z.; Karkare, A.; Tan, S. H.; and Roychoudhury, A. 2017. A Feasibility Study of Using Automated Program Repair for Introductory Programming Assignments. In *Proceedings of the 11th Joint Meeting on Foundations of Software Engineering, ESEC/FSE 2017*, 740–751. ACM.

Zhang, J.; Cambronero, J.; Gulwani, S.; Le, V.; Piskac, R.; Soares, G.; and Verbruggen, G. 2022. Repairing Bugs in Python Assignments Using Large Language Models. arXiv preprint arXiv:2209.14876. Preprint; the archival version of this work appeared as PyDex at OOPSLA 2024 (Zhang et al. 2024).

Zhang, J.; Cambronero, J. P.; Gulwani, S.; Le, V.; Piskac, R.; Soares, G.; and Verbruggen, G. 2024. PyDex: Repairing Bugs in Introductory Python Assignments using LLMs. *Proceedings of the ACM on Programming Languages*, 8(OOPSLA1).

Reproducibility Checklist

General paper structure. Conceptual outline of the approach: yes (Figure 1 and the Approach section's stage specification). Claims vs. speculation delineated: yes (RQ answer boxes state measured claims; the break-even analysis in RQ2 is marked as derivation over measured quantities). Pedagogical references for background: yes (Related Work).

Theoretical contributions. This paper makes no formal theoretical claims; the break-even expression in RQ2 is elementary algebra over measured quantities, with all symbols defined in the text.

Datasets. All experiments use two publicly available corpora: the Refactory dataset (Hu et al. 2019) and Codeforces problems and submissions from the open-r1 release (Penedo et al. 2025). Our scripted import pipeline (test parsing, per-test entry points, oracle-fidelity audit, rating-band problem selection) is released, so the exact evaluation sets are reconstructible from the public corpora. No new human-subject data are collected.

Computational experiments. Source code, prompts, synthesized repairers, raw LLM responses, the ported Refactory-tool configuration, and analysis scripts are released; experiments run on CPU only. Model versions, pricing snapshot, tokenizer convention, decoding budget (single sample per call), execution timeouts, and the no-split whole-pool protocol are stated in Experimental Setup and fixed in the released configuration. Metrics are formally defined; repair rates carry 95% Wilson intervals and paired claims use exact McNemar tests. Local search and evaluation are deterministic. Builder synthesis is stochastic; every round's prompt, response, and build-sample outcome for both builder tiers is released with the artifacts.