ZPDPatch: Trading Repair Coverage for Student Code in Programming-Exercise Feedback

***Abstract*—We present ZPDPATCH, a trajectory-supervised technique that aims repair feedback at a student's own code by constructing targets from execution evidence rather than from accepted solutions. A repair returned to a student is feedback, so how much of their program it replaces matters alongside whether the tests pass. We call repair whose supervision depends on that history *trajectory-conditioned*, and no single comparison establishes a benefit for it, because more candidates alone improve a history-aware system and a new target rule also changes the training population. Our goal is to separate the target rule's effect from those of extra candidates and serialized history. ZPDPATCH mines three execution-evidence relations, trains independent adapters, and selects a validation-frozen portfolio behind a gate that returns the submission unchanged rather than a regression. On 181 student-held-out Introductory Programming (CS1) Java trajectories under source- and count-matched training, terminal targets repair 155 and progress targets 92, leading on 15 of 17 exercises. On the 90 trajectories both rules repair, the retention advantage is zero for 63.3% of students, positive for 31.1%, and negative for 5.6%. An online-judge corpus of 997 inputs from problems seen in training and 250 from held-out problems reproduces the tradeoff, with 19.2 and 11.2 percentage points less coverage and 5.6 and 6.5 points more retained tokens. Three fixed candidate draws alone add 15.1 points of repair rate, and these numbers describe the feedback, not learning. We therefore retain the current-only terminal portfolio.**

***Index Terms*—programming-exercise feedback, automated program repair, submission trajectories, target construction, CS1**

I. INTRODUCTION

Automated Program Repair (APR) [1]–[4] has been widely studied for programming assignments as a way to give every rejected submission feedback that a course cannot write by hand [5]. Given a buggy submission and the problem's test suite, a technique returns a patch, that is, a program that passes every test, so the student receives a working version of their own assignment [6], [7]. To this end, a technique decides which part of the submission to change, synthesizes a replacement from the material it is given, and returns only a candidate that the tests accept. A student submits repeatedly to the same assignment, so the technique faces a sequence rather than one buggy program [8].

The key design decision is what that material is, that is, what the repair is supervised toward. Existing techniques for programming assignments fall into three groups by where they take it from. Alignment-based techniques align the submission with other students' passing programs or an instructor's solution [9]–[14]; language-model-based techniques generate a patch from the buggy program and the problem statement [6], [7], [15]–[19]; and retrieval-based techniques look up a learner-specific solution to steer that generation [20]. In addition, next-step hint generators draw one edit from a solution space built out of past correct programs [21]–[24]. These techniques have raised the repair rate for student submissions considerably, and put a next step within reach of more students than a tutor can see [5], [25].

However, existing techniques do not know how far a student can get with guidance. Where a return aims is settled without reference to which tests the student currently passes. Feedback works better when it is specific to the learner's own work [26], [27], and it helps only as far as the student can follow what the returned program changed in theirs [28], [29]. The Zone of Proximal Development divides a learner's ability into what they can do unaided, what they can do with guidance, and what stays out of reach, and support has to land in the middle region [30]. A submission is what the student produced unaided, so it marks where that first region ends, and feedback chosen without regard to the student's level can land anywhere beyond it. Locating those regions takes measurement of its own [31]–[33], but the distance between a return and the submission is observable (Section II-B). An average return of the most recent technique, LSGen [20], is 2.5 times an average student step. Consequently, existing techniques hand back somebody else's finished solution rather than the next step the student could take. In this work, we define *trajectory-conditioned repair* as repair whose supervision depends on the sequence leading to the current submission, and we ask separately whether that sequence has to be this student's own.

In this paper, we present ZPDPATCH, a new trajectory-supervised technique that repairs a buggy submission toward the next step the student could reach with guidance. Our key idea is that the student's own trajectory already records that step, since the submission that actually came next is a program the student reached unaided soon after. This target, however, cannot be swapped in on its own (Section II-B). ZPDPATCH therefore holds the sources, the example counts, and the candidate budget fixed, and adds a matched-peer target control. To this end, ZPDPATCH operates in three stages, Mine, Train, and Select. The Mine stage pairs a buggy submission, or a retained prefix of the trajectory, with a later submission under three rules. Progress takes the next state that improves the verdict or passes more tests at an unchanged verdict, Strict the next better-verdict state, and Answer the accepted endpoint, the conventional target we keep for comparison. Unlike retrieval-based techniques that mine the same chronological pairs to look up a solution for the submission, these pairs supply the supervision signal itself.

The Train stage trains an independent adapter per rule. The Select stage freezes a triple of checkpoints by their executed validation repairs rather than by training loss. As a result, what a student receives is a complete program, so how much of their own submission it replaces can be measured and bounded.

Experimental results demonstrate that ZPDPATCH changes the least of a student's program among the techniques we compare, and under a bounded edit repairs more submissions than LSGen. We evaluated it on 1,247 Python submissions from 382 CodeNet problems [34] and 181 Java submissions from 17 Introductory Programming (CS1) exercises [8], against LSGen [20] and the same base model used zero-shot. In terms of repair rate under a declared edit budget, ZPDPATCH fixed 44.0% of the Python submissions at 20 Abstract Syntax Tree (AST) operations against LSGen's 13.9%, and 14.7 points more on average across six budgets. Regarding patch size, its patches changed 21.05 AST nodes on average, less than a quarter of LSGen's 88.27. Under matched sources, Progress targets kept 5.6 and 6.5 percentage points more of the student's tokens on the inputs both rules fixed, although they fixed 19.2 and 11.2 points fewer. We further show the same two directions on student-disjoint CS1 Java, where Answer targets lead on 15 of 17 exercises, and that three fixed candidate draws alone account for 15.1 points of the repair rate. Unrestricted, however, no configuration of ours exceeded LSGen's 80.2%, so we retain the current-only Answer triple and report the Progress rule as the option for when locality binds (Section IV).

Contributions. We summarize our contributions below:

- **Observation.** We show that solution-supervised repair seldom returns a step from where a student stands, and that within a step of 20 AST operations a trajectory target repairs 3.2 times as many submissions (Section II-B), motivating repair that takes its target from the student's own trajectory.
- **New technique.** We present ZPDPATCH, a trajectory-supervised repair technique for programming assignments. Our core technical contribution is an algorithm that pairs each buggy submission with a later submission of its own trajectory under execution-evidence rules, trains one adapter per rule, and freezes a checkpoint triple by executed validation repairs, with the sources, the example counts and the candidate budget held fixed.
- **Evaluation.** We demonstrate the effectiveness of ZPDPATCH by comparing it with LSGen, a zero-shot model, and controls on the target's source, prompt, decoder and candidate budget: it changes the least of the student's program, while no configuration of ours leads unrestricted. We supply the paired outcomes, condition manifests, metric code, and a claim-to-evidence map as anonymous supplementary material.

II. PRELIMINARIES

A. Automated Program Repair for Programming Assignments

Existing techniques for repairing programming assignments aim to turn a buggy submission into a program that passes every test of its problem. A problem p, whether an online judge poses it or a course assigns it, comes with a problem context d_p, its statement and resource limits, and an available test suite $\mathcal{E}$. That aim asks only whether a return passes the tests, and nothing about what the student submitted. We define the rest of the setting on the student's submissions themselves. A student working on p submits repeatedly. We define a submission as a triple $s = (c, v, o)$, where c represents its source code, v denotes the verdict the platform recorded, and o indicates execution evidence that sends each test of $\mathcal{E}$ to its re-executed outcome. The recorded verdict and the replayed outcome stay in separate fields, because runtime variability can change what a program is observed to do. The *trajectory* $\tau = [s_1, \ldots, s_n, s_{ac}]$ orders those states chronologically, with $s_1, \ldots, s_n$ buggy and s_{ac} the first accepted submission, which serves only as evaluation ground truth and never reaches a technique. The submission to be repaired is the latest buggy one, and we call it the *buggy program* $b = s_n$. Cutting each τ at its first recorded acceptance yields the *canonical* dataset and its frozen split, on which every measurement below is taken.

Algorithm 1 APR for Programming Assignments

Input: Buggy program (b), Context (x), Ordered generators (S), Tests ($\mathcal{E}$), Edit budget (B)
Output: Returned program (f)

```
1:  procedure REPAIR(b, x, S, E, B)
2:      f ← b; q* ← EXECUTE(b, E)
3:      for g ∈ S do
4:          z ← Generate(g, x)
5:          if B < ∞ and ted†(b, z) > B then
6:              continue
7:          q ← EXECUTE(z, E)
8:          if q = 1 then
9:              return z
10:         if (q, −ted†(b, z)) > (q*, −ted†(b, f)) then
11:             f ← z; q* ← q
12:     return f
```

Algorithm 1 describes a generic repair procedure for programming assignments in the style of existing techniques [9]–[11]. It takes five inputs, a buggy program b, a context x, an ordered set S of generators, a test suite $\mathcal{E}$, and an edit budget B, and returns one program f. Line 2 makes the buggy program b the fallback for the return f and uses EXECUTE to record in q^* the fraction q of tests that b passes. Lines 3–4 take each generator g of the ordered set S in turn, and Generate builds one complete candidate z from the context x. Lines 5–6 skip a candidate whose $\mathrm{ted}^\dagger$ from b exceeds the edit budget B. Here $\mathrm{ted}^\dagger$ is AST edit distance when both programs parse, zero for unchanged code, and infinity otherwise. An unrestricted B therefore admits syntax repair, whereas a finite one rejects changes whose distance is undefined. Line 7 executes the candidate and lines 8–9 return it as soon as every test passes. Lines 10–11 replace f with a candidate that passes a larger fraction, or the same fraction from closer to b, and line 12 returns f when no candidate passes. For now, let us set aside what the context x holds and where S and B come from; all three are fixed in Section III.

Existing techniques instantiate Algorithm 1 in differ-

ent ways. Alignment-based techniques replace the generator at line 4 with an alignment against reference programs. CLARA [9] uses the expressions of a reference cluster sharing the control flow of b, Sarfgen [10] aligns same-control-flow references on their ASTs, Refactory [11] refactors references toward the control flow of b, and assignment-aware techniques vary how references are chosen [12]–[14]. Language-model-based techniques [6], [7], [15]–[19] replace line 4 and often the generator set at line 3 with a model. Retrieval-based LSGen [20] keeps that model and retrieves a learner-specific solution into the context x. Next-step hint generators [21]–[24] return one edit rather than a program, so neither line 7 nor line 5 applies to them. In every case the generator is steered toward an accepted solution or a solution space, never toward the later submissions of the student being helped.

B. Limitation of Solution-Supervised Repair




Fig. 1. Students' own steps and LSGen's returns within each budget

Our key observation is that solution-supervised repair does not return a step from where the student stands. A return that replaces most of b is not a continuation of it, whether or not the student could reach it with guidance. As Section I notes, locating a student's regions takes measurement of its own, so we count what separates a continuation from a replacement, namely how much of b the return keeps. We measure it by the $\mathrm{ted}^{\dagger}$ of Algorithm 1 and by token retention, the fraction of the tokens of b that the return preserves (Section IV). For example, a return that changes a loop bound from `i<j` to `i<=j` is one operation away on the tree, whereas one that replaces the loop with a counting expression over the same input is dozens away. More precisely, we call a return whose distance from b is at most a declared budget B a *bounded step*, where B is the amount of a student's program a course is willing to give up to one repair.

Figure 1 measures how large a step the students themselves take, and what LSGen repairs within it, as the distance between consecutive submissions in the stored trajectories of the 997 Seen evaluation inputs, on the scale the returns are measured on. On Seen the 2,581 steps with a defined distance have a median of 15, and one step leaves a median of 96.1% of the submission's tokens in place. Unrestricted, the returns of LSGen sit at 88.27 and those of the zero-shot model at 27.25. We call the largest step a student took unaided on a problem their *demonstrated reach*. Its median is 39, with quartiles at 15 and 83. An average LSGen return is 2.5 times an average student step and larger than the biggest step the median student took alone. Twenty AST operations is close to the median student step and within the reach of 30.9% of students, where LSGen repairs 13.9%, and 160 covers the reach of 90.3% of students. Surprisingly, four out of five of the submissions LSGen can repair are not repaired within one step, since it repairs 80.2% of them when nothing bounds the step. This measurement counts what a student changes at once, not which steps lay inside that student's region.

Prior techniques already ask for a small change: Refactory synthesizes minimal repairs [11] and LSGen instructs the model to make minimal changes [20]. The LSGen returns measured above are what that instruction produces. One alternative is to bound the step of an existing technique. The 13.9% above is that alternative, and it costs LSGen 66.3 of its 80.2 points, because a generator steered toward an accepted solution has no smaller candidate to fall back on. Returning a hint instead of a program sidesteps the budget altogether, but then the student still has to write the step, and what the hint is fitted to is still a solution space [22]–[24]. Another alternative is to swap the target for the student's own later submission and leave everything else alone. That is not a one-variable intervention: from the same trajectories the Answer rule yields 40,454 examples but Strict and Progress yield 16,973 and 21,416, and the source frequencies move with the rule as well. What a rule retains moves with it too: among three wrong-answer submissions with pass vectors $(1,0,0)$, $(1,1,0)$, and $(0,1,1)$, verdict-only filtering cannot tell the second from the third, while test-wise progress retains the second, which keeps every passed test and gains one, and not the third, which gains one but loses another. Extra candidates also raise the repair rate on their own: three fixed draws alone account for 15.1 points (Section IV), so a comparison that does not hold the candidate budget fixed credits the target with them [7], [17], [19], [20], [25].

These limitations motivate our approach, which repairs under the guidance of the student's own trajectory. The goal of this paper is to repair a buggy program into one that passes the tests while keeping as much of the submission as possible, and to make the gain readable as the target's. In terms of Algorithm 1, we train the generator toward the student's own later submission rather than toward an accepted solution or a solution space. A later submission is a program the student actually produced, so it is reachable by construction, but it need not be correct; we therefore use it as a preference and let the tests decide what is returned. Our work thus tackles two challenges, (1) that the student's later submission marks the next step only coarsely and may itself be accepted, and (2) that attributing a gain to the target requires holding the sources, the example counts, and the candidate budget fixed.




Fig. 2. Overview of ZPDPATCH

Algorithm 2 ZPDPATCH

Input: Trajectories ($\mathcal{T}$), Execution evidence ($\mathcal{O}$), Validation inputs (U), Seeds (Σ), Portfolio size (η_k), Edit budget (B)
Output: Frozen ordered checkpoint portfolio (S)

1: **procedure** ZPDPATCH($\mathcal{T}, \mathcal{O}, U, \Sigma, \eta_k, B$)
/ Stage 1. Mine */*
2: $(D_A, D_S, D_P) \leftarrow (\emptyset, \emptyset, \emptyset)$
3: **for** $\tau = [s_1, \ldots, s_n] \in \mathcal{T}$ **do**
4: $D_A \leftarrow D_A \cup \mathsf{TerminalPairs}(\tau)$ ▷ Answer
5: **for** $\rho \in \{S, P\}$ **do**
6: $R \leftarrow [s_1]$ ▷ retained prefix
7: **for** $s_t \in [s_2, \ldots, s_n]$ **do**
8: **if** $\mathsf{Improves}_{\rho}(R[-1], s_t; \mathcal{O})$ **then**
9: $D_\rho \leftarrow D_\rho \cup \{(R, c_t)\}$; $R \leftarrow R \,\|\, [s_t]$
/ Stage 2. Train */*
10: $V \leftarrow \emptyset$
11: **for** $(\rho, \sigma) \in \{A, S, P\} \times \Sigma$ **do**
12: $V \leftarrow V \cup \{\mathsf{Train}(D_\rho, \sigma)\}$
/ Stage 3. Select */*
13: **for** $g \in V$ **do**
14: $R_g^B \leftarrow \mathsf{Validate}(g, U, B)$ ▷ $R_g^B \subseteq U$
15: $S \leftarrow \mathsf{Select}(\{R_g^B\}_{g \in V}, \eta_k)$ ▷ $\eta_k = 3$
16: **return** $\mathsf{FreezeAndOrder}(S)$

III. Our Approach

A. Overview

Figure 2 illustrates how ZPDPATCH repairs a buggy program under the guidance of the student's own trajectory. ZPDPATCH takes the inputs of Algorithm 1, namely the buggy program b, the context x, and the test suite $\mathcal{E}$, together with the trajectories $\mathcal{T}$ of a training corpus and their execution evidence $\mathcal{O}$. It processes these inputs in the three stages of Algorithm 2, namely Mine, Train, and Select. The Mine stage pairs each buggy submission of a $\tau \in \mathcal{T}$, or a retained prefix of it, with a later submission under three target rules, yielding one dataset per rule (Section III-C). The Train stage trains one adapter per rule and seed, giving a pool of checkpoints (Section III-D). The Select stage runs each checkpoint on validation inputs and freezes the ordered triple whose executed repairs cover the most of them (Section III-E). At deployment the frozen checkpoints are the generator set S of Algorithm 1, which returns the first candidate that passes every test and otherwise returns the submission unchanged.

TABLE I
CORPUS AFTER WHOLE-TRAJECTORY FILTERING

Group	Part.	Probl.	Tests	Traj.	Subm.	Prefixes	Users
Seen	Train	492	9,446	14,027	54,481	40,454	4,012
	Valid	492	9,446	1,754	6,719	4,965	1,248
	Test	492	9,446	1,754	6,598	4,844	1,250
Unseen	Test	54	642	259	954	695	236
Total		546	10,088	17,794	68,752	50,958	–

ZPDPATCH differs from existing techniques in where it obtains the target and in what it holds fixed around it. First, the target is the student's own later submission. Existing techniques supervise the generator toward an accepted solution [9]–[11], a solution space built from past correct programs [21]–[23], or a retrieved learner-specific solution [20], so what a return aims at is settled without the student's own evidence; the target of ZPDPATCH is the next state of the same trajectory that execution evidence shows to be an improvement. Second, because swapping the target also moves the training population and the candidate budget (Section II-B), ZPDPATCH holds the sources, the example counts, and the candidate budget fixed across rules and admits a matched-peer target as a control, so a difference in outcome can be read as the target's. The three stages run once per corpus, and deployment issues at most one call per selected checkpoint, so the deployed budget is three calls.

B. ZPDPATCH

Algorithm 2 details how ZPDPATCH instantiates Algorithm 1. Taking $\mathcal{T}$ and $\mathcal{O}$ in addition to the inputs of Algorithm 1, it builds the generator set offline and requires no instructor solution, no pool of reference programs, and no learner model.

At lines 2–9, Mine scans each trajectory τ and emits the pairs of each rule (Section III-C). The Answer rule pairs every non-accepted state with the accepted endpoint (line 4), whereas the Strict and Progress rules carry a retained prefix R and append a state only when the rule's improvement predicate holds on the execution evidence $\mathcal{O}$ (lines 7–9), emitting (R, c_t) before the state is appended. At lines 10–12, Train fits one adapter per rule and seed, so the pool V holds $|\Sigma|$ checkpoints per rule (Section III-D). At lines 13–16, Select runs each checkpoint on the validation inputs U under the edit budget B, records the inputs it repairs, and freezes the ordered triple whose union covers the most of U, where $\eta_k = 3$ in our experiments (Section III-E). The returned portfolio S is what line 3 of Algorithm 1 iterates over at deployment.

The order of S affects which passing program a student receives, not whether one is found, because every checkpoint of S is invoked until a candidate passes and the gate returns b unchanged when none does. Hence, given deterministic test outcomes, the repair set of the portfolio contains that of each of its members.

C. Mine

The goal of Mine is to make every supervision pair traceable to an observed source and a later submission. Submissions are grouped by problem and user, chronologically ordered, and cut at the first acceptance. Canonical normalization removes consecutive duplicates while preserving the source code used for generation and execution. A whole-trajectory filter instead excludes a trajectory before splitting if any required prompt–target configuration exceeds 4,096 tokens. Exclusion changes the evaluated population, but never truncates a program or history.

The coarse severity function assigns 0 to Accepted (AC), 1 to Wrong Answer (WA), 2 to Time or Memory Limit Exceeded (TLE/MLE), 3 to Runtime Error (RE), and 4 to Compile Error (CE); unrecognized and internal outcomes occupy the most severe category. Strict compares recorded verdicts. Progress additionally compares replayed outcomes when the recorded verdict strings agree. Its cache must be complete, and compared vectors must have equal, nonempty testcase keys. Provenance includes problem, code, tests, and execution configuration.

For equal testcase universes, $o_t \prec_\times o_r$ holds when every test in o_t has severity no greater than its counterpart in o_r, with a strict decrease on at least one. Formally, the improvement predicates are:

$$\begin{aligned} \mathsf{Improves}_S(r,t) &\iff \mathrm{sev}(v_t) < \mathrm{sev}(v_r), \\ \mathsf{Improves}_P(r,t) &\iff \mathsf{Improves}_S(r,t) \\ &\quad \vee\ (v_t = v_r \wedge o_t \prec_\times o_r). \end{aligned} \tag{1}$$

Intuitively, Equation (1) retains coarse improvements and progress hidden by an unchanged verdict. A severity improvement such as RE to WA need not increase the pass fraction, and a verdict-improving edge does not require test-wise dominance.

Answer emits an independent pair for each non-AC source and the accepted endpoint. Thus $[s_1, \ldots, s_9]$ yields $([s_1], c_9), \ldots, ([s_8], c_9)$; it does not expose accumulated prefixes to Answer training. Strict and Progress start with $R = [s_1]$, compare each later state with the *last retained* state, and append it only when the predicate holds. Before appending s_t, the builder emits (R, c_t). For WA, improved WA, AC, Strict emits $([s_1], c_3)$, whereas Progress emits $([s_1], c_2)$ and $([s_1, s_2], c_3)$. The accepted endpoint remains eligible in both rules. Although Strict's pairwise predicate is contained in Progress's, their independently scanned edge sets need not be nested.

Chronological indices strictly increase, so construction terminates without cycles. With fixed-key evidence, retained edges also decrease the appropriate verdict/test severity rank. These are builder invariants, not evidence of a learned ZPD effect. Binary accepted/non-accepted mining retains 14,027 of 16,973 Strict pairs and 18,009 of 21,416 Progress pairs. Models retrained on them agree with the canonical ones on 84.6% and 87.5% of Seen repair decisions (Section IV-E), so we read the ranking as operational rather than universal.

D. Train

The goal of the Train stage is to learn each relation independently while keeping model and optimization comparable (lines 10–12). The implementation fine-tunes Qwen2.5-Coder-7B-Instruct with 4-bit Quantized Low-Rank Adaptation (QLoRA) [35], [36]. Adapters have rank 16, scaling 32, and dropout 0.05, targeting attention and feed-forward projections. Canonical training uses one epoch, learning rate 2×10^{-4}, and seeds 2027–2029. Assistant target tokens supply cross-entropy loss. The role-neutral prompt contains the statement, limits, permitted submissions, execution/edit summaries, and a request for a complete solution. It names neither the rule nor a preferred patch size, so specialization must come from the data rather than explicit instructions.

Targets are future submissions available offline; inference inputs contain only observed states. Current-only controls reset positions and remove earlier entries, preventing length leakage through position labels. Answer training is already single-source, so supplying history at inference creates a distribution change. The history-removal retraining control instead holds targets fixed and changes earlier-submission serialization. Source-matched target training holds current input and count fixed.

The paired-target control inner-joins records by problem, user, submission identifier, and the exact buggy program, retaining sources with distinct Answer and Progress targets. Its 7,389 training and 931 validation examples per condition use identical current-only inputs. The separate peer control requires another user on the same problem and in the same split, with exactly equal target execution evidence. Writing y_u for the same-user target and y_v for its peer replacement, for semantic-token diff distance d the discrepancy $\delta = |d(c, y_v) - d(c, y_u)|$ must satisfy $\delta \le 2$ or $\delta / \max(1, d(c, y_u)) \le 0.1$. Scarce evidence groups are visited first; ties prioritize distance discrepancy, reuse, and identifier, with donor reuse capped at three. This greedy rule yields 5,231 training and 306 validation examples per condition. Equal outcomes and nearby distances do not equate structure or style, so its measured effect belongs to the entire replacement rule, not isolated provenance.

E. Select

The goal of the Select stage is to deploy a bounded portfolio chosen without final-test outcomes (lines 13–16). For validation inputs U, let R_v^B be inputs repaired by checkpoint v within edit budget B. Formally, selection maximizes:

$$f_B(S) = \frac{1}{|U|} \left| \bigcup_{v \in S} R_v^B \right|, \qquad |S| = 3. \tag{2}$$

Intuitively, Equation (2) rewards complementary successes, not low training loss or the presence of every relation. Validation uses one fixed-hash trajectory from each of 461 eligible problems. The mixed pool has nine checkpoints and 84 triples; requiring one checkpoint per relation instead permits 27. The primary unconstrained mixed choice is Answer2027, Answer2028, and Progress2027. The relation-constrained choice

is a different condition. Answer-9Choose3 receives nine Answer checkpoints and the same 84-triple search. Ties use recorded pass-rate, improvement, and deterministic identifier priorities. Budget-indexed selection repeats the declared objective at $B \in \{5, 10, 20, 40, 80, 160\}$, without choosing a budget from test results.

Selected checkpoints and order are frozen. Each emits at most one independent candidate, and the first observed acceptance stops generation. If none passes all tests, Algorithm 1 prioritizes pass fraction and then smaller distance. Because unchanged code is feasible, for the same fixed execution measurements the returned pass fraction cannot decrease, and a finite edit budget cannot be exceeded. This is not per-test non-regression: equal fractions can conceal gains and losses on different tests. It also does not guarantee non-regression under fresh execution, an unseen suite, or resource variability.

Terminal pairing is linear in trajectory length; replaying n submissions on m tests requires $O(nm)$ executions and evidence storage. The 84-triple search is bounded at our pool size, not a scalable optimizer.

IV. Experiments

In this section, we evaluate ZPDPatch to answer the following research questions:

- **RQ1: Repair Effectiveness.** Which configuration provides the strongest unrestricted repair performance?
- **RQ2: Target Construction and Locality.** How do matched targets affect correctness and locality, and how do both distribute across exercises and students?
- **RQ3: Component Efficacy.** What do candidate breadth, checkpoint identity, and serialized history contribute?
- **RQ4: Generality.** Which findings replicate across problems, prefixes, scales, and Java populations?

We implemented ZPDPatch on top of Qwen2.5-Coder-7B-Instruct [35], an open code model of a scale a course can host. All experiments were conducted on a single machine equipped with one NVIDIA RTX 5090.

A. Experimental Settings

TABLE II
Primary Python evaluation. H: history input; C: current-only

Method	Input	Seen		Unseen	
		RR (%)	TED	RR (%)	TED
Zero-shot	H	30.7	27.25	62.0	17.46
LSGen	H	80.2	88.27	–	–
Answer-1	C	58.1	30.27	69.6	15.30
Answer-3Seed	H	61.7	24.52	73.2	13.38
Answer-9Choose3	H	59.8	25.46	74.8	15.19
Mixed-9Choose3	H	61.5	21.05	74.8	11.40
Answer-3Seed	C	72.0	37.94	81.2	16.01
Answer-9Choose3	C	69.5	35.41	82.0	20.06

Baselines. Zero-shot uses the same base model without fine-tuning and appends verdict/pass-count feedback after failure. LSGen retains repair-pair filtering, edit-vector retrieval, diff-guided generation, and re-retrieval [20]; its same-problem Seen-Train references are unavailable under our Unseen information constraint, so that condition is not evaluated. Answer-1 uses one Answer checkpoint. Answer-3Seed uses seeds 2027–2029 on the same 40,454 Answer pairs, controlling independent training without heterogeneous targets. Answer-9Choose3 adds seeds 2030–2035 and selects three from nine. Mixed-9Choose3 denotes the primary unconstrained ZPDPatch pool.

Benchmarks. Table I describes the Project CodeNet Python800 corpus [34] by partition (Part.) and submissions (Subm.); its Seen problems and tests are shared across partitions, so the user counts are not additive. We retain trajectories with at least three submissions, a non-AC state before the first acceptance, and an accepted endpoint in the benchmark reference set. Users must appear in at least three problems, and retained problems contain at least two trajectories. The refined corpus has 546 problems, 21,454 trajectories, 99,432 submissions, and 10,088 tests. Whole-trajectory 4,096-token filtering removes 3,660 trajectories before splitting. Problems ranked by eligible trajectory count supply the top 90% to Seen (492) and the remaining 54 low-resource problems to Unseen. Seen trajectories are split 80:10:10 within every problem, retaining at least one in each partition.

The primary endpoint is the last recorded non-AC submission of an eventually successful trajectory. Runtime eligibility requires the buggy program to remain non-AC and the recorded accepted endpoint to pass the available tests on replay. This leaves 997 of 1,754 Seen test trajectories, from 328 problems, and 250 of 259 Unseen trajectories, from all 54 problems. Excluded trajectories do not enter the denominator. CodeNet users are online-judge participants, not a verified classroom population. We also use TIKTOC's release of authentic Java CodeWorkout submissions and tests from an Introductory Programming (CS1) course [8]: 1,125 trajectories from 224 students and 17 exercises, with 181 test trajectories from 33 held-out students. CodeWorkout is a practice platform on which a course assigns short method-level exercises with instructor-authored tests, the setting a returned repair would enter. This corpus supplies the classroom population and CodeNet the scale. A separate exercise split has 10/3/4 train/validation/test exercises and 605/216/304 trajectories.

Other Settings. Canonical Python evaluation runs one subprocess per test with a 2.5-second timeout and a 2GB address-space limit, whereas Java 21 runs in a network-disabled, read-only container (16GB shared) with 15-second compilation and whole-harness limits; these are different harnesses, not a common per-test budget. The primary comparison permits three generations of at most 4,096 output tokens each. Matched-target training uses batch size 2 with accumulation 8. Each target rule uses the three seeds in order with greedy decoding and current-only prompts, and does not search nine-checkpoint portfolios. The supplement maps these conditions and source hashes.

Evaluation Metrics. We measure three kinds of outcome:

whether the returned program passes the tests, how large its change is, and how much of the submission it keeps. Repair Rate (RR) is the fraction of eligible inputs whose returned program passes every test. Pass Rate (PR) averages passed-test fractions; Improvement Rate (IR) records an increased fraction. Tree Edit Distance (TED) between ASTs measures current-to-returned change [37], [38] and is undefined when either program does not parse. Undefined cases remain in unrestricted RR but not TED summaries; finite gates reject undefined-distance changes. Unpaired TED averages successful, parseable returns; paired locality uses joint successes. Retention divides tokens or nonempty stripped lines matched by `SequenceMatcher` (autojunk disabled) by the source count. Python tokenization omits layout tokens but keeps comments; Java separates words and punctuation. Retention differences are percentage points (pp), not token counts or learning measures.

Unless stated otherwise, brackets give 95% percentile bootstrap intervals from 10,000 problem-cluster resamples with replacement, preserving all paired inputs in each sampled cluster [39]. Java separately resamples students and exercises. Instance-weighted estimates divide pooled differences by sampled inputs; equal-problem estimates average problem means. Exact two-sided McNemar tests are supplementary to the cluster-aware intervals, not substitutes for them [40]. Holm adjustment covers the four history-removal retraining tests (Strict/Progress $\times$ Seen/Unseen), not every exploratory contrast [41]; individual-rate Wilson intervals are reported separately [42]. Protocols identify when controls were frozen, but the study was not externally preregistered, and adaptively inspected development remains exploratory.

Research process. OpenAI Codex assisted with design, code, orchestration, diagnostics, and manuscript preparation under author instructions, and automated agents executed authorized jobs; we do not claim authors manually ran every job. Outcomes come from retained execution records rather than generated prose. The experiment program stopped at its declared cutoff of 21 October 2026, and this synthesis adds no training, generation, or testcase rerun.

B. RQ1: Repair Effectiveness

TABLE III
SOURCE- AND COUNT-MATCHED TARGET REPLACEMENT

Population	RR (%)		Retention (pp)	
	Answer	Progress	Tokens	Lines
Seen (997)	53.2	34.0	+5.6	+8.9
Unseen (250)	76.8	65.6	+6.5	+10.4
Java (181)	85.6	50.8	+4.8	+5.1

Results. Table II identifies current-only Answer-3Seed as the retained deployment configuration within our implementation, at 72.0% Seen and 81.2% Unseen. It repairs 718/997 and 203/250 inputs. Relative to current-only Answer-1, its paired gain is 13.9 points [11.71, 16.29] and 11.6 points [7.32, 16.23]. This contrast changes both checkpoint identity and opportunity count; RQ3 separates them. It is not universally best: current-only Answer-9Choose3 repairs two more Unseen inputs (205/250), but 25 fewer Seen inputs (693/997). We retain the simpler fixed triple rather than a different method per test split. Current-only mixed-pool reselection chooses exactly that Answer triple, providing no evidence that relation diversity improves this deployment setting.

The history-input mixed portfolio repairs 613/997 Seen and 187/250 Unseen inputs. Its Seen gain over Zero-shot is 30.8 points [26.43, 35.09], or 26.1 [21.24, 30.93] with equal problem weights. Mixed-only and Zero-shot-only successes number 342 and 35 (McNemar $p < 10^{-63}$). This is not a history-specific effect: Mixed nearly ties Answer-3Seed, while its matched nine-checkpoint contrast is +1.7 points [-0.79, 4.29] on Seen and 0.0 [-3.70, 3.75] on Unseen.

LSGen repairs 800/997 Seen inputs versus Mixed's 613/997, a difference of -18.8 points [-23.04, -14.46]; 80 versus 267 exclusive successes give $p < 10^{-23}$. On joint repairs, Mixed's TED is lower by 43.34 [38.47, 48.44] relative to LSGen and 8.46 [5.05, 12.55] relative to Zero-shot. Conditioning excludes unilateral successes, so smaller patches do not cancel the primary correctness deficit. Overall, none of our configurations is an unrestricted winner: LSGen leads on Seen and Answer-9Choose3 is marginally higher on Unseen, so we retain current-only Answer-3Seed.

C. RQ2: Target Construction and Locality

Matched targets. Table III changes the target while holding current inputs and training counts fixed. Progress-minus-Answer RR is -19.2 points [-22.96, -15.54] on Seen and -11.2 [-17.37, -4.88] on Unseen, with exact McNemar $p = 7.85 \times 10^{-34}$ and $p = 6.17 \times 10^{-5}$. Thus the canonical Answer dataset's advantage cannot be attributed only to having more training records. The paired population is restricted to sources with distinct targets, and a Progress target can itself be accepted, so the intervention is the retained-evidence target rule rather than a clean contrast between incorrect and correct targets. A returned program can move a submission forward without finishing it. Under the matched inputs the Progress rule repairs 34.0% of Seen inputs and improves 43.4%, so a further 9.4 points receive a program that advances without passing, against 53.2% and 65.0% for the Answer rule. The same two gaps are 6.4 and 7.6 points on Unseen, and 9.4 against 2.2 on Java, where Answer targets already repair 85.6% outright. Part of the coverage the Progress rule gives up therefore returns as partial progress, counted by test execution and not by comprehension.

Progress's locality benefit is visible on joint successes. Among 299 Seen and 154 Unseen jointly repaired inputs, 278 and 134 have defined source-to-repair TED for both methods. Answer-minus-Progress mean TED is 10.08 [7.53, 12.99] and 6.83 [4.58, 9.39]. Token retention improves by 5.6 [4.29, 6.94] and 6.5 [4.26, 8.95] points; line retention improves by 8.9 [6.64, 11.16] and 10.4 [6.95, 14.25]. The 21 and 20 undefined-TED cases remain in RR and are not declared unrepairable. These measures describe successful

outputs that retain more of the submission, but they establish neither easier comprehension nor which method best helps a particular student.

TABLE IV
JAVA MATCHED-TARGET OUTCOMES OVER 17 EXERCISES AND 90 JOINTLY REPAIRED STUDENTS

Repairs (17 exercises)		Retention (90 students)	
Answer higher	15	Answer higher	5.6%
Tied	2	Tied	63.3%
Progress higher	0	Progress higher	31.1%
Extra Answer repairs	63	Median gain	9.6
Largest gap	12	Retention range	-21.1 / 49.7

```
N=int(input())
S=input()
ans=0
i=0
j=N-1
while i<=j:
  while i<N:
    ...
  while j>0:
    ...
print(ans)
```

(a) submission

```
N=int(input())
S=input()
cnt=S.count('R')
ans=S[:cnt].count('W')
print(ans)
```

(b) Answer-target repair

Fig. 3. A jointly repaired Python case, post hoc and outside every estimate

Java retraining uses 600 training and 118 validation pairs per target and reproduces this direction without Python AST distance. Answer targets repair 155 trajectories and Progress targets 92, a difference of 34.8 points; Progress-minus-Answer intervals are [-44.91, -25.47] under student clustering and [-47.31, -23.79] under exercise clustering. Among 90 joint repairs, Progress targets increase lexical-token retention by 4.8 points and line retention by 5.1 points, with intervals [2.79, 7.19] and [2.92, 7.25]. This is evidence for a coverage–locality tradeoff across these two languages and populations. It is not evidence that the same magnitude generalizes to other classrooms, nor a replication of the Python peer-target intervention. **What a student receives.** Cohort means do not describe an individual student, so Table IV resolves the Java contrast by exercise and by student. The coverage cost is concentrated rather than uniform. One exercise accounts for 12 of the 63 additional Answer repairs, and there Progress targets repair 3 of 15 trajectories against 15. The retention gain is a minority effect with a long tail. Most students who receive a working repair from either rule get back the same amount of their own code, about a third get more, by a median of 9.6 points, and a few get less. Line retention behaves the same, zero for 64.4% of students with maximum 47.6. Figure 3 illustrates that tail on Python. Submission (a) passes 93.3% of tests after the student's own preceding edit changed `i<j` to `i<=j`, the Progress-target repair differs from it only in `j>0` becoming `j>=0` (TED 1), and the Answer-target repair (b) replaces the approach (TED 83). Both pass every test under the same gate and budget. Which rule a course deploys therefore depends on the exercise and on whether coverage or locality binds.

Peer targets. The separate outcome- and distance-matched replacement raises RR from 50.4% to 54.7% on Seen and from 78.4% to 84.4% on Unseen. Same-minus-peer intervals are [-7.71, -0.84] and [-11.79, -0.41], with exact McNemar $p = 0.005$ and $p = 0.032$. The result concerns this caliper, donor cap, and replacement rule, and equal outcomes with nearby edit distance still permit differences in structure and length, so the contrast does not isolate user identity. Matched peer targets improve coverage here; one's own trajectory is not uniquely necessary under this control.

Operational locality. A declared structural budget gives patch size an explicit engineering meaning: the deployment admits only changes within it. Per-budget Seen rates are 16.9/22.5/4.8% at TED 5, 28.5/32.4/8.0 at 10, 40.3/44.0/13.9 at 20, 51.4/50.9/30.4 at 40, 61.0/56.0/50.8 at 80, and 66.8/57.9/67.6 at 160 for current-only Answer-3Seed/Mixed/LSGen, each over 997 inputs. At TED 20, Mixed repairs 44.0% of Seen inputs versus LSGen's 13.9%, a 30.1-point difference [26.45, 33.82]. Across the six prespecified budgets its mean advantage over LSGen is 14.7 points [12.03, 17.43]. This is a budget-indexed outcome, not an unrestricted superiority claim: LSGen wins at 160, and current-only Answer-3Seed overtakes Mixed from 40 onward. On Unseen, Mixed versus current-only Answer-3Seed is 38.8% versus 32.0% at 5, 48.0% versus 40.8% at 10, and 57.6% versus 54.8% at 20; the order reverses at 40. Overall, target construction moves coverage and locality in opposite directions under matched inputs, in the same direction on student-held-out Java, and not uniformly across exercises or students, and matched peer targets also improve coverage, so the effect is not uniquely personal supervision.

D. RQ3: Component Efficacy

Fixed candidate breadth. For three stored draws with success indicators a_{ij}, the expected uniformly selected one-draw success for input i is $\frac{1}{3}\sum_j a_{ij}$, whereas the three-draw union succeeds when $\max_j a_{ij} = 1$. Their paired difference isolates additional opportunities within the identical candidate set. Replacing greedy decoding by one stochastic draw costs 7.6 points [-9.81, -5.41], whereas execution-selecting three of those identical fixed draws contributes 15.1 points [13.48, 16.76] on Seen. This is a descriptive decomposition of stored executions, and it shows why comparing a portfolio only with one adapter overstates the evidence for its training signal.

The temperature sweep retains all declared conditions instead of selecting the best one for the headline. Through $T = 1.0$ the one-draw rate stays within 41.1–43.1% on Seen, the three-draw union reaches 60.0/75.2%, and at $T = 1.5$ the decoder collapses to 15.8/35.2%. A separate 20-draw stream at $T = 0.8$ reaches 74.8% Seen and 84.0% Unseen, using on average 7.44 and 5.08 calls under early stopping. Those higher rates spend a different generation budget and do not replace the three-call primary results. Fine-tuning also matters: the matched base-model three-draw union reaches

only 30.4/65.6%, so adaptation adds 27.2 points [22.99, 31.41] on Seen and 6.4 points [1.19, 11.34] on Unseen. Breadth alone therefore does not explain all improvement over the base model.

At matched temperature, replacing three draws of one checkpoint by one draw from each of three checkpoints changes RR by -0.1 points [-2.00, 1.80] on Seen and 2.4 points [-0.41, 5.31] on Unseen. These intervals do not establish a consistent advantage from checkpoint diversity. They also do not show equivalence. A deterministic multi-seed gain can coexist with this result because sampling from one checkpoint already supplies diversity.

A current-only factorial on one inference stack tests this explanation. Three greedy checkpoints gain 9.8 [7.85, 11.92] and 10.8 [7.23, 14.64] points over one, but under the matched stochastic decoder distinct checkpoints add only 2.1 points [0.00, 4.16] and 1.2 points [-2.93, 5.93]. The equal-problem Seen interval includes zero, so the rounded instance-weighted lower bound does not establish a robust checkpoint benefit. Absolute Seen/Unseen rates on that stack are 53.1/67.2% for one greedy checkpoint, 62.9/78.0% for three greedy checkpoints, 66.8/79.6% for a same-checkpoint stochastic triple, and 68.9/80.8% for a distinct-checkpoint triple, against 72.0/81.2% on the historical one. Backend sensitivity is material, and the deployment recommendation is restricted to the evaluated stack rather than asserted as backend-independent superiority.

Serialized history. Removing earlier submissions from the frozen triples raises repair for both pools. The gains are 8.8/11.1 Seen points and 7.6/6.0 Unseen points for Mixed/Answer, with all intervals excluding zero. Matched retraining without that context shows no significant difference after Holm correction, with smallest adjusted $p = 0.313$, so serialized history is not part of the measured advantage and the deployed configuration uses current-only prompts.

Selection-space controls also fail to establish a general heterogeneous-target benefit. Answer-9Choose3 receives the same nine-checkpoint pool size and 84-subset opportunity as Mixed. The primary five-fold cross-fitted mixed-minus-Answer contrast is +2.2 points [-0.19, 4.63], compared with the non-cross-fitted +1.7 [-0.79, 4.29]. These estimates are positive but uncertain. Overall, candidate breadth and adaptation each contribute measured gains, whereas distinct checkpoints add no consistent advantage once the stochastic decoder is matched and serialized history is not supported as a necessary input.

E. RQ4: Generality

Problems and execution suites. Within Unseen, Mixed exceeds Zero-shot by 12.8 points [6.83, 18.75], with 45 versus 13 exclusive successes and exact McNemar $p = 3.01 \times 10^{-5}$. Among 142 joint repairs, 122 have defined TED for both methods; on those 122 it reduces TED by 6.41 [3.43, 9.89]. The higher absolute Unseen than Seen RR is not evidence of stronger generalization: the partitions differ in trajectory availability and problem composition. Matching all 54 Unseen problems to distinct Seen problems on six pre-repair difficulty covariates changes the raw gap into -4.6 equal-problem points [-14.18, 5.30]. We therefore rely on within-split paired contrasts rather than the raw cross-split difference, since matching cannot balance unobserved difficulty.

A complementary observed/hidden-slice check partitions the existing authored suite. On Unseen, Mixed and Answer-9Choose3 jointly pass observed and held-back slices on 189/250 and 184/250 inputs, respectively. Conditional confirmation among observed-suite successes is 189/192 (98.4%) and 184/186 (98.9%); 13 versus 8 exclusive joint successes yield $p = 0.383$. Repeating the procedure on all 328 Seen problems with a distinct seed yields 97.8% and 97.9% confirmation, but joint success is 452/997 versus 469/997. High confirmation thus does not demonstrate that Mixed wins. These are held-back slices of the same authored tests, so the conditional percentage must not replace the full-denominator repair rate.

Earlier prefixes. Across 2,770 Seen and 674 Unseen executable prefixes of eventually successful trajectories, current-only Answer-3Seed reaches 69.6% and 80.1% RR. The early, middle, and last thirds reach 70.0%, 67.6%, and 71.4% on Seen and 82.9%, 77.3%, and 81.8% on Unseen. It extends evaluation beyond the last failed submission and finds no monotonic position effect. It does not cover trajectories that never reach acceptance and multiple prefixes from one trajectory are dependent, so the 2,770-prefix rate is not added to the 997-input result.

Model scale and classroom data. At 1.5B parameters three checkpoints still gain 13.4 points over one [11.16, 15.92], but mixed-minus-Answer is -0.8 [-2.62, 1.07]. Mixed reaches 50.25% and the nine-checkpoint Answer control 51.05% on Seen. This smaller model reproduces the utility of multiple opportunities, not an unrestricted mixed-target advantage.

The Java portfolio results differ from RQ2's direct matched-target retraining. Mixed-minus-Answer-9Choose3 is positive on four held-out exercises (3.9 points [2.99, 5.11]) and inconclusive on held-out students (0.6 [-1.20, 2.59]). Absolute RR is 56.25% versus 52.30% over 304 exercise-held-out trajectories and 83.98% versus 83.43% over 181 student-held-out trajectories. The exercise estimate rests on four clusters only: refitting with one exercise left out keeps the contrast between 3.6 and 4.4 points, and single exercises range from 2.5 to 5.5 points. Four clusters cannot support a broad classroom-population claim. The matched-target tradeoff has clearer cross-population support than a universal portfolio benefit.

Representation and overlap. Binary accepted/non-accepted mining removes the fine severity ordering but also changes the target set. Retraining changes Progress RR by +2.3 Seen and -2.8 Unseen points in the canonical-minus-alternative direction. The nonuniform changes show that the ordering is not an innocuous implementation detail. For Mixed and Answer-9Choose3, exact matches between a returned repair and a training-time accepted program occur in 0.6% and 1.3% of selections, near-duplicates above a 0.90 token-similarity threshold in 3.8% and 5.3%, and median maximum similarity to a same-problem training target is 66.7% and 68.6%. Low

exact-copy rates do not exclude structural reuse, pretraining contamination, or user-level overlap [43]. Overall, the matched-target tradeoff replicates on student-held-out Java and candidate breadth remains useful at a smaller model scale, whereas mixed-target unrestricted superiority does not replicate consistently.

F. Threats to Validity

(1) Runtime variability, undefined source ASTs, and Python whitespace affect labels and distances. We retain unknowns, denominators, and whitespace-sensitive corrections, but hashes establish provenance, not correctness, and source and peer matching do not equate all target semantics or styles. (2) Acceptance is not proof of semantic correctness [44], same-suite slices are not independent specifications, and TED and retention do not measure cognitive load or subsequent learning. CodeNet does not identify novices or measure mastery, Java supplies classroom submissions rather than an intervention observing feedback use, and the per-exercise and per-student resolution describes which students would receive a different repair, not which students benefit, with Figure 3 one post-hoc case that carries no estimate. We display a CodeNet program because the course data terms do not permit redistributing student submissions. (3) Filtering favors short, eventually successful Python trajectories and permits Seen user overlap, Java adds one course context and only four held-out exercises, and cluster bootstrap and equal-problem estimates do not eliminate small-cluster uncertainty, multiplicity, or the bias of analyses chosen after earlier results. These distinctions limit educational and target-quality interpretations.

V. Related Work

Repair and Generation Budgets. Generate-and-validate repair spans search, learned transformations, and language models [1]–[4]. Search analyses [45] and execution-based evaluation [46], [47] separate candidate quality from exposure. Neural patches, ensembles, synthetic corruption, and execution-informed self-supervision provide different training signals [48]–[51]; zero-shot studies examine repair without task adaptation [52], [53]. We do not introduce portfolio repair; we isolate trajectory targets with same-target seeds, equal search spaces, fixed draws, and current-only controls.

Programming-Assignment Feedback. Educational repair exploits correct programs through clustering, alignment, and refactoring [9]–[11]; related representations and tutoring systems propagate feedback and generate hints [21]–[23], [54]. Language models support repair, syntax feedback, conversations, peers, and counterexamples [6], [7], [15]–[19]. Assignment-aware and diversified feedback use further reference strategies [12]–[14]. LSGen also mines chronological wrong-to-later-correct submission pairs for retrieval [20], so trajectories are not our novelty, and it retains its strong Seen advantage here. It does not separate the history's contribution from that of extra candidates, however, which is why we hold the history and the candidate budget fixed together. Next-step hint generators differ from this work in what their guidance is fitted to. Data-driven hints read a solution space or a past cohort's paths and project the submission onto it, so two students at the same position in that space receive the same next step independently of which tests their own code currently passes [22]–[24]. Our target rule reads the submission's own execution evidence instead and returns a complete program rather than a textual hint, so the two kinds of output are measured on different scales [5], [25], [55]. Our narrower intervention replaces the target for matched sources and exposes a coverage–locality tradeoff, not dominance over feedback strategies.

History and Learner Evidence. ZPD and scaffolding concern supported performance, not program edit distance [30]–[33]. Knowledge tracing models proficiency from interactions [56]–[58]; TIKTOC incorporates testcase evidence [8]. Next-step hints, feedback ladders, and novice-response studies examine guidance more directly [24], [59], [60], while feedback theory emphasizes its interpretation and use [26]–[29]. This paper does not claim that conditioning on a learner's serialized history improves generated repairs. Our deployed configuration prompts with the current submission alone, and the supplement reports the matched retraining and prompt controls behind that choice, including their negative outcomes.

VI. Conclusion

Automated Program Repair has substantially raised the repair rate for buggy student submissions. However, existing techniques settle what a return aims at without reference to the student's own attempts, so a return can replace most of the submission. This paper aims to repair a buggy submission toward a step taken from the student's own trajectory, and to make the gain readable as the target's. To this end, ZPDPatch mines supervision pairs from execution evidence, trains one adapter per rule, and freezes a portfolio by executed validation repairs. Matched Python and student-held-out Java experiments show the same coverage–locality tradeoff, uneven across exercises and students, and candidate breadth, model adaptation, and matched peer targets account for the measurable part of the remaining improvement, so the retained-evidence target is not uniquely personal supervision. We therefore retain the current-only Answer triple and report the Progress rule as the option for when locality binds, while educational benefit and broader model-family generality remain unmeasured.

Data Availability

An anonymous supplement contains code-free paired outcomes, condition manifests, metric code, negative results, claim–evidence links, and the complete inventory of the development runs that this paper does not report; its offline verifier checks hashes and recomputes every reported contrast. Because the CodeWorkout/TIKTOC [8] and CodeNet [34] terms govern redistribution of student submissions and the adapters exceed the supplement budget, we exclude student source and model weights and submit the data as anonymous supplementary material. No student intervention was conducted.

References

[1] L. Gazzola, D. Micucci, and L. Mariani, "Automatic software repair: A survey," *IEEE Transactions on Software Engineering*, vol. 45, no. 1, pp. 34–67, 2019.

[2] M. Monperrus, "Automatic software repair: A bibliography," *ACM Computing Surveys*, vol. 51, no. 1, pp. 1–24, 2018.

[3] W. Weimer, T. Nguyen, C. Le Goues, and S. Forrest, "Automatically finding patches using genetic programming," in *Proceedings of the 31st International Conference on Software Engineering*, 2009, pp. 364–374.

[4] C. Le Goues, T. Nguyen, S. Forrest, and W. Weimer, "GenProg: A generic method for automatic software repair," *IEEE Transactions on Software Engineering*, vol. 38, no. 1, pp. 54–72, 2012.

[5] H. Keuning, J. Jeuring, and B. Heeren, "A systematic literature review of automated feedback generation for programming exercises," *ACM Transactions on Computing Education (TOCE)*, vol. 19, no. 1, pp. 1–43, 2018.

[6] H. Joshi, J. C. Sanchez, S. Gulwani, V. Le, G. Verbruggen, and I. Radiček, "Repair is nearly generation: Multilingual program repair with LLMs," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 37, no. 4, 2023, pp. 5131–5140.

[7] J. Zhang, J. P. Cambronero, S. Gulwani, V. Le, R. Piskac, G. Soares, and G. Verbruggen, "PyDex: Repairing bugs in introductory Python assignments using LLMs," *Proceedings of the ACM on Programming Languages*, vol. 8, no. OOPSLA1, pp. 1100–1124, 2024.

[8] Z. Duan, N. Fernandez, A. Hicks, and A. Lan, "Test case-informed knowledge tracing for open-ended coding tasks," in *Proceedings of the 15th International Learning Analytics and Knowledge Conference*, 2025, pp. 238–248.

[9] S. Gulwani, I. Radiček, and F. Zuleger, "Automated clustering and program repair for introductory programming assignments," *ACM SIGPLAN Notices*, vol. 53, no. 4, pp. 465–480, 2018.

[10] K. Wang, R. Singh, and Z. Su, "Search, align, and repair: data-driven feedback generation for introductory programming exercises," in *Proceedings of the 39th ACM SIGPLAN conference on programming language design and implementation*, 2018, pp. 481–495.

[11] Y. Hu, U. Z. Ahmed, S. Mechtaev, B. Leong, and A. Roychoudhury, "Re-factoring based program repair applied to programming assignments," in *Proceedings of the 34th IEEE/ACM International Conference on Automated Software Engineering (ASE)*. IEEE, 2019, pp. 388–398.

[12] J. Heo, H. Jeong, D. Choi, and E. Lee, "REFERENT: Transformer-based feedback generation using assignment information for programming course," in *2023 IEEE/ACM 45th International Conference on Software Engineering: Software Engineering Education and Training (ICSE-SEET)*. IEEE, 2023, pp. 101–106.

[13] D. Choi, J. Heo, and E. Lee, "Automated feedback generation for multiple function programs," in *2021 28th Asia-Pacific Software Engineering Conference (APSEC)*. IEEE, 2021, pp. 582–583.

[14] D. Choi and E. Lee, "Automated feedback generation for programming assignments through diversification," in *2025 IEEE/ACM 37th International Conference on Software Engineering Education and Training (CSEE&T)*. IEEE, 2025, pp. 230–241.

[15] T. Phung, J. Cambronero, S. Gulwani, T. Kohn, R. Majumdar, A. Singla, and G. Soares, "Generating high-precision feedback for programming syntax errors using large language models," in *Proceedings of the 16th International Conference on Educational Data Mining*, 2023, pp. 370–377.

[16] F. Liu, Z. Liu, Q. Zhao, J. Jiang, L. Zhang, Z. Sun, G. Li, Z. Li, and Y. Ma, "FastFixer: An efficient and effective approach for repairing programming assignments," in *Proceedings of the 39th IEEE/ACM International Conference on Automated Software Engineering*, 2024, pp. 669–680.

[17] B. Yang, H. Tian, W. Pian, H. Yu, H. Wang, J. Klein, T. F. Bissyandé, and S. Jin, "CREF: An LLM-based conversational software repair framework for programming tutors," in *Proceedings of the 33rd ACM SIGSOFT International Symposium on Software Testing and Analysis*, 2024, pp. 882–894.

[18] Q. Zhao, F. Liu, L. Zhang, Y. Liu, Z. Yan, Z. Chen, Y. Zhou, J. Jiang, and G. Li, "Peer-aided repairer: Empowering large language models to repair advanced student assignments," *arXiv preprint arXiv:2404.01754*, 2024.

[19] P. Orvalho, M. Janota, and V. M. Manquinho, "Counterexample guided program repair using zero-shot learning and maxsat-based fault localization," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 39, no. 1, 2025, pp. 649–657.

[20] Z. Dai, Z. Zhao, H. Wang, X. Tang, S. Wu, C. Yao, Z. Gao, and J. Chen, "Learner-tailored program repair: A solution generator with iterative edit-driven retrieval enhancement," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 40, no. 36, 2026, pp. 30 467–30 475.

[21] C. Piech, J. Huang, A. Nguyen, M. Phulsuksombati, M. Sahami, and L. Guibas, "Learning program embeddings to propagate feedback on student code," in *Proceedings of the 32nd International Conference on Machine Learning*, 2015, pp. 1093–1102.

[22] K. Rivers and K. R. Koedinger, "Data-driven hint generation in vast solution spaces: A self-improving python programming tutor," *International Journal of Artificial Intelligence in Education*, vol. 27, no. 1, pp. 37–64, 2017.

[23] T. W. Price, Y. Dong, and D. Lipovac, "iSnap: towards intelligent tutoring in novice programming environments," in *Proceedings of the 2017 ACM SIGCSE Technical Symposium on computer science education*, 2017, pp. 483–488.

[24] L. Roest, H. Keuning, and J. Jeuring, "Next-step hint generation for introductory programming using large language models," in *Proceedings of the 26th Australasian Computing Education Conference*, 2024, pp. 144–153.

[25] C. Koutcheme, N. Dainese, S. Sarsa, J. Leinonen, A. Hellas, and P. Denny, "Benchmarking educational program repair," *arXiv preprint arXiv:2405.05347*, 2024.

[26] J. Hattie and H. Timperley, "The power of feedback," *Review of Educational Research*, vol. 77, no. 1, pp. 81–112, 2007.

[27] V. J. Shute, "Focus on formative feedback," *Review of Educational Research*, vol. 78, no. 1, pp. 153–189, 2008.

[28] S. Narciss, "Feedback strategies for interactive learning tasks," in *Handbook of research on educational communications and technology*. Routledge, 2008, pp. 125–143.

[29] V. Aleven and K. R. Koedinger, "Limitations of student control: Do students know when they need help?" in *International conference on intelligent tutoring systems*. Springer, 2000, pp. 292–303.

[30] L. S. Vygotsky, *Mind in Society: The Development of Higher Psychological Processes*, M. Cole, V. John-Steiner, S. Scribner, and E. Souberman, Eds. Cambridge, MA: Harvard University Press, 1978.

[31] T. Murray and I. Arroyo, "Toward measuring and maintaining the zone of proximal development in adaptive instructional systems," in *International conference on intelligent tutoring systems*. Springer, 2002, pp. 749–758.

[32] I.-A. Chounta, P. Albacete, P. Jordan, S. Katz, and B. M. McLaren, "The "grey area": A computational approach to model the zone of proximal development," in *European conference on technology enhanced learning*. Springer, 2017, pp. 3–16.

[33] N. Schulze Bernd and I.-A. Chounta, "Beyond the grey area: exploring the effectiveness of scaffolding as a learning measure," in *International Conference on Artificial Intelligence in Education*. Springer, 2024, pp. 365–378.

[34] R. Puri, D. Kung, G. Janssen, W. Zhang, G. Domeniconi, V. Zolotov, J. Dolby, J. Chen, M. Choudhury, L. Decker *et al.*, "CodeNet: A large-scale AI for code dataset for learning a diversity of coding tasks," in *Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks*, vol. 1, 2021.

[35] B. Hui, J. Yang, Z. Cui, J. Yang, D. Liu, L. Zhang, T. Liu, J. Zhang, B. Yu, K. Lu *et al.*, "Qwen2.5-Coder technical report," *arXiv preprint arXiv:2409.12186*, 2024.

[36] T. Dettmers, A. Pagnoni, A. Holtzman, and L. Zettlemoyer, "QLoRA: Efficient finetuning of quantized LLMs," *Advances in neural information processing systems*, vol. 36, pp. 10 088–10 115, 2023.

[37] K. Zhang and D. Shasha, "Simple fast algorithms for the editing distance between trees and related problems," *SIAM Journal on Computing*, vol. 18, no. 6, pp. 1245–1262, 1989.

[38] M. Pawlik and N. Augsten, "Tree edit distance: Robust and memory-efficient," *Information Systems*, vol. 56, pp. 157–173, 2016.

[39] B. Efron, "Bootstrap methods: Another look at the jackknife," *The Annals of Statistics*, vol. 7, no. 1, pp. 1–26, 1979.

[40] Q. McNemar, "Note on the sampling error of the difference between correlated proportions or percentages," *Psychometrika*, vol. 12, no. 2, pp. 153–157, 1947.

[41] S. Holm, "A simple sequentially rejective multiple test procedure," *Scandinavian Journal of Statistics*, vol. 6, no. 2, pp. 65–70, 1979.

[42] E. B. Wilson, "Probable inference, the law of succession, and statistical inference," *Journal of the American Statistical Association*, vol. 22, no. 158, pp. 209–212, 1927.

[43] M. Allamanis, "The adverse effects of code duplication in machine learning models of code," in *Proceedings of the 2019 ACM SIGPLAN International Symposium on New Ideas, New Paradigms, and Reflections on Programming and Software*, 2019, pp. 143–153.

[44] E. K. Smith, E. T. Barr, C. Le Goues, and Y. Brun, "Is the cure worse than the disease? overfitting in automated program repair," in *Proceedings of the 10th Joint Meeting on Foundations of Software Engineering*, 2015, pp. 532–543.

[45] Y. Qi, X. Mao, Y. Lei, Z. Dai, and C. Wang, "The strength of random search on automated program repair," in *Proceedings of the 36th International Conference on Software Engineering*, 2014, pp. 254–265.

[46] M. M. A. Haque, W. U. Ahmad, I. Lourentzou, and C. Brown, "FixEval: Execution-based evaluation of program fixes for programming problems," in *2023 IEEE/ACM International Workshop on Automated Program Repair (APR)*. IEEE, 2023, pp. 11–18.

[47] M. Chen, J. Tworek, H. Jun, Q. Yuan, H. P. de Oliveira Pinto, J. Kaplan, H. Edwards, Y. Burda, N. Joseph, G. Brockman *et al.*, "Evaluating large language models trained on code," *arXiv preprint arXiv:2107.03374*, 2021.

[48] M. Tufano, C. Watson, G. Bavota, M. Di Penta, M. White, and D. Poshyvanyk, "An empirical study on learning bug-fixing patches in the wild via neural machine translation," *ACM Transactions on Software Engineering and Methodology*, vol. 28, no. 4, pp. 1–29, 2019.

[49] T. Lutellier, H. V. Pham, L. Pang, Y. Li, M. Wei, and L. Tan, "Coconut: Combining context-aware neural translation models using ensemble for program repair," in *Proceedings of the 29th ACM SIGSOFT International Symposium on Software Testing and Analysis*, 2020, pp. 101–114.

[50] M. Yasunaga and P. Liang, "Break-it-fix-it: Unsupervised learning for program repair," in *International conference on machine learning*. PMLR, 2021, pp. 11 941–11 952.

[51] H. Ye, M. Martinez, X. Luo, T. Zhang, and M. Monperrus, "SelfAPR: Self-supervised program repair with test execution diagnostics," in *Proceedings of the 37th IEEE/ACM International Conference on Automated Software Engineering*, 2022, pp. 1–13.

[52] C. S. Xia and L. Zhang, "Less training, more repairing please: Revisiting automated program repair via zero-shot learning," in *Proceedings of the 30th ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, 2022, pp. 959–971.

[53] N. Jiang, K. Liu, T. Lutellier, and L. Tan, "Impact of code language models on automated program repair," in *Proceedings of the 45th International Conference on Software Engineering*, 2023, pp. 1430–1442.

[54] E. L. Glassman, J. Scott, R. Singh, P. J. Guo, and R. C. Miller, "Overcode: Visualizing variation in student solutions to programming problems at scale," *ACM Transactions on Computer-Human Interaction*, vol. 22, no. 2, pp. 1–35, 2015.

[55] J. Yi, U. Z. Ahmed, A. Karkare, S. H. Tan, and A. Roychoudhury, "A feasibility study of using automated program repair for introductory programming assignments," in *Proceedings of the 2017 11th joint meeting on foundations of software engineering*, 2017, pp. 740–751.

[56] A. T. Corbett and J. R. Anderson, "Knowledge tracing: Modeling the acquisition of procedural knowledge," *User modeling and user-adapted interaction*, vol. 4, no. 4, pp. 253–278, 1994.

[57] C. Piech, J. Bassen, J. Huang, S. Ganguli, M. Sahami, L. J. Guibas, and J. Sohl-Dickstein, "Deep knowledge tracing," *Advances in neural information processing systems*, vol. 28, 2015.

[58] A. Ghosh, N. Heffernan, and A. S. Lan, "Context-aware attentive knowledge tracing," in *Proceedings of the 26th ACM SIGKDD international conference on knowledge discovery & data mining*, 2020, pp. 2330–2339.

[59] H. Heickal and A. Lan, "Generating feedback-ladders for logical errors in programming using large language models," in *Proceedings of the 17th International Conference on Educational Data Mining*, 2024, pp. 947–951.

[60] R. Xiao, X. Hou, and J. Stamper, "Exploring how multiple levels of gpt-generated programming hints support or disappoint novices," in *Extended Abstracts of the CHI Conference on Human Factors in Computing Systems*, 2024, pp. 1–10.