

Company: e-Tech Racing	e-techracing.es		
Project: Inverter Control	Variant: [No Variations]		
Size: -	Page Contents: Inverter_Control.SchDoc	Version: 1.0	
		Department: Powertrain	
Author: David Redondo	dredondovinolo@gmail.com	Sheet 1 of 1	
Checked by: _		Date: 21/02/2024	

LV battery supply



Supply OK



Battery voltage sense



USB supply



INPUTS/OUTPUTS



5 V selection



PMOS disconnects USB power when the DCDC is supplying. Gate drivers should be disabled when the DCDC is not supplying via software (read LV+_in).

LDO



Company: e-Tech Racing	e-techracing.es		
Project: Inverter Control	Variant: [No Variations]		
Size: -	Page Contents: [1] Supply.SchDoc	Version: 1.0	
		Department: Powertrain	
Author: David Redondo	dredondovinolo@gmail.com	Sheet * of *	
Checked by: _		Date: 21/02/2024	

INPUTS/OUTPUTS



Timers

PWM L → TIM1
PWM R → TIM8
- PWM1 → CH1N
- PWM2 → CH1
- PWM3 → CH2N
- PWM4 → CH2
- PWM5 → CH3N
- PWM6 → CH3

Enc. L → TIM4
- A → CH1
- B → CH3
- Z → CH4

Enc. R → TIM4
- A → CH1
- B → CH3
- Z → CH4

ADC

ADC1:
- ia_meas_R (IN0)
- ib_meas_R (IN1)
- ic_meas_R (IN2)
- VDC_R (IN3)
- Vbat (LV+_sns) (IN18)

ADC2:
- ia_meas_L (IN6)
- ib_meas_L (IN7)
- ic_meas_L (IN8)
- VDC_L (IN9)

ADC3:
- Tinv_L (IN10)
- Tinv_R (IN11)
- Tmot_L (IN12)
- Tmot_R (IN13)

ST-link



Trace asynchronous SWD

STM32F777VIT



EEPROM (I2C1)



Oscillator



USB connector



Company: e-Tech Racing	e-techracing.es		
Project: Inverter Control	Variant: [No Variations]		
Size: -	Page Contents: [2]MCU.SchDoc	Version: 1.0	
		Department: Powertrain	
Author: David Redondo	dredondovinolo@gmail.com	Sheet * of *	
Checked by: _		Date: 21/02/2024	

Decoupling



Transceiver



ESD



INPUTS/OUTPUTS



Status LEDs



Company: e-Tech Racing	e-techracing.es		
Project: Inverter Control	Variant: [No Variations]		
Size: -	Page Contents: [3] CAN.SchDoc	Version: 1.0	
		Department: Powertrain	
Author: David Redondo	dredondovinolo@gmail.com	Sheet * of *	
Checked by: _		Date: 21/02/2024	

Feedback connector



Auxiliary warning (WRN)



Incremental encoder



As the motors' temperature sensors are not specified, the user may modify the resistor combination to find a suitable input for the ADC, then load a custom lookup table to have an appropiate reading.

Example



The WRN circuit can be used so that the MCU can detect a specified alarm. A resistive sensor can be used to detect any physical signal, such as overtemperature in any component (e.g. water outlet, gearbox, ...), underpressure of the cooling system, etc. Similar to the motor temperature sensors, the user may modify the resistor combination to have a suitable reading and adjust the voltage divider in order to set the treshold. Other types of sensors can be used, given a previous study and correct implementation.

Comparator supply



Motor thermistor

Only compatible with resistive temperature sensors.



INPUTS/OUTPUTS



Company: e-Tech Racing	e-techracing.es		
Project: Inverter Control	Variant: [No Variations]		
Size: -	Page Contents: [4] Feedback.SchDoc	Version: 1.0	
		Department: Powertrain	
Author: David Redondo	dredondovinolo@gmail.com	Sheet * of *	
Checked by: _		Date: 21/02/2024	

Power PCB Connector



VDC sense AFE



Difference amplifier

LT SPICE simulation for reference.

VDC = Vref + (VDC_sns+ - VDC_sns-) = Vref + 1/3 · 0.011388 · (TS+ - TS-)

Maximum error due to using a voltage divider as a voltage reference is 1.79mV in ADC, which translates to 0.47V in (TS+ - TS-). Lowering the resistance values (while keeping proportionality) will reduce the error, but more current will be drawn.

INPUTS/OUTPUTS



Current sense

Resistor combination can be adjusted for increased measuring range at the cost of lower resolution.



Temperature selection



ENABLE is output directly from the MCU, it has been checked that UC21732 is able to detect it at 3.3V. Similarly, TRIP comes at 5V, and uses a 5V tolerant GPIO in the MCU.

VDC_offset = Vref · 2^12 bits / (3.3V) = 0.02083 · 2^12 bits / (3.3V) = 129 bits
VDC_gain = 1/((1/3 · 0.011388 V/V) · (2^12 bits / 3.3 V)) = 0.212240269 V / bit
VDC_max = 0.212240269 V / bit · 2^12 bits = 869.34V

ix_offset = (10k/(3.3k+10k)) · 2.5V · 2^12 bits / (3.3V) = 2333 bits
ix_gain = (10k/(3.3k+10k)) / (12.5 mV/A · (2^12 bits / 3.3 V))) = 0.0484609962 A / bit
ix_max(+/-) = +/- 0.0484609962 A / bit · 2^12 bits / 2 = +/- 99 A

Inverters temperature should be calculated with a lookup table according to this graph. The lookup table and graph is generated with a MATLAB script which can be found in the simulations folder.



Tinv is a pulsated signal that can read directly as a PWM input or be passed through an RC filter (in Inverter_Power) to convert it into an analog signal. This board intends to read it with the ADC. The reading itself is in the TS part of the power board and connected to the AIN pin of UCC21732.

Based on the sensed voltage, the duty cycle (D) of the UCC21732 isolated output signal is calculated using the following relationship: D = -20 · V_AIN + 100

If filtered, the voltage at Tinv is calculated as: V_Tinv = VCC_GD · D/100 = 5V · (-20 · V_AIN + 100)/100

Company: e-Tech Racing	e-techracing.es		
Project: Inverter Control		Variant: [No Variations]	
Size: -	Page Contents: [5] Power_AFE.SchDoc		Version: 1.0
			Department: Powertrain
Author: David Redondo	dredondovinolo@gmail.com		Sheet * of *
Checked by: _			Date: 21/02/2024

Reverse direction



SC detection



Status LEDs



INPUTS/OUTPUTS



Company: e-Tech Racing	e-techracing.es	
Project: Inverter Control	Variant: [No Variations]	
Size: -	Page Contents: [6] Extras.SchDoc	Version: 1.0
		Department: Powertrain
Author: David Redondo	dredondovinolo@gmail.com	Sheet * of *
Checked by: _		Date: 21/02/2024


Left
Right
David Redondo
Feedback_L
Feedback_R
DCDC101
XTAL201
TVS301
ST-LINK
3V3
CLK
GND
DIO
RST
SWO
RUN
OK
FLT
PWR


Left
Right
STM32F777VI
Feedback_L
Feedback_R
David Redondo
RUN
OK
FLT
3V3
CLK
GND
DIO
RST
SWO
XT
XR



PWR_L
R509_L
F101
L101
R102
R103
D101
J1
TVS301
XTAL201
L301
XT
C406_R C405_R
R406_R R405_R
C409_R
Feedback_R
R507_L
R508_L
U501_L
C503_L
R503_L
R504_L
C501_L
R505_L
R506_L
C502_L
DCDC101
PWR
R101
D104
C202
C201
U301
U401_R
R501_L
R502_L
C403_L C401_L C402_L C404_L
R403_L R401_L R402_L R404_L
Left
U201
STM32F777VI
C306
C307
Right
R404_R R402_R R401_R R403_R
C404_R C402_R C401_R C403_R
C502_R
R506_R
R505_R
R502_R
R501_R
R606
R604
Q603
Q601
U202
Feedback_L
U401_L
C410_L
C409_L
R609
R607
D602
David Redondo
DIR
R202
R201
TVS1
USB
3V3
CLK
GND
DIO
RST
SWO
ST-LINK
C501_R
R504_R
R503_R
C503_R
U501_R
R508_R
R507_R
R405_L R406_L
C405_L C406_L
D603
D601
RUN
OK
FLT
F102
R509_R
PWR_R


Left
Right
STM32F777VI
David Redondo
RUN
OK
FLT
3V3
CLK
GND
DIO
RST
SWO
USB
PWR
XT
Feedback_L
Feedback_R
PWM2_R

Inverter Control



Bill Of Materials

Designator	Name	Quantity
C101, C105, C204, C207, C209, C212, C215, C218, C221, C307	885012207103	10
C102, C103, C106, C107, C110, C409_L, C409_R	10uF	7
C104, C203, C208, C211, C214, C217, C306, C407_L, C407_R, C410_L, C410_R, C501_L, C501_R, C502_L, C502_R, C503_L, C503_R	885012207098	17
C108, C109	885012107014	2
C201, C202	885012007052	2
C205, C210, C213, C216	885012107011	4
C206, C401_L, C401_R, C402_L, C402_R, C403_L, C403_R, C404_L, C404_R, C405_L, C405_R, C406_L, C406_R	885012207092	13
C219, C220	2.2uF	2
D101	824501261	1
D102	MBR0530	1
D104	150080YS75000	1
D601	150080RS75000	1
D602	150080GS75000	1
D603	150080BS75000	1
DCDC101	RPMB5.0-3.0	1
DIR	450405020524	1
F101, F102	0437001.WRA	2
Feedback_L, Feedback_R	1053101112	2
J1	105310-1108	1
L101, L102	47uH	2
L201	744764147	1
L301	DLW32SH510XF2	1
MP_L, MP_R	M3	2
PWR_L, PWR_R	61302621121	2
Q601, Q602, Q603	CPH3455-TL-H	3
R101, R401_L, R401_R, R403_L, R403_R, R405_L, R405_R, R502_L, R502_R	CR0805-FX-1000ELF	9
R102, R607, R608, R609	47kR	4
R103, R501_L, R501_R, R503_L, R503_R, R505_L, R505_R, R507_L, R507_R	CR0805-JW-472ELF	9
R201, R202, R203, R402_L, R402_R, R404_L, R404_R, R406_L, R406_R, R504_L, R504_R, R506_L, R506_R, R508_L, R508_R, R610	CR0805-JW-103ELF	16
R407_L, R407_R, R601, R602, R603, R604, R605, R606, R611	CR0805-JW-102ELF	9
R408_L, R408_R, R409_L, R409_R, R509_L, R509_R	CPF0805B15RE	6
ST-LINK	61300611121	1
TVS1	USBLC6-2P6	1
TVS301	Diode 4D	1
U101	LM1117IMP-3.3/NOPB	1
U201	STM32F777VIT6	1
U202	24AA024H-I/SN	1
U301	MCP2551-I/SN	1
U401_L, U401_R	LM339D	2
U501_L, U501_R	AD8479ARZ-RL	2
USB	629105136821	1
XTAL201	20MHz	1

Layer Stack Legend



Material	Layer	Thickness	Dielectric Material	Type	Gerber
	Top Overlay			Legend	GTO
Surface Material	Top Solder	0.010mm	Solder Resist	Solder Mask	GTS
CF-004	**TOP**	**0.035mm**		**Signal**	**GTL**
Prepreg		*0.100mm*	*PP-006*	*Dielectric*	
Prepreg		*0.100mm*	*PP-006*	*Dielectric*	
Copper	**GND**	**0.035mm**		**Signal**	**G1**
		1.040mm	*FR-4*	*Dielectric*	
Copper	**PWR**	**0.035mm**		**Signal**	**G2**
Prepreg		*0.100mm*	*PP-006*	*Dielectric*	
Prepreg		*0.100mm*	*PP-006*	*Dielectric*	
CF-004	**BOT**	**0.035mm**		**Signal**	**GBL**
Surface Material	Bottom Solder	0.010mm	Solder Resist	Solder Mask	GBS
	Bottom Overlay			Legend	GBO

Total thickness: 1.600mm