

# Nodes: A Basis for Implementing Linear Data Structures

## CMPT 145

## Copyright Notice

©2020 Michael C. Horsch

This document is provided as is for students currently registered in CMPT 145.

All rights reserved. This document shall not be posted to any website for any purpose without the express consent of the author.

# Learning Objectives

After studying this chapter, a student should be able to:

- To describe the concept and structure of a node.
- To explain the operations of the Node ADT.
- To employ Node ADT operations in Python programs.


# Motivation

- Python lists are very useful for programmers.
  - Easy for novices to learn.
  - Very practical for many applications.
- Python lists are based on **fixed length blocks of memory**.
  - You will study this idea in CMPT 214 (C/C++ arrays).
- It's educational to consider alternatives.
  - In CMPT 145 we study **node-chains** and **linked lists**.
- We study these ideas because:
  - Very good programming practice
  - Deepen your understanding of Python
  - Broaden your understanding of computer science

# Data Structure: Node

A node is a very simple object:

```
1 anode = node(1, None)
```



It stores 2 values only.


1. Any **data** value.
2. A **reference** to another node (or `None`)

The Node ADT is not built into Python. Use the module provided by CMPT 145.

# Nodes create chains of data values

Two nodes, linked together:

```
1 anode = node(1, None)
2 bnode = node(2, anode)
```



We use the second argument to refer to another node.

# Node ADT

- Purpose:
  - Building block for data sequences.
- Implementations:
  - Object with 2 attributes
    1. A **data** value
    2. A **reference** to another node (or None)
- Operations:
  - Create a node
  - Set the **data** value for a given node
  - Set the **reference** to the next node for a given node
  - Return the **data** value of a given node
  - Return the **reference** to the node of a given node

## Code Walk Through



# Python keyword arguments

- Normal function parameters are based on **position**.

```
1 def fun3(a, b, c):  
2     pass  
3 fun3(1,2,3)
```

- **keyword arguments** use the parameter name:

```
1 def fun2(a, b, c=0):  
2     pass  
3 fun2(1,2,c=3)
```

- The assignment in the parameter list establishes a default value

# Python keyword arguments

- You only need to give a value if you want something other than the default:

```
1 fun2(1,2,c=3)    # ignore the default value
2 fun2(1,2)        # use the default value
```


- Position based parameters must precede keyword arguments in the definition.

## Analogy: Nodes are freight cars

- A node object is like a freight car in a railroad train.
- Each node can contain some cargo (**data**)
  - The data can be any kind of value.
  - We will keep it simple in our examples.
- Each node points to a node that comes after it (**next**)
  - We must take care to use this attribute only for another node.

## Analogy: Node chains are trains

- A node chain is like a railroad train.
  - Each node is like a freight car.
- A node points to the next node in the chain.
  - By design, a node does not know what's in front of it.



- Each node can contain some cargo (**data**)
- A variable that knows the first node in a chain is called the anchor.
- The last node in the chain must have **None** stored as its **next** value.

## Common questions 1

- Can we create a chain that has a loop back to the beginning?

*This is useful in some applications, but confusing for beginners. We won't study them in CMPT 145.*

- Can we create a different kind of node that points backwards and forwards?

*This is useful in some applications, but confusing for beginners. We won't study them in CMPT 145.*

## Common questions 2

- Is this how Python lists work?  
*No. Python lists are based on fixed length blocks of memory. This is a design decision based on a compromise. Python lists are good at some things, but not the best for every application.*
- Why are we studying node chains?
  - Node chains are better than Python lists for some applications!
  - We need this idea for Chapters 16, 17, 20-23.
  - You will study more advanced ideas in CMPT 280.

# Example 1


Draw a diagram for the following code sequence:

```
1 x = N.node(5, None)
2
3 y = N.node(1, x)
4
5 z = N.node(8, y)
6
7 print(x.get_data())
8 print(z.get_next().get_data())
9 print(z.get_next().get_next().get_data())
```

You cannot do this reliably in your head. Draw a diagram.

## Example 2


Write the code to produce the following sequence:






## Example 3

Write the code to produce the following sequence:



## Example 4

Given the following sequence:




Write a print statement using the above chain that:

1. Uses the data in the chain to evaluate to 1
2. Uses the data in the chain to evaluate to 6
3. Uses the data in the chain to evaluate to 9

## Simple algorithms on Node records


Suppose the variable `first` is a reference to the first node in the sequence:




Use the Node ADT to:

1. Remove the 3 from the sequence
2. Add a new value 6 at the beginning of the sequence
3. Add a new value 7 at the end of the sequence


# Removing 3 from the sequence




# Removing 3 from the sequence




# Removing 3 from the sequence



# Removing 3 from the sequence




# Add 6 at the beginning







## Add 6 at the beginning




## Add 6 at the beginning




# Add 7 at the end




# Add 7 at the end



# Add 7 at the end



# Add 7 at the end



## Simple algorithms on Node records

- Nodes chains can have any number of nodes: 0, 1, 2, ...
- Many algorithms on node chains require a loop. e.g.,
  - Count the number of nodes in a node chain
  - Print the data values in the node chain
  - Does the node chain contain the data value 4?
  - Replace every occurrence of the value 4 with the value -4.
  - Add the data value to the chain after the value 4.
- Loops on node chains have a common pattern!

## Simple walking loop

This loop takes one step along the node chain, stopping at the end of the chain.

```
1 chain = ...  
2 walker = chain  
3 while walker is not None:  
4     # do something with walker  
5     walker = walker.get_next()
```

- We use a `walker` to step along the node chain
- If we change `chain` we are moving the anchor point!
- After the loop is over, `walker` has jumped of the end of the node chain
- This is useful when the algorithm works exclusively `walker`.



## Lookahead loop

This loop takes one step along the node chain, stopping on the last node in the chain:

```
1 chain = ...
2 walker = chain
3 while walker.get_next() is not None:
4     # do something with walker and walker.get_next()
5     walker = walker.get_next()
```

- After the loop is over, `walker` remains on the last node in the node chain.
- This is useful when the algorithm has to work on `walker`, and the node after it.

## Double-walker loop


This loop takes one step along the node chain, remembering the node in front of it.

```
1 chain = ...
2 walker = chain
3 previous = None
4 while walker is not None:
5     # do something with walker and previous
6     previous = walker
7     walker = walker.get_next()
```

- After the loop is over, `walker` remains on the last node in the node chain.
- This is useful when the algorithm has to work on `walker`, and the node before it.

## Simple algorithms on Node records

Suppose the variable `chain` is a reference to the first node in the sequence:



Use the Node ADT to:

1. Count the number of nodes in the node chain.
2. Display all numbers in the chain
3. Does the node chain contain the value 4?
4. Remove the 4 from the sequence
5. Change the list so that 5 follows 2 ("delete 1")

# The Node ADT

- A simple data structure, hidden behind an interface.
- Chaining nodes together creates a sequence.
- Stacks and queues can be implemented using nodes.
- Nodes are seriously valuable!