

S2S-10: Migration Scripts

Series: S2S — SaaS to SaaS Migration | **Notebook:** 10 | **Created:** April 2026 | **Last Updated:** 09/28/2026

Overview

Reusable scripts for SaaS-to-SaaS configuration export. They download Monaco, export the source tenant's configuration with a short-lived read-only token, and leave a timestamped export folder that you review, commit to Git, and **deploy directly to the target with `monaco deploy`**. Both Bash (macOS/Linux/WSL) and PowerShell (Windows) versions are provided.

Why scripts instead of raw `monaco download`? They handle platform detection, Monaco binary download, checksum verification, temporary token creation and revocation, and the export in a single command — and they leave the Monaco binary in place for the deploy step.

Table of Contents

1. [Why Monaco Direct Deploy](#)
 2. [Monaco Configuration Export \(Bash\)](#)
 3. [Monaco Configuration Export \(PowerShell\)](#)
 4. [Usage Notes](#)
 5. [Post-Export Workflow](#)
-

Prerequisites

Requirement	Details
API Token	Token with <code>apiTokens.write</code> scope on the source tenant — the scripts use it to create, then revoke, a short-lived export token
Shell (Option A)	Bash (macOS, Linux, or WSL) with <code>curl</code> , <code>jq</code> , <code>shasum</code>
Shell (Option B)	PowerShell 5.1+ on Windows 10/11
Network	HTTPS access to <code>github.com</code> (Monaco download), the source tenant URL, and — for the deploy — the target tenant URL
Target credentials	For the deploy: a target API token for classic configuration and settings, plus a platform token or OAuth client for platform configuration (documents, automations, buckets, segments, SLOs, OpenPipeline)

1. Why Monaco Direct Deploy

This notebook does not package exports for the SaaS Upgrade Assistant (SUA), because that path is not documented for a SaaS source. The SUA documentation describes a Managed source: *"SaaS Upgrade Assistant imports your Dynatrace Managed environment configuration."* No SaaS-to-SaaS import is described there, so this series does not rely on it.

The supported building blocks for SaaS → SaaS are the configuration-as-code tools themselves:

Tool	Export from the source	Import into the target
Monaco (this notebook)	<code>monaco download</code>	<code>monaco deploy <manifest> --environment <target></code>
Terraform (IAM, and teams already on Terraform)	<code>terraform-provider-dynatrace -export</code>	<code>terraform apply</code> with target credentials (see S2S-06 §4 for workflows and AUTOM for the provider)

Sources: [SaaS Upgrade Assistant \(DT docs\)](#) — "SaaS Upgrade Assistant imports your Dynatrace Managed environment configuration", [Monaco CLI commands \(DT docs\)](#).

2. Monaco Configuration Export (Bash)

Downloads Monaco, exports all configuration from the source tenant, and stages it in a timestamped folder for `monaco deploy`.

Deprecation — Dynatrace API 1.348 (pre-release; staged rollout planned from 09/22/2026). The API 1.348 changelog marks the whole `/apiTokens` endpoint family deprecated — "*The following endpoints are deprecated*", covering `POST /apiTokens`, `POST /apiTokens/lookup` and the per-token `GET / PUT / DELETE`. No successor is named. Deprecated endpoints keep working during the deprecation period, so both scripts below (which mint a temporary export token with `POST /api/v2/apiTokens`) remain the working path — re-check the [API 1.348 changelog \(DT docs\)](#) at GA before building new automation on that endpoint. Separately, once an environment opts into **Phase 3** of the upgrade to Latest Dynatrace, "*classic API token creation is disabled; all new integrations must use platform tokens*" ([Best practices for upgrading App Observability API endpoints \(DT docs\)](#)) — check your environment's upgrade phase before running these scripts, since each one mints a classic token.

Usage:

```
export ENV_TOKEN="dt0c01.XXXX..."
./monaco-export-migration.sh &lt;source-tenant-id>

# Example
./monaco-export-migration.sh abc12345
```

Script:

```

#!/bin/bash
#
# Monaco Configuration Export for SaaS-to-SaaS migration
# Produces a timestamped export folder for review and `monaco deploy` to the
# target.
#
# Usage: ENV_TOKEN=<api-token> ./monaco-export-migration.sh
# <tenantId>

set -euo pipefail

MONACO_VERSION="2.30.0" # pinned; check the releases page before reuse

# --- Argument validation ---
if [ $# -ne 1 ]; then
    echo "Usage: $0 <tenantId>"
    echo ""
    echo "Example: ENV_TOKEN=\$MY_TOKEN $0 abc12345"
    exit 1
fi

if [ -z "${ENV_TOKEN:-}" ]; then
    echo "Error: ENV_TOKEN environment variable is not set."
    echo "Create a token with apiTokens.write scope at:"
    echo "  https://$1.live.dynatrace.com/#settings/integration/apikeys"
    exit 1
fi

tenantId="$1"
echo "=== Monaco Export v${MONACO_VERSION} ==="
echo "Tenant: ${tenantId}"
echo ""

# --- Detect platform ---
OS=$(uname -s)
ARCH=$(uname -m)

case "${OS}-${ARCH}" in
    Darwin-arm64) platform="darwin-arm64" ;;
    Darwin-x86_64) platform="darwin-amd64" ;;
    Linux-x86_64) platform="linux-amd64" ;;
    Linux-aarch64) platform="linux-arm64" ;;
    Linux-i386) platform="linux-386" ;;
    *)
        echo "Error: Unsupported platform ${OS}-${ARCH}"
        exit 1
        ;;

```

```

esac

echo "Platform: ${platform}"

# --- Download Monaco ---
binary_url="https://github.com/Dynatrace/dynatrace-configuration-as-code/releases/download/v${MONACO_VERSION}/monaco-${platform}"
checksum_url="${binary_url}.sha256"

echo "Downloading Monaco v${MONACO_VERSION}..."
curl -sL -o "monaco-${platform}" "${binary_url}"
curl -sL -o monaco_checksum "${checksum_url}"

echo "Verifying checksum..."
if shasum --quiet -c monaco_checksum 2>/dev/null; then
    echo "Checksum verified"
else
    echo "Checksum verification failed"
    rm -f "monaco-${platform}" monaco_checksum
    exit 1
fi

mv "monaco-${platform}" monaco
chmod +x monaco
echo "Monaco v${MONACO_VERSION} ready"
echo ""

# --- Revoke the export token on exit (success or failure) ---
MONACO_TOKEN_ID=""
revoke_export_token() {
    if [ -n "${MONACO_TOKEN_ID}" ] && [ "${MONACO_TOKEN_ID}" != "null" ]; then
        echo "Revoking temporary export token..."
        curl -s -o /dev/null -w "DELETE apiTokens -> HTTP %{http_code}\n" \
-X DELETE \

"https://${tenantId}.live.dynatrace.com/api/v2/apiTokens/${MONACO_TOKEN_ID}" \
-H "Authorization: Api-Token ${ENV_TOKEN}" \
|| echo "Revoke failed: delete token ${MONACO_TOKEN_ID} manually"
    fi
}
trap revoke_export_token EXIT

# --- Create short-lived export token (read scopes only, expires in 24 h) ---
echo "Creating temporary export token..."
expiry=$(date -u -v+1d +%Y-%m-%dT%H:%M:%S 2>/dev/null || date -u -d '+1 day' +%Y-%m-%dT%H:%M:%S)
token_body=$(jq -n --arg exp "${expiry}" '{

```

```

    name: "s2s-monaco-export-temp",
    expirationDate: $exp,
    scopes: [
        "attacks.read",
        "entities.read",
        "extensionConfigurations.read",
        "extensionEnvironment.read",
        "extensions.read",
        "geographicRegions.read",
        "javaScriptMappingFiles.read",
        "networkZones.read",
        "settings.read",
        "slo.read",
        "syntheticExecutions.read",
        "syntheticLocations.read",
        "DataExport",
        "ReadConfig",
        "ReadSyntheticData"
    ]
}'')

token_response=$(curl -s -X POST
"https://${tenantId}.live.dynatrace.com/api/v2/apiTokens" \
-H "accept: application/json; charset=utf-8" \
-H "Content-Type: application/json; charset=utf-8" \
-H "Authorization: Api-Token ${ENV_TOKEN}" \
-d "${token_body}")
MONACO_TOKEN=$(echo "${token_response}" | jq -r '.token // empty')
MONACO_TOKEN_ID=$(echo "${token_response}" | jq -r '.id // empty')

if [ -z "${MONACO_TOKEN}" ]; then
    echo "  Failed to create export token. Check ENV_TOKEN permissions
(apiTokens.write)."
    rm -f monaco monaco_checksum
    exit 1
fi
export MONACO_TOKEN
echo "  Export token created (expires ${expiry} UTC)"
echo ""

# --- Create manifest ---
cat > manifest.yaml <<<EOF
manifestVersion: 1.0

projects:
- name: saas
  path: saas/${tenantId}

```

```

environmentGroups:
- name: saas
  environments:
  - name: ${tenantId}
    url:
      value: https://${tenantId}.live.dynatrace.com
    auth:
      token:
        name: MONACO_TOKEN
EOF

# --- Run Monaco download ---
echo "Running Monaco download..."
echo "  This may take several minutes depending on configuration volume."
echo ""
./monaco download --environment "${tenantId}" --output-folder "${tenantId}"
echo ""

# The export token is no longer needed: revoke it now (the EXIT trap covers
failures)
revoke_export_token
MONACO_TOKEN_ID=""
unset MONACO_TOKEN
echo ""

# --- Stage the export for review and deploy ---
datetime=$(date +"%Y-%m-%d_%H-%M-%S")
export_dir="export-${tenantId}-${datetime}"
mv "${tenantId}" "${export_dir}"

# --- Summary ---
echo ""
echo "=== Export Summary ==="
echo "Tenant:    ${tenantId}"
echo "Monaco:    v${MONACO_VERSION}"
echo "Output:    ${export_dir}/ (manifest.yaml + project/)"
echo ""

config_count=$(find "${export_dir}" -name "*.json" -o -name "*.yaml"
2>/dev/null | wc -l | tr -d ' ')
echo "Configs exported: ~${config_count} files"
echo ""

echo "Next steps:"
echo "  1. Commit ${export_dir}/ to Git"
echo "  2. Add the target environment to ${export_dir}/manifest.yaml (S2S-05,
section 2)"
echo "  3. Remap entity IDs (S2S-05, section 4)"

```

```
echo " 4. ./monaco deploy ${export_dir}/manifest.yaml --environment target-tenant --dry-run"
echo " 5. ./monaco deploy ${export_dir}/manifest.yaml --environment target-tenant"
echo ""

# --- Cleanup (the monaco binary is kept for the deploy step) ---
rm -f monaco_checksum manifest.yaml

echo "Done."
```

3. Monaco Configuration Export (PowerShell)

Windows equivalent of the Bash script above. Produces the same timestamped export folder for `monaco deploy`.

Usage:

```
$env:ENV_TOKEN = "dt0c01.XXXX..."
.\Monaco-Export-Migration.ps1 -TenantId abc12345
```

Script:

```

#Requires -Version 5.1
<#
.SYNOPSIS
    Monaco Configuration Export for SaaS-to-SaaS migration
.DESCRIPTION
    Downloads Monaco, exports all configuration from a source tenant,
    and stages the result in a timestamped folder for monaco deploy.
.PARAMETER TenantId
    The Dynatrace tenant identifier (e.g., abc12345)
.EXAMPLE
    $env:ENV_TOKEN = "dt0c01.XXXX..."
    .\Monaco-Export-Migration.ps1 -TenantId abc12345
#>
param(
    [Parameter(Mandatory)]
    [string]$TenantId
)

$ErrorActionPreference = "Stop"
$MonacoVersion = "2.30.0" # pinned; check the releases page before reuse

# --- Validate token ---
if (-not $env:ENV_TOKEN) {
    Write-Error "ENV_TOKEN environment variable is not set.`nCreate a token
with apiTokens.write scope at:`n
https://$TenantId.live.dynatrace.com/#settings/integration/apikeys"
}

Write-Host "=== Monaco Export v$MonacoVersion ==="
Write-Host "Tenant: $TenantId"
Write-Host ""

# --- Download Monaco (Windows amd64) ---
$platform = "windows-amd64"
$binaryUrl = "https://github.com/Dynatrace/dynatrace-configuration-as-
code/releases/download/v$MonacoVersion/monaco-$platform.exe"
$checksumUrl = "$binaryUrl.sha256"

Write-Host "Downloading Monaco v$MonacoVersion..."
Invoke-WebRequest -Uri $binaryUrl -OutFile "monaco.exe" -UseBasicParsing
Invoke-WebRequest -Uri $checksumUrl -OutFile "monaco_checksum" -
UseBasicParsing

Write-Host "Verifying checksum..."
$expectedHash = (Get-Content monaco_checksum -Raw).Split()[0].Trim()
$actualHash = (Get-FileHash -Algorithm SHA256 monaco.exe).Hash.ToLower()
if ($actualHash -ne $expectedHash) {

```

```

        Remove-Item -Force monaco.exe, monaco_checksum
        Write-Error "Checksum verification failed"
    }
    Write-Host "    Checksum verified"
    Write-Host "    Monaco v$MonacoVersion ready"
    Write-Host ""

    # --- Create short-lived export token (read scopes only, expires in 24 h) ---
    Write-Host "Creating temporary export token..."
    $expiry = (Get-Date).ToUniversalTime().AddDays(1).ToString("yyyy-MM-ddTHH:mm:ss")
    $tokenBody = @{
        name          = "s2s-monaco-export-temp"
        expirationDate = $expiry
        scopes        = @(
            "attacks.read", "entities.read", "extensionConfigurations.read",
            "extensionEnvironment.read", "extensions.read",
            "geographicRegions.read",
            "javascriptMappingFiles.read", "networkZones.read", "settings.read",
            "slo.read", "syntheticExecutions.read", "syntheticLocations.read",
            "DataExport", "ReadConfig", "ReadSyntheticData"
        )
    } | ConvertTo-Json

    $headers = @{
        "Authorization" = "Api-Token $($env:ENV_TOKEN)"
        "Content-Type"  = "application/json; charset=utf-8"
    }

    $response = Invoke-RestMethod `
        -Uri "https://$TenantId.live.dynatrace.com/api/v2/apiTokens" `
        -Method Post -Headers $headers -Body $tokenBody

    if (-not $response.token) {
        Remove-Item -Force monaco.exe, monaco_checksum -ErrorAction
        SilentlyContinue
        Write-Error "Failed to create export token. Check ENV_TOKEN permissions."
    }
    $env:MONACO_TOKEN = $response.token
    $tokenId = $response.id
    Write-Host "    Export token created (expires $expiry UTC)"
    Write-Host ""

    # --- Create manifest ---
    @"
manifestVersion: 1.0

projects:

```

```

- name: saas
  path: saas/$TenantId

environmentGroups:
- name: saas
  environments:
- name: $TenantId
  url:
    value: https://$TenantId.live.dynatrace.com
  auth:
    token:
      name: MONACO_TOKEN
"@ | Set-Content -Path "manifest.yaml" -Encoding UTF8

# --- Run Monaco download ---
Write-Host "Running Monaco download..."
Write-Host "  This may take several minutes depending on configuration
volume."
Write-Host ""
.\monaco.exe download --environment $TenantId --output-folder $TenantId
$downloadExit = $LASTEXITCODE
Write-Host ""

# --- Revoke the export token (also when the download failed) ---
Write-Host "Revoking temporary export token..."
try {
  Invoke-RestMethod `
    -Uri "https://$TenantId.live.dynatrace.com/api/v2/apiTokens/$tokenId"
    `
    -Method Delete -Headers $headers | Out-Null
  Write-Host "  Export token revoked"
} catch {
  Write-Warning "Revoke failed: delete token $tokenId manually (it expires
$expiry UTC regardless)"
}
Remove-Item Env:\MONACO_TOKEN -ErrorAction SilentlyContinue
if ($downloadExit -ne 0) {
  Write-Error "monaco download failed with exit code $downloadExit"
}
Write-Host ""

# --- Stage the export for review and deploy ---
$datetime = Get-Date -Format "yyyy-MM-dd_HH-mm-ss"
$exportDir = "export-$TenantId-$datetime"
Rename-Item -Path $TenantId -NewName $exportDir

# --- Summary ---
Write-Host ""

```

```

Write-Host "=== Export Summary ==="
Write-Host "Tenant:    $TenantId"
Write-Host "Monaco:     v$MonacoVersion"
Write-Host "Output:     $exportDir\ (manifest.yaml + project\)"
Write-Host ""

$configCount = (Get-ChildItem -Path $exportDir -Recurse -Include *.json,
*.yaml).Count
Write-Host "Configs exported: ~$configCount files"
Write-Host ""

Write-Host "Next steps:"
Write-Host "  1. Commit $exportDir\ to Git"
Write-Host "  2. Add the target environment to $exportDir\manifest.yaml (S2S-05, section 2)"
Write-Host "  3. Remap entity IDs (S2S-05, section 4)"
Write-Host "  4. .\monaco.exe deploy $exportDir\manifest.yaml --environment target-tenant --dry-run"
Write-Host "  5. .\monaco.exe deploy $exportDir\manifest.yaml --environment target-tenant"
Write-Host ""

# --- Cleanup (monaco.exe is kept for the deploy step) ---
Remove-Item -Force monaco_checksum, manifest.yaml -ErrorAction SilentlyContinue

Write-Host "Done."

```

4. Usage Notes

Bash (macOS / Linux / WSL)

- Save the Bash script to a file (e.g., `monaco-export-migration.sh`) and run `chmod +x monaco-export-migration.sh`
- Requires `curl`, `jq` and `shasum`

PowerShell (Windows)

- Save the PowerShell script to a file (e.g., `Monaco-Export-Migration.ps1`)
- If execution policy blocks the script, run: `Set-ExecutionPolicy -Scope Process -ExecutionPolicy Bypass`

Both Scripts

- The script downloads Monaco automatically — no pre-installation required — and keeps the binary for the deploy step
- A short-lived export token (`s2s-monaco-export-temp`) is created with read scopes only, expires after 24 hours, and is revoked as soon as the download finishes — also when it fails
- The export token is a classic API token, so the download covers classic configuration and Settings 2.0. Platform configuration (documents, automations, buckets, segments, SLOs, OpenPipeline) needs a platform token or OAuth client — Monaco's `--platform-token` flag takes the *"Platform token environment variable"*, and `--oauth-client-id` / `--oauth-client-secret` name an OAuth client's variables (**S2S-04** §3)
- Monaco is pinned to v2.30.0 (released 09/23/2026); check the [releases page](#) before reuse and bump `MONACO_VERSION` / `$MonacoVersion`
- Output is a folder `export-<tenant>-<timestamp>/` holding the Monaco manifest and the `project/` configuration

Sources: [monaco download flags](#), [v2.30.0](#) (Dynatrace GitHub).

Multi-Source Consolidation

When consolidating multiple source tenants into a single target, run the script once per source tenant:

```
# Source 1
ENV_TOKEN=$SOURCE1_TOKEN ./monaco-export-migration.sh tenant-id-1

# Source 2
ENV_TOKEN=$SOURCE2_TOKEN ./monaco-export-migration.sh tenant-id-2
```

Deploy Source 1 first, validate, then deploy Source 2. Sequential migration isolates issues to a single source at a time. See **S2S-02** for the multi-source consolidation pattern.

5. Post-Export Workflow

After running the export script:

Step	Action	Reference
1	Commit the export folder to Git	The reviewed baseline for everything that follows
2	Add the target environment to the export's <code>manifest.yaml</code>	S2S-05 §2: Monaco Deploy Workflow
3	Audit for entity ID references	Search exported config for <code>HOST-</code> , <code>SERVICE-</code> , <code>PROCESS_GROUP-</code> patterns
4	Remap entity IDs to tag-, segment- or dimension-based filters	S2S-05 §4: Entity ID Remapping
5	<code>monaco deploy <manifest> --environment <target> --dry-run</code>	Checks structure and references only — it does not contact the target
6	<code>monaco deploy <manifest> --environment <target></code> (per project, for phased deployment)	S2S-05 §1: Configuration Deployment Order
7	Validate data flow after each wave	S2S-05 §8: Wave Execution and Validation

Deploy to the Target

```
export DT_TARGET_URL="https://&lt;target-env-id&gt;.live.dynatrace.com"
export DT_TARGET_TOKEN="dt0c01.xxx..." # the manifest names this variable;
it never holds the token

./monaco deploy export-&lt;tenant&gt;-&lt;timestamp&gt;/manifest.yaml --
environment target-tenant --dry-run
./monaco deploy export-&lt;tenant&gt;-&lt;timestamp&gt;/manifest.yaml --
environment target-tenant
```

A clean dry-run is not a guarantee: Monaco's flag help says a dry-run *"can not validate the content of JSON payloads. After a successful dry-run, deployments may still fail with Dynatrace API errors if the content of JSONs is not valid."* Deploy to a non-production target first.

Sources: [monaco deploy flags, v2.30.0 \(Dynatrace GitHub\)](#).

When NOT to Use These Scripts

Scenario	Use Instead
You only need specific config types	<code>monaco download --only-settings , --settings-schema <schema> or --api <api></code>
You want ongoing config management	Terraform with state management
The source is a Managed environment	The SaaS Upgrade Assistant (see the M2S series)
You need IAM migration	Terraform — Monaco cannot manage IAM

Script vs. Manual Monaco

Feature	Script	Manual <code>monaco download</code>
Monaco installation	Automatic (downloads + verifies checksum)	Manual pre-installation required
Export token	Auto-created with read scopes, 24 h expiry, revoked after download	Manual token creation and revocation
Output	Timestamped export folder, ready for <code>monaco deploy</code>	Whatever <code>--output-folder</code> you choose
Cleanup	Automatic (removes temp files, keeps the binary)	Manual cleanup
Cross-platform	Bash + PowerShell versions	Single platform

This notebook was AI-generated from community-submitted and publicly available sources. This notebook series is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.