

OPMIG-06: Processing, Parsing & Transformation

Series: OPMIG — OpenPipeline Migration | **Notebook:** 6 of 10 | **Created:** December 2025 | **Last Updated:** 09/28/2026

Table of Contents

1. [DQL Processor Commands](#)
 2. [Dynatrace Pattern Language \(DPL\)](#)
 3. [Real-World Log Format Examples](#) ★ NEW
 4. [Common Parsing Patterns](#)
 5. [Data Transformation Examples](#)
 6. [Parsing Pattern Library](#) ★ NEW
 7. [ELK/Logstash Migration Patterns](#) ★ NEW
 8. [Technology Bundle Parsers](#)
 9. [Drop Processors](#)
 10. [Advanced Processing Patterns](#)
 11. [Validating Your Processing](#)
 12. [DPL Architect Tool](#)
 13. [Complete Processing Pipeline Example](#)
-

Learning Objectives

By completing this notebook, you will:

1. Master Dynatrace Pattern Language (DPL) for log parsing
2. Configure DQL processors for data transformation

3. ★ **NEW:** Parse Apache, Nginx, and JSON logs with production-ready patterns
4. ★ **NEW:** Migrate from ELK/Logstash (Grok to DPL conversion)
5. ★ **NEW:** Use the complete Parsing Pattern Library (timestamps, stack traces, HTTP)
6. Implement drop processors for cost optimization
7. Validate parsing success rates and troubleshoot failures

Prerequisites

Requirement	Details
Dynatrace Environment	Dynatrace SaaS with Grail and OpenPipeline access — Managed is not covered by this series
Permissions	<code>settings:read</code> and <code>settings:write</code> (OpenPipeline configuration)
API Access	<code>logs.read</code> token scope
DPL Architect	Access to <code>https://{env}.apps.dynatrace.com/ui/apps/dynatrace.dpl.architect</code>
Knowledge	OPMIG-01 through OPMIG-05; basic regex or pattern matching familiarity

Processing Stage Overview

Masking, dropping, parsing and transformation are processors in the **Processing** stage — the first stage of every pipeline. The remaining stages (Smartscape node and edge, Permission, Product and Cost allocation, Bucket assignment, Metric extraction, Davis, Data extraction) follow in a fixed order that you cannot change; OPMIG-02 § *Understanding Processing Order* has the full ten-stage table. This notebook covers the Processing stage; OPMIG-07 covers extraction.

Processor Execution Order

Within the Processing stage, processors execute in the order they're defined, and *"each processor output becomes the input for the next one."* You can reorder them in the UI.

 **Best Practice:** Order processors logically — mask first, drop second, then parse, then enrich with computed fields based on parsed values.

Sources: [Processing in OpenPipeline \(DT docs\)](#) — *"The sequence of stages is fixed for all pipelines and cannot be modified."*

DQL Processor Commands

The DQL processor supports a subset of DQL commands for data transformation.

Available Commands

Command	Purpose	Example
<code>fieldsAdd</code>	Add new fields	<code>fieldsAdd env = "production"</code>
<code>fieldsRemove</code>	Remove fields	<code>fieldsRemove sensitive_field</code>
<code>fieldsRename</code>	Rename fields	<code>fieldsRename old = new_name</code>
<code>parse</code>	Extract with DPL	<code>parse content, "INT:count"</code>

fieldsAdd Examples

Static Values

```
fieldsAdd environment = "production"
| fieldsAdd application = "checkout-service"
| fieldsAdd team = "platform-engineering"
```

Conditional Values (if/else)

```
fieldsAdd severity = if(loglevel == "ERROR", "critical",
                        else: if(loglevel == "WARN", "warning",
                                else: "info"))
```

Computed Values

```
fieldsAdd message_length = stringLength(content)
| fieldsAdd short_host = substring(host.name, from: 0, to: 15)
| fieldsAdd is_error = loglevel == "ERROR"
```

String Operations

```
fieldsAdd normalized_status = lower(status)
| fieldsAdd log_prefix = substring(content, from: 0, to: 50)
| fieldsAdd clean_message = trim(content)
```

Coalesce (First Non-Null)

```
fieldsAdd effective_level = coalesce(loglevel, status, "UNKNOWN")
```

fieldsRemove Examples

```
// Remove a single field
fieldsRemove internal_id
```

```
// Remove multiple fields in one command
fieldsRemove temp_field, debug_info, internal_state
```

fieldsRename Examples

```
// Standardize field names
fieldsRename user_id = userId
| fieldsRename request_id = requestId
| fieldsRename transaction_id = transactionId
```

Dynatrace Pattern Language (DPL)

DPL is a powerful pattern matching language for extracting structured data from text.

Core Matchers

Matcher	Description	Matches
INT	Integer	42 , -17 , 0
LONG	Long integer	1234567890123
DOUBLE	Decimal	3.14 , -0.5 , 1.0
IPADDR	IP address	192.168.1.1 , ::1
IPV4ADDR	IPv4 only	10.0.0.1
IPV6ADDR	IPv6 only	2001:db8::1
LD	Line data (to delimiter)	Any text until next match
DATA	Greedy match	Everything remaining
SPACE	Whitespace	Spaces, tabs
NSPACE	Non-whitespace	Word-like content
WORD	Word chars	hello , user123
JSON	JSON object	{"key": "value"}
EOL	End of line	Line terminator

Pattern Syntax Elements

Syntax	Meaning	Example
MATCHER:field	Extract to named field	INT:count
MATCHER	Match but don't extract	SPACE
MATCHER?	Optional match	(':' INT:port)?
'literal'	Match exact text	'error_code='
(a\\ b)	Alternatives	('user='\\ 'userId=')
MATCHER{n,m}	Quantifier	WORD{1,3}

Quantifier caveat: `{n,m}` is not universal. `INT` accepts only `*` and `+` — `INT{3}` is rejected. For fixed-width digit runs use a character class: `[0-9]{3}`.

Basic Parse Examples

```
// Extract user ID after "user="
parse content, "'user=' LD:user_id"

// Extract error code (integer)
parse content, "'error_code=' INT:error_code"

// Extract IP and port
parse content, "IPADDR:client_ip ':' INT:port"

// Extract JSON payload
parse content, "LD JSON:payload"
```

Real-World Log Format Examples NEW

Production-ready DPL patterns for the most common log formats.

Apache Access Logs (Common Log Format)

Sample: `192.168.1.100 - frank [12/Dec/2024:10:30:45 +0000] "GET /api/users HTTP/1.1" 200 1234`

```
parse content, """
  IPADDR:client_ip SPACE '-' SPACE LD:user SPACE
  '[' TIMESTAMP('dd/MMM/yyyy:HH:mm:ss Z'):log_time ']' SPACE
  '"' LD:method SPACE LD:request_path SPACE LD:protocol '"' SPACE
  INT:status_code SPACE INT:response_bytes
  """
```

Extracted: `client_ip`, `user`, `log_time`, `method`, `request_path`, `protocol`, `status_code`, `response_bytes`

Nginx (with Response Time)

Sample: 192.168.1.50 - - [12/Dec/2024:10:30:45 +0000] "POST /api/checkout HTTP/1.1" 201 456 "-" "Mozilla/5.0" "0.342"

```
parse content, ""
  IPADDR:client_ip SPACE '-' SPACE '-' SPACE
  '[' TIMESTAMP('dd/MMM/yyyy:HH:mm:ss Z'):log_time ']' SPACE
  ''' LD:method SPACE LD:request_path SPACE LD:protocol ''' SPACE
  INT:status_code SPACE INT:response_bytes SPACE
  ''' LD:referrer ''' SPACE ''' LD:user_agent ''' SPACE
  ''' DOUBLE:response_time_sec '''
""
| fieldsAdd response_time_ms = toLong(response_time_sec * 1000)
```

JSON Application Logs

Sample: {"timestamp":"2024-12-12T10:30:45.123Z","level":"ERROR","service":"payment-api","message":"Payment gateway timeout"}

Option 1: Use Technology Parser (Recommended)

- Add **Technology** processor → Select **JSON** parser
- All fields automatically flattened

Option 2: DQL Parsing

```
parse content, "JSON:log_data"
| fieldsAdd service = log_data[service]
| fieldsAdd message = log_data[message]
| fieldsAdd level = log_data[level]
```

Syslog (RFC 3164)

Sample: <34>Dec 12 10:30:45 webserver sshd[1234]: Failed password for admin from 192.168.1.100

```

parse content, ""
  '&lt;' INT:priority '&gt;';
  TIMESTAMP('MMM dd HH:mm:ss'):log_time SPACE
  LD:hostname SPACE LD:app_name '[' INT:pid ']:' SPACE
  DATA:message
""
| fieldsAdd facility = toLong(priority / 8)
| fieldsAdd severity = toLong(priority % 8)

```

Java Application Logs (Log4j)

Sample: 2024-12-12 10:30:45,123 [http-nio-8080-exec-5] ERROR com.example.Service
- Payment failed

```

parse content, ""
  TIMESTAMP('yyyy-MM-dd HH:mm:ss,SSS'):log_timestamp SPACE
  '[' LD:thread ']' SPACE
  LD:level SPACE LD:logger SPACE '-' SPACE
  DATA:message
""

```

Stack Trace Extraction:

```

parse content, "LD:exception_class ':' SPACE LD:exception_message EOL"
| parse content, "'at ' LD:error_location '(' LD:file ':' INT:line_number ')"

```

Kubernetes / Container Logs

Sample: 2024-12-12T10:30:45.123456789Z stdout F {"level":"info","msg":"Request processed"}

The `T` separator is written as a plain letter inside `TIMESTAMP('...')` — a quoted `\'T\'` is rejected (*Named pattern element 'T' is not valid*). The parsed value keeps millisecond precision.

```
parse content, """
    TIMESTAMP('yyyy-MM-ddTHH:mm:ss.SSSSSSSSZ'):k8s_timestamp SPACE
    LD:stream SPACE LD:log_tag SPACE
    JSON:log_payload
    """
| fieldsAdd level = log_payload[level]
| fieldsAdd msg = log_payload[msg]
```

Common Parsing Patterns

Apache/Nginx Access Logs

Sample log:

```
192.168.1.100 - - [12/Dec/2024:10:30:45 +0000] "GET /api/users HTTP/1.1" 200
1234
```

DPL Pattern:

```
parse content, "IPADDR:client_ip SPACE '-' SPACE LD:user SPACE '[' LD:log_time
']' SPACE '\"' LD:method SPACE LD:path SPACE LD:protocol '\"' SPACE
INT:status_code SPACE INT:bytes"
```

Key-Value Logs

Sample log:

```
userId=12345, action=login, status=success, duration=150ms
```

DPL Patterns:

```
// Extract each key-value pair
parse content, "'userId=' INT:user_id"
parse content, "'action=' LD:action ','"
parse content, "'status=' LD:status ','"
parse content, "'duration=' INT:duration_ms 'ms'"
```

Flexible User ID Extraction

Sample logs with varying formats:

```
Processing request for user=john123
User userId=john123 authenticated
Request from user_id=john123 received
```

DPL Pattern (alternatives):

```
parse content, "('user='|'userId='|'user_id=') LD:user_id"
```

Timestamp Parsing

DPL with timestamp format:

```
parse content, "TIMESTAMP('yyyy-MM-dd HH:mm:ss'):log_timestamp"
parse content, "TIMESTAMP('dd/MMM/yyyy:HH:mm:ss Z'):apache_time"
```

Optional Fields

Sample log:

```
Request to server:8080 completed
Request to server completed
```

DPL Pattern (optional port):

```
parse content, "'Request to ' LD:server (':' INT:port)? ' completed'"
```

Stack Trace Extraction

DPL Pattern:

```
parse content, "LD:exception_class ':' LD:exception_message"
```

Data Transformation Examples

Example 1: Parse and Enrich Application Logs

Input:

```
{"content": "[2024-12-12T10:30:45] ERROR PaymentService - Payment failed for  
orderId=12345, amount=99.99"}
```

Processor 1: Parse log structure

```
parse content, '[' TIMESTAMP('yyyy-MM-ddTHH:mm:ss'):log_time ']' SPACE  
LD:level SPACE LD:service ' - ' DATA:message"
```

Processor 2: Extract payment details

```
parse content, "'orderId=' INT:order_id ','"  
| parse content, "'amount=' DOUBLE:amount"
```

Processor 3: Add computed fields

```
fieldsAdd severity = if(level == "ERROR", "critical", else: "normal")  
| fieldsAdd application_tier = "payment"
```

Example 2: JSON Log Processing

Input:

```
{"content": "{\"level\":\"info\",\"msg\":\"Request  
processed\",\"duration_ms\":150}"}
```

Processor: Parse JSON and flatten

```
parse content, "JSON:json_data"
```

Using a Technology Parser (JSON) is often easier for JSON logs.

Example 3: Multi-Format Log Normalization

Processor: Normalize different log level formats

```
fieldsAdd normalized_level = if(contains(content, "ERROR") OR
contains(content, "error"), "ERROR",
    else: if(contains(content, "WARN") OR
contains(content, "warn"), "WARN",
    else: if(contains(content, "INFO") OR
contains(content, "info"), "INFO",
    else: if(contains(content, "DEBUG") OR
contains(content, "debug"), "DEBUG",
    else: "UNKNOWN"))))
```

Parsing Pattern Library ★ NEW

Timestamp Patterns (10+ Formats)

Format	Example	DPL
ISO 8601	2024-12-12T10:30:45Z	<code>TIMESTAMP('yyyy-MM-ddTHH:mm:ssZ')</code>
ISO + MS	2024-12-12T10:30:45.123Z	<code>TIMESTAMP('yyyy-MM-ddTHH:mm:ss.SSSZ')</code>
Apache	12/Dec/2024:10:30:45 +0000	<code>TIMESTAMP('dd/MMM/yyyy:HH:mm:ss Z')</code>
Syslog	Dec 12 10:30:45	<code>TIMESTAMP('MMM dd HH:mm:ss')</code>
Java	2024-12-12 10:30:45,123	<code>TIMESTAMP('yyyy-MM-dd HH:mm:ss,SSS')</code>
MySQL	2024-12-12 10:30:45	<code>TIMESTAMP('yyyy-MM-dd HH:mm:ss')</code>
Unix Epoch	1702380645	<code>LONG:epoch → toTimestamp(epoch * 1000)</code>

HTTP Request Patterns

```
// Full request line (a literal " inside the DQL string is escaped as \")
parse content, "'\" LD:method SPACE LD:path SPACE LD:protocol '\""

// Separate path and query
parse content, "'\" LD:method SPACE LD:path ('?' LD:query)? SPACE LD:protocol
'\""

// RESTful API paths (/api/v1/users/12345)
parse content, "'/api/v' INT:api_version '/' LD:resource '/' INT:id"
```

Key-Value Patterns

```
// Simple: user=john count=42
parse content, "'user=' LD:user SPACE 'count=' INT:count"

// Quoted: user="John Doe" email="john@example.com"
parse content, "'user=\"\" LD:user '\"' SPACE 'email=\"\" LD:email '\""

// Logfmt: level=info msg="OK" duration=150ms
parse content, "'level=' LD:level SPACE 'msg=\"\" LD:msg '\"' SPACE 'duration='
INT:dur 'ms'"
```

Stack Trace Patterns

```
// Java exception
parse content, "LD:exception_class ':' SPACE LD:exception_message EOL"

// Stack trace line
parse content, "'at ' LD:class_method '(' LD:file ':' INT:line ')"

// Caused by
parse content, "'Caused by: ' LD:caused_by ':' SPACE LD:message"

// Python traceback
parse content, "'File \"\" LD:file '\", line ' INT:line ', in ' LD:function"
```

PII Masking Patterns

Masking uses `replacePattern`, which takes a **DPL** pattern (not a regular expression — there is no `replaceAll` function). See OPMIG-08 for the full masking set.

```
// Credit cards (1234-5678-9012-3456 → ****-****-****-****)
fieldsAdd content = replacePattern(content, "CREDITCARD", replacement: "****-
****-****-****")

// Email addresses
| fieldsAdd content = replacePattern(content, "[a-zA-Z0-9._%+-]+ '@' [a-zA-Z0-
9.-]++", replacement: "****@****.****")

// SSN (123-45-6789 → ***-**-****)
| fieldsAdd content = replacePattern(content, "[0-9]{3} '-' [0-9]{2} '-' [0-9]
{4}", replacement: "***-**-****")
```

Partial masking ("keep the last 4 digits") has no DPL equivalent — `replacePattern` has no back-references, so the previous `$4` example cannot be expressed. Mask the whole number.

Network Patterns

```
// IP and port
parse content, "IPADDR:ip ':' INT:port"

// IPv4 only
parse content, "IPV4ADDR:ipv4"

// IPv6 only
parse content, "IPV6ADDR:ipv6"

// URL parsing (an LD must be followed by something it can stop at, so the
path starts at '/')
parse content, "LD:protocol '://' LD:hostname (':' INT:port)? '/' LD:path"
```

ELK/Logstash Migration Patterns NEW

Grok vs. DPL: Key Differences

Grok (Logstash)	DPL (OpenPipeline)
<code>%{IP:client_ip}</code>	<code>IPADDR:client_ip</code>
<code>%{INT:count}</code>	<code>INT:count</code>
<code>%{WORD:user}</code>	<code>WORD:user</code>
<code>%{GREEDYDATA:msg}</code>	<code>DATA:msg</code>
<code>\\s+</code>	<code>SPACE</code>

Apache Log Migration

Grok: `%{COMBINEDAPACHELOG}`

DPL:

```
parse content, ""
  IPADDR:client_ip SPACE LD:ident SPACE LD:auth SPACE
  '[' TIMESTAMP('dd/MMM/yyyy:HH:mm:ss Z'):log_time ']' SPACE
  ''' LD:method SPACE LD:request_path (SPACE LD:http_version)? ''' SPACE
  INT:status_code SPACE (INT:response_bytes | '-') SPACE
  ''' LD:referrer ''' SPACE ''' LD:user_agent '''
  ""
```

Logstash Filter → OpenPipeline Mapping

Logstash Filter	OpenPipeline
<code>grok { }</code>	DQL parse processor
<code>mutate { add_field }</code>	<code>fieldsAdd field = "value"</code>
<code>mutate { remove_field }</code>	<code>fieldsRemove field</code>
<code>mutate { rename }</code>	<code>fieldsRename old = new</code>
<code>drop { }</code>	Drop processor

Logstash Filter	OpenPipeline
<code>json { }</code>	JSON Technology Parser
<code>date { }</code>	TIMESTAMP in parse

Complete Migration Example

Logstash:

```
filter {
  if [level] == "DEBUG" { drop { } }
  grok { match => { "message" => "%{TIMESTAMP_ISO8601:ts} %{LOGLEVEL:level} %{GREEDYDATA:msg}" } }
  mutate { add_field => { "env" => "production" } }
}
```

OpenPipeline:

1. Drop processor: `loglevel == "DEBUG"`
2. DQL parse: `parse content, "TIMESTAMP('yyyy-MM-dd HH:mm:ss'):ts SPACE LD:level SPACE DATA:msg"`
3. DQL add: `fieldsAdd env = "production"`

Technology Bundle Parsers

OpenPipeline includes built-in parsers for common log formats.

Available Technology Parsers

Parser	Log Format	Extracted Fields
Apache	Apache access logs	client_ip, method, path, status, bytes
Nginx	Nginx access logs	Similar to Apache
JSON	JSON-formatted logs	All JSON fields flattened
Syslog	RFC 3164/5424 syslog	facility, severity, hostname, message

Parser	Log Format	Extracted Fields
Log4j	Java Log4j format	level, logger, thread, message
AWS CloudWatch	AWS logs	AWS-specific fields

When to Use Technology Parsers

Use Technology Parser	Use Custom DQL/DPL
Standard log format	Custom/proprietary format
Quick setup needed	Specific field extraction
Common technology	Conditional parsing
All fields needed	Selective extraction

Configuring Technology Parsers

1. Open pipeline in OpenPipeline settings
2. Go to **Processing** tab
3. Click **+ Processor** → **Technology**
4. Select parser type
5. Configure matching condition
6. Save

Drop Processors

Drop processors remove records from the pipeline before storage.

Common Drop Patterns

Use Case	Matching Condition
Debug logs	<code>loglevel == "DEBUG"</code>
Trace logs	<code>loglevel == "TRACE"</code>

Use Case	Matching Condition
Health checks	<code>matchesValue(content, "**health**")</code>
Readiness probes	<code>matchesValue(content, "**/ready**")</code>
Metrics endpoints	<code>matchesValue(content, "**/metrics**")</code>
Heartbeats	<code>matchesPhrase(content, "heartbeat")</code>

Matching conditions accept `matchesValue` (with `*` wildcards, any substring) and `matchesPhrase` (whole tokens); `contains()` is not enabled in a matcher.

| Specific source | `log.source == "noisy-service"` |

Drop Processor Configuration

Processor Type: Drop

Name: Drop debug logs

Matching Condition: `loglevel == "DEBUG" OR status == "DEBUG"`

Combining Drop Conditions

```
// Drop all non-essential logs
loglevel == "DEBUG"
OR loglevel == "TRACE"
OR matchesValue(content, "**health**")
OR matchesValue(content, "**/metrics**")
```

 **Important:** Dropped data is gone forever. Test drop conditions carefully before deploying.

Advanced Processing Patterns

Pattern 1: Fix Missing Timestamp

When logs have a custom timestamp format that's not recognized:

```
// Parse timestamp from content
parse content, '[' TIMESTAMP('yyyy-MM-dd HH:mm:ss'):parsed_timestamp ']'
```

Parse into a **new** field (`parsed_timestamp` , `log_time`). Overwriting `timestamp` risks the record failing log schema validation — a stored log must have a `timestamp` *"Within the ingestion range"*, and one that is not is dropped. Set `timestamp` deliberately and only from a parsed `TIMESTAMP` value.

Sources: [OpenPipeline limits \(DT docs\)](#) — *Schema validation for logs: "A processed log record is persisted only if all the following field conditions are satisfied. If the schema is not valid, the log is dropped."*

Pattern 2: Fix Missing Log Level

When logs don't have a standard loglevel field:

```
// Extract level from content
fieldsAdd loglevel = if(contains(content, "[ERROR]") OR contains(content,
"ERROR:"), "ERROR",
                        else: if(contains(content, "[WARN]") OR contains(content,
"WARN:"), "WARN",
                        else: if(contains(content, "[INFO]") OR contains(content,
"INFO:"), "INFO",
                        else: if(contains(content, "[DEBUG]") OR
contains(content, "DEBUG:"), "DEBUG",
                        else: "NONE"))))
```

Pattern 3: Parse JSON from Within Text

When JSON is embedded in a log message:

```
// Extract JSON from text
parse content, "LD JSON:embedded_json LD"
```

Pattern 4: Compute Response Time Categories

```
fieldsAdd response_category = if(duration_ms < 100, "fast",
                                else: if(duration_ms < 500, "normal",
                                else: if(duration_ms < 1000, "slow",
                                else: "very_slow"))
```

Pattern 5: Standardize Boolean Fields

```
fieldsAdd is_success = if(status == "success" OR status == "ok" OR status ==
"200", true, else: false)
```

Pattern 6: Extract Service Name from Path

```
// From /api/v1/users → users
parse content, "'/api/v' INT '/' LD:service_name"
```

Validating Your Processing

After configuring processors, validate that parsing is working correctly.

```
// Check parsing success rate across all pipelines
fetch logs, from: now() - 1h
| summarize {
    total = count(),
    with_loglevel = countIf(isNotNull(loglevel)),
    with_status = countIf(isNotNull(status)),
    with_either = countIf(isNotNull(loglevel) OR isNotNull(status))
}
| fieldsAdd parsing_rate = round((toDouble(with_either) / toDouble(total)) *
100, decimals: 1)
```

```
// Parsing success rate by pipeline
fetch logs, from: now() - 1h
| filter isNotNull(dt.openpipeline.pipelines)
| summarize {
    total = count(),
    parsed = countIf(isNotNull(loglevel))
}, by: {dt.openpipeline.pipelines}
| fieldsAdd parsing_rate = round((toDouble(parsed) / toDouble(total)) * 100,
decimals: 1)
| sort parsing_rate asc
```

```
// Sample logs that failed parsing (no loglevel extracted)
fetch logs, from: now() - 1h
| filter isNull(loglevel) AND isNull(status)
| fields timestamp, log.source, dt.openpipeline.pipelines, content
| limit 25
```

```
// Verify specific parsed fields exist
// Replace 'your_field' with fields your parsing should create
fetch logs, from: now() - 1h
| filter isNotNull(dt.openpipeline.pipelines)
| summarize {
    total = count(),
    with_user_id = countIf(isNotNull(user_id)),
    with_request_id = countIf(isNotNull(request_id))
}, by: {dt.openpipeline.pipelines}
```

```
// Sample successfully parsed logs to verify field extraction
fetch logs, from: now() - 1h
| filter isNotNull(loglevel)
| limit 20
```

```
// Verify drop processors are working
// If drops are configured, debug log count should be low
fetch logs, from: now() - 1h
| summarize {debug_count = countIf(loglevel == "DEBUG")}
| fieldsAdd message = if(debug_count == 0, "✅ Drop processor working - no
debug logs",
                        else: "⚠️ Debug logs still present - check drop
configuration")
```

```
// Check log level distribution after processing
fetch logs, from: now() - 1h
| summarize {log_count = count()}, by: {loglevel}
| sort log_count desc
```

DPL Architect Tool

Dynatrace provides a **DPL Architect** tool for building and testing patterns:

Accessing DPL Architect

1. Navigate to **Settings** → **OpenPipeline**
2. When adding a parse processor, click **Open DPL Architect**
3. Or access via: `https://{your-environment}.apps.dynatrace.com/ui/apps/dynatrace.dpl.architect`

Using DPL Architect

1. Paste sample log content
2. Build pattern interactively
3. See extracted fields in real-time
4. Copy pattern to processor definition

 **Tip:** Always test patterns in DPL Architect before deploying to production pipelines.

Complete Processing Pipeline Example

Pipeline: `application-logs`

Processor 1: Drop Debug (Drop)

```
Matching: loglevel == "DEBUG" OR matchesValue(content, "**[DEBUG]*")
```

Processor 2: Parse Application Log (DQL)

```
parse content, '[' TIMESTAMP('yyyy-MM-dd HH:mm:ss'):log_ts ']' SPACE '['  
LD:level ']' SPACE '[' LD:thread ']' SPACE LD:class ' - ' DATA:message"
```

Processor 3: Extract Request ID (DQL)

```
parse content, "'requestId=' LD:request_id"
```

Processor 4: Add Environment Tags (DQL)

```
fieldsAdd environment = "production"  
| fieldsAdd application = "checkout-service"  
| fieldsAdd team = "platform"
```

Processor 5: Compute Severity (DQL)

```
fieldsAdd severity = if(level == "ERROR", "P1",  
                        else: if(level == "WARN", "P2",  
                        else: "P3"))
```

Next Steps

Now that you can transform data, continue with:

Notebook	Focus Area
OPMIG-07	Metric & Event Extraction
OPMIG-08	Security, Masking & Compliance
OPMIG-09	Troubleshooting & Validation

References

- [OpenPipeline Processing](#)
 - [Processing Examples](#)
 - [Dynatrace Pattern Language](#)
 - [DPL Architect Tool](#)
 - [DQL Functions in OpenPipeline](#)
-

This notebook was AI-generated from community-submitted and publicly available sources. This notebook series is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.