

Description of Operations

Mountain Lion Detection System

By: Maximus Conaway

Alarm - dismiss(String status): Void

This operation allows the ranger to turn off an active alarm after an alert is received. The status parameter records the status connected to the alarm when it is dismissed. After the alarm is turned off, it will stay off until another separate noise is detected at a different location.

Alerts - summary(String status, int time): Void

This operation creates a summary of alerts using a classification and a certain time period. The status parameter can be definite, suspected, or false, and the time parameter is used to decide which alerts should be included in the summary.

Alerts - summary(String status): Void

This operation creates a summary based on the classification of the alerts. It allows the ranger to view alerts that were classified as definite, suspected, or false.

Alerts - summary(int sensor): Void

This operation creates a summary for a specific sensor. The sensor parameter identifies the sensor so the system can show the detections that came from that sensor location.

Alerts - summaryMap(): Void

This operation creates the information needed for a graphical map report. The map shows where detections happened in the park and in the areas within two miles of the park.

Alerts - summaryRanger(int id): Void

This operation creates a summary for a specific ranger. The id parameter identifies the ranger so the system can show the detection classifications made by that ranger.

How the Operations Work Together

When a sensor detects a programmed animal noise, the detection information is placed into a report and sent to the controlling computer. The computer uses the report to trigger the alarm and store the alert. The ranger can then turn off the alarm and classify the alert as definite, suspected, or false. The stored information can later be used by the Alerts operations to create summaries by classification, time, sensor, map location, or ranger.