

Agenda

- Naming Convention
- Class
- Object
- Namespace
- Console I/O
- Menu Driven Code
- Function Overloading
- Default Argument Function
- this pointer

Naming Convention

- The naming convention used for software development are
 1. Camel Case Convention
 - In this case, except word, first Character of each word must be in upper case.
 - Consider following example.
 - `main()`
 - `parseInt()`
 - `showInputDialog`
 - `addNumberOfDays(int days)`
 - We should use this convention for
 - Data member
 - Member function
 - Function Parameter
 - Local and global variable
 2. Pascal Case Convention
 - In this case, including first word, first character of each word must be in upper case.
 - Consider following example
 - `System`
 - `StringBuilder`
 - `NullPointerException`
 - `IndexOutOfBoundsException`
 - We should use this convention for
 - Union Name
 - Structure Name
 - Class Name

- Enum Name

3. Convention For macro and constant

- Name of constant, enum constant and macro should be in upper case.

```
#define NULL 0
#define EOF -1
#define SIZE 5

const float PI = 3.142;

enum ShapeType
{
    EXIT, LINE, RECT, OVAL
};
```

4. Naming Convention for namespace

- Name of the namespace should be in lowercase.

```
namespace collection
{
    class Stack
    {
    };
}
```

Class

- Class is a logical entity.
- It is a collection of data member and member function.
- Structure and behavior of an object depends on class hence class is considered as a template/model/blueprint for an object.
- Class represents encapsulation.
- Example: Mobile Phone,Laptop,Car

Object

- It is physical entity.
- Object is a variable/instance of a class.
- An entity, which get space inside memory is called object.
- With the help of instantiation we achieve abstraction.
- Example: Nokia 1100, MacBook Pro, sMaruti 800

Characteristics of object

- Object defines 3 things

1. State

- Value stored inside object is called state of the object.
- Value of data member represent state of the object.

2. Behavior

- Set of operation that we perform on object is called behavior of an object.
- Member function of class represent behavior of the object.

3. Identity

- Value of any data member, which is used to identify object uniquely is called its identity.
- If state of object is same the its address can be considered as its identity.

Object Size

- If we create object of the class then only non static data members get space inside object.
- Hence size of object is depends on size of all the non static data members declared inside class.
- Member function do not get space inside object.
- Data members get space once per object according to the order of data member declaration.
- Member function do not get space per object rather it gets space on code segment and all the objects of same class share single copy of it.
- Object of an empty class is 1 byte.

Access Specifiers

- If we want to control visibility of members of structure/class then we should use access specifier.
- Access specifiers in C++

1. private(-)

- visibility only within the class

2. protected(#)

- visibility in the derived classes

3. public(+)

- visibility every where on structure/class object

- In C++, structure members are by default considered as public and class members are by default considered as private

Namespace

- If we want to access value of global variable then we should use scope resolution operator(::)

```
int num1 = 10;
int main()
{
    int num1 = 10;
    printf("value of local num1 = %d\n", num1);
    printf("value of global num1 = %d\n", ::num1);
}
```

```
    return 0;
}
```

- Namespace in C++ language is used:

1. To avoid name clashing/collision/ambiguity.
2. To group functionally equivalent/related types together.

- Namespace can contain:

1. Variable
2. Function
3. Types[structure/union/class]
4. Enum
5. Nested Namespace

- Namespaces are used to organize code into logical groups and to prevent name collisions that can occur especially when your code base includes multiple libraries.s
- We can not instantiate namespace.
- If we want to define namespace then we should use namespace keyword.
- namespaces can only be defined in global or namespace scope. In other words, we can not define namespace inside function/class.
- If we want to access members of namespace then we should use namespace name and scope resolution operator.
- If name of the namespaces are different then we can give same/different name to the members of namespace.
- If name of the namespaces are same then name of members must be different.
- We can define namespace inside another namespace. It is called nested namespace.
- If we define member without namespace then it is considered as member of global namespace.
- If we want to access members of namespace frequently then we should use using directive.

```
namespace na
{
    int num1 = 10;
}

int main( void )
{
    printf("Num1 : %d\n", na::num1);
    return 0;
}
```

Console Input and OutPut Operation

- C++ provides an easier way for input and output.
- Console Input -> Keyboard
- Console Output -> Monitor

- Console = Keyboard + Monitor
- iostream is standard header file of C++.

1. cout

- cout is external object of ostream class.
- cout is member of std namespace and std namespace is declared in iostream header file.
- cout represents monitor.
- An insertion operator(<<) is designed to use with cout.

2. cin

- cin is an external object of istream class.
- cin is a member of std namespace and std namespace is declared in iostream header file.
- Extraction operator(>>) is designed to use with cin object.
- cin represents keyboard.

string class

- is standard header file of C++ which contains std namespace and std contains basic_string class.
- size of string object is 24 bytes(on 32 bit compiler)
- In the case of strings, memory is allocated dynamically. More memory can be allocated at run time on demand. As no memory is preallocated, no memory is wasted.

Menu driven code

- When we want to execute the code in continuous manner and want to execute the code based on users choice then we can write a menu driven code.

Function Overloading

- Functions with same name and different signature are called as overloaded functions.
- Return type is not considered for function overloading.
- Function call is resolved according to types of arguments passed.
- Function overloading is possible due to name mangling done by the C++ compiler (Name mangling process , mangled name)
- Differ in number of input arguments
- Differ in data type of input arguments
- Differ at least in the sequence of the input arguments

Default Argument Function

- In C++, functions may have arguments with the default values. Passing these arguments while calling a function is optional.
- A default argument is a default value provided for a function parameter/argument.
- If the user does not supply an explicit argument for a parameter with a default argument, the default value will be used.
- If such argument is not passed, then its default value is considered. Otherwise arguments are treated as normal arguments.

- Default arguments should be given in right to left order.

this pointer

- If we call member function on object then compiler implicitly pass address of that object as a argument to the function implicitly.
- To store address of object compiler implicitly declare one pointer as a parameter inside member function. Such parameter is called this pointer.
- this is a keyword. "this" pointer is a constant pointer.
- General type of this pointer is:
 - `Classname * const this;`

Member Functions

- The functions declared inside the class are called as Member Functions.
- The member functions according to their behaviour are classified into following types
 1. constructor
 2. destructor
 3. Mutator
 4. Inspector
 5. Facilitator

Assignments

1. Solve Assignment-1 first
2. create nested namespace with same name and different variables and print the values of all the variables.
3. create nested namespace add some variables and display them using namespace name and `::` and also try `using` directive