Overview

	Passed	Failed	Known	Undefined	Total	%Passed
Features	0	1	0	0	1	0%
Scenarios	0	2	0	0	2	0%
Steps	0	2	0	4	6	0%

Overall Duration: 0h 00m 16s

Table of Contents

Detailed Results Report

Feature: Google Test			
Passed: 0	Failed: 2	Undefined: 0	Duration: 16.79s

Scenario Outline: Search keywords in Google			
Passed: 0	Failed: 1	Undefined: 2	Duration: 8.43s

Given Google homepage is open	8.12s

org.openqa.selenium.WebDriverException: chrome not reachable
(Session info: chrome=80.0.3987.162)
Build info: version: '3.141.59', revision: 'e82be7d358', time: '2018-11-14T08:17:03'
System info: host: 'USER1-PC', ip: '192.168.0.109', os.name: 'Windows 7', os.arch: 'x86', os.
version: '6.1', java.version: '1.8.0_201'
Driver info: org.openqa.selenium.chrome.ChromeDriver
Capabilities {acceptInsecureCerts: false, browserName: chrome, browserVersion:
80.0.3987.162, chrome: {chromedriverVersion: 80.0.3987.106 (f68069574609..., userDataDir: C:
\Users\user1\AppData\Loca...}, goog:chromeOptions: {debuggerAddress: localhost:61570},
javascriptEnabled: true, networkConnectionEnabled: false, pageLoadStrategy: normal,
platform: WINDOWS, platformName: WINDOWS, proxy: Proxy(), setWindowRect: true,

strictFileInteractability: false, timeouts: {implicit: 0, pageLoad: 300000, script: 30000}, unhandledPromptBehavior: dismiss and notify}
Session ID: 63df9a59106bc59acb8ac5d61aa53b62
at sun.reflect.NativeConstructorAccessorImpl.newInstance0(Native Method)
at sun.reflect.NativeConstructorAccessorImpl.newInstance(NativeConstructorAccessorImpl.java:62)
at sun.reflect.DelegatingConstructorAccessorImpl.newInstance(DelegatingConstructorAccessorImpl.java:45)
at java.lang.reflect.Constructor.newInstance(Constructor.java:423)
at org.openqa.selenium.remote.http.W3CHttpResponseCodec.createException(W3CHttpResponseCodec.java:187)
at org.openqa.selenium.remote.http.W3CHttpResponseCodec.decode(W3CHttpResponseCodec.java:122)
at org.openqa.selenium.remote.http.W3CHttpResponseCodec.decode(W3CHttpResponseCodec.java:49)
at org.openqa.selenium.remote.HttpCommandExecutor.execute(HttpCommandExecutor.java:158)
at org.openqa.selenium.remote.service.DriverCommandExecutor.execute(DriverCommandExecutor.java:83)
at org.openqa.selenium.remote.RemoteWebDriver.execute(RemoteWebDriver.java:552)
at org.openqa.selenium.remote.RemoteWebDriver.get(RemoteWebDriver.java:277)
at stepDefinitions.GoogleStepDef.googleHomepageIsOpen(GoogleStepDef.java:39)
at .Given Google homepage is open(C:/DevEnvironment/IntelliJ Workspace/MPOS_Suite/./src/test/resources/features/Google.feature:5)

When Enter "USA" in Search box	0.00s
Then Google displays relevant search result	0.00s
After	0.32s

org.openqa.selenium.WebDriverException: chrome not reachable
(Session info: chrome=80.0.3987.162)
Build info: version: '3.141.59', revision: 'e82be7d358', time: '2018-11-14T08:17:03'
System info: host: 'USER1-PC', ip: '192.168.0.109', os.name: 'Windows 7', os.arch: 'x86', os.version: '6.1', java.version: '1.8.0_201'
Driver info: org.openqa.selenium.chrome.ChromeDriver
Capabilities {acceptInsecureCerts: false, browserName: chrome, browserVersion: 80.0.3987.162, chrome: {chromedriverVersion: 80.0.3987.106 (f68069574609..., userDataDir: C:\Users\user1\AppData\Loca...}, goog:chromeOptions: {debuggerAddress: localhost:61570}, javascriptEnabled: true, networkConnectionEnabled: false, pageLoadStrategy: normal, platform:

WINDOWS, platformName: WINDOWS, proxy: Proxy(), setWindowRect: true,
strictFileInteractability: false, timeouts: {implicit: 0, pageLoad: 300000, script: 30000},
unhandledPromptBehavior: dismiss and notify}
Session ID: 63df9a59106bc59acb8ac5d61aa53b62
at sun.reflect.NativeConstructorAccessorImpl.newInstance0(Native Method)
at sun.reflect.NativeConstructorAccessorImpl.newInstance(NativeConstructorAccessorImpl.java:
62)
at sun.reflect.DelegatingConstructorAccessorImpl.newInstance
(DelegatingConstructorAccessorImpl.java:45)
at java.lang.reflect.Constructor.newInstance(Constructor.java:423)
at org.openqa.selenium.remote.http.W3CHttpResponseCodec.createException
(W3CHttpResponseCodec.java:187)
at org.openqa.selenium.remote.http.W3CHttpResponseCodec.decode(W3CHttpResponseCodec.
java:122)
at org.openqa.selenium.remote.http.W3CHttpResponseCodec.decode(W3CHttpResponseCodec.
java:49)
at org.openqa.selenium.remote.HttpCommandExecutor.execute(HttpCommandExecutor.java:
158)
at org.openqa.selenium.remote.service.DriverCommandExecutor.execute
(DriverCommandExecutor.java:83)
at org.openqa.selenium.remote.RemoteWebDriver.execute(RemoteWebDriver.java:552)
at org.openqa.selenium.remote.RemoteWebDriver.execute(RemoteWebDriver.java:609)
at org.openqa.selenium.remote.RemoteWebDriver.close(RemoteWebDriver.java:442)
at stepDefinitions.Hooks.wrapUp(Hooks.java:16)
at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:62)
at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
at java.lang.reflect.Method.invoke(Method.java:498)
at cucumber.runtime.Utils$1.call(Utils.java:40)
at cucumber.runtime.Timeout.timeout(Timeout.java:16)
at cucumber.runtime.Utils.invoke(Utils.java:34)
at cucumber.runtime.java.JavaHookDefinition.execute(JavaHookDefinition.java:60)
at cucumber.runtime.ExtendedRuntime.runHookIfTagsMatch(ExtendedRuntime.java:236)
at cucumber.runtime.ExtendedRuntime.runHooks(ExtendedRuntime.java:224)
at cucumber.runtime.ExtendedRuntime.runAfterHooks(ExtendedRuntime.java:218)
at cucumber.runtime.model.CucumberScenario.run(CucumberScenario.java:46)
at com.github.mkolisnyk.cucumber.runner.ExtendedExecutionUnitRunner.run
(ExtendedExecutionUnitRunner.java:32)
at com.github.mkolisnyk.cucumber.runner.ExtendedExamplesRunner.retry

(ExtendedExamplesRunner.java:151)
at com.github.mkolisnyk.cucumber.runner.ExtendedExamplesRunner.runChild
(ExtendedExamplesRunner.java:120)
at com.github.mkolisnyk.cucumber.runner.ExtendedExamplesRunner.runChild
(ExtendedExamplesRunner.java:21)
at org.junit.runners.ParentRunner$3.run(ParentRunner.java:290)
at org.junit.runners.ParentRunner$1.schedule(ParentRunner.java:71)
at org.junit.runners.ParentRunner.runChildren(ParentRunner.java:288)
at org.junit.runners.ParentRunner.access$000(ParentRunner.java:58)
at org.junit.runners.ParentRunner$2.evaluate(ParentRunner.java:268)
at org.junit.runners.ParentRunner.run(ParentRunner.java:363)
at com.github.mkolisnyk.cucumber.runner.ExtendedExamplesRunner.run
(ExtendedExamplesRunner.java:94)
at org.junit.runners.Suite.runChild(Suite.java:128)
at com.github.mkolisnyk.cucumber.runner.ExtendedScenarioOutlineRunner.runChild
(ExtendedScenarioOutlineRunner.java:75)
at com.github.mkolisnyk.cucumber.runner.ExtendedScenarioOutlineRunner.runChild
(ExtendedScenarioOutlineRunner.java:18)
at org.junit.runners.ParentRunner$3.run(ParentRunner.java:290)
at org.junit.runners.ParentRunner$1.schedule(ParentRunner.java:71)
at org.junit.runners.ParentRunner.runChildren(ParentRunner.java:288)
at org.junit.runners.ParentRunner.access$000(ParentRunner.java:58)
at org.junit.runners.ParentRunner$2.evaluate(ParentRunner.java:268)
at org.junit.runners.ParentRunner.run(ParentRunner.java:363)
at com.github.mkolisnyk.cucumber.runner.ExtendedScenarioOutlineRunner.run
(ExtendedScenarioOutlineRunner.java:70)
at com.github.mkolisnyk.cucumber.runner.ExtendedFeatureRunner.runChild
(ExtendedFeatureRunner.java:81)
at com.github.mkolisnyk.cucumber.runner.ExtendedFeatureRunner.runChild
(ExtendedFeatureRunner.java:23)
at org.junit.runners.ParentRunner$3.run(ParentRunner.java:290)
at org.junit.runners.ParentRunner$1.schedule(ParentRunner.java:71)
at org.junit.runners.ParentRunner.runChildren(ParentRunner.java:288)
at org.junit.runners.ParentRunner.access$000(ParentRunner.java:58)
at org.junit.runners.ParentRunner$2.evaluate(ParentRunner.java:268)
at org.junit.runners.ParentRunner.run(ParentRunner.java:363)
at cucumber.runtime.junit.FeatureRunner.run(FeatureRunner.java:70)
at com.github.mkolisnyk.cucumber.runner.ExtendedCucumber.runChild(ExtendedCucumber.
java:108)

at com.github.mkolisnyk.cucumber.runner.ExtendedCucumber.runChild(ExtendedCucumber.java:32)
at org.junit.runners.ParentRunner$3.run(ParentRunner.java:290)
at org.junit.runners.ParentRunner$1.schedule(ParentRunner.java:71)
at org.junit.runners.ParentRunner.runChildren(ParentRunner.java:288)
at org.junit.runners.ParentRunner.access$000(ParentRunner.java:58)
at org.junit.runners.ParentRunner$2.evaluate(ParentRunner.java:268)
at org.junit.runners.ParentRunner.run(ParentRunner.java:363)
at com.github.mkolisnyk.cucumber.runner.ExtendedCucumber.run(ExtendedCucumber.java:148)
at com.github.mkolisnyk.cucumber.runner.parallel.CucumberRunnerThread.run(CucumberRunnerThread.java:25)
at java.lang.Thread.run(Thread.java:748)

[Back to Table of Contents](#)

Scenario Outline: Search keywords in Google

Passed: 0	Failed: 1	Undefined: 2	Duration: 8.36s

Given Google homepage is open			8.12s

org.openqa.selenium.WebDriverException: chrome not reachable
(Session info: chrome=80.0.3987.162)
Build info: version: '3.141.59', revision: 'e82be7d358', time: '2018-11-14T08:17:03'
System info: host: 'USER1-PC', ip: '192.168.0.109', os.name: 'Windows 7', os.arch: 'x86', os.version: '6.1', java.version: '1.8.0_201'
Driver info: org.openqa.selenium.chrome.ChromeDriver
Capabilities {acceptInsecureCerts: false, browserName: chrome, browserVersion: 80.0.3987.162, chrome: {chromedriverVersion: 80.0.3987.106 (f68069574609..., userDataDir: C:\Users\user1\AppData\Loca...}, goog:chromeOptions: {debuggerAddress: localhost:61570}, javascriptEnabled: true, networkConnectionEnabled: false, pageLoadStrategy: normal, platform: WINDOWS, platformName: WINDOWS, proxy: Proxy(), setWindowRect: true, strictFileInteractability: false, timeouts: {implicit: 0, pageLoad: 300000, script: 30000}, unhandledPromptBehavior: dismiss and notify}
Session ID: 63df9a59106bc59acb8ac5d61aa53b62
at sun.reflect.GeneratedConstructorAccessor16.newInstance(Unknown Source)
at sun.reflect.DelegatingConstructorAccessorImpl.newInstance(DelegatingConstructorAccessorImpl.java:45)
at java.lang.reflect.Constructor.newInstance(Constructor.java:423)
at org.openqa.selenium.remote.http.W3CHttpResponseCodec.createException(W3CHttpResponseCodec.java:187)

at org.openqa.selenium.remote.http.W3CHttpResponseCodec.decode
(W3CHttpResponseCodec.java:122)
at org.openqa.selenium.remote.http.W3CHttpResponseCodec.decode
(W3CHttpResponseCodec.java:49)
at org.openqa.selenium.remote.HttpCommandExecutor.execute(HttpCommandExecutor.java:
158)
at org.openqa.selenium.remote.service.DriverCommandExecutor.execute
(DriverCommandExecutor.java:83)
at org.openqa.selenium.remote.RemoteWebDriver.execute(RemoteWebDriver.java:552)
at org.openqa.selenium.remote.RemoteWebDriver.get(RemoteWebDriver.java:277)
at stepDefinitions.GoogleStepDef.googleHomepageIsOpen(GoogleStepDef.java:39)
at .Given Google homepage is open(C:/DevEnvironment/IntelliJ Workspace/MPOS_Suite/./src
/test/resources/features/Google.feature:5)

| When Enter "Uganda" in Search box | 0.00s |
| Then Google displays relevant search result | 0.00s |

| After | | 0.24s |

org.openqa.selenium.WebDriverException: chrome not reachable
(Session info: chrome=80.0.3987.162)
Build info: version: '3.141.59', revision: 'e82be7d358', time: '2018-11-14T08:17:03'
System info: host: 'USER1-PC', ip: '192.168.0.109', os.name: 'Windows 7', os.arch: 'x86', os.
version: '6.1', java.version: '1.8.0_201'
Driver info: org.openqa.selenium.chrome.ChromeDriver
Capabilities {acceptInsecureCerts: false, browserName: chrome, browserVersion: 80.0.3987.162,
chrome: {chromedriverVersion: 80.0.3987.106 (f68069574609..., userDataDir: C:
\Users\user1\AppData\Loca...}, goog:chromeOptions: {debuggerAddress: localhost:61570},
javascriptEnabled: true, networkConnectionEnabled: false, pageLoadStrategy: normal, platform:
WINDOWS, platformName: WINDOWS, proxy: Proxy(), setWindowRect: true,
strictFileInteractability: false, timeouts: {implicit: 0, pageLoad: 300000, script: 30000},
unhandledPromptBehavior: dismiss and notify}
Session ID: 63df9a59106bc59acb8ac5d61aa53b62
at sun.reflect.GeneratedConstructorAccessor16.newInstance(Unknown Source)
at sun.reflect.DelegatingConstructorAccessorImpl.newInstance
(DelegatingConstructorAccessorImpl.java:45)
at java.lang.reflect.Constructor.newInstance(Constructor.java:423)
at org.openqa.selenium.remote.http.W3CHttpResponseCodec.createException
(W3CHttpResponseCodec.java:187)
at org.openqa.selenium.remote.http.W3CHttpResponseCodec.decode(W3CHttpResponseCodec.

```
java:122)
at org.openqa.selenium.remote.http.W3CHttpResponseCodec.decode(W3CHttpResponseCodec.
java:49)
at org.openqa.selenium.remote.HttpCommandExecutor.execute(HttpCommandExecutor.java:
158)
at org.openqa.selenium.remote.service.DriverCommandExecutor.execute
(DriverCommandExecutor.java:83)
at org.openqa.selenium.remote.RemoteWebDriver.execute(RemoteWebDriver.java:552)
at org.openqa.selenium.remote.RemoteWebDriver.execute(RemoteWebDriver.java:609)
at org.openqa.selenium.remote.RemoteWebDriver.close(RemoteWebDriver.java:442)
at stepDefinitions.Hooks.wrapUp(Hooks.java:16)
at sun.reflect.GeneratedMethodAccessor49.invoke(Unknown Source)
at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
at java.lang.reflect.Method.invoke(Method.java:498)
at cucumber.runtime.Utils$1.call(Utils.java:40)
at cucumber.runtime.Timeout.timeout(Timeout.java:16)
at cucumber.runtime.Utils.invoke(Utils.java:34)
at cucumber.runtime.java.JavaHookDefinition.execute(JavaHookDefinition.java:60)
at cucumber.runtime.ExtendedRuntime.runHookIfTagsMatch(ExtendedRuntime.java:236)
at cucumber.runtime.ExtendedRuntime.runHooks(ExtendedRuntime.java:224)
at cucumber.runtime.ExtendedRuntime.runAfterHooks(ExtendedRuntime.java:218)
at cucumber.runtime.model.CucumberScenario.run(CucumberScenario.java:46)
at com.github.mkolisnyk.cucumber.runner.ExtendedExecutionUnitRunner.run
(ExtendedExecutionUnitRunner.java:32)
at com.github.mkolisnyk.cucumber.runner.ExtendedExamplesRunner.retry
(ExtendedExamplesRunner.java:151)
at com.github.mkolisnyk.cucumber.runner.ExtendedExamplesRunner.runChild
(ExtendedExamplesRunner.java:120)
at com.github.mkolisnyk.cucumber.runner.ExtendedExamplesRunner.runChild
(ExtendedExamplesRunner.java:21)
at org.junit.runners.ParentRunner$3.run(ParentRunner.java:290)
at org.junit.runners.ParentRunner$1.schedule(ParentRunner.java:71)
at org.junit.runners.ParentRunner.runChildren(ParentRunner.java:288)
at org.junit.runners.ParentRunner.access$000(ParentRunner.java:58)
at org.junit.runners.ParentRunner$2.evaluate(ParentRunner.java:268)
at org.junit.runners.ParentRunner.run(ParentRunner.java:363)
at com.github.mkolisnyk.cucumber.runner.ExtendedExamplesRunner.run
(ExtendedExamplesRunner.java:94)
at org.junit.runners.Suite.runChild(Suite.java:128)
```

at com.github.mkolisnyk.cucumber.runner.ExtendedScenarioOutlineRunner.runChild (ExtendedScenarioOutlineRunner.java:75)
at com.github.mkolisnyk.cucumber.runner.ExtendedScenarioOutlineRunner.runChild (ExtendedScenarioOutlineRunner.java:18)
at org.junit.runners.ParentRunner$3.run(ParentRunner.java:290)
at org.junit.runners.ParentRunner$1.schedule(ParentRunner.java:71)
at org.junit.runners.ParentRunner.runChildren(ParentRunner.java:288)
at org.junit.runners.ParentRunner.access$000(ParentRunner.java:58)
at org.junit.runners.ParentRunner$2.evaluate(ParentRunner.java:268)
at org.junit.runners.ParentRunner.run(ParentRunner.java:363)
at com.github.mkolisnyk.cucumber.runner.ExtendedScenarioOutlineRunner.run (ExtendedScenarioOutlineRunner.java:70)
at com.github.mkolisnyk.cucumber.runner.ExtendedFeatureRunner.runChild (ExtendedFeatureRunner.java:81)
at com.github.mkolisnyk.cucumber.runner.ExtendedFeatureRunner.runChild (ExtendedFeatureRunner.java:23)
at org.junit.runners.ParentRunner$3.run(ParentRunner.java:290)
at org.junit.runners.ParentRunner$1.schedule(ParentRunner.java:71)
at org.junit.runners.ParentRunner.runChildren(ParentRunner.java:288)
at org.junit.runners.ParentRunner.access$000(ParentRunner.java:58)
at org.junit.runners.ParentRunner$2.evaluate(ParentRunner.java:268)
at org.junit.runners.ParentRunner.run(ParentRunner.java:363)
at cucumber.runtime.junit.FeatureRunner.run(FeatureRunner.java:70)
at com.github.mkolisnyk.cucumber.runner.ExtendedCucumber.runChild(ExtendedCucumber. java:108)
at com.github.mkolisnyk.cucumber.runner.ExtendedCucumber.runChild(ExtendedCucumber. java:32)
at org.junit.runners.ParentRunner$3.run(ParentRunner.java:290)
at org.junit.runners.ParentRunner$1.schedule(ParentRunner.java:71)
at org.junit.runners.ParentRunner.runChildren(ParentRunner.java:288)
at org.junit.runners.ParentRunner.access$000(ParentRunner.java:58)
at org.junit.runners.ParentRunner$2.evaluate(ParentRunner.java:268)
at org.junit.runners.ParentRunner.run(ParentRunner.java:363)
at com.github.mkolisnyk.cucumber.runner.ExtendedCucumber.run(ExtendedCucumber.java: 148)
at com.github.mkolisnyk.cucumber.runner.parallel.CucumberRunnerThread.run (CucumberRunnerThread.java:25)
at java.lang.Thread.run(Thread.java:748)