

Dynamics Of A Quadcopter

Daniel Wood

April 7, 2020

1 Introduction

In recent years the development of smaller and cheaper electronics, specifically inertial measurement systems, has led to a rise in popularity of lightweight unmanned aerial vehicles. Unmanned aerial vehicles come in many configurations, this work focuses on a symmetric quadrotor configuration. With a rise in general usage of quadrotor vehicles, there has surfaced the need to autonomously control these vehicles, some applications include automated delivery services, military usage, aerial imagery. For these applications it is critical to achieve stable flight

The formation of autonomous control consists of a valid dynamical model of the vehicle, and a fast, stable, robust controller. The dynamics of a quadrotor is not trivial and requires an indepth understanding of advanced dynamics topics. The unsimplified dynamical model inherently leads to a non-linear controller. There are many algorithms to choose from, some that are currently being utilized are discussed. Picking a control algorithm stems from the goal of making the output stable as well as having a robust controller. A system is said to be stable if it can remain at an equilibrium point under the stress of external disturbances [cite something here], where as robustness is defined as a controller that can operate under parameters that vary from the original design [cite something here].

There are many researchers dedicating time to improving controller stability through different control schemes such as Multiple Input Multiple Output state variable (MIMO)[2], Linear Quadratic Regulator (LQR), Model Predictive Control (MPC), and Sliding Mode Control (SMC). In general this research focuses on nuances of the choosen algorithm with the goal of improvement in disturbance rejection[5] and robustness. Because of the scope of the research, the dynamics model of the quadrotor is generally linearized for simplicity, or assumptions that were made lead to reduced order of the system[2].

The goal of this research is to start with the concrete fundamentals of dynamics to derive a state space model of the quadrotor in 3D space, relative to a fixed global frame. Then create a stable and robust non-linear controller for accurate path tracking. This controller will be based on the Sliding Mode Control technique. This technique is a valid choice for the dynamics system,

because it allows the controller to quickly jump to different equilibrium points, and forces state variables towards the equilibrium points, or in the case of SMC, the sliding manifold as it is noted in literature.

Derivation of the equations of motion of the quadrotor requires defining two coordinate systems, the global, or fixed frame, and the body, or inertial frame[1],[2],[3],[5]. The path that is defined is always given in reference to the global frame, whereas the equations of motion that define our controllable states, is in reference to the body frame. Rotations of the body such as yaw, pitch, roll, are determined through sensors such as accelerometers and IMUs physically placed on the body. While physical position in space is defined by a global positioning system (GPS), which requires knowledge of the body as well as the reference frame.

References

- [1] Mohamed Fanni and Ahmed Khalifa. A new 6-dof quadrotor manipulation system: Design, kinematics, dynamics, and control. *IEEE/ASME Transactions on Mechatronics*, 22(3):1315–1326, 2017.
- [2] Veeravat Faramae and Viboon Sangveraphunsiri. Experiment of the state variable feedback for a quadrotor. *Applied Mechanics and Materials*, 619(Mechanical and Electrical Technology VI):267–272, 2014.
- [3] Haomiao Huang, G.M Hoffmann, S.L Waslander, and C.J Tomlin. Aerodynamics and control of autonomous quadrotor helicopters in aggressive maneuvering. In *2009 IEEE International Conference on Robotics and Automation*, pages 3277–3282. IEEE, 2009.
- [4] A Khalifa, M Fanni, A Ramadan, and Ahmed Abo-Ismail. Modeling and control of a new quadrotor manipulation system. In *2012 First International Conference on Innovative Engineering Systems*, pages 109–114. IEEE, 2012.
- [5] Denis Kotarski, Zoran Benić, and Matija Krznar. Control design for unmanned aerial vehicles with four rotors. *Interdisciplinary Description of Complex Systems*, 14(2):236–245, 2016.