

🔌 Quick-Start Guide

🔌 What Guitar Tap Does

Guitar Tap uses your device's microphone to capture the brief ring-out after you tap a guitar or wood sample. A 65,536-point FFT (≈ 0.67 Hz resolution) reveals the resonant peaks that carry information about structural modes and material stiffness.

Three main workflows are supported:

- **Guitar mode** — classify resonant modes of a completed instrument.
- **Plate mode** — measure Young's modulus and quality of a raw tonewood plate.
- **Brace mode** — measure Young's modulus and quality of a brace strip (single longitudinal tap).

🔧 First-Time Setup

Grant Microphone Access

The first time the app launches it will ask for microphone permission. Without it the analyzer cannot run.

Select Audio Input

Open Settings. The Audio Input & Calibration section appears at the top. Choose your microphone or audio interface here. If you have a calibration file for your measurement mic, import it in this section too.

Choose a Measurement Type

In Settings, the Measurement Type section is directly below Audio Input. Pick Generic Guitar (the default, with broad ranges that work for any guitar), Acoustic / Steel String, Classical, Flamenco, Material (Plate), or Material (Brace). The right choice determines which mode-frequency ranges are used and which measurements are calculated.

Advanced Settings

Display range and FFT processing options are grouped under the Advanced section at the bottom of Settings. These rarely need changing after initial setup — expand the section by clicking the Advanced row.

Quiet Environment

Background noise raises the noise floor. A quiet workbench with the device resting on a folded cloth a few centimetres from the tap point gives the most repeatable results.

🎵 Guitar Mode

Overview

Guitar mode identifies the key structural resonances of a completed body: Air (Helmholtz cavity resonance), Top (main top-plate resonance), Back, Dipole, Ring Mode, and Upper Modes.

Step 1 — Configure

In Settings choose the guitar type in the Measurement Type section. Generic Guitar (the default) uses broad ranges that work for any guitar; Acoustic / Steel String, Classical, and Flamenco use narrower calibrated windows shown in the same section. The Show Unknown Modes toggle is in the Advanced section.

Step 2 — Position the Microphone

The spectrum updates in real time as soon as the app opens. Set the device microphone 5–15 cm from the guitar, aimed at the sound hole or tap point.

Step 3 — Tap New Tap

Click the New Tap button to arm the detector, then give the guitar top (or back, side, etc.) a firm knuckle rap. The spectrum freezes automatically when a tap is detected.

Step 4 — Inspect Peaks

Coloured markers label each resonant peak with its mode, frequency, and pitch. In guitar mode, one peak per mode is auto-selected based on the strongest peak in each frequency range, working lowest-to-highest so overlapping ranges resolve in favour of the lower mode. Click a peak label to toggle its selection. Use the Annotations button to cycle through All / Selected / None label modes. In the Results panel, the wand button resets selections back to automatic if you have made manual changes. On desktop, clicking a peak's dot highlights it and scrolls its Analysis Results row into view (and clicking a row highlights its dot); click either again to clear. This only locates a peak — it is separate from selection.

Step 5 — Read the Results

The results panel shows the peak list with frequency, magnitude, Q factor, bandwidth, and pitch. Decay time (ring-out in seconds) and Tap Tone Ratio (Top ÷ Air) are shown when applicable. Typical top/air ratios range from 1.8 to 2.4 for quality instruments.

Multi-Tap Averaging

Setting the tap count to 2–10 averages multiple taps together, reducing noise from finger squeaks and ambient sounds. Progress is shown in the status bar. Use Pause between taps to let the ring-out decay.

Multi-Tap Comparison

After a multi-tap guitar sequence (2–10 taps), the Results panel header shows a **Taps** button. Click it to switch to Multi-Tap Comparison view: the chart overlays each individual tap's spectrum in a distinct colour alongside the averaged spectrum, and the Results panel shows an Air / Top / Back frequency table with one row per tap plus a final Averaged row. Click the button again to return to the normal averaged view. The per-tap data is saved with the measurement and reloads correctly — the Taps button reappears whenever a measurement with multi-tap data is loaded.

Overriding Mode Classification

If a peak is labelled Unknown, or misclassified, click it in the Results list and assign the correct mode manually. An overridden mode is shown in italics with a trailing asterisk (*) so it stands out from the automatic classification. Your override is saved with the measurement. Reclassifying a peak from unknown to another mode — an existing mode or a user-defined one — means the Show Unknown Modes setting no longer hides it.

Step 6 — Save

Click Save. Enter a measurement name (e.g. “Martin D-28” or “Ramirez 1075”) and any notes. The measurement is stored with all peaks, the spectrum snapshot, and a chart image.

Plate Mode

Overview

Plate material mode measures the stiffness of a rectangular tonewood sample using three free-free beam bending taps: Longitudinal (fL, along grain), Cross-grain (fC), and optionally Diagonal (fLC, torsional). From the tap frequencies and the sample dimensions it derives Young's modulus, speed of sound, specific modulus, radiation ratio, and a quality rating.

Prepare the Sample

Cut or plane a rectangular blank. Measure length (along grain), width (cross grain), thickness, and mass precisely — accuracy here directly affects the calculated moduli. A kitchen scale accurate to 0.1 g is adequate for most samples.

Select Plate Mode

Open Settings → Measurement Type → Plate, and enable Measure Diagonal (fLC) Tap if you'll capture the third tap. That is all Settings needs before you tap: you enter this sample's dimensions in the Analysis Results after capturing (see Reading the Results), where they drive the numbers live. The dimension fields in Settings are just the defaults for a new measurement.

Suspension Technique

Hold the plate at one point 22% from one end along the dimension being measured, positioned near one edge in the other dimension (not on that dimension's nodal line). This damps the unwanted resonance while approximating the free-free boundary condition. The other hand taps.

Tap 1 — Longitudinal

With the grain running left-right, hold the plate at one point 22% from one end along the length, near one long edge (not at the width nodal line — this damps the cross-grain resonance). Tap center. Click New Tap and follow the on-screen prompt “Step 1: Longitudinal (fL) Mode”. The app selects the strongest peak as the longitudinal frequency.

Tap 2 — Cross-Grain

Rotate the plate 90° so the grain runs front-back. Hold at one point 22% from one end along the width, near one short edge (not at the length nodal line — this damps the longitudinal resonance). Tap center. The app advances to “Step 2: Cross-grain (fC) Mode” automatically after the longitudinal tap is accepted.

Tap 3 — Diagonal (Optional)

Enable Measure Diagonal (fLC) Tap in Settings. Hold the plate at the midpoint of one long edge and tap near the opposite corner (~22% from both the end and the side). This adds a shear modulus measurement used in the Gore target-thickness calculation. Omitting it over-estimates target thickness by roughly 5–7%.

Reading the Results

The Results panel is where you turn the captured frequencies into properties. Enter this sample's Sample Dimensions (Length, Width, Thickness, Mass) and Body Dimensions (Body Length, Lower Bout Width, Panel Stiffness); every number recomputes live. The panel shows:

- E_L / E_C — Young's modulus along and across grain (GPa); GLC (Shear) appears here when the Diagonal tap was measured
- c_L / c_C — Speed of sound in each direction (m/s)
- Specific modulus E/ρ — The primary quality metric (GPa per g/cm³)
- Radiation ratio — Sound radiation efficiency
- Cross/Long ratio — Anisotropy (spruce: typically 0.04–0.08)
- Quality rating — Excellent / Very Good / Good / Fair / Poor (spruce scale)
- Gore target thickness — Recommended finished plate thickness for a guitar of your specified body dimensions (requires the Diagonal (fLC) tap or uses an approximation)

Spruce Quality Scale

Specific modulus (longitudinal): $\geq 25 \rightarrow$ Excellent (Master grade); $\geq 22 \rightarrow$ Very Good (AAA); $\geq 19 \rightarrow$ Good (AA); $\geq 16 \rightarrow$ Fair (A); $< 16 \rightarrow$ Poor.

Gore Target Thickness

In the Analysis Results, enter the finished guitar body length and lower bout width and choose the Panel Stiffness preset: Steel String Top (f_{vs} 75), Steel String Back (55), Classical Top (60), Classical Back (50), or Custom. The result is the plate thickness that hits the preset vibrational stiffness after bracing is factored in — a direct implementation of Gore Equation 4.5-7.

Brace Mode

Overview

Brace mode is a fast single-tap variant of Plate mode designed for brace strips. Only a longitudinal (fL) tap is needed; cross-grain and the Diagonal (fLC) tap are skipped.

Brace Orientation

The dimension in the tap direction (the brace standing upright on the bench) is the t value in the stiffness formula. Length is along the grain. Settings labels this dimension Height (tap direction); the Analysis Results field is labelled Thickness — they are the same value.

Technique

Hold the brace at one point 22% from one end along the length, near one edge in the width direction (not on the width nodal line). Tap the top face at the center. The same one-point hold technique as Plate mode. Because braces are small and stiff, their tap resonance is much quieter than a plate or guitar body — the app uses an adaptive noise-floor threshold for brace tap detection and always picks the strongest peak.

Results

Enter the strip's dimensions in the Analysis Results to compute E_L , c_L , specific modulus, and a spruce quality rating. No cross-grain or Gore thickness calculation is available in Brace mode.

New Tap

Starts a fresh measurement — arms the detector (or begins a plate/brace sequence). Disabled only while a measurement is being captured; enabled at all other times, including after a measurement completes (use Cancel to abandon one in progress). A green indicator shows when a tap has been registered.

Pause / Resume • Accept (plate/brace review)

Pause temporarily suspends tap detection while keeping the spectrum live — use it to let the ring-out decay between taps in a multi-tap sequence, or to reposition a plate or brace before continuing. Resume re-arms the detector.

In plate and brace mode, after each phase is captured the spectrum freezes for review. While in a review state the button changes to Accept. Click Accept to confirm the captured spectrum and advance to the next phase (or complete the measurement if it was the last phase).

Cancel • Redo (plate/brace review)

Cancel restarts the measurement — it discards all partial data and immediately re-arms a fresh sequence, so you can tap again without clicking New Tap. Cancel is available while a measurement is in progress.

In plate and brace mode, while reviewing a captured phase the button changes to Redo. Click Redo to discard only the current phase's data and re-capture it, preserving earlier phases. Either way the detector re-arms immediately.

Analysis Results

The Analysis Results panel shows the peak list, decay time, plate properties, quality rating, and (for Plate mode) the Gore target thickness. It also contains Export Spectrum and Export PDF Report buttons. On iPhone, tap the Results button (doc icon) in the toolbar to open the panel as a sheet. On iPad and desktop, the panel is permanently visible on the right side of the window.

Re-analyze Peaks

Shown in the results panel header next to the microphone name. Re-runs peak detection on the frozen spectrum of any completed guitar measurement — live or loaded — re-classifies the modes from scratch, and returns peak selection to automatic. Custom mode names you have assigned are kept, though the peak carrying one may end up deselected. Useful for trying a different guitar type without re-tapping, or for a clean classification after manual changes. It no longer disables itself after one press, and does not apply to Plate or Brace measurements.

Auto dB

Scales the magnitude axis to fit the current signal. Click it after each measurement to keep peaks visible.

Annotations

Cycles through three label modes: All peaks annotated, Selected peaks only, or None. For plate and brace there is no per-peak selection, so All and Selected show the same thing — all three identified frequencies (Longitudinal, Cross-grain, and Diagonal) — while None hides them.

Peak Labels

Drag any peak label to reposition it and avoid overlaps. To reset an individual label: right-click it and choose “Reset Position”. To reset all labels at once: right-click the chart area (not a label) and choose “Reset Labels”.

Play Audio File

Feeds a WAV or audio file through the FFT pipeline instead of the microphone. The file's tap is analysed exactly as a live microphone tap — tap detection fires automatically, peaks are found, and results appear in the panel. The chart title shows the filename while the file plays. After playback the microphone restarts automatically. Access via File menu → Play Audio File... (Ctrl+Alt+O).

 **Plate and brace files need half a second of room tone before the first tap.** Those modes measure the room's noise floor from the audio ahead of the tap and detect relative to it, so the file must actually contain that lead-in. Recordings made by Guitar Tap always do. A file recorded elsewhere may not: if its first tap falls inside that opening half-second the tap is treated as part of the settling period, is not detected, and nothing is captured — re-record with a moment of silence in front of the first tap. Guitar files are unaffected.

Save

Saves the current measurement — enabled when the spectrum is frozen, peaks have been detected, and you have entered a measurement name (the name is required; notes are optional).

Measurements

Lists all saved measurements. Double-click a row to load the measurement into the main view — the measurements window closes automatically after loading. Click a row's $\cdots$ button or right-click it to access: Load into View, View Details, Edit Name & Notes, Export Measurement (saves the .guitartap file via a save dialog), Export Spectrum (saves the chart image), Export PDF Report, or Delete. Use Import Measurement to load a .guitartap file from disk or another device. Use Export All to write your whole library to a single .guitartap file — for backing it up or moving the complete set of measurements to another platform; re-import it with Import Measurement. Use Compare to enter multi-select mode and overlay 2–5 saved guitar measurements on the main chart for side-by-side comparison. The measurement name and notes can also be edited from the Edit button in the Measurement Details dialog.

Compare Measurements

In the Measurements list, click Compare to enter selection mode. Select 2–5 saved guitar measurements (plate and brace measurements cannot be compared). Click Compare Selected to overlay all selected spectra on the main chart as colour-coded curves with a legend. The chart, cursor, zoom, and pan all work normally. Press New Tap to exit comparison and return to single-measurement mode.

While comparing: Annotations is disabled; Threshold and Peak Min sliders are disabled. **Export Spectrum** produces an overlay image with all curves, their colours, and a legend. **Export PDF Report** generates a comparison report showing the spectrum image and an Air / Top / Back peak frequency table for each spectrum. **Save** stores the entire comparison as a single record in the Measurements list — it can be reloaded later to restore the overlay view exactly as it was, and can itself be exported as a PDF or spectrum image from the list.

Metrics

Shows FFT engine statistics: frame rate, bin width (Hz/bin), sample rate, and buffer size.

Menu Bar

The menu bar has four menus:

GuitarTap menu:

- **About Guitar Tap...** — shows app description
- **Settings...** — Ctrl+, (⌘, on macOS)

On macOS these items are automatically moved to the system Application menu.

File menu:

- **Close** — Ctrl+W (⌘W on macOS) — closes the window
- **Play Audio File...** — Ctrl+Alt+O — feeds a WAV or audio file through the FFT pipeline instead of the microphone
- **Save Measurement...** — Ctrl+S
- **Export Spectrum Image...** — Ctrl+E
- **Export PDF Report...** — Ctrl+Shift+E

Save and Export items are disabled until a measurement is complete.

View menu:

- **Auto dB** — Ctrl+0 — toggles auto-scaling of the dB axis
- **Cycle Annotations** — Ctrl+` — cycles Selected → None → All
- **Show Metrics** — Ctrl+M — opens the FFT diagnostics panel
- **Show Measurements** — Ctrl+L — opens the saved measurements browser

Help menu:

- **Quick Start Guide** — F1 (⌘? on macOS) — opens this window
- **User Manual** — opens the full User Manual at dolcesfogato.com in your default browser

User Manual (online)

For a complete reference — every measurement mode walked through in detail, full settings and controls reference, troubleshooting, glossary, and file-format specs — see the User Manual, hosted at dolcesfogato.com. Open it from the Help menu, or from the Settings → About & Help section.

Chart Options (…)

The ellipsis (….) button in the top-right corner of the spectrum opens the Chart Options menu. From here you can reset either or both axes to the values you last saved in Settings (“Reset to Saved”), or restore the factory defaults (“Reset to Defaults”). If peak labels have been dragged from their auto-positions, “Reset Labels” moves them back. Right-clicking the chart opens the same menu.

Zoom & Pan Help

Scroll over the chart to zoom — the axis depends on where the pointer is: over the plot area it zooms both axes; over the frequency axis (bottom) it zooms frequency only; over the magnitude axis (left) it zooms magnitude only. Drag to pan the same way. Modifier keys: Shift+Scroll — pan frequency; Alt+Scroll — pan magnitude; Cmd/Ctrl+Scroll — zoom both axes. To reset the axes, click the … Chart Options button (top-right) or right-click anywhere inside the chart.

Tap Controls

Taps (stepper)

How many taps to average together (1–10). Averaging reduces noise from tap-position variability and ambient sound. Values of 3–5 are a good starting point for material work.

Threshold (slider)

The signal level that triggers tap detection. If taps are being missed, move the slider left (lower). If ambient noise triggers false detections, move it right (higher). Displayed in dB. In Plate and Brace mode the threshold is relative — it sets the headroom above an adaptive noise floor estimate, so the trigger adapts to the ambient noise level.

Peak Min (slider)

Minimum magnitude a peak must reach to be shown — in the results list and annotated on the chart. Peak Min is a display filter over the measurement’s stored peaks: moving it shows or hides peaks but never re-detects them, changes which are selected, or how they are classified — so a peak hidden then revealed returns exactly as it was. (Every detected peak is kept with the saved measurement regardless of Peak Min.) In brace/plate mode the tap capture uses its own adaptive noise floor, and Peak Min affects only what is visible on the chart. Move the slider left to show quieter peaks; right to suppress noise. Displayed in dB.

Reset arrows

Each slider has a small reset button that resets it to the factory default value.

Settings Reference

Audio Input & Calibration

Shown at the top of Settings. Select your microphone or audio interface here. Import a frequency-response calibration file (.txt/.cal) to compensate for microphone coloration; calibrations are automatically associated with each device. Audio input and calibration changes take effect immediately and are not affected by Cancel.

Measurement Type

Shown below Audio Input. Choose Generic Guitar (the default), Acoustic/Steel String, Classical, Flamenco, Material (Plate), or Material (Brace). Determines which mode frequency windows are applied and which calculations appear in Results.

Advanced (collapsed section)

Click the Advanced row to expand Display Settings, Analysis Settings, and FFT Processing. These options rarely need changing after initial setup.

Show Unknown Modes

Guitar mode only — found in Advanced → Analysis Settings. When off, peaks outside the known mode frequency windows are hidden, reducing clutter. A peak you have manually reclassified from unknown to another mode — an existing mode or a user-defined one — is no longer unknown and stays visible.

Display Frequency Range

Advanced → Display Settings. Sets the horizontal zoom of the spectrum chart. Narrow the range to zoom in on a region of interest. Use Save Current View to persist the current pan/zoom as the default.

Display Magnitude Range

Advanced → Display Settings. Sets the vertical scale (dB). Use Auto dB in the main view for a quick fit, or set explicit Min/Max here.

Peak Min

Advanced → Analysis Settings. Sets the minimum magnitude (dB) for a peak to be shown in the results and annotated on the chart. It is a display filter over the measurement's stored peaks — it does not re-detect peaks or change which are selected or classified. In brace/plate mode it affects only what is annotated on the live chart. Typical useful range: -60 to -40 dB.

Tips & Technique

Tap Technique

Use a short, crisp knuckle, fingertip tap, or a bouncy ball on a stick. A slow, pressing contact excites fewer overtones and produces a cleaner fundamental. Avoid tapping near the edges — aim for the centre of the plate or brace in Plate and Brace modes and near the bridge area for guitar-body mode surveys.

Consistent Mic Position

Keep the microphone at the same distance and angle between measurements for the most comparable magnitude values. Frequency readings are position-independent, but relative magnitudes are not.

Damping Check with Decay Time

The decay time (ring-out) appears in Results. A longer decay on the top plate typically correlates with lower internal damping — desirable in a soundboard. Compare braced vs. unbraced sections this way.

Air Mode for Setup

The Helmholtz air resonance is easily produced by holding the assembled body near the microphone and clapping your palm over the sound hole. It does not require tapping the wood itself.

Comparing Guitar Measurements

Save a measurement for each build stage or measurement name with a descriptive label. Use the Measurements list Compare button to overlay 2–5 saved guitar measurements as colour-coded spectra on the main chart — ideal for tracking how bracing or finishing changes the resonant modes over time.

PDF Reports

Each saved measurement can generate a PDF report containing the spectrum chart, peak table, and analysis summary. Open Measurements, select a measurement, then use the PDF export button. Saved comparison records generate a comparison PDF showing the overlay spectrum and an Air / Top / Back frequency table for each spectrum. A comparison PDF can also be exported directly from the main view while a live comparison is active, using Export PDF Report in the Analysis Results panel.

Zooming the Spectrum

Scroll over the chart to zoom — the axis depends on where the pointer is: over the plot area it zooms both axes; over the frequency axis (bottom) it zooms frequency only; over the magnitude axis (left) it zooms magnitude only. Drag to pan the same way. Modifier keys: Shift+Scroll — pan frequency; Alt+Scroll — pan magnitude; Cmd/Ctrl+Scroll — zoom both axes. To reset the axes, click the ⋮ Chart Options button (top-right) or right-click anywhere inside the chart.

Glossary

Air (Helmholtz) mode

The resonance of the air mass in the sound hole, analogous to blowing across a bottle. Typically 80–110 Hz for classical guitar.

Top / Back mode

The fundamental bending resonance of the top or back plate. The relationship between these and the Air mode strongly influences the low-frequency response of the instrument.

Q Factor

Sharpness of a resonance peak. $Q = \text{frequency} \div -3 \text{ dB bandwidth}$. A higher Q means lower internal damping and a longer, purer ring-out.

Specific Modulus (E/ρ)

Young's modulus divided by density. The single best predictor of tonewood quality because it determines how fast sound travels through the wood relative to its weight. Higher is better for soundboards.

Young's Modulus (E)

A measure of how stiff the wood is along a given direction. E_L is along the grain; E_C is across. Reported in GPa.

Speed of Sound (c)

How fast longitudinal sound waves travel through the wood: $c = \sqrt{E/\rho}$. Sitka spruce averages ≈ 5500 m/s along the grain.

Radiation Ratio (R)

Sound radiation efficiency: $R = c/\rho$. A higher value means the plate radiates sound more efficiently for its weight.

Cross/Long Ratio

$E_C \div E_L$. A measure of wood anisotropy. For spruce guitar tops this typically falls between 0.04 and 0.08; lower values indicate stronger grain structure.

Tap Tone Ratio

Top mode frequency $\div$ Air mode frequency. A rough structural quality indicator for assembled guitars; values between 1.8 and 2.4 are typical for well-made instruments.

Gore Target Thickness

A plate thickness prediction based on Gore Equation 4.5-7, derived from E_L , E_C , shear modulus G_{LC} , the wood density, and the guitar body dimensions. It targets a specified vibrational stiffness (f_{vs}) preset.

Diagonal (fLC) Tap

A diagonal-mode tap that excites the torsional resonance of the plate. Used to calculate the shear modulus G_{LC} for the Gore thickness formula. Hold the plate at the midpoint of one long edge and tap near the opposite corner (~22% from both the end and the side).

Free-Free Beam

The boundary condition assumed by the tap-tone formula. The plate ends are unsupported (free), which is approximated by holding the sample at one nodal point (22% from one end along the dimension being measured). The formula constant 22.37 comes from the first mode shape of a free-free Euler-Bernoulli beam.

FFT (Fast Fourier Transform)

The algorithm that converts a time-domain audio signal into a frequency-domain spectrum. Guitar Tap uses a 65,536-point windowed FFT (Hann window) giving a frequency resolution of approximately 0.67 Hz per bin at a 44.1 kHz sample rate.