

Simulate a Live Attack for Kubernetes (lite)



Doc



Ctrl+K

Simulate a Live Attack for Kubernetes (lite)



The Wiz Runtime Sensor collects runtime events on Kubernetes workloads and translates them to detections.

Below are a set of commands that can be run on most environments to help you quickly test the Runtime Sensor detections. These commands do not require the deployment of a custom container image.

This scenario uses non-malicious commands for the simulation and should be safe to execute in your environment. Some of these commands will make changes to the container in which they are run, so we recommend using a dedicated target container in test or demo environments only.

Step 1: Deploy the Runtime Sensor evaluation pod

Step 2: Run attack-simulation commands

<u>Step 3</u>: Clean-up (remove the Runtime Sensor evaluation pod)

Prerequisites

- Kubernetes version 1.20 or higher, where the Runtime Sensor was successfully deployed on a cluster.
- Access credentials with permissions to deploy a pod and execute commands on it.
- Access to the Kubernetes cluster API from your machine with the ability to run kubectl commands.
- A local installation of kubectl.
- Wiz Sensor installed on the Kubernetes cluster.

Deploy the Runtime Sensor evaluation pod

- 1. <u>Download</u> the wiz-privileged-demo-pod.yaml file.
- 2. Deploy the target pod on your Kubernetes cluster:

English -

```
kubectl apply -f wiz-privileged-demo-pod.yaml
```

3. Initiate an interactive shell with the pod:

```
kubectl exec -it wiz-demo-pod -- bash
```

Run attack-simulation commands

In this step, you will run a series of commands on the target pod via the shell you just created and review the events generated by the Runtime Sensor. The Runtime Sensor detections are represented under the Explorer > Cloud Events page in your Wiz portal.


Suspicious access to process memory

Command to execute

Execute the following command: /usr/bin/cat /proc/\$/mem 2> /dev/null

Expected detection(s) in Wiz

 Process memory dump was detected (<u>T1003.007 OS Credential Dumping: Proc</u> <u>Filesystem</u>)



 Process memory data file was accessed (<u>T1003.007 OS Credential Dumping: Proc</u> <u>Filesystem</u>)




Command to execute

Execute the following command:

```
/usr/bin/curl https://www.wiz.io/ --retry 5 --output /tmp/test-drop && /usr/bin/chmod +x /tmp/test-drop
```

Expected detection(s) in Wiz

- Suspected drop and execute-ingress tool with payload decode or file/folder permission change commands were executed (<u>T1222.002 File and Directory</u> <u>Permissions Modification: Linux and Mac File and Directory Permissions</u> <u>Modification</u>)
- File created/modified by an ingress tool that established a remote connection (<u>T1105 Ingress Tool Transfer</u>)



Ingress tool was executed (<u>T1105 Ingress Tool Transfer</u>)

Evasion via hidden files

Command to execute

```
/usr/bin/mkdir -p /tmp/.testdir && cp /usr/bin/whoami /tmp/.testdir/test && /usr/bin/chmod +x /tmp/.testdir/test && /tmp/.testdir/test
```

- Process was executed from hidden location (<u>T1564.001 Hide Artifacts: Hidden Files</u> and <u>Directories</u>)
- Hidden directory was created (<u>T1564.001 Hide Artifacts: Hidden Files and Directories</u>)

Possible credential manipulation


Command to execute

Execute the following command:

```
/usr/bin/echo test >> /etc/shadow
```

Expected detection(s) in Wiz

Unrecognized write to user management file (<u>T1078.003 Valid Accounts</u>: <u>Local Accounts</u>)



Evasion via renamed binaries (living-off-the-land variant)

Command to execute

Execute the following command:

```
ls -1 /bin/*sh | grep -v \\.sh | xargs -I {} /usr/bin/cp -f {} {}.lotl
```

Expected detection(s) in Wiz

File created or modified in bin folder (<u>T1554 Compromise Client Software</u> English ←

Possible container escape via mount with cgroups

Command to execute

Execute the following command:

/usr/bin/mkdir -p /tmp/test && /usr/bin/mount -t cgroup /tmp/test 2>/dev/null

Expected detection(s) in Wiz

Mount with type cgroup was executed inside a container (<u>T1611 Escape to Host</u>)

Hijack Execution Flow: Dynamic Linker Hijacking

Command to execute

/usr/bin/touch /etc/ld.so.preload && /usr/bin/echo test >> /etc/ld.so.preload

Expected detection(s) in Wiz

Library preload configuration file was added/modified (<u>T1574.006 Hijack Execution Flow: Dynamic Linker Hijacking</u>)

Clean up (remove the Runtime Sensor evaluation pod)

To remove the pod, run:

Updated 3 months ago

kubectl delete -f wiz-privileged-demo-pod.yaml

- ← Attack Simulations for Runtime Sensors

Simulate a Live Attack for Kubernetes

Did this page help you? 🖒 Yes 🖓 No

English -