

AMERICAN LATIN CLASS ATTENDANCE SYSTEM

Postman Token Auth Proof

Table of Contents

Postman Token Authentication Proof

Environment

1. Protected URI Without Token
2. Login To Receive JWT Token
3. Protected URI With Bearer Token
4. Logout Revokes Token
5. Same Token After Logout

Automated Evidence

Postman Token Authentication Proof

This document describes the manual backend-only Postman proof for JWT authentication.

Environment

Use the Postman environment:

- `site_url` : `https://18-217-255-109.sslip.io`
- `base_url` : `https://18-217-255-109.sslip.io/api/v1`
- `login_email` : `verification-admin-real-20260624154645@alc.test`
- `login_password` : academic demo password configured for `POSTMAN_LOGIN_PASSWORD`
- `session_token` : blank before login; filled automatically by the login request

1. Protected URI Without Token

Method: `GET`

URI:

```
{{base_url}}/auth/me
```

Authorization:

No Auth

Expected response:

HTTP	Message
401 Unauthorized	{ "success": false, "message": "Authentication required" }

Postman request:

Auth & Session / Current Session - No Token

2. Login To Receive JWT Token

Method: POST

URI:

```
{{base_url}}/auth/login
```

JSON body:

```
{
  "email": "{{login_email}}",
  "password": "{{login_password}}"
}
```

Expected response:

HTTP	Message
200 OK	Response includes <code>data.sessionToken</code> , <code>data.tokenType = "Bearer"</code> and <code>data.user</code> .

Postman request:

Auth & Session / Password Login - Demo

The Postman test script stores:

```
session_token = data.sessionToken
```

3. Protected URI With Bearer Token

Method: **GET**

URI:

```
{{base_url}}/auth/me
```

Authorization:

Type: Bearer Token
Token: {{session_token}}

Expected response:

HTTP	Message
200 OK	Response includes the authenticated user object.

Postman request:

Auth & Session / Current Session - Bearer Token

4. Logout Revokes Token

Method: **POST**

URI:

```
{{base_url}}/auth/logout
```

Authorization:

Type: Bearer Token
Token: {{session_token}}

Expected response:

HTTP	Message
200 OK	Logout successful

Postman request:

Session Teardown / Logout

5. Same Token After Logout

Method: GET

URI:

{{base_url}}/auth/me

Authorization:

Type: Bearer Token
Token: the same token returned by login

Expected response:

HTTP	Message
401 Unauthorized	{ "success": false, "message": "Authentication required" }

Postman request:

Session Teardown / Current Session - After Logout

Automated Evidence

Latest Newman evidence:

Metric	Result
Requests	67 executed, 0 failed
Assertions	78 executed, 0 failed
API validation	102/102 passed
Jest tests	16 passed