

NAME

imcopy -- copy images

USAGE

imcopy input output

PARAMETERS**input**

Images to be copied.

output

Output images or directory.

verbose = yes

Print each operation as it takes place?

DESCRIPTION

Each of the input images, which may be given as a including sections, is copied to the corresponding output image list, which may also be given as an image template, or the output directory. If the output is a list of images then the number of input images must be equal to the number of output images and the input and output images are paired in order. If the output image name exists and contains a input image (provided it is the same size as the section) will be copied into that section of the input image. If the output image name does not have a section specification and if it is the same as the input image name then the input image is copied to a temporary file which replaces the input image when the copy is successfully concluded. Note that these are the only cases where clobber checking is bypassed; that is, if an output image name is not equal to the input image name or a subsection of an existing image and the file already exists then a clobber error will occur if clobber checking is in effect.

The verbose options prints for each copy lines of the form:

input image -> output image

EXAMPLES

1. For a simple copy of an image:

```
cl> imcopy image imagecopy
```

2. To copy a portion of an image:

```
cl> imcopy image[10:20,*] subimage
```

3. To copy several images:

```
cl> imcopy image1,image2,frame10 a,b,c
```

4. To trim an image:

```
cl> imcopy image[10:20,*] image
```

In the above example the specified section of the input image replaces the original input image. To trim several images using an image template:

```
cl> imcopy frame*[1:512,1:512] frame*
```

In this example all images beginning with "frame" are trimmed to 512 x

5. To copy a set of images to a new directory:

```
cl> imcopy image* directory
```

or

```
cl> imcopy image* directory$
```

or

```
cl> imcopy image* osdirectory
```

where "osdirectory" is an operating system directory name (i.e. /user/me in UNIX).

6. To copy a section of an image in an already existing image of sufficient size to contain the input section.

```
cl> imcopy image[1:512,1:512] outimage[257:768,257:768]
```

BUGS

The distinction between copying to a section of an existing image and overwriting a input image is rather inobvious.