



Introduction

Anti-microbial Peptides (AMPs)

Characteristics¹




Mechanisms of Action¹



Source: Hancock, R. E. W. & Sahl, H.-G. Antimicrobial and host-defense peptides as new anti-infective therapeutic strategies. *Nat. Biotechnol.* 24, 1551–1557 (2006) doi: [10.1038/nbt1267](https://doi.org/10.1038/nbt1267)

Motivation



Problem

- The rise of antibiotic resistance¹
- The antibiotic “discovery” void²: few new antibiotics, but old antibiotics less effective
- The need for novel methods to fight pathogen

Solution


- AMPs do not confer resistance as easily as antibiotics, due to co-evolution with the human microbiome¹
- AMPs are a potential alternative to antibiotics³
- AMPs can be mined from organisms of rich AMP diversity, such as the North American bullfrog⁴

Objectives


- To develop and execute a scalable bioinformatics-based AMP discovery pipeline (i.e. *rAMPage*) to mine for AMP sequences in publicly available genomic resources
- To package a fully functional bioinformatics pipeline
- To obtain a list of potential AMP sequences for
 - Downstream analysis
 - In vitro* bioactivity testing
 - Drug development



Methods



Peptide Structure¹



Results




Fig A.¹⁸ Count progression from transcripts to AMPs. Across the 84 datasets, *rAMPage* assembled > 53 million transcripts, and detected > 1000 putative AMPs (AMPlify score ≥ 0.50 is an AMP; stricter criteria used above).




Fig B.¹⁹ AMP counts after applying three filters. Three strict filters (AMPlify score ≥ 0.90 , length ≤ 30 aa, charge ≥ 2) are applied in *rAMPage*. [Left] 1,332 AMPs remain after filtering and duplicate sequence removal *within each dataset*. [Right] 1,007 AMPs remain after filtering and duplicate sequence removal *across all datasets*. If desired, more AMPs (of lower confidence) can be detected by adjusting the stringency of the filters.

C. rAMPage Benchmarking




Fig C.¹⁸ Runtime and memory usage of *rAMPage*. *rAMPage* is fast: with < 1 billion reads (74/84 datasets), results can be obtained within 24 hours, using < 200 GB of memory. Larger datasets with > 1 billion reads can be subsampled to reduce runtime and memory usage.

Conclusions

- Across the 84 assembled transcriptomes, 1,007 confident (AMPlify score ≥ 0.90), short (length ≤ 30 aa), and positive (charge ≥ 2) unique mature putative AMPs were found: 795 from amphibians, 212 from insects
- Of these 1,007 AMPs, 254 sequences align to known AMPs with 100% sequence identity in the mature region; 753 sequences are ‘novel’ AMPs
- rAMPage* is a fast, robust bioinformatics pipeline that, given raw reads, can detect known and novel putative AMPs

References

- Hancock, R. E. W. & Sahl, H.-G. Antimicrobial and host-defense peptides as new anti-infective therapeutic strategies. *Nat. Biotechnol.* 24, 1551–1557 (2006) doi: [10.1038/nbt1267](https://doi.org/10.1038/nbt1267)
- Koo, H. B. & Seo, J. Antimicrobial peptides under clinical investigation. *Peptide Science* vol. 111 (2019) doi: [10.1002/pep2.24122](https://doi.org/10.1002/pep2.24122)
- Reinhardt, A. & Neundorfer, I. Design and Application of Antimicrobial Peptide Conjugates. *Int. J. Mol. Sci.* 17, (2016) doi: [10.3390/ijms17050701](https://doi.org/10.3390/ijms17050701)
- Helbing, C. C. et al. Antimicrobial peptides from Rana [Lithobates] catesbeiana: Gene structure and bioinformatic identification of novel forms from tadpoles. *Sci. Rep.* 9, 1529 (2019) doi: [10.1038/s41598-018-38442-1](https://doi.org/10.1038/s41598-018-38442-1)
- Leinonen, R., Sugawara, H., Shumway, M. & International Nucleotide Sequence Database Collaboration. The sequence read archive. *Nucleic Acids Res.* 39, D19–21 (2011) doi: [10.1093/nar/gkq1019](https://doi.org/10.1093/nar/gkq1019)
- Chen, S., Zhou, Y., Chen, Y. & Gu, J. fastp: an ultra-fast all-in-one FASTQ preprocessor. *Bioinformatics* 34, i884–i890 (2018) doi: [10.1093/bioinformatics/bty560](https://doi.org/10.1093/bioinformatics/bty560)
- Nip, K. M. et al. RNA-Bloom enables reference-free and reference-guided sequence assembly for single-cell transcriptomes. *Genome Res.* 30, 1191–1200 (2020) doi: [10.1101/gr260174.119](https://doi.org/10.1101/gr260174.119)
- Patro, R., Duggal, G., Love, M. I., Izrarry, R. A. & Kingsford, C. Salmon provides fast and bias-aware quantification of transcript expression. *Nat. Methods* 14, 417–419 (2017) doi: [10.1038/nmeth.4197](https://doi.org/10.1038/nmeth.4197)
- Haas, B. J. et al. De novo transcript sequence reconstruction from RNA-seq using the Trinity platform for reference generation and analysis. *Nat. Protoc.* 8, 1494–1512 (2013) doi: [10.1038/nprot.2013.084](https://doi.org/10.1038/nprot.2013.084)
- Johnson, L. S., Eddy, S. R. & Portugaly, E. Hidden Markov model speed heuristic and iterative HMM search procedure. *BMC Bioinformatics* 11, 431 (2010) doi: [10.1186/1471-2105-11-431](https://doi.org/10.1186/1471-2105-11-431)
- Wang, G., Li, X. & Wang, Z. APD3: the antimicrobial peptide database as a tool for research and education. *Nucleic Acids Res.* 44, D1087–93 (2016) doi: [10.1093/nar/gkv1278](https://doi.org/10.1093/nar/gkv1278)
- Novkovic, M., Simunic, J., Bojovic, V., Tossi, A. & Juretic, D. DADP: the database of anuran defense peptides. *Bioinformatics* 28, 1406–1407 (2012) doi: [10.1093/bioinformatics/bts141](https://doi.org/10.1093/bioinformatics/bts141)
- Duckert, P., Brunak, S. & Blom, N. Prediction of proprotein convertase cleavage sites. *Protein Eng. Des. Sel.* 17, 107–112 (2004) doi: [10.1093/protein/gzh013](https://doi.org/10.1093/protein/gzh013)
- Li, C. et al. AMPlify: attentive deep learning model for discovery of novel antimicrobial peptides effective against WHO priority pathogens. *bioRxiv* 2020.06.16.155705 (2020) doi: [10.1101/2020.06.16.155705](https://doi.org/10.1101/2020.06.16.155705)
- Hart, A. J. et al. EnTAP: Bringing faster and smarter functional annotation to non-model eukaryotic transcriptomes. *Mol. Ecol. Resour.* 20, 591–604 (2020) doi: [10.1111/1755-0998.13106](https://doi.org/10.1111/1755-0998.13106)
- Slater, G. S. C. & Birney, E. Automated generation of heuristics for biological sequence comparison. *BMC Bioinformatics* 6, 31 (2005) doi: [10.1186/1471-2105-6-31](https://doi.org/10.1186/1471-2105-6-31)
- Adamczak, R., Porollo, A. & Meller, J. Combining prediction of secondary structure and solvent accessibility in proteins. *Proteins* 59, 467–475 (2005) doi: [10.1002/prot.20441](https://doi.org/10.1002/prot.20441)
- Wickham, H. et al. Welcome to the tidyverse. *J. Open Source Softw.* vol. 4 1686 (2019). doi: [10.21105/joss.01686](https://doi.org/10.21105/joss.01686)
- Yan, L. ggvenn: Draw Venn Diagram by ‘ggplot2’. *Comprehensive R Archive Network* (2021). <https://CRAN.R-project.org/package=ggvenn>

Funding & Acknowledgements

